

# Ficha de datos de seguridad

## MASTICE GUARNIZIONI ML 100



### Ficha de datos de seguridad del 9/7/2021, Revisión 6

#### SECCIÓN 1. Identificación de la sustancia o la mezcla y de la sociedad o la empresa

##### 1.1. Identificador de producto

Identificación del preparado:

Nombre comercial: MASTICE GUARNIZIONI ML 100

Código comercial: 0017

##### 1.2. Usos pertinentes identificados de la sustancia o de la mezcla y usos desaconsejados

Uso recomendado:

Adhesivo

##### 1.3. Datos del proveedor de la ficha de datos de seguridad

Proveedor:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Persona competente responsable de la ficha de datos de seguridad:

arexons@arexons.it

##### 1.4. Teléfono de emergencia

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Teléfono de emergencias: + 34 91 562 04 20 (Solo emergencias toxicológicas. Información en español (24h/365 días))

#### SECCIÓN 2. Identificación de los peligros

##### 2.1. Clasificación de la sustancia o de la mezcla

Criterios Reglamentación CE 1272/2008 (Clasificación, Etiquetado y Empacado):

⚠ Peligro, Flam. Liq. 2, Líquido y vapores muy inflamables.

⚠ Atención, Skin Sens. 1, Puede provocar una reacción alérgica en la piel.

Efectos físico-químicos nocivos para la salud humana y para el medio ambiente:

Ningún otro riesgo

##### 2.2. Elementos de la etiqueta

Pictogramas de peligro:



Peligro

Indicaciones de peligro:

H225 Líquido y vapores muy inflamables.

H317 Puede provocar una reacción alérgica en la piel.

Consejos de prudencia:

P101 Si se necesita consejo médico, tener a mano el envase o la etiqueta.

P102 Mantener fuera del alcance de los niños.

P103 Leer atentamente y seguir todas las instrucciones.

P210 Mantener alejado del calor, de superficies calientes, de chispas, de llamas abiertas y de cualquier otra fuente de ignición. No fumar.

P233 Mantener el recipiente herméticamente cerrado.

P280 Llevar guantes, prendas, gafas y máscara de protección.

P370+P378 En caso de incendio: Utilizar Espuma para alcoholes para la extinción.

P403+P235 Almacenar en un lugar bien ventilado. Mantener en lugar fresco.

## Ficha de datos de seguridad

### MASTICE GUARNIZIONI ML 100



P501 Eliminar el contenido/el recipiente en conformidad con la reglamentación.

Disposiciones especiales:

PACK2 El envase debe llevar una indicación de peligro detectable al tacto para invidentes.

Contiene

Resina de pino; colofonia

Disposiciones especiales de acuerdo con el anexo XVII del Reglamento REACH y sus posteriores modificaciones:

Ninguna

#### 2.3. Otros peligros

Ninguna sustancia PBT, mPmB o perturbador endocrino presente en concentración  $\geq 0.1\%$

Otros riesgos:

Ningún otro riesgo

---

### SECCIÓN 3. Composición/información sobre los componentes

#### 3.1. Sustancias

N.A.

#### 3.2. Mezclas

Componentes peligrosos según el Reglamento CLP y su correspondiente clasificación:

$\geq 35\%$  -  $< 40\%$  Etanol; alcohol etílico

REACH No.: 01-2119457610-43, Número Index: 603-002-00-5, CAS: 64-17-5, EC: 200-578-6

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

Límites de concentración específicos:

C  $\geq 50\%$ : Eye Irrit. 2 H319

Estimación de la toxicidad aguda:

$\geq 30\%$  -  $< 35\%$  Resina de pino; colofonia

REACH No.: 01-2119480418-32, Número Index: 650-015-00-7, CAS: 8050-09-7, EC: 232-475-7

⚠ 3.4.2/1 Skin Sens. 1 H317

$\geq 0.25\%$  -  $< 0.5\%$  propan-2-ol

REACH No.: 01-2119457558-25, CAS: 67-63-0, EC: 200-661-7

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

$\geq 0.25\%$  -  $< 0.5\%$  METILETILCHETONE MEK - BUTANONE

REACH No.: 01-2119457290-43, CAS: 78-93-3, EC: 201-159-0

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

EUH066

---

### SECCIÓN 4. Primeros auxilios

#### 4.1. Descripción de los primeros auxilios

En caso de contacto con la piel:

0017/6

Página nº. 2 de 11

## Ficha de datos de seguridad

### MASTICE GUARNIZIONI ML 100



Quítese inmediatamente la ropa contaminada.

Lavar inmediatamente con abundante agua corriente y eventualmente jabón las zonas del cuerpo que han entrado en contacto con el producto, incluso si fuera sólo una sospecha.

Lavar completamente el cuerpo (ducha o baño).

Quitarse de inmediato la indumentaria contaminada y eliminarla de manera segura.

En caso de contacto con los ojos:

En caso de contacto con los ojos, lávense inmediata y abundantemente con agua y acúdase a un médico.

En caso de ingestión:

No provocar el vómito en ningún caso. CONSULTAR INMEDIATAMENTE AL MÉDICO.

En caso de inhalación:

Llevar al accidentado al aire libre y mantenerlo en reposo y abrigado.

4.2. Principales síntomas y efectos, agudos y retardados

Ninguno

4.3. Indicación de toda atención médica y de los tratamientos especiales que deban dispensarse inmediatamente

En caso de accidente o malestar, consultar de inmediato con un médico (si es posible mostrarle las instrucciones de uso o la ficha de seguridad)

Tratamiento:

Ninguno

---

## SECCIÓN 5. Medidas de lucha contra incendios

5.1. Medios de extinción

Medios de extinción apropiados:

Con anhídrido carbónico.

Con polvo.

Espuma para alcoholes

Agua vaporizada.

Medios de extinción no recomendados:

No usar chorros de agua directos

5.2. Peligros específicos derivados de la sustancia o la mezcla

No inhalar los gases producidos por la explosión y por la combustión.

La combustión produce humo pesado.

5.3. Recomendaciones para el personal de lucha contra incendios

Utilizar equipos respiratorios apropiados.

Recoger por separado el agua contaminada utilizada para extinguir el incendio. No descargarla en la red de alcantarillado.

Si es posible, desde el punto de vista de la seguridad, retirar de inmediato del área los contenedores no dañados.

---

## SECCIÓN 6. Medidas en caso de vertido accidental

6.1. Precauciones personales, equipo de protección y procedimientos de emergencia

Usar los dispositivos de protección individual.

Quitar toda fuente de encendido.

Llevar las personas a un lugar seguro.

Consultar las medidas de protección expuestas en los puntos 7 y 8.

6.2. Precauciones relativas al medio ambiente

Evitar que el producto penetre en el suelo/subsuelo. Evitar que penetre en aguas superficiales o en el alcantarillado.

Conservar el agua de lavado contaminada y eliminarla.

En caso de fuga de gas o penetración en cursos de agua, suelo o sistema de alcantarillado, informar a las autoridades responsables.

Material apropiado para la recogida: material absorbente, orgánico, arena

6.3. Métodos y material de contención y de limpieza

## Ficha de datos de seguridad

### MASTICE GUARNIZIONI ML 100



- Lavar con abundante agua.
- 6.4. Referencia a otras secciones  
Véanse también los apartados 8 y 13.

#### SECCIÓN 7. Manipulación y almacenamiento

- 7.1. Precauciones para una manipulación segura
- Evitar el contacto con la piel y los ojos, la inhalación de vapores y vahos.  
No utilizar contenedores vacíos que no hayan sido previamente limpiados.  
Antes de realizar las operaciones de transferencia, asegurarse de que en los contenedores no haya materiales residuos incompatibles.  
Remitirse también al apartado 8 para los dispositivos de protección recomendados.
- La indumentaria contaminada debe ser sustituida antes de acceder a las áreas de almuerzo.  
No comer ni beber durante el trabajo.
- 7.2. Condiciones de almacenamiento seguro, incluidas posibles incompatibilidades
- Consérvese en ambientes siempre bien aireados.  
Debe almacenarse a temperaturas inferiores a 50 °C. Manténgase alejado de llamas libres y fuentes de calor. Evite la exposición directa al sol.  
Manténgase alejado de llamas libres, chispas y fuentes de calor. Evite la exposición directa al sol.  
Mantener alejado de comidas, bebidas y piensos.  
Ninguna en particular.  
Indicaciones para los locales:  
Frescos y adecuadamente aireados.
- 7.3. Usos específicos finales  
Ningún uso particular

#### SECCIÓN 8. Controles de exposición/protección individual

- 8.1. Parámetros de control
- Etanol; alcohol etílico - CAS: 64-17-5  
ACGIH - STEL: 1000 ppm - Notas: A3 - URT irr
- Resina de pino; colofonia - CAS: 8050-09-7  
ACGIH - Notas: (L), DSEN, RSEN - Skin sens, dermatitis, asthma
- propan-2-ol - CAS: 67-63-0  
ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notas: A4, BEI - Eye and URT irr, CNS impair  
UE - TWA(8h): 500 mg/m<sup>3</sup>, 200 ppm - STEL(): 1000 mg/m<sup>3</sup>, 400 ppm
- METILETILCHETONE MEK - BUTANONE - CAS: 78-93-3  
20101.13 - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL(): 900 mg/m<sup>3</sup>, 300 ppm  
20101.06 - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL(): 900 mg/m<sup>3</sup>, 300 ppm  
UE - TWA(8h): 600 mg/m<sup>3</sup>, 200 ppm - STEL: 900 mg/m<sup>3</sup>, 300 ppm  
ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notas: BEI - URT irr, CNS and PNS impair
- Valores límites de exposición DNEL
- propan-2-ol - CAS: 67-63-0  
Consumidor: 26 mg/kg - Exposición: Oral humana - Frecuencia: A largo plazo, efectos sistémicos  
Trabajador profesional: 500 mg/m<sup>3</sup> - Consumidor: 89 mg/m<sup>3</sup> - Exposición: Por inhalación humana - Frecuencia: A largo plazo, efectos sistémicos  
Trabajador profesional: 888 mg/kg - Consumidor: 319 mg/kg - Exposición: Dérmica humana - Frecuencia: A largo plazo, efectos sistémicos
- METILETILCHETONE MEK - BUTANONE - CAS: 78-93-3  
Consumidor: 31 mg/kg - Exposición: Oral humana - Frecuencia: A largo plazo, efectos sistémicos  
Trabajador profesional: 600 mg/m<sup>3</sup> - Consumidor: 106 mg/m<sup>3</sup> - Exposición: Por inhalación

## Ficha de datos de seguridad

### MASTICE GUARNIZIONI ML 100



humana - Frecuencia: A largo plazo, efectos sistémicos  
Trabajador profesional: 1161 mg/kg - Consumidor: 412 mg/kg - Exposición: Dérmica  
humana - Frecuencia: A largo plazo, efectos sistémicos

#### Valores límites de exposición PNEC

propan-2-ol - CAS: 67-63-0

Objetivo: agua dulce - Valor: 140.9 mg/l

Objetivo: Agua marina - Valor: 140.9 mg/l

Objetivo: Sedimentos de agua dulce - Valor: 552 mg/kg

Objetivo: agua dulce - Valor: 552 mg/kg

Objetivo: 09 - Valor: 2251 mg/l

METILETILCHETONE MEK - BUTANONE - CAS: 78-93-3

Objetivo: agua dulce - Valor: 55.8 mg/l

Objetivo: Agua marina - Valor: 55.8 mg/l

Objetivo: Sedimentos de agua dulce - Valor: 284.74 mg/l

Objetivo: Sedimentos de agua marina - Valor: 287.7 mg/l

Objetivo: 09 - Valor: 709 mg/l

#### 8.2. Controles de la exposición

##### Protección de los ojos:

Gafas con protección lateral.

Cumple con la norma EN 166

##### Protección de la piel:

Usar indumentaria que garantice una protección total para la piel, por ejemplo de algodón, caucho, PVC o viton.

##### Protección de las manos:

Guantes de nitrilo o de Viton.

Conformes EN 374.

##### Protección respiratoria:

No necesaria para el uso normal.

##### Riesgos térmicos:

Ninguno

##### Controles de la exposición ambiental:

Ninguno

##### Controles técnicos apropiados:

Ninguno

## SECCIÓN 9. Propiedades físicas y químicas

### 9.1. Información sobre propiedades físicas y químicas básicas

Propiedad	Valor	Método:	Notas
Estado físico:	Líquido	--	--
Color:	amarillo oscuro	--	--
Olor:	característico	--	--
Punto de fusión/punto de congelación:	N.A.	--	--
Punto de ebullición o punto inicial de ebullición e intervalo de ebullición:	78.5°C	--	--
Inflamabilidad:	Flam. Liq. 2, H225	--	--

**Ficha de datos de seguridad**  
**MASTICE GUARNIZIONI ML 100**



Límite superior e inferior de explosividad:	N.A.	--	--
Punto de ignición (flash point, fp):	18°C	--	--
Temperatura de autoencendido:	N.A.	--	--
Temperatura de descomposición:	N.A.	--	--
pH:	N.A.	--	--
Viscosidad cinemática:	N.A.	--	--
Hidrosolubilidad:	insoluble	--	--
Solubilidad en aceite:	N.A.	--	--
Coefficiente de reparto n-octanol/agua (valor logarítmico):	N.A.	--	--
Presión de vapor:	N.A.	--	--
Densidad y/o densidad relativa:	0.97 g/cm3	--	--
Densidad de vapor relativa:	N.A.	--	--
Características de las partículas:			
Tamaño de las partículas:	N.A.	--	--
9.2. Otros datos Ninguna otra información relevante			
Viscosidad:	600 cP	12	--

**SECCIÓN 10. Estabilidad y reactividad**

- 10.1. Reactividad  
Estable en condiciones normales
- 10.2. Estabilidad química  
Estable en condiciones normales
- 10.3. Posibilidad de reacciones peligrosas  
Ninguno
- 10.4. Condiciones que deben evitarse  
Estable en condiciones normales.
- 10.5. Materiales incompatibles  
Evitar el contacto con materiales oxidantes. El producto podría inflamarse.
- 10.6. Productos de descomposición peligrosos  
Ninguno.

## Ficha de datos de seguridad

### MASTICE GUARNIZIONI ML 100



#### SECCIÓN 11. Información toxicológica

11.1. Información sobre las clases de peligro definidas en el Reglamento (CE) n.o 1272/2008

Información toxicológica del producto:

MASTICE GUARNIZIONI ML 100

- a) toxicidad aguda  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- b) corrosión o irritación cutáneas  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- c) lesiones o irritación ocular graves  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- d) sensibilización respiratoria o cutánea  
El producto está clasificado: Skin Sens. 1 H317
- e) mutagenicidad en células germinales  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- f) carcinogenicidad  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- g) toxicidad para la reproducción  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- h) toxicidad específica en determinados órganos (STOT) – exposición única  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- i) toxicidad específica en determinados órganos (STOT) – exposición repetida  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- j) peligro de aspiración  
No clasificado  
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.

La información toxicológica de las sustancias principales halladas en el producto:

Etanol; alcohol etílico - CAS: 64-17-5

d) sensibilización respiratoria o cutánea:  
Ensayo: Sensibilización de la piel - Vía: Piel Negativo

e) mutagenicidad en células germinales:  
Ensayo: Genotoxicidad - Especies: vitro Negativo

f) carcinogenicidad:  
Ensayo: Carcinogenicidad - Especies: mam Positivo

g) toxicidad para la reproducción:  
Ensayo: NOAEL - Vía: Inhalación - Especies: Rata = 1600 ppm

propan-2-ol - CAS: 67-63-0

a) toxicidad aguda:  
Ensayo: LD50 - Vía: Oral - Especies: Rata 5840 mg/kg  
Ensayo: LD50 - Vía: Piel - Especies: Conejo 16.4 ml/kg  
Ensayo: LC50 - Vía: Inhalación - Especies: Rata > 10000 ppm - Duración: 6h

METILETILCHETONE MEK - BUTANONE - CAS: 78-93-3

a) toxicidad aguda:  
Ensayo: LD50 - Vía: Oral - Especies: Rata 2054 mg/kg  
Ensayo: LD50 - Vía: Oral - Especies: Rata 2328 mg/kg  
Ensayo: LD50 - Vía: Piel - Especies: Conejo > 10 ml/kg

i) toxicidad específica en determinados órganos (STOT) – exposición repetida:  
Ensayo: NOAEL - Especies: Rata 1002 ppm

## Ficha de datos de seguridad

### MASTICE GUARNIZIONI ML 100



- 11.2. Información relativa a otros peligros  
Propiedades de alteración endocrina:  
Ningún perturbador endocrino presente en concentración  $\geq 0.1\%$

---

## SECCIÓN 12. Información ecológica

- 12.1. Toxicidad  
Utilícese con técnicas de trabajo adecuadas, evitando la dispersión del producto en el medio ambiente.  
Etanol; alcohol etílico - CAS: 64-17-5
- a) Toxicidad acuática aguda:  
Parámetro: LC50 - Especies: Peces 14.2 GL - Duración h.: 96  
Parámetro: LC50 - Especies: Daphnia 29.6 GL - Duración h.: 24  
Parámetro: EC50 - Especies: Algas 19000 mg/l - Duración h.: 96  
Parámetro: EC50 - Especies: batteri 39.5 GL - Duración h.: 4
- b) Toxicidad acuática crónica:  
Parámetro: EC50 - Especies: Peces 14536 mg/l - Duración h.: 200  
Parámetro: LC50 - Especies: Daphnia 9248 mg/l - Duración h.: 48
- propan-2-ol - CAS: 67-63-0
- a) Toxicidad acuática aguda:  
Parámetro: LC50 - Especies: Peces 940 mg/l - Duración h.: 96  
Parámetro: LC50 - Especies: Daphnia > 10000 mg/l - Duración h.: 24  
Parámetro: LC50 - Especies: Algas 1800 mg/l - Duración h.: 184
- METILETILCHETONE MEK - BUTANONE - CAS: 78-93-3
- a) Toxicidad acuática aguda:  
Parámetro: LC50 - Especies: Peces 2993 mg/l - Duración h.: 96  
Parámetro: EC50 - Especies: Daphnia 308 mg/l - Duración h.: 78  
Parámetro: EC50 - Especies: Algas 2029 mg/l - Duración h.: 96
- 12.2. Persistencia y degradabilidad  
Ninguno  
propan-2-ol - CAS: 67-63-0  
Biodegradabilidad: Rápidamente degradable  
METILETILCHETONE MEK - BUTANONE - CAS: 78-93-3  
Biodegradabilidad: Rápidamente degradable
- 12.3. Potencial de bioacumulación  
N.A.
- 12.4. Movilidad en el suelo  
N.A.
- 12.5. Resultados de la valoración PBT y mPmB  
Sustancias vPvB: Ninguna - Sustancias PBT: Ninguna
- 12.6. Propiedades de alteración endocrina  
Ningún perturbador endocrino presente en concentración  $\geq 0.1\%$
- 12.7. Otros efectos adversos  
Ninguno

---

## SECCIÓN 13. Consideraciones relativas a la eliminación

- 13.1. Métodos para el tratamiento de residuos  
Recuperar si es posible. Enviar a centros de eliminación autorizados o a incineración en condiciones controladas. Operar conforme con las disposiciones locales y nacionales vigentes.  
Información adicional sobre eliminación:  
Recuperar si es posible. Trabajar según las disposiciones locales y nacionales vigentes.

---

## SECCIÓN 14. Información relativa al transporte



## Ficha de datos de seguridad MASTICE GUARNIZIONI ML 100



- 14.1. Número ONU o número ID  
ADR-UN Number: 1133  
IATA-UN Number: 1133  
IMDG-UN Number: 1133
- 14.2. Designación oficial de transporte de las Naciones Unidas  
ADR-Shipping Name: ADHESIVOS que contengan un líquido inflamable  
IATA-Shipping Name: ADHESIVOS que contengan un líquido inflamable  
IMDG-Shipping Name: ADHESIVOS que contengan un líquido inflamable
- 14.3. Clase(s) de peligro para el transporte  
ADR-Class: 3  
ADR - Número de identificación del peligro: -  
IATA-Class: 3  
IATA-Label: 3  
IMDG-Class: 3  
IMDG-Clase: Clase 3 UN 1133
- 14.4. Grupo de embalaje  
ADR-Packing Group: III  
IATA-Packing group: III  
IMDG-Packing group: III
- 14.5. Peligros para el medio ambiente  
ADR-Contaminante ambiental: No  
IMDG-Marine pollutant: No  
IMDG-EmS: F-E,  
S-D
- 14.6. Precauciones particulares para los usuarios  
ADR-Subsidiary hazards: -  
ADR-S.P.: -  
ADR-Categoría de transporte (Código de restricción en túneles): 3 (E)  
IATA-Passenger Aircraft: 355  
IATA-Subsidiary hazards: -  
IATA-Cargo Aircraft: 366  
IATA-S.P.: A3  
IATA-ERG: 3L  
IMDG-Subsidiary hazards: -  
IMDG-Stowage and handling: Category A  
IMDG-Segregation: -
- 14.7. Transporte marítimo a granel con arreglo a los instrumentos de la OMI  
N.A.  
Limited Quantity: 5 L  
Exempted Quantity: E1

### SECCIÓN 15. Información reglamentaria

15.1. Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

- Dir. 98/24/CE (Riesgos relacionados con los agentes químicos durante el trabajo)
- Dir. 2000/39/CE (Valores límite de exposición profesional)
- Reglamento (CE) n. 1907/2006 (REACH)
- Reglamento (CE) n. 1272/2008 (CLP)
- Reglamento (CE) n. 790/2009 (ATP 1 CLP) y (UE) n. 758/2013
- Reglamento (UE) n. 2020/878
- Reglamento (UE) n. 286/2011 (ATP 2 CLP)

## Ficha de datos de seguridad MASTICE GUARNIZIONI ML 100



Reglamento (UE) n. 618/2012 (ATP 3 CLP)  
Reglamento (UE) n. 487/2013 (ATP 4 CLP)  
Reglamento (UE) n. 944/2013 (ATP 5 CLP)  
Reglamento (UE) n. 605/2014 (ATP 6 CLP)  
Reglamento (UE) n. 2015/1221 (ATP 7 CLP)  
Reglamento (UE) n. 2016/918 (ATP 8 CLP)  
Reglamento (UE) n. 2016/1179 (ATP 9 CLP)  
Reglamento (UE) n. 2017/776 (ATP 10 CLP)  
Reglamento (UE) n. 2018/669 (ATP 11 CLP)  
Reglamento (UE) n. 2018/1480 (ATP 13 CLP)  
Reglamento (UE) n. 2019/521 (ATP 12 CLP)

Restricciones relacionadas con el producto o las sustancias contenidas, de acuerdo con el anexo XVII del Reglamento (CE) 1907/2006 (REACH) y las modificaciones posteriores:

Restricciones relacionadas con el producto:

Restricción 3

Restricción 40

Restricciones relacionadas con las sustancias contenidas:

Ninguna restricción.

Compuestos orgánicos volátiles - COV = 36.54 %

Compuestos orgánicos volátiles - COV = 365.41 g/Kg

Compuestos orgánicos volátiles - COV = 354.45 g/l

Cuando sean aplicables, hágase referencia a las siguientes normativas:

Directiva 2012/18/EU (Seveso III)

Reglamento (CE) no 648/2004 (detergentes).

Dir. 2004/42/CE (directiva COV)

Disposiciones sobre la directiva EU 2012/18 (Seveso III):

Categoría Seveso III de acuerdo con el anexo 1, parte 1  
el producto pertenece a la categoría: P5c

### 15.2. Evaluación de la seguridad química

No se ha realizado ninguna evaluación de la seguridad química para la mezcla

Sustancias para las cuales se ha realizado una evaluación de la seguridad química

Ninguna

## SECCIÓN 16. Otra información

Texto de las frases utilizadas en el párrafo 3:

H225 Líquido y vapores muy inflamables.

H319 Provoca irritación ocular grave.

H317 Puede provocar una reacción alérgica en la piel.

H336 Puede provocar somnolencia o vértigo.

EUH066 La exposición repetida puede provocar sequedad o formación de grietas en la piel.

Clase y categoría de peligro	Código	Descripción
Flam. Liq. 2	2.6/2	Líquidos inflamables, Categoría 2
Eye Irrit. 2	3.3/2	Irritación ocular, Categoría 2
Skin Sens. 1	3.4.2/1	Sensibilización cutánea, Categoría 1
STOT SE 3	3.8/3	Toxicidad específica en determinados órganos (exposiciones única), Categoría 3

# Ficha de datos de seguridad

## MASTICE GUARNIZIONI ML 100



Parágrafos modificados respecto la revisión anterior

### SECCIÓN 9. Propiedades físicas y químicas

Clasificación y procedimiento utilizado para determinar la clasificación de las mezclas con arreglo al Reglamento (CE) n° 1272/2008 [CLP]:

Clasificación con arreglo al Reglamento (CE) n° 1272/2008	Procedimiento de clasificación
Flam. Liq. 2, H225	Conforme a datos obtenidos de los ensayos
Skin Sens. 1, H317	Método de cálculo

Este documento ha sido preparado por una persona competente que ha recibido un entrenamiento adecuado

Principales fuentes bibliográficas:

ECDIN: Environmental Chemicals Data and Information Network, Centro Común de Investigación, Comisión de las Comunidades Europeas

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS, 8ª ed., Van Nostrand Reinold

La información aquí detallada se basa en nuestros conocimientos hasta la fecha señalada arriba. Se refiere exclusivamente al producto indicado y no constituye garantía de cualidades particulares. El usuario debe asegurarse de la idoneidad y exactitud de dicha información en relación al uso específico que debe hacer del producto.

Esta ficha anula y sustituye toda edición precedente.

ADR:	Acuerdo europeo relativo al transporte internacional de mercancías peligrosas por carretera.
CAS:	Chemical Abstracts Service (de la American Chemical Society).
CLP:	Clasificación, etiquetado, embalaje.
DNEL:	Nivel sin efecto derivado.
EINECS:	Catálogo Europeo de Sustancias Químicas Comercializadas.
ETA:	Estimación de la toxicidad aguda
ETAmix:	Estimación de Toxicidad Aguda (Mezclas)
GefStoffVO:	Ordenanza sobre sustancias peligrosas, Alemania.
GHS:	Sistema Globalmente Armonizado de clasificación y etiquetado de productos químicos.
IATA:	Asociación de Transporte Aéreo Internacional.
IATA-DGR:	Normas aplicadas a las mercancías peligrosas por la "Asociación de Transporte Aéreo Internacional" (IATA).
ICAO:	Organización de la Aviación Civil Internacional.
ICAO-TI:	Instrucciones Técnicas de la "Organización de la Aviación Civil Internacional" (OACI).
IMDG:	Código marítimo internacional de mercancías peligrosas.
INCI:	Nomenclatura internacional de ingredientes cosméticos.
KSt:	Coefficiente de explosión.
LC50:	Concentración letal para el 50% de la población expuesta.
LD50:	Dosis letal para el 50% de la población expuesta.
NA:	No aplicable
PNEC:	Concentración prevista sin efecto.
RID:	Normas relativas al transporte internacional de mercancías peligrosas por ferrocarril.

**Ficha de datos de seguridad**  
**MASTICE GUARNIZIONI ML 100**



STEL:	Nivel de exposición de corta duración.
STOT:	Toxicidad específica en determinados órganos.
TLV:	Valor límite del umbral.
TWA:	Promedio ponderado en el tiempo
WGK:	Clase de peligro para las aguas (Alemania).

# Exposure Scenario, 23/07/2019

Substance identity	
Chemical name	Etanolo
CAS No.	64-17-5
EINECS No.	200-578-6

## Table of contents

1. **ES 1** Consumer use; Anti-freeze and de-icing products (PC4)
2. **ES 2** Consumer use; Various products (PC39, PC28)
3. **ES 3** Use at industrial site
4. **ES 4** Use at industrial site
5. **ES 5** Widespread use by professional workers
6. **ES 6** Widespread use by professional workers
7. **ES 7** Consumer use; Fuels (PC13)
8. **ES 8** Consumer use; Various products (PC1, PC3, PC8, PC18, PC23)

## 1. ES 1 Consumer use; Anti-freeze and de-icing products (PC4)

### 1.1 TITLE SECTION

Exposure Scenario name	Car care and maintenance products - De-icing and anti-icing applications
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Anti-freeze and de-icing products (PC4)

### Environment Contributing Scenario

CS1 Covered by	ERC8d
----------------	-------

### Consumer Contributing Scenario

CS2 Car Care - De-icing and anti-icing applications	PC4 - PC4_1
CS3 Car Care - De-icing and anti-icing applications	PC4 - PC4_2
CS4 Car Care - De-icing and anti-icing applications	PC4 - PC4_3

## 1.2 Conditions of use affecting exposure

### 1.2. CS1: Environment Contributing Scenario: Covered by (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
----------------------------------	--

#### *Product (article) characteristics*

**Physical form of product:**

Liquid

**Vapour pressure:**

5726 Pa

#### *Conditions and measures related to treatment of waste (including article waste)*

**Waste treatment**

No specific measures identified.

#### *Other conditions affecting environmental exposure*

**Local marine water dilution factor:** 100

**Local freshwater dilution factor:** 10

### 1.2. CS2: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Product Categories	Anti-freeze and de-icing products (PC4)
Product (Sub-)Categories	Washing car window (PC4_1)

#### *Product (article) characteristics*

**Concentration of substance in product:**

Covers percentage substance in the product up to 1 %.

#### *Amount used, frequency and duration of use/exposure*

**Amounts used:**

Amount per use 0.5 g

**Duration:**

Covers use up to 0.017 h/event

**Frequency:**

Covers use up to 1 uses per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in a one car garage (>34 m<sup>3</sup>) under typical ventilation.

**Temperature:** Covers use at ambient temperatures.

## 1.2. CS3: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

<b>Product Categories</b>	Anti-freeze and de-icing products (PC4)
---------------------------	---

<b>Product (Sub-)Categories</b>	Pouring into radiator (PC4_2)
---------------------------------	-------------------------------

### *Product (article) characteristics*

#### **Concentration of substance in product:**

Covers concentrations up to 10 %

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 2000 g

#### **Duration:**

Covers use up to 0.17 h/event

#### **Frequency:**

Covers use up to 1 uses per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in a one car garage (>34 m<sup>3</sup>) under typical ventilation.

**Temperature:** Covers use at ambient temperatures.

#### **Additional conditions human health**

Covers skin contact area up to 482 cm<sup>2</sup>

## 1.2. CS4: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

<b>Product Categories</b>	Anti-freeze and de-icing products (PC4)
---------------------------	---

<b>Product (Sub-)Categories</b>	Lock de-icer (PC4_3)
---------------------------------	----------------------

### *Product (article) characteristics*

#### **Concentration of substance in product:**

Covers concentrations up to 50 %

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 4 g

#### **Duration:**

Covers use up to 0.25 h/event

#### **Frequency:**

Covers use up to 1 uses per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in a one car garage (>34 m<sup>3</sup>) under typical ventilation.

**Temperature:** Covers use at ambient temperatures.

#### **Additional conditions human health**

Covers skin contact area up to 214 cm<sup>2</sup>

## 1.3 Exposure estimation and reference to its source

### 1.3. CS1: Environment Contributing Scenario: Covered by (ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00443 mg/L	N/A	0.00461
freshwater sediment	0.0172 mg/kg bw/day	N/A	0.00467
marine water	0.000508 mg/L	N/A	0.000643
marine sediment	0.00194 mg/kg bw/day	N/A	0.00064
soil	0.00123 mg/kg bw/day	N/A	0.00724

### 1.2. CS2: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.000102 mg/m <sup>3</sup>	N/A	8.94E-07
inhalative, local, short-term	0.000102 mg/m <sup>3</sup>	N/A	8.94E-07
dermal, systemic, long-term	0 mg/kg bw/day	N/A	N/A
combined routes, systemic, long-term	N/A	N/A	8.94E-07

### 1.2. CS3: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	1.84 mg/m <sup>3</sup>	N/A	0.0161
inhalative, local, short-term	1.84 mg/m <sup>3</sup>	N/A	0.0161
dermal, systemic, long-term	5.62 mg/kg bw/day	N/A	0.0272
combined routes, systemic, long-term	N/A	N/A	0.0434

### 1.2. CS4: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.51 mg/m <sup>3</sup>	N/A	0.00447
inhalative, local, short-term	0.51 mg/m <sup>3</sup>	N/A	0.0447
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.0679
combined routes, systemic, long-term	N/A	N/A	0.0724

## 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

**Guidance to check compliance with the exposure scenario:**



Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 2. ES 2 Consumer use; Various products (PC39, PC28)

### 2.1 TITLE SECTION

Exposure Scenario name	Cosumer other uses
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Cosmetics, personal care products (PC39) - Perfumes, fragrances (PC28)

#### Environment Contributing Scenario

CS1 Covered by	ERC8a
----------------	-------

#### Consumer Contributing Scenario

CS2 Consumer	PC39 - PC28
--------------	-------------

## 2.2 Conditions of use affecting exposure

### 2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)
----------------------------------	---

#### *Product (article) characteristics*

##### Physical form of product:

Liquid

##### Vapour pressure:

5726 Pa

#### *Conditions and measures related to treatment of waste (including article waste)*

##### Waste treatment

No specific measures identified.

### 2.2. CS2: Consumer Contributing Scenario: Consumer (PC39, PC28)

Product Categories	Cosmetics, personal care products - Perfumes, fragrances (PC39, PC28)
--------------------	---

## 2.3 Exposure estimation and reference to its source

### 2.3. CS1: Environment Contributing Scenario: Covered by (ERC8a)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00236 mg/L	N/A	0.00246
freshwater sediment	0.00904 mg/kg bw/day	N/A	0.00246
marine water	0.000301 mg/L	N/A	0.000381
marine sediment	0.00115 mg/kg bw/day	N/A	0.00038
soil	0.00115 mg/kg bw/day	N/A	0.00676

## 2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### **Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### 3. ES 3 Use at industrial site

#### 3.1 TITLE SECTION

Exposure Scenario name	Solvent
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

#### Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

#### Worker Contributing Scenario

CS2 Industrial	PROC1
CS3 Industrial	PROC2
CS4 Industrial	PROC3
CS5 Industrial	PROC4
CS6 Industrial	PROC5
CS7 Industrial	PROC7
CS8 Industrial	PROC8a
CS9 Industrial	PROC8b
CS10 Industrial	PROC10
CS11 Industrial	PROC13
CS12 Industrial	PROC15

#### 3.2 Conditions of use affecting exposure

##### 3.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

##### *Product (article) characteristics*

**Vapour pressure:**  
< 10 kPa

##### *Amount used, frequency and duration of use (or from service life)*

**Amounts used:**

Annual site tonnage 3000 t(tonnes)/year

**Maximum allowable site tonnage (MSafe):** 124000 kg/day

**Release type:** Continuous release

**Emission days:** 300 days per year

##### *Technical and organisational conditions and measures*

**Control measures to prevent releases**

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 90 %
Prevent discharge of undissolved substance to or recover from onsite wastewater.	Water - minimum efficiency of: 87 %

### *Conditions and measures related to sewage treatment plant*

#### **STP type:**

Municipal Sewage Treatment Plant

**STP effluent (m<sup>3</sup>/day):** 2000

### *Conditions and measures related to treatment of waste (including article waste)*

#### **Waste treatment**

Incineration, disposal or recycling at specific offsite provider Contain and dispose of waste according to local regulations.	Waste - minimum efficiency of: 99.98 %
--	--

### *Other conditions affecting environmental exposure*

**Local marine water dilution factor:** 100

**Local freshwater dilution factor:** 10

**Receiving surface water flow:** 2000 m<sup>3</sup>/h

*Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.*

#### **Additional Good Practice Advice:**

Contain leaks or spills within cabinets with removable trays.

### **3.2. CS2: Worker Contributing Scenario: Industrial (PROC1)**

<b>Process Categories</b>	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
---------------------------	--

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid

#### **Vapour pressure:**

< 10 kPa

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Technical and organisational conditions and measures*

#### **Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Use suitable eye protection.

### *Other conditions affecting worker exposure*

**Temperature:** Covers use at ambient temperatures.

### **3.2. CS3: Worker Contributing Scenario: Industrial (PROC2)**

<b>Process Categories</b>	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
---------------------------	--

<b>Product (article) characteristics</b>	
<b>Physical form of product:</b> Liquid	
<b>Vapour pressure:</b> < 10 kPa	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<b>Amount used, frequency and duration of use/exposure</b>	
<b>Duration:</b> Covers daily exposures up to 8 hours	
<b>Technical and organisational conditions and measures</b>	
<b>Technical and organisational measures</b> Use in contained systems Store substance within a closed system.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
<b>Personal protection</b> Use suitable eye protection.	
<b>Other conditions affecting worker exposure</b>	
<b>Temperature:</b> Covers use at ambient temperatures.	
<b>3.2. CS4: Worker Contributing Scenario: Industrial (PROC3)</b>	
<b>Process Categories</b>	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
<b>Product (article) characteristics</b>	
<b>Physical form of product:</b> Liquid	
<b>Vapour pressure:</b> < 10 kPa	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<b>Amount used, frequency and duration of use/exposure</b>	
<b>Duration:</b> Covers daily exposures up to 8 hours	
<b>Technical and organisational conditions and measures</b>	
<b>Technical and organisational measures</b> Use in contained systems Store substance within a closed system.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
<b>Personal protection</b> Use suitable eye protection.	
<b>Other conditions affecting worker exposure</b>	
<b>Temperature:</b> Covers use at ambient temperatures.	
<b>3.2. CS5: Worker Contributing Scenario: Industrial (PROC4)</b>	
<b>Process Categories</b>	Chemical production where opportunity for exposure arises (PROC4)
<b>Product (article) characteristics</b>	

<b>Physical form of product:</b> Liquid	
<b>Vapour pressure:</b> < 10 kPa	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
<b>Duration:</b> Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
<b>Technical and organisational measures</b> Use in contained systems Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
<b>Personal protection</b> Use suitable eye protection.	
<i>Other conditions affecting worker exposure</i>	
<b>Temperature:</b> Covers use at ambient temperatures.	
<b>3.2. CS6: Worker Contributing Scenario: Industrial (PROC5)</b>	
<b>Process Categories</b>	Mixing or blending in batch processes (PROC5)
<i>Product (article) characteristics</i>	
<b>Physical form of product:</b> Liquid	
<b>Vapour pressure:</b> < 10 kPa	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
<b>Duration:</b> Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
<b>Technical and organisational measures</b> Use in contained systems Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
<b>Personal protection</b> Use suitable eye protection.	
<i>Other conditions affecting worker exposure</i>	
<b>Temperature:</b> Covers use at ambient temperatures.	
<b>3.2. CS7: Worker Contributing Scenario: Industrial (PROC7)</b>	
<b>Process Categories</b>	Industrial spraying (PROC7)
<i>Product (article) characteristics</i>	
<b>Physical form of product:</b> Liquid	

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

***Amount used, frequency and duration of use/exposure*****Duration:**

Covers daily exposures up to 8 hours

***Technical and organisational conditions and measures*****Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Use suitable eye protection.

***Other conditions affecting worker exposure***

**Temperature:** Covers use at ambient temperatures.

**3.2. CS8: Worker Contributing Scenario: Industrial (PROC8a)**

<b>Process Categories</b>	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

***Product (article) characteristics*****Physical form of product:**

Liquid

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

***Amount used, frequency and duration of use/exposure*****Duration:**

Covers daily exposures up to 8 hours

***Technical and organisational conditions and measures*****Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Use suitable eye protection.

***Other conditions affecting worker exposure***

**Temperature:** Covers use at ambient temperatures.

**3.2. CS9: Worker Contributing Scenario: Industrial (PROC8b)**

<b>Process Categories</b>	Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)
---------------------------	--

***Product (article) characteristics*****Physical form of product:**

Liquid



**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

*Other conditions affecting worker exposure*

**Temperature:** Covers use at ambient temperatures.

**3.2. CS10: Worker Contributing Scenario: Industrial (PROC10)****Process Categories**

Roller application or brushing (PROC10)

*Product (article) characteristics***Physical form of product:**

Liquid

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

*Other conditions affecting worker exposure*

**Temperature:** Covers use at ambient temperatures.

**3.2. CS11: Worker Contributing Scenario: Industrial (PROC13)****Process Categories**

Treatment of articles by dipping and pouring (PROC13)

*Product (article) characteristics***Physical form of product:**

Liquid

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

**Amount used, frequency and duration of use/exposure****Duration:**

Covers daily exposures up to 8 hours

**Technical and organisational conditions and measures****Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Use suitable eye protection.

**Other conditions affecting worker exposure****Temperature:** Covers use at ambient temperatures.**3.2. CS12: Worker Contributing Scenario: Industrial (PROC15)****Process Categories**

Use as laboratory reagent (PROC15)

**Product (article) characteristics****Physical form of product:**

Liquid

**Vapour pressure:**

&lt; 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

**Amount used, frequency and duration of use/exposure****Duration:**

Covers daily exposures up to 8 hours

**Technical and organisational conditions and measures****Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Use suitable eye protection.

**Other conditions affecting worker exposure****Temperature:** Covers use at ambient temperatures.**3.3 Exposure estimation and reference to its source****3.3. CS1: Environment Contributing Scenario: Covered by (ERC4)**

Release route	Release rate	Release estimation method
Air	0.98 %	N/A
Water	0.01 %	N/A
soil	0 %	N/A

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	6.32 mg/L	N/A	0.0109
freshwater	0.577 mg/L	N/A	0.601
freshwater sediment	2.21 mg/kg bw/day	N/A	0.601
marine water	0.0635 mg/L	N/A	0.0804
marine sediment	0.0635 mg/kg bw/day	N/A	0.0805
soil	0.0525 mg/kg bw/day	N/A	0.309

### 3.3. CS2: Worker Contributing Scenario: Industrial (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m <sup>3</sup>	N/A	< 0.01
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.01
combined routes, systemic, long-term	N/A	N/A	< 0.01

### 3.3. CS3: Worker Contributing Scenario: Industrial (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m <sup>3</sup>	N/A	0.01
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0141

### 3.3. CS4: Worker Contributing Scenario: Industrial (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m <sup>3</sup>	N/A	0.02
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.0222

### 3.3. CS5: Worker Contributing Scenario: Industrial (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, systemic, long-term	38 mg/m <sup>3</sup>	N/A	0.04
dermal, systemic, long-term	6.9 mg/kg bw/day	N/A	0.02
combined routes, systemic, long-term	N/A	N/A	0.0603

### 3.3. CS6: Worker Contributing Scenario: Industrial (PROC5)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.101
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

### 3.3. CS7: Worker Contributing Scenario: Industrial (PROC7)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	140 mg/m <sup>3</sup>	N/A	0.151
dermal, systemic, long-term	43 mg/kg bw/day	N/A	0.125
combined routes, systemic, long-term	N/A	N/A	0.276

### 3.3. CS8: Worker Contributing Scenario: Industrial (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.101
dermal, systemic, long-term	96 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

### 3.3. CS9: Worker Contributing Scenario: Industrial (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m <sup>3</sup>	N/A	0.05
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.0904

### 3.3. CS10: Worker Contributing Scenario: Industrial (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.101
dermal, systemic, long-term	27 mg/kg bw/day	N/A	0.08
combined routes, systemic, long-term	N/A	N/A	0.181

### 3.3. CS11: Worker Contributing Scenario: Industrial (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.101
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

### 3.3. CS12: Worker Contributing Scenario: Industrial (PROC15)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m <sup>3</sup>	N/A	0.02
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.01
combined routes, systemic, long-term	N/A	N/A	0.0212

## 3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 4. ES 4 Use at industrial site

### 4.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

### Environment Contributing Scenario

CS1 Covered by	ERC7
----------------	------

### Worker Contributing Scenario

CS2 Industrial	PROC1
CS3 Industrial	PROC2
CS4 Industrial	PROC3
CS5 Industrial	PROC8a
CS6 Industrial	PROC8b
CS7 Industrial	PROC15
CS8 Industrial	PROC16

## 4.2 Conditions of use affecting exposure

### 4.2. CS1: Environment Contributing Scenario: Covered by (ERC7)

Environmental release categories	Use of functional fluid at industrial site (ERC7)
----------------------------------	---

### *Product (article) characteristics*

#### Physical form of product:

Liquid

#### Vapour pressure:

< 10 kPa

### *Amount used, frequency and duration of use (or from service life)*

#### Amounts used:

Annual site tonnage 20000 t(tonnes)/year

**Maximum allowable site tonnage (MSafe):** 14500000 kg/day

**Release type:** Continuous release

**Emission days:** 300 days per year

### *Technical and organisational conditions and measures*

#### Control measures to prevent releases

Provide onsite wastewater removal efficiency of <sup>3</sup> (%):

Water - minimum efficiency of: 87 %

### *Conditions and measures related to sewage treatment plant*

**STP type:**

Municipal Sewage Treatment Plant  
Water - minimum efficiency of: = 87 %

**STP effluent (m<sup>3</sup>/day):** 2000

### *Conditions and measures related to treatment of waste (including article waste)*

**Waste treatment**

Product residual disposal complies with applicable regulations.

### *Other conditions affecting environmental exposure*

**Local marine water dilution factor:** 100

**Local freshwater dilution factor:** 10

**Receiving surface water flow:** 2000 m<sup>3</sup>/day

### *Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.*

**Additional Good Practice Advice:**

Adequate closed storage facilities (e.g., bulk storage tanks, intermediate bulk containers, drums) are required.

### **4.2. CS2: Worker Contributing Scenario: Industrial (PROC1)**

**Process Categories**

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

### *Product (article) characteristics*

**Physical form of product:**

Liquid

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

**Duration:**

Covers daily exposures up to 8 hours

### *Technical and organisational conditions and measures*

**Technical and organisational measures**

Handle substance within a closed system.  
Store substance within a closed system.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

### **4.2. CS3: Worker Contributing Scenario: Industrial (PROC2)**

**Process Categories**

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

### *Product (article) characteristics*

**Physical form of product:**

Liquid

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

<b>Duration:</b> Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
<b>Technical and organisational measures</b> Handle substance within a closed system. Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
<b>Personal protection</b> Use suitable eye protection.	
<b>4.2. CS4: Worker Contributing Scenario: Industrial (PROC3)</b>	
<b>Process Categories</b>	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
<i>Product (article) characteristics</i>	
<b>Physical form of product:</b> Liquid	
<b>Vapour pressure:</b> < 10 kPa	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
<b>Duration:</b> Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
<b>Technical and organisational measures</b> Handle substance within a closed system. Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
<b>Personal protection</b> Use suitable eye protection.	
<b>4.2. CS5: Worker Contributing Scenario: Industrial (PROC8a)</b>	
<b>Process Categories</b>	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
<i>Product (article) characteristics</i>	
<b>Physical form of product:</b> Liquid	
<b>Vapour pressure:</b> < 10 kPa	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
<b>Duration:</b> Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
<b>Technical and organisational measures</b> Handle substance within a closed system. Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	



**Personal protection**

Use suitable eye protection.

**4.2. CS6: Worker Contributing Scenario: Industrial (PROC8b)****Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

*Product (article) characteristics***Physical form of product:**

Liquid

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

**4.2. CS7: Worker Contributing Scenario: Industrial (PROC15)****Process Categories**

Use as laboratory reagent (PROC15)

*Product (article) characteristics***Physical form of product:**

Liquid

**Vapour pressure:**

< 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

**4.2. CS8: Worker Contributing Scenario: Industrial (PROC16)****Process Categories**

Use of fuels (PROC16)

*Product (article) characteristics***Physical form of product:**

Liquid

**Vapour pressure:**

&lt; 10 kPa

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

**Amount used, frequency and duration of use/exposure****Duration:**

Covers daily exposures up to 8 hours

**Technical and organisational conditions and measures****Technical and organisational measures**

Handle substance within a closed system.  
Store substance within a closed system.

**Conditions and measures related to personal protection, hygiene and health evaluation****Personal protection**

Use suitable eye protection.

**4.3 Exposure estimation and reference to its source****4.3. CS1: Environment Contributing Scenario: Covered by (ERC7)**

Release route	Release rate	Release estimation method
Air	0.0025 %	N/A
Water	1E-05 %	N/A
soil	0 %	N/A

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	0.0421 mg/L	N/A	7.26E-05
freshwater	0.00657 mg/L	N/A	0.00684
freshwater sediment	0.00685 mg/kg bw/day	N/A	0.00685
marine water	0.00363 mg/L	N/A	0.00459
marine sediment	0.0139 mg/kg bw/day	N/A	0.00459
soil	0.00694 mg/kg bw/day	N/A	0.0408

**4.3. CS2: Worker Contributing Scenario: Industrial (PROC1)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m <sup>3</sup>	N/A	< 0.001
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	< 0.001

#### 4.3. CS3: Worker Contributing Scenario: Industrial (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m <sup>3</sup>	N/A	0.01
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0222

#### 4.3. CS4: Worker Contributing Scenario: Industrial (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m <sup>3</sup>	N/A	0.02
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.222

#### 4.3. CS5: Worker Contributing Scenario: Industrial (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.101
dermal, systemic, long-term	14 mg/m <sup>3</sup>	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

#### 4.3. CS6: Worker Contributing Scenario: Industrial (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m <sup>3</sup>	N/A	0.05
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.0904

#### 4.3. CS7: Worker Contributing Scenario: Industrial (PROC15)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m <sup>3</sup>	N/A	0.02
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.001

combined routes, systemic, long-term	N/A	N/A	0.0112
--------------------------------------	-----	-----	--------

### 4.3. CS8: Worker Contributing Scenario: Industrial (PROC16)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m <sup>3</sup>	N/A	0.01
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	0.0111

### 4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 5. ES 5 Widespread use by professional workers

### 5.1 TITLE SECTION

Exposure Scenario name	Solvent
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

#### Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

#### Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC3
CS5 General use from professional operators	PROC4
CS6 General use from professional operators	PROC5 - PROC8a
CS7 General use from professional operators	PROC8b
CS8 General use from professional operators	PROC10
CS9 General use from professional operators	PROC11
CS10 General use from professional operators	PROC11
CS11 General use from professional operators	PROC13
CS12 General use from professional operators	PROC19

### 5.2 Conditions of use affecting exposure

#### 5.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

#### *Product (article) characteristics*

##### Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### *Amount used, frequency and duration of use (or from service life)*

##### Amounts used:

Annual site tonnage 0.1 t(tonnes)/year

**Maximum allowable site tonnage (MSafe):** 715 kg/day

**Release type:** Continuous release

**Emission days:** 365 days per year

#### *Technical and organisational conditions and measures*

## Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 90 %
Prevent discharge of undissolved substance to or recover from onsite wastewater.	

## Conditions and measures related to treatment of waste (including article waste)

### Waste treatment

Hazardous waste incineration	Waste - minimum efficiency of: 99.98 %
------------------------------	--

## 5.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

### Product (article) characteristics

#### Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

### Amount used, frequency and duration of use/exposure

#### Duration:

Covers daily exposures up to 8 hours

### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Use suitable eye protection.

## 5.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Process Categories	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
--------------------	--

### Product (article) characteristics

#### Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

### Amount used, frequency and duration of use/exposure

#### Duration:

Covers daily exposures up to 8 hours

### Conditions and measures related to personal protection, hygiene and health evaluation

#### Personal protection

Use suitable eye protection.

## 5.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Process Categories	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
--------------------	--

### Product (article) characteristics

#### Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Use suitable eye protection.

## **5.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)**

#### **Process Categories**

Chemical production where opportunity for exposure arises (PROC4)

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Use suitable eye protection.

## **5.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC5, PROC8a)**

#### **Process Categories**

Mixing or blending in batch processes - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC5, PROC8a)

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Use suitable eye protection.

## **5.2. CS7: Worker Contributing Scenario: General use from professional operators (PROC8b)**

#### **Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

**5.2. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)****Process Categories**

Roller application or brushing (PROC10)

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

**5.2. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)****Process Categories**

Non industrial spraying (PROC11)

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

Wear suitable gloves tested to EN374.

*Other conditions affecting worker exposure*

Indoor use

**5.2. CS10: Worker Contributing Scenario: General use from professional operators (PROC11)****Process Categories**

Non industrial spraying (PROC11)

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours



### *Technical and organisational conditions and measures*

#### **Technical and organisational measures**

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Use suitable eye protection.

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

### *Other conditions affecting worker exposure*

Outdoor use

## **5.2. CS11: Worker Contributing Scenario: General use from professional operators (PROC13)**

#### **Process Categories**

Treatment of articles by dipping and pouring (PROC13)

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Use suitable eye protection.

Wear suitable gloves tested to EN374.

## **5.2. CS12: Worker Contributing Scenario: General use from professional operators (PROC19)**

#### **Process Categories**

Manual activities involving hand contact (PROC19)

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Conditions and measures related to personal protection, hygiene and health evaluation*

#### **Personal protection**

Use suitable eye protection.

Wear suitable gloves tested to EN374.

## **5.3 Exposure estimation and reference to its source**

### **5.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)**

Release route	Release rate	Release estimation method
Air	0.98 %	N/A
Water	0.01 %	N/A

soil	0.01 %	N/A
------	--------	-----

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	0.000173 mg/L	N/A	2.98E-07
freshwater	0.00238 mg/L	N/A	0.00248
freshwater sediment	0.00912 mg/kg bw/day	N/A	0.00248
marine sediment	0.000303 mg/L	N/A	0.000384
marine sediment	0.00116 mg/kg bw/day	N/A	0.000383
soil	0.00116 mg/kg bw/day	N/A	0.00682

### 5.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m <sup>3</sup>	N/A	< 0.001
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	< 0.001

### 5.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	38 mg/m <sup>3</sup>	N/A	0.04
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0443

### 5.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m <sup>3</sup>	N/A	0.05
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.0524

### 5.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.101
dermal, systemic, long-term	6.9 mg/kg bw/day	N/A	0.02
combined routes, systemic, long-term	N/A	N/A	0.121

### 5.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC5, PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m <sup>3</sup>	N/A	0.202
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.242

### 5.3. CS7: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.202
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

### 5.3. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m <sup>3</sup>	N/A	0.202
dermal, systemic, long-term	27 mg/kg bw/day	N/A	0.08
combined routes, systemic, long-term	N/A	N/A	0.282

### 5.3. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	290 mg/m <sup>3</sup>	N/A	0.303
dermal, systemic, long-term	21 mg/kg bw/day	N/A	0.062
combined routes, systemic, long-term	N/A	N/A	0.365

### 5.3. CS10: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	67 mg/m <sup>3</sup>	N/A	0.071
dermal, systemic, long-term	21 mg/kg bw/day	N/A	0.062
combined routes, systemic, long-term	N/A	N/A	0.133

### 5.3. CS11: Worker Contributing Scenario: General use from professional operators (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m <sup>3</sup>	N/A	0.202
dermal, systemic, long-term	2.7 mg/kg bw/day	N/A	0.008
combined routes, systemic, long-term	N/A	N/A	0.21

### 5.3. CS12: Worker Contributing Scenario: General use from professional operators (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m <sup>3</sup>	N/A	0.202
dermal, systemic, long-term	28 mg/kg bw/day	N/A	0.082
combined routes, systemic, long-term	N/A	N/A	0.284

## 5.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 6. ES 6 Widespread use by professional workers

### 6.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

#### Environment Contributing Scenario

CS1 Covered by	ERC9a - ERC9b
----------------	---------------

#### Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC3
CS5 General use from professional operators	PROC8a
CS6 General use from professional operators	PROC8b
CS7 General use from professional operators	PROC16

## 6.2 Conditions of use affecting exposure

### 6.2. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)

Environmental release categories	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)
----------------------------------	---

#### *Product (article) characteristics*

##### Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### *Amount used, frequency and duration of use (or from service life)*

##### Amounts used:

Annual site tonnage 1 t(tonnes)/year

**Maximum allowable site tonnage (MSafe):** 7190 kg/day

**Release type:** Continuous release

**Emission days:** 365 days per year

#### *Technical and organisational conditions and measures*

##### Control measures to prevent releases

Prevent discharge of undissolved substance to or recover from onsite wastewater.

#### *Conditions and measures related to treatment of waste (including article waste)*

##### Waste treatment

Product residual disposal complies with applicable regulations.

### 6.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

### *Product (article) characteristics*

**Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Technical and organisational conditions and measures*

**Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

## **6.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)**

<b>Process Categories</b>	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
---------------------------	--

### *Product (article) characteristics*

**Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Technical and organisational conditions and measures*

**Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

## **6.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)**

<b>Process Categories</b>	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
---------------------------	--

### *Product (article) characteristics*

**Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Technical and organisational conditions and measures*

**Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

## **6.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC8a)**

<b>Process Categories</b>	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

### *Product (article) characteristics*

**Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

***Technical and organisational conditions and measures*****Technical and organisational measures**

Handle substance within a closed system.  
Store substance within a closed system.

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Use suitable eye protection.

**6.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)****Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

***Product (article) characteristics*****Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

***Technical and organisational conditions and measures*****Technical and organisational measures**

Handle substance within a closed system.  
Store substance within a closed system.

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Use suitable eye protection.

**6.2. CS7: Worker Contributing Scenario: General use from professional operators (PROC16)****Process Categories**

Use of fuels (PROC16)

***Product (article) characteristics*****Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

***Technical and organisational conditions and measures*****Technical and organisational measures**

Handle substance within a closed system.  
Store substance within a closed system.

***Conditions and measures related to personal protection, hygiene and health evaluation*****Personal protection**

Use suitable eye protection.

**6.3 Exposure estimation and reference to its source****6.3. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)**

Release route	Release rate	Release estimation method
Air	0.01 %	N/A
Water	1E-05 %	N/A

soil	0 %	N/A
------	-----	-----

### 6.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m <sup>3</sup>	N/A	< 0.001
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	< 0.001

### 6.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	38 mg/m <sup>3</sup>	N/A	0.04
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0443

### 6.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m <sup>3</sup>	N/A	0.05
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.0524

### 6.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m <sup>3</sup>	N/A	0.202
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.242

### 6.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m <sup>3</sup>	N/A	0.101
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04



combined routes, systemic, long-term	N/A	N/A	0.141
--------------------------------------	-----	-----	-------

### 6.3. CS7: Worker Contributing Scenario: General use from professional operators (PROC16)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m <sup>3</sup>	N/A	0.02
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	0.0212

### 6.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 7. ES 7 Consumer use; Fuels (PC13)

### 7.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Fuels (PC13)

#### Environment Contributing Scenario

CS1 Covered by	ERC9b
----------------	-------

#### Consumer Contributing Scenario

CS2 Consumer	PC13 - PC13_1
CS3 Consumer	PC13 - PC13_2
CS4 Consumer	PC13 - PC13_3
CS5 Consumer	PC13 - PC13_4

## 7.2 Conditions of use affecting exposure

### 7.2. CS1: Environment Contributing Scenario: Covered by (ERC9b)

Environmental release categories	Widespread use of functional fluid (outdoor) (ERC9b)
----------------------------------	--

#### *Product (article) characteristics*

##### Physical form of product:

Liquid

##### Vapour pressure:

5726 Pa

#### *Conditions and measures related to treatment of waste (including article waste)*

##### Waste treatment

Product residual disposal complies with applicable regulations.

#### *Other conditions affecting environmental exposure*

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

### 7.2. CS2: Consumer Contributing Scenario: Consumer (PC13)

Product Categories	Fuels (PC13)
Product (Sub-)Categories	Liquid: Automotive Refuelling (PC13_1)

#### *Product (article) characteristics*

##### Concentration of substance in product:

Covers concentrations up to 85 %

#### *Amount used, frequency and duration of use/exposure*

##### Amounts used:

Amount per use 37500 g

**Duration:**

Exposure duration 0.05 h/event

**Frequency:**

Covers use up to 51 times per year

*Other conditions affecting consumers exposure*

Outdoor use

**Additional conditions human health**Covers skin contact area up to 210 cm<sup>2</sup>**7.2. CS3: Consumer Contributing Scenario: Consumer (PC13)****Product Categories**

Fuels (PC13)

**Product (Sub-)Categories**

Liquid Scooter Refuelling (PC13\_2)

*Product (article) characteristics***Concentration of substance in product:**

Covers concentrations up to 85 %

*Amount used, frequency and duration of use/exposure***Amounts used:**

Amount per use 37500 g

**Duration:**

Exposure duration 0.033 h/event

**Frequency:**

Covers use up to 51 times per year

*Other conditions affecting consumers exposure*

Outdoor use

**Additional conditions human health**Covers skin contact area up to 210 cm<sup>2</sup>**7.2. CS4: Consumer Contributing Scenario: Consumer (PC13)****Product Categories**

Fuels (PC13)

**Product (Sub-)Categories**

Liquid, Garden equipment - Use (PC13\_3)

*Product (article) characteristics***Concentration of substance in product:**

Covers concentrations up to 15 %

*Amount used, frequency and duration of use/exposure***Amounts used:**

Amount per use 750 g

**Duration:**

Exposure duration 2 h/event

**Frequency:**

Covers use up to 25 times per year

*Other conditions affecting consumers exposure*

Outdoor use

**Additional conditions human health**Covers skin contact area up to 210 cm<sup>2</sup>**7.2. CS5: Consumer Contributing Scenario: Consumer (PC13)****Product Categories**

Fuels (PC13)

<b>Product (Sub-)Categories</b>	Liquid: Garden equipment - Refuelling (PC13_4)
<b>Product (article) characteristics</b>	
<b>Concentration of substance in product:</b> Covers concentrations up to 85 %	
<b>Amount used, frequency and duration of use/exposure</b>	
<b>Amounts used:</b> Amount per use 750 g	
<b>Duration:</b> Exposure duration 0.05 h/event	
<b>Frequency:</b> Covers use up to 25 times per year	
<b>Other conditions affecting consumers exposure</b>	
<b>Room size:</b> Covers use in a one car garage (>34 m <sup>3</sup> ) under typical ventilation.	
<b>Temperature:</b> Covers use at ambient temperatures.	
<b>Additional conditions human health</b> Covers skin contact area up to 210 cm <sup>2</sup>	

## 7.3 Exposure estimation and reference to its source

### 7.3. CS1: Environment Contributing Scenario: Covered by (ERC9b)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.0236 mg/L	N/A	0.00246
freshwater sediment	0.00905 mg/kg bw/day	N/A	0.00246
marine water	0.0003 mg/L	N/A	0.00038
marine sediment	0.0015 mg/kg bw/day	N/A	0.00038
marine sediment	0.0015 mg/kg bw/day	N/A	0.00676

### 7.2. CS2: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.187 mg/m <sup>3</sup>	N/A	0.00164
inhalative, local, short-term	1.3 mg/m <sup>3</sup>	N/A	0.0114
dermal, systemic, long-term	0.117 mg/kg bw/day	N/A	8.1E-05
combined routes, systemic, long-term	N/A	N/A	0.0114

### 7.2. CS3: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0612 mg/m <sup>3</sup>	N/A	0.000544

inhalative, local, short-term	0.434 mg/m <sup>3</sup>	N/A	0.0038
dermal, systemic, long-term	0.117 mg/kg bw/day	N/A	8.1E-05
combined routes, systemic, long-term	N/A	N/A	0.00388

## 7.2. CS4: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0764 mg/m <sup>3</sup>	N/A	0.00067
inhalative, local, short-term	1.09 mg/m <sup>3</sup>	N/A	0.00956
dermal, systemic, long-term	4.13 mg/kg bw/day	N/A	0.0014
combined routes, systemic, long-term	N/A	N/A	0.0109

## 7.2. CS5: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.079 mg/m <sup>3</sup>	N/A	0.000692
inhalative, local, short-term	1.12 mg/m <sup>3</sup>	N/A	0.00982
dermal, systemic, long-term	0.117 mg/kg bw/day	N/A	3.98E-05
combined routes, systemic, long-term	N/A	N/A	0.00986

## 7.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 8. ES 8 Consumer use; Various products (PC1, PC3, PC8, PC18, PC23)

### 8.1 TITLE SECTION

Exposure Scenario name	Cosumer other uses
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Adhesives, sealants (PC1) - Air care products (PC3) - Biocidal products (PC8) - Ink and toners (PC18) - Leather treatment products (PC23) - Lubricants, greases, release products (PC24) - Plant protection products (PC27) - Polishes and wax blends (PC31) - Textile dyes and impregnating products (PC34)

### Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

### Consumer Contributing Scenario

CS2 Consumer	PC1 - PC1_1
CS3 Consumer	PC1 - PC1_3
CS4 Consumer	PC1 - PC1_4
CS5 Consumer	PC3 - PC3_1
CS6 Consumer	PC3 - PC3_2
CS7 Consumer	PC8 - PC35_1, PC8_1
CS8 Consumer	PC8 - PC8_2, PC35_2
CS9 Consumer	PC8 - PC8_3, PC35_3
CS10 Consumer	PC18
CS11 Consumer	PC23 - PC23_1, PC31_1
CS12 Consumer	PC23 - PC23_2, PC31_2
CS13 Consumer	PC24 - PC16_1, PC17_1, PC24_1, 36
CS14 Consumer	PC27
CS15 Consumer	PC31 - PC23_1, PC31_1
CS16 Consumer	PC31 - PC23_2, PC31_2

## 8.2 Conditions of use affecting exposure

### 8.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

### *Product (article) characteristics*

#### Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

### *Conditions and measures related to treatment of waste (including article waste)*

## Waste treatment

Hazardous waste incineration

Waste - minimum efficiency of: 99.8 %

### *Other conditions affecting environmental exposure*

**Local marine water dilution factor:** 100

**Local freshwater dilution factor:** 10

**Receiving surface water flow:** 2000 m<sup>3</sup>/day

### 8.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

**Product Categories** Adhesives, sealants (PC1)

**Product (Sub-)Categories** Glues, hobby use (PC1\_1)

### *Product (article) characteristics*

**Concentration of substance in product:**

Covers concentrations up to 70 %

### *Amount used, frequency and duration of use/exposure*

**Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 4 h/event

**Frequency:**

Covers exposure up to 1 events per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Additional conditions human health**

Covers skin contact area up to 35 cm<sup>2</sup>

### 8.2. CS3: Consumer Contributing Scenario: Consumer (PC1)

**Product Categories** Adhesives, sealants (PC1)

**Product (Sub-)Categories** Glue from spray (PC1\_3)

### *Product (article) characteristics*

**Concentration of substance in product:**

Covers concentrations up to 30 %

### *Amount used, frequency and duration of use/exposure*

**Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 4 h/event

**Frequency:**

Covers exposure up to 6 times per year

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Additional conditions human health**

Covers skin contact area up to 35 cm<sup>2</sup>

### 8.2. CS4: Consumer Contributing Scenario: Consumer (PC1)

**Product Categories** Adhesives, sealants (PC1)

<b>Product (Sub-)Categories</b>	Sealants (PC1_4)
<i>Product (article) characteristics</i>	
<b>Concentration of substance in product:</b> Covers concentrations up to 30 %	
<i>Amount used, frequency and duration of use/exposure</i>	
<b>Amounts used:</b> Amount per use 50 g	
<b>Duration:</b> Exposure duration 1 h/event	
<b>Frequency:</b> Covers exposure up to 1 events per day	
<i>Other conditions affecting consumers exposure</i>	
<b>Room size:</b> Covers use in room size of 20 m <sup>3</sup>	
<b>Additional conditions human health</b> Covers skin contact area up to 35 cm <sup>2</sup>	
<b>8.2. CS5: Consumer Contributing Scenario: Consumer (PC3)</b>	
<b>Product Categories</b>	Air care products (PC3)
<b>Product (Sub-)Categories</b>	Air care, instant action (aerosol sprays) (PC3_1)
<i>Product (article) characteristics</i>	
<b>Concentration of substance in product:</b> Covers concentrations up to 40 %	
<i>Amount used, frequency and duration of use/exposure</i>	
<b>Amounts used:</b> Amount per use 50 g	
<b>Duration:</b> Exposure duration 0.3 h/event	
<b>Frequency:</b> Covers exposure up to 4 events per day	
<i>Other conditions affecting consumers exposure</i>	
<b>Room size:</b> Covers use in room size of 20 m <sup>3</sup>	
<b>Additional conditions human health</b> Covers skin contact area up to 35 cm <sup>2</sup>	
<b>8.2. CS6: Consumer Contributing Scenario: Consumer (PC3)</b>	
<b>Product Categories</b>	Air care products (PC3)
<b>Product (Sub-)Categories</b>	Air care, continuous action (solid and liquid) (PC3_2)
<i>Product (article) characteristics</i>	
<b>Concentration of substance in product:</b> Covers concentrations up to 10 %	
<i>Amount used, frequency and duration of use/exposure</i>	
<b>Amounts used:</b> Amount per use 50 g	
<b>Duration:</b> Exposure duration 8 h/event	
<b>Frequency:</b>	



Covers exposure up to 1 events per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

### **Additional conditions human health**

Covers skin contact area up to 35 cm<sup>2</sup>

## **8.2. CS7: Consumer Contributing Scenario: Consumer (PC8)**

<b>Product Categories</b>	Biocidal products (PC8)
---------------------------	-------------------------

<b>Product (Sub-)Categories</b>	Laundry and dish washing products (PC35_1, PC8_1)
---------------------------------	---

### *Product (article) characteristics*

### **Concentration of substance in product:**

Covers percentage substance in the product up to 5 %.

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 15 g

#### **Duration:**

Exposure duration 0.5 h/event

#### **Frequency:**

Covers exposure up to 1 events per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

### **Additional conditions human health**

Covers skin contact area up to 857 cm<sup>2</sup>

## **8.2. CS8: Consumer Contributing Scenario: Consumer (PC8)**

<b>Product Categories</b>	Biocidal products (PC8)
---------------------------	-------------------------

<b>Product (Sub-)Categories</b>	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) (PC8_2, PC35_2)
---------------------------------	--

### *Product (article) characteristics*

### **Concentration of substance in product:**

Covers percentage substance in the product up to 5 %.

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 50 g

#### **Duration:**

Exposure duration 0.3 h/event

#### **Frequency:**

Covers exposure up to 125 times per year

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

### **Additional conditions human health**

Covers skin contact area up to 857 cm<sup>2</sup>

## **8.2. CS9: Consumer Contributing Scenario: Consumer (PC8)**

<b>Product Categories</b>	Biocidal products (PC8)
---------------------------	-------------------------

<b>Product (Sub-)Categories</b>	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (PC8_3, PC35_3)
---------------------------------	--

### *Product (article) characteristics*

**Concentration of substance in product:**

Covers concentrations up to 15 %

### *Amount used, frequency and duration of use/exposure*

**Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 0.2 h/event

**Frequency:**

Covers exposure up to 125 times per year

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Ventilation rate:** Covers use under typical household ventilation.

**Additional conditions human health**

Covers skin contact area up to 428 cm<sup>2</sup>

## 8.2. CS10: Consumer Contributing Scenario: Consumer (PC18)

**Product Categories**

Ink and toners (PC18)

### *Product (article) characteristics*

**Concentration of substance in product:**

Covers concentrations up to 50 %

### *Amount used, frequency and duration of use/exposure*

**Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 8 h/event

**Frequency:**

Covers exposure up to 1 uses per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Ventilation rate:** Covers use under typical household ventilation.

**Additional conditions human health**

Covers skin contact area up to 71 cm<sup>2</sup>

## 8.2. CS11: Consumer Contributing Scenario: Consumer (PC23)

**Product Categories**

Leather treatment products (PC23)

**Product (Sub-)Categories**

Polishes, wax/cream (floor, furniture, shoes) (PC23\_1, PC31\_1)

### *Product (article) characteristics*

**Concentration of substance in product:**

Covers concentrations up to 50 %

### *Amount used, frequency and duration of use/exposure*

**Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 1.2 h/event

**Frequency:**

Covers exposure up to 29 times per year

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Ventilation rate:** Covers use under typical household ventilation.

#### **Additional conditions human health**

Covers skin contact area up to 430 cm<sup>2</sup>

### **8.2. CS12: Consumer Contributing Scenario: Consumer (PC23)**

<b>Product Categories</b>	Leather treatment products (PC23)
---------------------------	-----------------------------------

<b>Product (Sub-)Categories</b>	Polishes, spray (furniture, shoes) (PC23_2, PC31_2)
---------------------------------	---

### *Product (article) characteristics*

#### **Concentration of substance in product:**

Covers concentrations up to 20 %

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 50 g

#### **Duration:**

Exposure duration 0.3 h/event

#### **Frequency:**

Covers exposure up to 8 times per year

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Ventilation rate:** Covers use under typical household ventilation.

#### **Additional conditions human health**

Covers skin contact area up to 430 cm<sup>2</sup>

### **8.2. CS13: Consumer Contributing Scenario: Consumer (PC24)**

<b>Product Categories</b>	Lubricants, greases, release products (PC24)
---------------------------	--

<b>Product (Sub-)Categories</b>	Liquids (PC16_1, PC17_1, PC24_1, 36)
---------------------------------	--------------------------------------

### *Product (article) characteristics*

#### **Concentration of substance in product:**

Covers concentrations up to 20 %

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 50 g

#### **Duration:**

Exposure duration 0.2 h/event

#### **Frequency:**

Covers exposure up to 4 times per year

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Ventilation rate:** Covers use under typical household ventilation.

#### **Additional conditions human health**

Covers skin contact area up to 468 cm<sup>2</sup>

### **8.2. CS14: Consumer Contributing Scenario: Consumer (PC27)**

<b>Product Categories</b>	Plant protection products (PC27)
---------------------------	----------------------------------

### *Product (article) characteristics*

**Concentration of substance in product:**

Covers concentrations up to 50 %

**Amount used, frequency and duration of use/exposure****Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 0.3 h/event

**Frequency:**

Covers exposure up to 29 times per year

**Other conditions affecting consumers exposure****Room size:** Covers use in room size of 20 m<sup>3</sup>**Ventilation rate:** Covers use under typical household ventilation.**Additional conditions human health**Covers skin contact area up to 857 cm<sup>2</sup>**8.2. CS15: Consumer Contributing Scenario: Consumer (PC31)****Product Categories**

Polishes and wax blends (PC31)

**Product (Sub-)Categories**

Polishes, wax/cream (floor, furniture, shoes) (PC23\_1, PC31\_1)

**Product (article) characteristics****Concentration of substance in product:**

Covers concentrations up to 50 %

**Amount used, frequency and duration of use/exposure****Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 1.2 h/event

**Frequency:**

Covers exposure up to 29 times per year

**Other conditions affecting consumers exposure****Room size:** Covers use in room size of 20 m<sup>3</sup>**Ventilation rate:** Covers use under typical household ventilation.**Additional conditions human health**Covers skin contact area up to 430 cm<sup>2</sup>**8.2. CS16: Consumer Contributing Scenario: Consumer (PC31)****Product Categories**

Polishes and wax blends (PC31)

**Product (Sub-)Categories**

Polishes, spray (furniture, shoes) (PC23\_2, PC31\_2)

**Product (article) characteristics****Concentration of substance in product:**

Covers concentrations up to 10 %

**Amount used, frequency and duration of use/exposure****Amounts used:**

Amount per use 50 g

**Duration:**

Exposure duration 0.3 h/event

**Frequency:**

Covers exposure up to 8 times per year

### Other conditions affecting consumers exposure

**Room size:** Covers use in room size of 20 m<sup>3</sup>

**Ventilation rate:** Covers use under typical household ventilation.

#### Additional conditions human health

Covers skin contact area up to 430 cm<sup>2</sup>

## 8.3 Exposure estimation and reference to its source

### 8.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	0.273 mg/L	N/A	0.000471
freshwater	0.0297 mg/L	N/A	0.0309
freshwater sediment	0.114 mg/kg bw/day	N/A	0.031
marine water	0.00304 mg/L	N/A	0.00385
marine sediment	0.0116 mg/kg bw/day	N/A	0.00383
soil	0.116 mg/kg bw/day	N/A	0.00676

### 8.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	111 mg/m <sup>3</sup>	N/A	0.973
inhalative, local, short-term	111 mg/m <sup>3</sup>	N/A	0.973
dermal, systemic, long-term	3.28 mg/kg bw/day	N/A	0.0159
combined routes, systemic, long-term	N/A	N/A	0.989

### 8.2. CS3: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.788 mg/m <sup>3</sup>	N/A	0.00682
inhalative, local, short-term	47.3 mg/m <sup>3</sup>	N/A	0.414
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.000112
combined routes, systemic, long-term	N/A	N/A	0.212

### 8.2. CS4: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, systemic, long-term	23.5 mg/m <sup>3</sup>	N/A	0.206
inhalative, local, short-term	23.5 mg/m <sup>3</sup>	N/A	0.206
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.00679
combined routes, systemic, long-term	N/A	N/A	0.212

### 8.2. CS5: Consumer Contributing Scenario: Consumer (PC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	38.7 mg/m <sup>3</sup>	N/A	0.339
inhalative, local, short-term	38.7 mg/m <sup>3</sup>	N/A	0.339
dermal, systemic, long-term	7.51 mg/kg bw/day	N/A	0.0364
combined routes, systemic, long-term	N/A	N/A	0.375

### 8.2. CS6: Consumer Contributing Scenario: Consumer (PC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	17.1 mg/m <sup>3</sup>	N/A	0.15
inhalative, local, short-term	17.1 mg/m <sup>3</sup>	N/A	0.15
dermal, systemic, long-term	0.469 mg/kg bw/day	N/A	0.00227
combined routes, systemic, long-term	N/A	N/A	0.152

### 8.2. CS7: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.672 mg/m <sup>3</sup>	N/A	0.00589
inhalative, local, short-term	0.672 mg/m <sup>3</sup>	N/A	0.00589
dermal, systemic, long-term	5.63 mg/kg bw/day	N/A	0.000273
combined routes, systemic, long-term	N/A	N/A	0.00616

### 8.2. CS8: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.543 mg/m <sup>3</sup>	N/A	0.00476
inhalative, local, short-term	1.55 mg/m <sup>3</sup>	N/A	0.0135

dermal, systemic, long-term	5.63 mg/kg bw/day	N/A	0.00956
combined routes, systemic, long-term	N/A	N/A	0.0231

### 8.2. CS9: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.885 mg/m <sup>3</sup>	N/A	0.00776
inhalative, local, short-term	2.52 mg/m <sup>3</sup>	N/A	0.0221
dermal, systemic, long-term	8.43 mg/kg bw/day	N/A	0.0143
combined routes, systemic, long-term	N/A	N/A	0.0364

### 8.2. CS10: Consumer Contributing Scenario: Consumer (PC18)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	86 mg/m <sup>3</sup>	N/A	0.754
inhalative, local, short-term	86 mg/m <sup>3</sup>	N/A	0.754
dermal, systemic, long-term	4.69 mg/kg bw/day	N/A	0.0227
combined routes, systemic, long-term	N/A	N/A	0.777

### 8.2. CS11: Consumer Contributing Scenario: Consumer (PC23)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	3.62 mg/m <sup>3</sup>	N/A	0.0317
inhalative, local, short-term	45.3 mg/m <sup>3</sup>	N/A	0.397
dermal, systemic, long-term	28.2 mg/kg bw/day	N/A	0.0109
combined routes, systemic, long-term	N/A	N/A	0.408

### 8.2. CS12: Consumer Contributing Scenario: Consumer (PC23)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.136 mg/m <sup>3</sup>	N/A	0.00119
inhalative, local, short-term	6.24 mg/m <sup>3</sup>	N/A	0.0547
dermal, systemic, long-term	1.23 mg/kg bw/day	N/A	6.5E-05
combined routes, systemic, long-term	N/A	N/A	0.0295

**8.2. CS13: Consumer Contributing Scenario: Consumer (PC24)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0368 mg/m <sup>3</sup>	N/A	0.000322
inhalative, local, short-term	3.36 mg/m <sup>3</sup>	N/A	0.0294
dermal, systemic, long-term	1.23 mg/kg bw/day	N/A	6.5E-05
combined routes, systemic, long-term	N/A	N/A	0.0295

**8.2. CS14: Consumer Contributing Scenario: Consumer (PC27)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	15.7 mg/m <sup>3</sup>	N/A	0.137
inhalative, local, short-term	15.7 mg/m <sup>3</sup>	N/A	0.137
dermal, systemic, long-term	11.2 mg/kg bw/day	N/A	0.0543
combined routes, systemic, long-term	N/A	N/A	0.226
oral, systemic, long-term	131.2 mg/kg bw/day	N/A	0.0344

**8.2. CS15: Consumer Contributing Scenario: Consumer (PC31)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	3.62 mg/m <sup>3</sup>	N/A	0.0317
inhalative, local, short-term	45.3 mg/m <sup>3</sup>	N/A	0.397
dermal, systemic, long-term	28.2 mg/kg bw/day	N/A	0.0109
combined routes, systemic, long-term	N/A	N/A	0.408

**8.2. CS16: Consumer Contributing Scenario: Consumer (PC31)**

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0684 mg/m <sup>3</sup>	N/A	0.0006
inhalative, local, short-term	3.12 mg/m <sup>3</sup>	N/A	0.0273
dermal, systemic, long-term	5.65 mg/kg bw/day	N/A	0.000597
combined routes, systemic, long-term	N/A	N/A	0.0279



## 8.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### **Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

# Exposure Scenario, 16/07/2019

Substance identity	
Chemical name	ALCOOL ISOPROPILICO; PROPAN-2-OLO
CAS No.	67-63-0
EINECS No.	200-661-7

## Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Use at industrial site
3. **ES 3** Widespread use by professional workers
4. **ES 4** Widespread use by professional workers
5. **ES 5** Widespread use by professional workers
6. **ES 6** Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)
7. **ES 7** Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)
8. **ES 8** Consumer use; Anti-freeze and de-icing products (PC4)

1. ES 1 Use at industrial site	
<b>1.1 TITLE SECTION</b>	
Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)
<b>Environment Contributing Scenario</b>	
CS1 Solvent-based process	ERC4
<b>Worker Contributing Scenario</b>	
CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
<b>1.2 Conditions of use affecting exposure</b>	
<b>1.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)</b>	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
<b>1.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)</b>	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)
<b>Product (article) characteristics</b>	
<b>Physical form of product:</b> Liquid, vapour pressure 0,5 - 10 kPa at STP	
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.	
<b>Amount used, frequency and duration of use/exposure</b>	
<b>Duration:</b> Covers daily exposures up to 8 hours	
<b>Technical and organisational conditions and measures</b>	
<b>Technical and organisational measures</b> Keep drains in watertight containers while awaiting dismantling or subsequent recycling Ensure that direct skin contact is avoided. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Drain down system prior to equipment break-in or maintenance.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
<b>Personal protection</b> Use suitable eye protection.	
<b>Other conditions affecting worker exposure</b>	

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

### 1.3 Exposure estimation and reference to its source

N/A

### 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 2. ES 2 Use at industrial site

### 2.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

#### Environment Contributing Scenario

CS1 Solvent-based process	ERC4
---------------------------	------

#### Worker Contributing Scenario

CS2 Industrial	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13 - PROC15
----------------	--

## 2.2 Conditions of use affecting exposure

### 2.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

### 2.2. CS2: Worker Contributing Scenario: Industrial (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)
--------------------	---

#### *Product (article) characteristics*

##### Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

##### Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

#### *Amount used, frequency and duration of use/exposure*

##### Duration:

Covers daily exposures up to 8 hours

#### *Technical and organisational conditions and measures*

##### Technical and organisational measures

Keep drains in watertight containers while awaiting dismantling or subsequent recycling  
Ensure that direct skin contact is avoided.  
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).  
Carry out in a vented booth or extracted enclosure.

#### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

***Other conditions affecting worker exposure***

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**2.3 Exposure estimation and reference to its source**

N/A

**2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES****Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 3. ES 3 Widespread use by professional workers

### 3.1 TITLE SECTION

<b>Exposure Scenario name</b>	Use in coatings
<b>Date - Version</b>	16/07/2019 - 1.0
<b>Life Cycle Stage</b>	Widespread use by professional workers
<b>Main user group</b>	Professional uses
<b>Sector(s) of use</b>	Professional uses (SU22)

#### Environment Contributing Scenario

<b>CS1 Solvent-based process</b>	ERC8a - ERC8d
----------------------------------	---------------

#### Worker Contributing Scenario

<b>CS2 General use from professional operators</b>	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15 - PROC19
--	--

## 3.2 Conditions of use affecting exposure

### 3.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

<b>Environmental release categories</b>	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
---	---

### 3.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)

<b>Process Categories</b>	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent - Manual activities involving hand contact (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)
---------------------------	---

#### *Product (article) characteristics*

##### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

##### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

#### *Amount used, frequency and duration of use/exposure*

##### **Duration:**

Covers daily exposures up to 8 hours

#### *Technical and organisational conditions and measures*

##### **Technical and organisational measures**

Ensure that direct skin contact is avoided.  
Carry out in a vented booth or extracted enclosure.  
Store substance within a closed system.

#### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

Wear a respirator conforming to EN140.

**3.3 Exposure estimation and reference to its source**

N/A

**3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES****Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



## 4. ES 4 Widespread use by professional workers

### 4.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

### Environment Contributing Scenario

CS1 Solvent-based process ERC8a - ERC8d

### Worker Contributing Scenario

CS2 General use from professional operators PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15

## 4.2 Conditions of use affecting exposure

### 4.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

**Environmental release categories**  
Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)

### 4.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)

**Process Categories**  
Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

### *Amount used, frequency and duration of use/exposure*

#### **Duration:**

Covers daily exposures up to 8 hours

### *Technical and organisational conditions and measures*

#### **Technical and organisational measures**

Ensure that direct skin contact is avoided.  
Avoid carrying out activities involving exposure for more than 15 minutes per day.  
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).  
Store substance within a closed system.

### *Conditions and measures related to personal protection, hygiene and health evaluation*

**Personal protection**

Use suitable eye protection.

***Other conditions affecting worker exposure***

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

**4.3 Exposure estimation and reference to its source**

N/A

**4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES****Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 5. ES 5 Widespread use by professional workers

### 5.1 TITLE SECTION

<b>Exposure Scenario name</b>	De-icing and anti-icing applications
<b>Date - Version</b>	16/07/2019 - 1.0
<b>Life Cycle Stage</b>	Widespread use by professional workers
<b>Main user group</b>	Professional uses
<b>Sector(s) of use</b>	Professional uses (SU22)

#### Environment Contributing Scenario

<b>CS1 Solvent-based process</b>	ERC8d
----------------------------------	-------

#### Worker Contributing Scenario

<b>CS2 General use from professional operators</b>	PROC1 - PROC2 - PROC8a - PROC8b - PROC11
--	--

### 5.2 Conditions of use affecting exposure

#### 5.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8d)

<b>Environmental release categories</b>	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
---	--

#### 5.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC8a, PROC8b, PROC11)

<b>Process Categories</b>	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Non industrial spraying (PROC1, PROC2, PROC8a, PROC8b, PROC11)
---------------------------	--

#### *Product (article) characteristics*

##### **Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

##### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

#### *Amount used, frequency and duration of use/exposure*

##### **Duration:**

Covers daily exposures up to 8 hours

#### *Technical and organisational conditions and measures*

##### **Technical and organisational measures**

Ensure that direct skin contact is avoided.  
Avoid carrying out activities involving exposure for more than 1 hour per day.  
Clear transfer lines prior to de-coupling.

#### *Conditions and measures related to personal protection, hygiene and health evaluation*

##### **Personal protection**

Use suitable eye protection.

#### *Other conditions affecting worker exposure*

**Temperature:** Assumes use at not more than 20 °C above ambient temperature.

### 5.3 Exposure estimation and reference to its source

N/A

## 5.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### **Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 6. ES 6 Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)

### 6.1 TITLE SECTION

<b>Exposure Scenario name</b>	Use in coatings
<b>Date - Version</b>	16/07/2019 - 1.0
<b>Life Cycle Stage</b>	Consumer use
<b>Main user group</b>	Consumer uses
<b>Sector(s) of use</b>	Consumer uses (SU21)
<b>Product Categories</b>	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Non-metal surface treatment products (PC15) - Ink and toners (PC18) - Lubricants, greases, release products (PC24) - Polishes and wax blends (PC31) - Textile dyes and impregnating products (PC34)

### Environment Contributing Scenario

<b>CS1 Solvent-based process</b>	ERC8a - ERC8d
----------------------------------	---------------

### Consumer Contributing Scenario

<b>CS2 Use in coatings</b>	PC9b - PC9a - PC1 - PC4 - PC8 - PC15 - PC18 - PC24 - PC31 - PC34
----------------------------	--

## 6.2 Conditions of use affecting exposure

### 6.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

<b>Environmental release categories</b>	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
---	---

### 6.2. CS2: Consumer Contributing Scenario: Use in coatings (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)

<b>Product Categories</b>	Fillers, putties, plasters, modelling clay - Coatings and paints, thinners, paint removers - Adhesives, sealants - Anti-freeze and de-icing products - Biocidal products - Non-metal surface treatment products - Ink and toners - Lubricants, greases, release products - Polishes and wax blends - Textile dyes and impregnating products (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)
---------------------------	---

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure > 10 kPa at STP

#### **Concentration of substance in product:**

Covers concentrations up to 50 %

#### **Additional conditions human health**

Covers skin contact area up to 430 cm<sup>2</sup>

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 10 g

#### **Frequency:**

Covers exposure up to 1 events per day

#### **Frequency:**

Covers frequency up to: 365 days per year

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in a one car garage (>34 m<sup>3</sup>) under typical ventilation.

**Temperature:** Covers use at ambient temperatures.

## 6.3 Exposure estimation and reference to its source

N/A

## 6.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### **Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## 7. ES 7 Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)

### 7.1 TITLE SECTION

<b>Exposure Scenario name</b>	Use in cleaning agents
<b>Date - Version</b>	16/07/2019 - 1.0
<b>Life Cycle Stage</b>	Consumer use
<b>Main user group</b>	Consumer uses
<b>Sector(s) of use</b>	Consumer uses (SU21)
<b>Product Categories</b>	Air care products (PC3) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Lubricants, greases, release products (PC24) - Washing and cleaning products (PC35) - Welding and soldering products, flux products (PC38)

### Environment Contributing Scenario

<b>CS1 Solvent-based process</b>	ERC8a - ERC8d
----------------------------------	---------------

### Consumer Contributing Scenario

<b>CS2 Detergent liquids</b>	PC9a - PC3 - PC4 - PC8 - PC24 - PC35 - PC38
------------------------------	---

## 7.2 Conditions of use affecting exposure

### 7.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

<b>Environmental release categories</b>	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
---	---

### 7.2. CS2: Consumer Contributing Scenario: Detergent liquids (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)

<b>Product Categories</b>	Coatings and paints, thinners, paint removers - Air care products - Anti-freeze and de-icing products - Biocidal products - Lubricants, greases, release products - Washing and cleaning products - Welding and soldering products, flux products (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)
---------------------------	---

### *Product (article) characteristics*

#### **Physical form of product:**

Liquid, vapour pressure > 10 kPa at STP

#### **Concentration of substance in product:**

Covers concentrations up to 50 %

### *Amount used, frequency and duration of use/exposure*

#### **Amounts used:**

Amount per use 100 g

#### **Frequency:**

Covers use up to 365 days per year

#### **Frequency:**

Covers use up to 1 uses per day

### *Other conditions affecting consumers exposure*

**Room size:** Covers use in a one car garage (>34 m<sup>3</sup>) under typical ventilation.

**Temperature:** Covers use at ambient temperatures.

#### **Additional conditions human health**

Covers skin contact area up to 428 cm<sup>2</sup>

## 7.3 Exposure estimation and reference to its source

N/A

## 7.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

### **Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.



## 8. ES 8 Consumer use; Anti-freeze and de-icing products (PC4)

### 8.1 TITLE SECTION

Exposure Scenario name	De-icing and anti-icing applications
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Anti-freeze and de-icing products (PC4)

#### Environment Contributing Scenario

CS1 Solvent-based process	ERC4
---------------------------	------

#### Consumer Contributing Scenario

CS2 De-icing and anti-icing applications	PC24
--	------

## 8.2 Conditions of use affecting exposure

### 8.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

### 8.2. CS2: Consumer Contributing Scenario: De-icing and anti-icing applications (PC24)

Product Categories	Lubricants, greases, release products (PC24)
--------------------	--

#### *Product (article) characteristics*

##### Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

##### Concentration of substance in product:

Covers concentrations up to 10 %

#### *Amount used, frequency and duration of use/exposure*

##### Amounts used:

Amount per use 2000 g

##### Duration:

Covers use up to 0.25 h/event

##### Frequency:

Covers exposure up to 365 days per year

#### *Other conditions affecting consumers exposure*

**Room size:** Covers use in a one car garage (>34 m<sup>3</sup>) under typical ventilation.

**Temperature:** Covers use at ambient temperatures.

##### Additional conditions human health

Covers skin contact area up to 428 cm<sup>2</sup>

## 8.3 Exposure estimation and reference to its source

N/A

## 8.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.