

**Safety Data Sheet**  
**SEAL 5661 BIANCA guarnizione siliconica**  
**originale**



**Safety Data Sheet dated 19/1/2022, version 8**

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Mixture identification:

Trade name: SEAL 5661 BIANCA guarnizione siliconica originale

Trade code: 0076

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Liquid seal

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: Beaumont Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 - 22:00)

In South Africa: Poison Information Helpline 0861 555 777

In Malta: emergency number 112

---

**SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H319 Causes serious eye irritation.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/clothing and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

**Safety Data Sheet**  
**SEAL 5661 BIANCA guarnizione siliconica**  
**originale**



lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$ :

$\geq 0.5\% - < 1\%$  Dodecamethylcyclohexasiloxane - REACH No.: 01-2119517435-42, CAS:  
540-97-6, EC: 208-762-8:

PBT, vPvB

$\geq 0.1\% - < 0.25\%$  ottametilciclotetrasilossano - REACH No.: 01-2119529238-36, CAS:  
556-67-2, EC: 209-136-7:

PBT, vPvB

Other Hazards:

1

No hazards identified as the maximum bio-available concentration of octamethylcyclotetrasiloxane (D4) in the aquatic environment is below the expected threshold for the NOEC. Experimental analyzes have shown that the mixture is not dangerous for the environment.

No other hazards

# Safety Data Sheet

## SEAL 5661 BIANCA guarnizione siliconica originale



### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 2% - < 3% Methylsilanetriyl triacetate

REACH No.: 01-2119987097-22, CAS: 4253-34-3, EC: 224-221-9

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.2/1B Skin Corr. 1B H314

>= 2% - < 3% acetic acid...%

REACH No.: 01-2119475328-30, CAS: 64-19-7, EC: 200-580-7

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.2/1A Skin Corr. 1A H314

Specific Concentration Limits:

10% <= C < 25%: Skin Irrit. 2 H315

10% <= C < 25%: Eye Irrit. 2 H319

25% <= C < 90%: Skin Corr. 1B H314

C >= 90%: Skin Corr. 1A H314

>= 0.5% - < 1% Dodecamethylcyclohexasiloxane

REACH No.: 01-2119517435-42, CAS: 540-97-6, EC: 208-762-8

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

>= 0.1% - < 0.25% ottametilciclotetrasilossano

REACH No.: 01-2119529238-36, CAS: 556-67-2, EC: 209-136-7

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.7/2 Repr. 2 H361f

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=10.

SVHC, PBT, vPvB, endocrine disruptor substances:

>= 0.5% - < 1% Dodecamethylcyclohexasiloxane

REACH No.: 01-2119517435-42, CAS: 540-97-6, EC: 208-762-8

PBT, vPvB, SVHC

>= 0.1% - < 0.25% ottametilciclotetrasilossano

REACH No.: 01-2119529238-36, CAS: 556-67-2, EC: 209-136-7

PBT, vPvB, SVHC

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.



## Safety Data Sheet

### SEAL 5661 BIANCA guarnizione siliconica originale

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

#### SECTION 5: Firefighting measures

5.1. Extinguishing media

Appropriate Extinguishing Media:

Foam

To carbon dioxide.

To dust.

Water spray.

Not Recommended Extinguishing Media:

Do not use direct water jets.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

---

#### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.



## Safety Data Sheet

### SEAL 5661 BIANCA guarnizione siliconica originale

#### 7.2. Conditions for safe storage, including any incompatibilities

Store in hermetically sealed containers, preferably in a cool place, away from sources of heat and direct sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

#### 7.3. Specific end use(s)

None in particular

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

acetic acid...% - CAS: 64-19-7

EU - TWA(8h): 25 mg/m<sup>3</sup>, 10 ppm - STEL: 50 mg/m<sup>3</sup>, 20 ppm

ACGIH - TWA(8h): 10 ppm - STEL: 15 ppm - Notes: URT and eye irr, pulm func

ottametilciclotetrasilossano - CAS: 556-67-2

20101.04 - TWA: 120 mg/m<sup>3</sup>, 10 ppm

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

### 8.2. Exposure controls

Eye protection:

Safety goggles.

Face protection shield.

Compliant with EN 166

Protection for skin:

protective clothing

Protection for hands:

Nitrile.

Neoprene.

Compliant with EN 374.

Respiratory protection:

In case of insufficient ventilation, use adequate respiratory protection equipment.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid	--	--
Colour:	White	--	--
Odour:	aceto	--	--
Melting point/freezing point:	N.A.	--	--

**Safety Data Sheet**  
**SEAL 5661 BIANCA guarnizione siliconica**  
**originale**



Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	N.A.	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	> 150°C	11	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	>200°C	--	--
pH:	N.A.	--	--
Kinematic viscosity:	> 20,5 mm <sup>2</sup> /sec (40 °C)	--	--
Solubility in water:	Insoluble	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	1,14	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information  
 No other relevant information

**SECTION 10: Stability and reactivity**

- 10.1. Reactivity  
 Vulcanizes at room temperature in contact with humid air.
- 10.2. Chemical stability  
 Stable at room temperature, not in contact with air.
- 10.3. Possibility of hazardous reactions  
 None
- 10.4. Conditions to avoid  
 Stable under normal conditions.
- 10.5. Incompatible materials  
 Strong oxidising agents. Water.
- 10.6. Hazardous decomposition products  
 Thermal decomposition or combustion can release carbon oxides and other toxic gases and

# Safety Data Sheet

## SEAL 5661 BIANCA guarnizione siliconica originale



vapours. Amorphous silica.  
May produce hazardous substances during use or in contact with water.

### SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

SEAL 5661 BIANCA guarnizione siliconica originale

- a) acute toxicity  
Not classified  
Based on available data, the classification criteria are not met  
Test: oecd 10 - Route: Oral 54398.89 mg/kg
- b) skin corrosion/irritation  
Not classified  
Based on available data, the classification criteria are not met
- c) serious eye damage/irritation  
The product is classified: Eye Irrit. 2 H319
- d) respiratory or skin sensitisation  
Not classified  
Based on available data, the classification criteria are not met
- e) germ cell mutagenicity  
Not classified  
Based on available data, the classification criteria are not met
- f) carcinogenicity  
Not classified  
Based on available data, the classification criteria are not met
- g) reproductive toxicity  
Not classified  
Based on available data, the classification criteria are not met
- h) STOT-single exposure  
Not classified  
Based on available data, the classification criteria are not met
- i) STOT-repeated exposure  
Not classified  
Based on available data, the classification criteria are not met
- j) aspiration hazard  
Not classified  
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Methylsilanetriyl triacetate - CAS: 4253-34-3

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: CAVIA Negative - Notes: OECD 406

e) germ cell mutagenicity:

Test: oecd Negative

g) reproductive toxicity:

Test: NOAEL - Route: Inhalation - Species: Rat > 1000 mg/kg - Notes: Metodo: OECD 422

acetic acid...% - CAS: 64-19-7

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 40 mg/l

e) germ cell mutagenicity:

Test: oecd - Species: vitro Negative

g) reproductive toxicity:

Test: arx1 - Route: Oral - Species: Rat 1600 mg/kg

Dodecamethylcyclohexasiloxane - CAS: 540-97-6

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Species: CAVIA Negative - Notes: OECD 406

## Safety Data Sheet

### SEAL 5661 BIANCA guarnizione siliconica originale



- e) germ cell mutagenicity:  
Test: oecd 2 - Species: vitro Negative
- g) reproductive toxicity:  
Test: NOAEL - Route: Oral - Species: Rat > 1000 mg/kg - Notes: OECD 422  
Test: arx1 - Species: Rabbit > 1000 mg/kg - Notes: OECD 414
- h) STOT-single exposure:  
Test: oecd 11 Negative
- i) STOT-repeated exposure:  
Negative
- ottametilciclotetrasilossano - CAS: 556-67-2
- d) respiratory or skin sensitisation:  
Test: Skin Sensitization - Route: Skin - Species: CAVIA Negative
- e) germ cell mutagenicity:  
Test: Mutagenesis - Species: vitro Negative
- f) carcinogenicity:  
Test: Carcinogenecity - Species: Rat Negative - Notes: OECD 453
- g) reproductive toxicity:  
Test: NOAEL - Route: Inhalation - Species: Rat 3.64 mg/l - Notes: OECD 416  
Test: arx1 - Route: Inhalation - Species: Rat > 6.066 mg/l - Notes: OECD 414

#### 11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration  $\geq$  0.1%

---

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Methylsilanetriyl triacetate - CAS: 4253-34-3

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96

Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 660 mg/l - Duration h: 96

acetic acid...% - CAS: 64-19-7

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae > 1000 mg/l

#### b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae = 1000 mg/l

Dodecamethylcyclohexasiloxane - CAS: 540-97-6

#### a) Aquatic acute toxicity:

Endpoint: CE6 - Species: Algae > 0.002 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish > 0.016 mg/l - Duration h: 96

#### b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia > 0.0046 mg/l - Duration h: 504

Endpoint: NOEC - Species: Algae > 0.002 mg/l - Duration h: 72

Endpoint: NOEC - Species: Fish 0.046 mg/l - Duration h: 504

Endpoint: EC50 - Species: Daphnia > 0.0029 mg/l - Duration h: 48

ottametilciclotetrasilossano - CAS: 556-67-2

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 0.022 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 0.015 mg/l - Duration h: 48

#### b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Fish > 0.0044 mg/l - Duration h: 2232

Endpoint: NOEC - Species: Daphnia 0.0015 mg/l - Duration h: 504



# Safety Data Sheet

## SEAL 5661 BIANCA guarnizione siliconica originale




- e) Plant toxicity:  
Endpoint: EC50 - Species: Algae > 0.022 mg/l - Duration h: 96
- 12.2. Persistence and degradability  
None  
Methylsilanetriyl triacetate - CAS: 4253-34-3  
Biodegradability: 4 - Duration: 21GG - %: 74  
acetic acid...% - CAS: 64-19-7  
Biodegradability: Readily biodegradable - Duration: 20dd - %: 96  
Dodecamethylcyclohexasiloxane - CAS: 540-97-6  
Biodegradability: Non-readily biodegradable - Test: OECD TG 310 - Duration: 28gg - %: 4.5  
ottametilciclotetrasilossano - CAS: 556-67-2  
Biodegradability: Non-readily biodegradable - Duration: 28gg - %: 3.7
- 12.3. Bioaccumulative potential  
acetic acid...% - CAS: 64-19-7  
Test: BCF - Bioconcentration factor 3.16  
Dodecamethylcyclohexasiloxane - CAS: 540-97-6  
Bioaccumulation: Bioaccumulative - Test: BCF - Bioconcentration factor 2860  
ottametilciclotetrasilossano - CAS: 556-67-2  
Test: BCF - Bioconcentration factor 12400
- 12.4. Mobility in soil  
N.A.
- 12.5. Results of PBT and vPvB assessment  
PBT Substances:  
>= 0.5% - < 1% Dodecamethylcyclohexasiloxane - CAS: 540-97-6  
>= 0.1% - < 0.25% ottametilciclotetrasilossano - CAS: 556-67-2  
vPvB Substances:  
>= 0.5% - < 1% Dodecamethylcyclohexasiloxane - CAS: 540-97-6  
>= 0.1% - < 0.25% ottametilciclotetrasilossano - CAS: 556-67-2
- 12.6. Endocrine disrupting properties  
No endocrine disruptor substances present in concentration >= 0.1%
- 12.7. Other adverse effects  
None

### SECTION 13: Disposal considerations

- 13.1. Waste treatment methods  
Recover if possible. In so doing, comply with the local and national regulations currently in force.  
Additional disposal information:  
Contaminated packaging must be emptied as far as possible. After cleaning, send to an authorised centre for recycling or disposal.

### SECTION 14: Transport information



- 14.1. UN number or ID number  
ADR-UN Number: 3082  
IATA-UN Number: 3082  
IMDG-UN Number: 3082
- 14.2. UN proper shipping name  
ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

# Safety Data Sheet

## SEAL 5661 BIANCA guarnizione siliconica originale



IATA-Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
IMDG-Shipping Name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	
14.3. Transport hazard class(es)		
ADR-Class:	9	
ADR - Hazard identification number:	90	
IATA-Class:	9	
IATA-Label:	9	
IMDG-Class:	9	
Sea (IMO):	NC	
14.4. Packing group		
ADR-Packing Group:	III	
IATA-Packing group:	III	
IMDG-Packing group:	III	
14.5. Environmental hazards		
ADR-Environmental Pollutant:	Yes	
IMDG-Marine pollutant:	Marine Pollutant	
IMDG-EmS:	F-A, S-F	
14.6. Special precautions for user		
ADR-Subsidiary hazards:	-	
ADR-S.P.:	274 335 375 601	
ADR-Transport category (Tunnel restriction code):	3 (-)	
IATA-Passenger Aircraft:	964	
IATA-Subsidiary hazards:	-	
IATA-Cargo Aircraft:	964	
IATA-S.P.:	A97 A158 A197	
IATA-ERG:	9L	
IMDG-Subsidiary hazards:	-	
IMDG-Stowage and handling:	Category A	
IMDG-Segregation:	-	
14.7. Maritime transport in bulk according to IMO instruments		
N.A.		
Limited Quantity:	5 L	
Exempted Quantity:	E1	

### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 98/24/EC (Risks related to chemical agents at work)
  - Dir. 2000/39/EC (Occupational exposure limit values)
  - Regulation (EC) n. 1907/2006 (REACH)
  - Regulation (EC) n. 1272/2008 (CLP)
  - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
  - Regulation (EU) n. 2020/878
  - Regulation (EU) n. 286/2011 (ATP 2 CLP)
  - Regulation (EU) n. 618/2012 (ATP 3 CLP)
  - Regulation (EU) n. 487/2013 (ATP 4 CLP)
  - Regulation (EU) n. 944/2013 (ATP 5 CLP)
  - Regulation (EU) n. 605/2014 (ATP 6 CLP)
  - Regulation (EU) n. 2015/1221 (ATP 7 CLP)
  - Regulation (EU) n. 2016/918 (ATP 8 CLP)
  - Regulation (EU) n. 2016/1179 (ATP 9 CLP)
  - Regulation (EU) n. 2017/776 (ATP 10 CLP)
  - Regulation (EU) n. 2018/669 (ATP 11 CLP)



## Safety Data Sheet

### SEAL 5661 BIANCA guarnizione siliconica originale

Regulation (EU) n. 2018/1480 (ATP 13 CLP)  
Regulation (EU) n. 2019/521 (ATP 12 CLP)  
Regulation (EU) n. 2020/217 (ATP 14 CLP)  
Regulation (EU) n. 2020/1182 (ATP 15 CLP)  
Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 40

Restriction 70

Pronto all'Uso

Volatile Organic compounds - VOCs = 0.24 %

Volatile Organic compounds - VOCs = 2.40 g/Kg

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.08

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

SVHC Substances:

Substances in candidate list (Art. 59 Reg. 1907/2006, REACH):

Dodecamethylcyclohexasiloxane

PBT, vPvB

ottametilciclotetrasilossano

PBT, vPvB

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

None

## SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H361f Suspected of damaging the unborn child.

H410 Very toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4

**Safety Data Sheet**  
**SEAL 5661 BIANCA guarnizione siliconica**  
**originale**



Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Repr. 2	3.7/2	Reproductive toxicity, Category 2
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 8: Exposure controls/personal protection
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
Eye Irrit. 2, H319	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- ATE: Acute Toxicity Estimate
- ATEmix: Acute toxicity Estimate (Mixtures)
- CAS: Chemical Abstracts Service (division of the American Chemical Society).
- CLP: Classification, Labeling, Packaging.
- DNEL: Derived No Effect Level.
- EINECS: European Inventory of Existing Commercial Chemical Substances.
- GefStoffVO: Ordinance on Hazardous Substances, Germany.
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
- IATA: International Air Transport Association.

**Safety Data Sheet**  
**SEAL 5661 BIANCA guarnizione siliconica**  
**originale**



IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.