

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



Safety Data Sheet dated 4/7/2019, version 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ODOR CANCEL NEW FRESH CAR spray ml 75
Trade code: 1928

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Anti-odour agents

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.
via Antica di Cassano, 23, 20063
Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.
Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Centro Antiveleni di Pavia IRCCS- Fondazione Maugeri tel. +39 (0)382 24444 (h24; it, en)

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: Beaumont Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 - 22:00)

In South Africa: Poison Information Helpline 0861 555 777

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

⚠ Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Special Provisions:

None

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 60% - < 70% ethanol

REACH No.: 01-2119457610-43, Index number: 603-002-00-5, CAS: 64-17-5, EC: 200-578-6

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

Specific Concentration Limits:

C >= 50%: Eye Irrit. 2 H319

>= 30% - < 40% Hydrocarbons, C3-4

REACH No.: 01-2119486557-22, Index number: 649-199-00-1, CAS: 68476-40-4, EC: 270-681-9

⚠ 2.2/1 Flam. Gas 1 H220

⚠ 2.5/L Press. Gas (Liq.) H280

DECLK (CLP)*

>= 3% - < 5% propan-2-ol

REACH No.: 01-2119457558-25, Index number: 603-117-00-0, CAS: 67-63-0, EC: 200-661-7

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

>= 0.25% - < 0.5% Butanone

REACH No.: 01-2119457290-43, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

EUH066

*DECLK (CLP): Substance classified in accordance with Note K, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (Einecs No 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3.

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Appropriate Extinguishing Media:

To carbon dioxide.

To dust.

Foam for alcohols

Water spray.

Not Recommended Extinguishing Media:

Do not use direct water jets.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
- 6.4. Reference to other sections
See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
Store at below 50 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
Keep away from food, drink and feed.
None in particular.
Instructions as regards storage premises:
Cool and adequately ventilated.
- 7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
ethanol - CAS: 64-17-5
ACGIH - STEL: 1000 ppm - Notes: A3 - URT irr
Hydrocarbons, C3-4 - CAS: 68476-40-4
MAK - TWA: 2400 mg/m³, 1000 ppm
TLV TWA - 1900 mg/m³, 800 ppm
propan-2-ol - CAS: 67-63-0
ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair
Butanone - CAS: 78-93-3
EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm
ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair
- DNEL Exposure Limit Values
propan-2-ol - CAS: 67-63-0
Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
Worker Professional: 500 mg/kg - Consumer: 89 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Professional: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
- PNEC Exposure Limit Values
propan-2-ol - CAS: 67-63-0
Target: Fresh Water - Value: 140.9 mg/l
Target: Marine water - Value: 140.9 mg/l
Target: Freshwater sediments - Value: 552 mg/kg
Target: Marine water sediments - Value: 552 mg/kg
Target: Soil (agricultural) - Value: 28 mg/kg
- 8.2. Exposure controls
Eye protection:

Safety Data Sheet
ODOR CANCEL NEW FRESH CAR spray ml 75



Eye glasses with side protection.
 Compliant with EN 166
 Protection for skin:
 protective clothing
 Protection for hands:
 Nitrile or Viton gloves.
 Compliant with EN 374.
 Respiratory protection:
 Not needed for normal use.
 Thermal Hazards:
 None
 Environmental exposure controls:
 None
 Appropriate engineering controls:
 None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Aerosol	--	--
Odour:	Characteristic	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	N.A.	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

NA=not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

ODOR CANCEL NEW FRESH CAR spray ml 75

a) acute toxicity

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

Based on available data, the classification criteria are not met

c) serious eye damage/irritation

The product is classified: Eye Irrit. 2 H319

d) respiratory or skin sensitisation

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Based on available data, the classification criteria are not met

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



f) carcinogenicity

Based on available data, the classification criteria are not met

g) reproductive toxicity

Based on available data, the classification criteria are not met

h) STOT-single exposure

Based on available data, the classification criteria are not met

i) STOT-repeated exposure

Based on available data, the classification criteria are not met

j) aspiration hazard

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

ethanol - CAS: 64-17-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 120 mg/l - Duration: 4h

propan-2-ol - CAS: 67-63-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 4710 mg/kg

Test: LD50 - Route: Skin - Species: Rat 12800 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 72.6 mg/l - Duration: 4h

Butanone - CAS: 78-93-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 2737 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 6480 mg/kg

Test: LD50 - Route: Inhalation - Species: Rat 23.5 mg/l - Duration: 8h

propan-2-ol - CAS: 67-63-0

OBSERVATIONS ON HUMAN SUBJECTS:

propan-1-ol (propyl alcohol): oral, woman (LDLo): 5700 mg/kg propan-2-ol (isopropyl alcohol): oral, man (LDLo): 5272 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Hydrocarbons, C3-4 - CAS: 68476-40-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia = 14.22 mg/l - Duration h: 48

12.2. Persistence and degradability

None

ethanol - CAS: 64-17-5

Biodegradability: Persistent and Biodegradable - %: 1000-10000 - Notes: mg/l

propan-2-ol - CAS: 67-63-0

Biodegradability: Readily biodegradable

Butanone - CAS: 78-93-3

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

propan-2-ol - CAS: 67-63-0

Test: Kow - Partition coefficient 0.05

Butanone - CAS: 78-93-3

Test: Kow - Partition coefficient 0.3

12.4. Mobility in soil

N.A.

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.
- Additional disposal information:
Reuse if possible. Act in accordance with the local and national laws in force.

SECTION 14: Transport information



- 14.1. UN number
ADR-UN Number: 1950
IATA-UN Number: 1950
IMDG-UN Number: 1950
- 14.2. UN proper shipping name
ADR-Shipping Name: AEROSOLS, flammable
IATA-Shipping Name: AEROSOLS, flammable
IMDG-Shipping Name: AEROSOLS, flammable
- 14.3. Transport hazard class(es)
ADR-Class: 2
ADR - Hazard identification number: -
IATA-Class: 2
IATA-Label: 2.1
IMDG-Class: 2
- 14.4. Packing group
ADR-Packing Group: -
IATA-Packing group: -
IMDG-Packing group: -
- 14.5. Environmental hazards
ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
- 14.6. Special precautions for user
ADR-Subsidiary hazards: See SP63
ADR-S.P.: 190 327 344 625
ADR-Transport category (Tunnel restriction code): 2 (D)
IATA-Passenger Aircraft: 203
IATA-Subsidiary hazards: See SP63
IATA-Cargo Aircraft: 203
IATA-S.P.: A145 A167 A802
IATA-ERG: 10L
IMDG-EmS: F-D,
S-U
IMDG-Subsidiary hazards: See SP63
IMDG-Stowage and handling: SW1 SW22
IMDG-Segregation: SG69
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
No
Limited Quantity: 1 L

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



Exempted Quantity: E0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Dir. 98/24/EC (Risks related to chemical agents at work)
- Dir. 2000/39/EC (Occupational exposure limit values)
- Regulation (EC) n. 1907/2006 (REACH)
- Regulation (EC) n. 1272/2008 (CLP)
- Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
- Regulation (EU) 2015/830
- Regulation (EU) n. 286/2011 (ATP 2 CLP)
- Regulation (EU) n. 618/2012 (ATP 3 CLP)
- Regulation (EU) n. 487/2013 (ATP 4 CLP)
- Regulation (EU) n. 944/2013 (ATP 5 CLP)
- Regulation (EU) n. 605/2014 (ATP 6 CLP)
- Regulation (EU) n. 2015/1221 (ATP 7 CLP)
- Regulation (EU) n. 2016/918 (ATP 8 CLP)
- Regulation (EU) n. 2016/1179 (ATP 9 CLP)
- Regulation (EU) n. 2017/776 (ATP 10 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

- Restriction 3
- Restriction 40

Restrictions related to the substances contained:

No restriction.

Pronto all'Uso

Volatile Organic compounds - VOCs = 99.01 %

Volatile Organic compounds - VOCs = 990.06 g/Kg

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 36.38

Where applicable, refer to the following regulatory provisions :

- Directive 2012/18/EU (Seveso III)
- Regulation (EC) nr 648/2004 (detergents).
- Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

- Seveso III category according to Annex 1, part 1
- Product belongs to category: P3a

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

None

SECTION 16: Other information

Text of phrases referred to under heading 3:

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H220 Extremely flammable gas.
- H280 Contains gas under pressure; may explode if heated.
- H336 May cause drowsiness or dizziness.
- EUH066 Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas (Liq.)	2.5/L	Gases under pressure (Liquefied gas)
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3

Paragraphs modified from the previous revision:

SECTION 3: Composition/information on ingredients
SECTION 7: Handling and storage
SECTION 8: Exposure controls/personal protection
SECTION 14: Transport information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Eye Irrit. 2, H319	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.
EINECS: European Inventory of Existing Commercial Chemical Substances.
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of

Safety Data Sheet

ODOR CANCEL NEW FRESH CAR spray ml 75



	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.