

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



Safety Data Sheet dated 6/2/2023, version 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: Cockpit Protectant - HIGH GLOSS

Trade code: 31002

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Detergent for plastic parts

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: Beaumont Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 - 22:00)

In South Africa: Poison Information Helpline 0861 555 777

In Malta: emergency number 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

⚠ Warning, Skin Sens. 1A, May cause an allergic skin reaction.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Warning

Hazard statements:

H317 May cause an allergic skin reaction.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P280 Wear protective gloves/clothing and eye/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

31002/12

Page n. 1 of 13

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



None
Contains
2-Methyl-2H-isothiazol-3-one
Special provisions according to Annex XVII of REACH and subsequent amendments:
None

Regulation (EC) nr 648/2004 (detergents).

Product contents:

Non-ionic surfactants < 5 %

The product also contains: Perfumes

Preservatives: Laurylamine Dipropylenediamine, Pyridine-2-thiol 1-oxide, sodium salt., 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, 2-Methyl-2H-isothiazol-3-one

2.3. Other hazards

PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$:

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

$\geq 1\%$ - $< 2\%$ ethanediol; ethylene glycol

REACH No.: 01-2119456816-28, Index number: 603-027-00-1, CAS: 107-21-1, EC: 203-473-3

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.9/2 STOT RE 2 H373 (kidneys) (oral)

$\geq 0.05\%$ - $< 0.1\%$ N-C12-16 ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE.

REACH No.: 01-2119970550-39, CAS: 68424-85-1, EC: 939-350-2

⚠ 2.16/1 Met. Corr. 1 H290

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 3.2/1B Skin Corr. 1B H314

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 4.1/A1 Aquatic Acute 1 H400 M=10.

⚠ 4.1/C1 Aquatic Chronic 1 H410

$\geq 0.02\%$ - $< 0.05\%$ Esadeciltrimetilaammoniocloruro

CAS: 112-02-7, EC: 203-928-6

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.

⚠ 3.1/3/Dermal Acute Tox. 3 H311

⚠ 4.1/A1 Aquatic Acute 1 H400 M=10.

⚠ 3.2/1C Skin Corr. 1C H314

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.1/4/Oral Acute Tox. 4 H302

$\geq 0.001\%$ - $< 0.005\%$ octamethylcyclotetrasiloxane; [D4]

REACH No.: 01-2119529238-36, Index number: 014-018-00-1, CAS: 556-67-2, EC: 209-136-7

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.7/2 Repr. 2 H361f

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=10.

$\geq 0.001\%$ - $< 0.005\%$ DYPHENYL OXYDE

31002/12

Page n. 2 of 13

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



REACH No.: 01-2119472545-33, CAS: 101-84-8, EC: 202-981-2

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.001% - < 0.005% 2-Methyl-2H-isothiazol-3-one

CAS: 2682-20-4, EC: 220-239-6

⚠ 3.1/2/Inhal Acute Tox. 2 H330

⚠ 3.1/3/Dermal Acute Tox. 3 H311

⚠ 3.1/3/Oral Acute Tox. 3 H301

⚠ 3.2/1B Skin Corr. 1B H314

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1A Skin Sens. 1A H317

⚠ 4.1/A1 Aquatic Acute 1 H400 M=10.

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.

EUH071

Specific Concentration Limits:

C >= 0,00015%: EUH208

C >= 0,0015%: Skin Sens. 1A H317

<1 ppb toluene

REACH No.: 01-2119471310-51, CAS: 108-88-3, EC: 203-625-9

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.8/3 STOT SE 3 H336

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.7/2 Repr. 2 H361

⚠ 3.9/2 STOT RE 2 H373

SVHC, PBT, vPvB, endocrine disruptor substances:

>= 0.001% - < 0.005% octamethylcyclotetrasiloxane; [D4]

REACH No.: 01-2119529238-36, Index number: 014-018-00-1, CAS: 556-67-2, EC:

209-136-7

PBT, vPvB, SVHC

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Appropriate Extinguishing Media:
To carbon dioxide.
 - Not Recommended Extinguishing Media:
To dust.
- 5.2. Special hazards arising from the substance or mixture
 - Do not inhale explosion and combustion gases.
 - Burning produces heavy smoke.
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.
 - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - See also section 8 for recommended protective equipment.
 - Advice on general occupational hygiene:
Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
 - Keep away from food, drink and feed.
 - None in particular.
 - Instructions as regards storage premises:
Adequately ventilated premises.
- 7.3. Specific end use(s)
 - None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



ethanediol; ethylene glycol - CAS: 107-21-1

EU - TWA(8h): 52 mg/m³, 20 ppm - STEL: 104 mg/m³, 40 ppm - Notes: Skin

ACGIH - TWA(8h): 25 ppm - STEL: 50 ppm - Notes: (V), A4 - URT irr

ACGIH - STEL: 10 mg/m³ - Notes: (I, H), A4 - URT irr

DYPHENYL OXYDE - CAS: 101-84-8

EU - TWA(8h): 7 mg/m³, 1 ppm - STEL: 14 mg/m³, 2 ppm

ACGIH - TWA(8h): 1 ppm - STEL: 2 ppm - Notes: (V) - URT and eye irr, nausea

toluene - CAS: 108-88-3

EU - TWA(8h): 192 mg/m³, 50 ppm - STEL: 384 mg/m³, 100 ppm - Notes: Skin

ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - Visual impair, female repro, pregnancy loss

DNEL Exposure Limit Values

Esadeciltrimetilaammoniocloruro - CAS: 112-02-7

Worker Professional: 3.32 mg/m³ - Consumer: 0.98 mg/m³ - Exposure: Human Inhalation

- Frequency: Long Term, systemic effects

Worker Professional: 4.7 mg/kg - Consumer: 2.83 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Consumer: 2.83 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2

Worker Professional: 73 mg/m³ - Consumer: 13 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Professional: 73 mg/m³ - Consumer: 13 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term, local effects

Consumer: 3.7 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

DYPHENYL OXYDE - CAS: 101-84-8

Worker Industry: 59 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 58.3 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 9.68 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

effects

Worker Industry: 14 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

effects

PNEC Exposure Limit Values

Esadeciltrimetilaammoniocloruro - CAS: 112-02-7

Target: Fresh Water - Value: 0.00068 mg/l

Target: Marine water - Value: 0.000068 mg/l

Target: Freshwater sediments - Value: 9.27 mg/kg

Target: Marine water sediments - Value: 0.927 mg/kg

Target: 09 - Value: 0.4 mg/l

octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2

Target: Fresh Water - Value: 0.0015 mg/l

Target: Marine water - Value: 0.00015 mg/l

Target: Freshwater sediments - Value: 3 mg/kg

Target: Marine water sediments - Value: 0.3 mg/kg

Target: 09 - Value: 10 mg/l

DYPHENYL OXYDE - CAS: 101-84-8

Target: Fresh Water - Value: 0.0017 mg/l

Target: Marine water - Value: 0.00017 mg/l

Target: Freshwater sediments - Value: 0.345 mg/kg

Target: Marine water sediments - Value: 0.0345 mg/kg

Target: Soil (agricultural) - Value: 0.0681 mg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Compliant with EN 166

Protection for skin:

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



protective clothing
 Protection for hands:
 Nitrile or Viton gloves.
 Compliant with EN 374.
 Respiratory protection:
 Not needed for normal use.
 Thermal Hazards:
 None
 Environmental exposure controls:
 None
 Appropriate engineering controls:
 None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid	--	--
Colour:	Cream	--	--
Odour:	Characteristic	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	N.A.	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	Not flammable	IP 170	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
pH:	7	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	Soluble	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	0,998 g/cm ³	--	--

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

- 9.2. Other information
No other relevant information

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

Cockpit Protectant - HIGH GLOSS ML 400

- a) acute toxicity
Not classified
Based on available data, the classification criteria are not met
- b) skin corrosion/irritation
Not classified
Based on available data, the classification criteria are not met
- c) serious eye damage/irritation
Not classified
Based on available data, the classification criteria are not met
- d) respiratory or skin sensitisation
The product is classified: Skin Sens. 1A H317
- e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
- f) carcinogenicity
Not classified
Based on available data, the classification criteria are not met
- g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
- h) STOT-single exposure
Not classified
Based on available data, the classification criteria are not met
- i) STOT-repeated exposure
Not classified
Based on available data, the classification criteria are not met

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



j) aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

N-C12-16 ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE. - CAS: 68424-85-1

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 426 mg/kg

Test: LD50 - Route: Skin - Species: Rat 400-2000 mg/kg

Esadeciltrimetilaammoniocloruro - CAS: 112-02-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 36 mg/l

Test: LD50 - Route: Oral - Species: Rat > 4800 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2400 mg/kg

DYPHENYL OXYDE - CAS: 101-84-8

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 2830 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 7940 mg/kg

2-Methyl-2H-isothiazol-3-one - CAS: 2682-20-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 120 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 0.11 mg/l - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit 242 mg/kg

b) skin corrosion/irritation:

Test: Skin Corrosive - Route: Skin - Species: Rabbit Positive

c) serious eye damage/irritation:

Test: Eye Corrosive - Route: EYE - Species: Rabbit Positive

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Species: IND Positive

f) carcinogenicity:

Test: Carcinogeneticity Negative

h) STOT-single exposure:

Test: oecd 11 3

toluene - CAS: 108-88-3

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LD50 - Route: Inhalation - Species: Rat > 20 mg/l - Duration: 4h

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

N-C12-16 ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE. - CAS: 68424-85-1

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae 670 $\mu\text{g/l}$ - Duration h: 96

Endpoint: EC50 - Species: Daphnia 5.9 ppb - Duration h: 48

Endpoint: LC50 - Species: Fish 0.28 Ppm - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia 0.025 mg/l - Duration h: 504

Esadeciltrimetilaammoniocloruro - CAS: 112-02-7

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48
octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2
- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish > 0.22 mg/l - Duration h: 96
Endpoint: LC50 - Species: Fish > 0.0063 mg/l - Duration h: 336
Endpoint: EC50 - Species: Daphnia > 0.015 mg/l - Duration h: 48
- b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Fish > 0.0044 mg/l - Duration h: 2232
Endpoint: NOEC - Species: Daphnia 0.0079 mg/l - Duration h: 504
- e) Plant toxicity:
Endpoint: CE6 - Species: Algae > 0.022 mg/l - Duration h: 72
DYPHENYL OXYDE - CAS: 101-84-8
- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish 4.2 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia 1.7 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae 0.455 mg/l - Duration h: 72
Endpoint: NOEC - Species: Algae 0.24 mg/l - Duration h: 72
2-Methyl-2H-isothiazol-3-one - CAS: 2682-20-4
- a) Aquatic acute toxicity:
Endpoint: LC50 - Species: Fish 4.77 mg/l - Duration h: 96
Endpoint: EC50 - Species: Daphnia 0.93-1.9 mg/l - Duration h: 48
Endpoint: EC50 - Species: Algae 0.0695 mg/l - Duration h: 24
- b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Daphnia 0.04 mg/l - Duration h: 504
Endpoint: NOEC - Species: Fish 2.1 mg/l - Duration h: 792
- 12.2. Persistence and degradability
None
N-C12-16 ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE. - CAS: 68424-85-1
Biodegradability: Readily biodegradable - Test: BIOGDG08 - Duration: 28gg - %: 61
Esadeciltrimetilaammoniocloruro - CAS: 112-02-7
Biodegradability: Readily biodegradable
octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2
Biodegradability: Non-readily biodegradable - Test: OECD TG 310 - Duration: 28gg - %: 3.7
2-Methyl-2H-isothiazol-3-one - CAS: 2682-20-4
Biodegradability: 4 - %: 0.38
- 12.3. Bioaccumulative potential
octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2
Test: BCF - Bioconcentration factor 12400
Test: log Pow 6.49
toluene - CAS: 108-88-3
Bioaccumulation: Bioaccumulative - Test: BCF - Bioconcentration factor 90
- 12.4. Mobility in soil
N.A.
- 12.5. Results of PBT and vPvB assessment
PBT Substances:
>= 0.001% - < 0.005% octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2
vPvB Substances:
>= 0.001% - < 0.005% octamethylcyclotetrasiloxane; [D4] - CAS: 556-67-2
- 12.6. Endocrine disrupting properties
No endocrine disruptor substances present in concentration >= 0.1%
- 12.7. Other adverse effects
None

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

14.6. Special precautions for user

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 40

Restriction 48

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



Restriction 70
Restriction 75

Volatile Organic compounds - VOCs = 1.01 %
Volatile Organic compounds - VOCs = 10.12 g/Kg
Volatile Organic compounds - VOCs = 10.10 g/l
Where applicable, refer to the following regulatory provisions :
Directive 2012/18/EU (Seveso III)
Regulation (EC) nr 648/2004 (detergents).
Dir. 2004/42/EC (VOC directive)

SVHC Substances:
Substances in candidate list (Art. 59 Reg. 1907/2006, REACH):
octamethylcyclotetrasiloxane; [D4]
PBT, vPvB

Provisions related to directive EU 2012/18 (Seveso III):
Seveso III category according to Annex 1, part 1
None

15.2. Chemical safety assessment
No Chemical Safety Assessment has been carried out for the mixture.
Substances for which a Chemical Safety Assessment has been carried out:
None

SECTION 16: Other information

Text of phrases referred to under heading 3:
H226 Flammable liquid and vapour.
H361f Suspected of damaging the unborn child.
H410 Very toxic to aquatic life with long lasting effects.
H302 Harmful if swallowed.
H373 (kidneys) (oral) May cause damage to organs (kidneys) through prolonged or repeated exposure if swallowed.
H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H400 Very toxic to aquatic life.
H311 Toxic in contact with skin.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H330 Fatal if inhaled.
H301 Toxic if swallowed.
H317 May cause an allergic skin reaction.
EUH071 Corrosive to the respiratory tract.
EUH208 Contains (name of sensitising substance). May produce an allergic reaction.
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Hazard class and hazard category	Code	Description
Met. Corr. 1	2.16/1	Substance or mixture corrosive to metals, Category 1

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 2	3.1/2/Inhal	Acute toxicity (inhalation), Category 2
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Corr. 1C	3.2/1C	Skin corrosion, Category 1C
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1A	3.4.2/1A	Skin Sensitisation, Category 1A
Repr. 2	3.7/2	Reproductive toxicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking
SECTION 2: Hazards identification
SECTION 3: Composition/information on ingredients
SECTION 4: First aid measures
SECTION 7: Handling and storage
SECTION 8: Exposure controls/personal protection
SECTION 11: Toxicological information
SECTION 12: Ecological information
SECTION 14: Transport information
SECTION 15: Regulatory information
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Safety Data Sheet

Cockpit Protectant - HIGH GLOSS



Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Skin Sens. 1A, H317	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.

Exposure Scenario, 19/07/2019

Substance identity	
Chemical name	ETHYLENE GLYCOL
CAS No.	107-21-1
EINECS No.	203-473-3

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Widespread use by professional workers
4. **ES 4** Consumer use; Various products (PC9a, PC1, PC4, PC8, PC15)

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1
CS3 Industrial	PROC2
CS4 Industrial	PROC3
CS5 Industrial	PROC4
CS6 Industrial	PROC8b
CS7 Industrial	PROC7
CS8 Industrial	PROC8a
CS9 Industrial	PROC10
CS10 Industrial	PROC13

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

1.2. CS2: Worker Contributing Scenario: Industrial (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS3: Worker Contributing Scenario: Industrial (PROC2)

Process Categories

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS4: Worker Contributing Scenario: Industrial (PROC3)

Process Categories

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS5: Worker Contributing Scenario: Industrial (PROC4)

Process Categories

Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS6: Worker Contributing Scenario: Industrial (PROC8b)**Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS7: Worker Contributing Scenario: Industrial (PROC7)**Process Categories**

Industrial spraying (PROC7)

Product (article) characteristics**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 1 L/min

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 5 days per week

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of: 90 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 1000 m³**1.2. CS8: Worker Contributing Scenario: Industrial (PROC8a)****Process Categories**

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics**Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

Ventilation rate: > 90 %

1.2. CS9: Worker Contributing Scenario: Industrial (PROC10)

Process Categories

Roller application or brushing (PROC10)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

1.2. CS10: Worker Contributing Scenario: Industrial (PROC13)

Process Categories

Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

1.3 Exposure estimation and reference to its source

1.3. CS2: Worker Contributing Scenario: Industrial (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.001
inhalative, local, long-term	N/A	EASY TRA v2.0	0.001
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.004

1.3. CS3: Worker Contributing Scenario: Industrial (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.07
inhalative, local, long-term	N/A	EASY TRA v2.0	0.07
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.08

1.3. CS4: Worker Contributing Scenario: Industrial (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.22
inhalative, local, long-term	N/A	EASY TRA v2.0	0.22
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.223

1.3. CS5: Worker Contributing Scenario: Industrial (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS6: Worker Contributing Scenario: Industrial (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37

inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS7: Worker Contributing Scenario: Industrial (PROC7)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.28
inhalative, local, long-term	N/A	EASY TRA v2.0	0.28
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.52
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.8

1.3. CS8: Worker Contributing Scenario: Industrial (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS9: Worker Contributing Scenario: Industrial (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.03
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.77

1.3. CS10: Worker Contributing Scenario: Industrial (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01

combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.75
--------------------------------------	-----	---------------	------

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers

2.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC3
CS5 General use from professional operators	PROC4
CS6 General use from professional operators	PROC8b
CS7 General use from professional operators	PROC8a
CS8 General use from professional operators	PROC10
CS9 General use from professional operators	PROC11
CS10 General use from professional operators	PROC13

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)**Process Categories**

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)**Process Categories**

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Process Categories Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Process Categories Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS7: Worker Contributing Scenario: General use from professional operators (PROC8a)

Process Categories Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %**2.2. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)****Process Categories**

Roller application or brushing (PROC10)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Wear suitable respiratory protection.

Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %**2.2. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)****Process Categories**

Non industrial spraying (PROC11)

Product (article) characteristics**Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 0.05 L/min

Duration:

Exposure duration 180 min

Frequency:

Use frequency < 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374. Use suitable eye protection.	Inhalation - minimum efficiency of: 90 %
Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 100 m³

Ventilation rate: 80 %

2.2. CS10: Worker Contributing Scenario: General use from professional operators (PROC13)

Process Categories Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency < 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374. Use suitable eye protection.	Inhalation - minimum efficiency of: 90 %
---	--

Other conditions affecting worker exposure

Indoor use

2.3 Exposure estimation and reference to its source

2.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.001
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.001
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.003

dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.004
-----------------------------	-----	------------------------	-------

2.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.01
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.38

2.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.22
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.22
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.003
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.223

2.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.006
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.8

2.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.06
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.8

2.3. CS7: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.13
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.5

2.3. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.3
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.4

2.3. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.4
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.4
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.51
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.91

2.3. CS10: Worker Contributing Scenario: General use from professional operators (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.01
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.75

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Widespread use by professional workers

3.1 TITLE SECTION

Exposure Scenario name	Use in antifreeze products
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8d
----------------	-------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC8a
CS5 General use from professional operators	PROC8b
CS6 General use from professional operators	PROC11

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

3.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

3.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Process Categories

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

3.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC8a)

Process Categories

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear suitable respiratory protection.

Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %

3.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC8b)

Process Categories

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

3.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC11)

Process Categories

Non industrial spraying (PROC11)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Exposure duration 180 min

Frequency:

Covers exposure up to 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of: 90 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 100 m³

3.3 Exposure estimation and reference to its source

3.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.001
inhalative, local, long-term	N/A	EASY TRA v2.0	0.001
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003

combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.004
--------------------------------------	-----	---------------	-------

3.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.38

3.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.13
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.5

3.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.8

3.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.4
inhalative, local, long-term	N/A	EASY TRA v2.0	0.4
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.51
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.91

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Consumer use; Various products (PC9a, PC1, PC4, PC8, PC15)

4.1 TITLE SECTION

Exposure Scenario name	Consumer goods
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Non-metal surface treatment products (PC15) - Heat transfer fluids (PC16) - Hydraulic fluids (PC17) - Ink and toners (PC18) - Leather treatment products (PC23) - Polishes and wax blends (PC31) - Polymer preparations and compounds (PC32) - Textile dyes and impregnating products (PC34) - Washing and cleaning products (PC35)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8c - ERC8d - ERC8f - ERC9a - ERC9b
-----------------------	---

Consumer Contributing Scenario

CS2 Consumer	PC1
CS3 Consumer	PC4 - PC16 - PC17 - PC4_1
CS4 Consumer	PC4 - PC4_2
CS5 Consumer	PC9a - PC15 - PC9a_2, PC15_2
CS6 Consumer	PC8
CS7 Consumer	PC18
CS8 Consumer	PC31
CS9 Consumer	PC32
CS10 Consumer	PC35 - PC8_2, PC35_2
CS11 Consumer	PC35 - PC8_3, PC35_3
CS12 Consumer	PC15 - PC23 - PC34 - PC9a_1, PC15_1

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8c, ERC8d, ERC8f, ERC9a, ERC9b)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use leading to inclusion into/onto article (indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) - Widespread use leading to inclusion into/onto article (outdoor) - Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC8a, ERC8c, ERC8d, ERC8f, ERC9a, ERC9b)
---	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

4.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Product Categories	Adhesives, sealants (PC1)
---------------------------	---------------------------

<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 0.75 %	
4.2. CS3: Consumer Contributing Scenario: Consumer (PC4, PC16, PC17)	
Product Categories	Anti-freeze and de-icing products - Heat transfer fluids - Hydraulic fluids (PC4, PC16, PC17)
Product (Sub-)Categories	Washing car window (PC4_1)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 45 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Exposure duration < 15 min	
4.2. CS4: Consumer Contributing Scenario: Consumer (PC4)	
Product Categories	Anti-freeze and de-icing products (PC4)
Product (Sub-)Categories	Pouring into radiator (PC4_2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
4.2. CS5: Consumer Contributing Scenario: Consumer (PC9a, PC15)	
Product Categories	Coatings and paints, thinners, paint removers - Non-metal surface treatment products (PC9a, PC15)
Product (Sub-)Categories	Solvent rich, high solid, water borne paint (PC9a_2, PC15_2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 10 %	
4.2. CS6: Consumer Contributing Scenario: Consumer (PC8)	
Product Categories	Biocidal products (PC8)
4.2. CS7: Consumer Contributing Scenario: Consumer (PC18)	
Product Categories	Ink and toners (PC18)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
4.2. CS8: Consumer Contributing Scenario: Consumer (PC31)	
Product Categories	Polishes and wax blends (PC31)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 10 %	
4.2. CS9: Consumer Contributing Scenario: Consumer (PC32)	
Product Categories	Polymer preparations and compounds (PC32)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
4.2. CS10: Consumer Contributing Scenario: Consumer (PC35)	

Product Categories	Washing and cleaning products (PC35)
Product (Sub-)Categories	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) (PC8_2, PC35_2)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 20 %

4.2. CS11: Consumer Contributing Scenario: Consumer (PC35)

Product Categories	Washing and cleaning products (PC35)
Product (Sub-)Categories	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (PC8_3, PC35_3)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

4.2. CS12: Consumer Contributing Scenario: Consumer (PC15, PC23, PC34)

Product Categories	Non-metal surface treatment products - Leather treatment products - Textile dyes and impregnating products (PC15, PC23, PC34)
Product (Sub-)Categories	Waterborne latex wall paint (PC9a_1, PC15_1)

4.3 Exposure estimation and reference to its source

4.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.59
dermal, systemic, long-term	N/A	N/A	0.005
combined routes, systemic, long-term	N/A	N/A	0.505

4.2. CS3: Consumer Contributing Scenario: Consumer (PC4, PC16, PC17)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.28
dermal, systemic, long-term	N/A	N/A	0.08
combined routes, systemic, long-term	N/A	N/A	0.36

4.2. CS4: Consumer Contributing Scenario: Consumer (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0
dermal, systemic, long-term	N/A	N/A	0.09
combined routes, systemic, long-term	N/A	N/A	0.09

4.2. CS5: Consumer Contributing Scenario: Consumer (PC9a, PC15)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.04
dermal, systemic, long-term	N/A	N/A	0.02
combined routes, systemic, long-term	N/A	N/A	0.06

4.2. CS6: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0
dermal, systemic, long-term	N/A	N/A	0.006
combined routes, systemic, long-term	N/A	N/A	0.006

4.2. CS7: Consumer Contributing Scenario: Consumer (PC18)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.18
dermal, systemic, long-term	N/A	N/A	0
combined routes, systemic, long-term	N/A	N/A	0.18

4.2. CS8: Consumer Contributing Scenario: Consumer (PC31)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.56
dermal, systemic, long-term	N/A	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.6

4.2. CS9: Consumer Contributing Scenario: Consumer (PC32)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.009
dermal, systemic, long-term	N/A	N/A	0.001
combined routes, systemic, long-term	N/A	N/A	0.01

4.2. CS10: Consumer Contributing Scenario: Consumer (PC35)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.09
dermal, systemic, long-term	N/A	N/A	0.22
combined routes, systemic, long-term	N/A	N/A	0.31

4.2. CS11: Consumer Contributing Scenario: Consumer (PC35)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.02
dermal, systemic, long-term	N/A	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.022

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.