

Ficha de datos de seguridad

Glass Cleaner



Ficha de datos de seguridad del 11/2/2022, Revisión 13

SECCIÓN 1. Identificación de la sustancia o la mezcla y de la sociedad o la empresa

1.1. Identificador de producto

Identificación del preparado:

Nombre comercial: Glass Cleaner

Código comercial: 31006

1.2. Usos pertinentes identificados de la sustancia o de la mezcla y usos desaconsejados

Uso recomendado:

Detergente/limpiador

1.3. Datos del proveedor de la ficha de datos de seguridad

Proveedor:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Persona competente responsable de la ficha de datos de seguridad:

arexons@arexons.it

1.4. Teléfono de emergencia

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Teléfono de emergencias: + 34 91 562 04 20 (Solo emergencias toxicológicas. Información en español (24h/365 días))

SECCIÓN 2. Identificación de los peligros

2.1. Clasificación de la sustancia o de la mezcla

Criterios Reglamentación CE 1272/2008 (Clasificación, Etiquetado y Empacado):

El producto no se considera peligroso de acuerdo con el Reglamento CE 1272/2008 (CLP).

Efectos físico-químicos nocivos para la salud humana y para el medio ambiente:

Ningún otro riesgo

2.2. Elementos de la etiqueta

El producto no se considera peligroso de acuerdo con el Reglamento CE 1272/2008 (CLP).

Pictogramas de peligro:

Ninguna

Indicaciones de peligro:

Ninguna

Consejos de prudencia:

Ninguna

Disposiciones especiales:

Ninguna

Disposiciones especiales de acuerdo con el anexo XVII del Reglamento REACH y sus posteriores modificaciones:

Ninguna

Reglamento (CE) no 648/2004 (detergentes).

Contiene también: Perfumes

2.3. Otros peligros

Ninguna sustancia PBT, mPmB o perturbador endocrino presente en concentración $\geq 0.1\%$

Otros riesgos:

Ficha de datos de seguridad

Glass Cleaner



Ningún otro riesgo

SECCIÓN 3. Composición/información sobre los componentes

3.1. Sustancias

N.A.

3.2. Mezclas

Componentes peligrosos según el Reglamento CLP y su correspondiente clasificación:

>= 5% - < 7% alcohol etílico

REACH No.: 01-2119457610-43, CAS: 64-17-5, EC: 200-578-6

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

Límites de concentración específicos:

C >= 50%: Eye Irrit. 2 H319

>= 2% - < 3% 3-Butoxiopropan-2-ol; éter monobutílico de propilenglicol

REACH No.: 01-2119475527-28, Número Index: 603-052-00-8, CAS: 5131-66-8, EC: 225-878-4

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/2 Eye Irrit. 2 H319

Límites de concentración específicos:

C >= 20%: undefined H315;3.3/2;H319

SECCIÓN 4. Primeros auxilios

4.1. Descripción de los primeros auxilios

En caso de contacto con la piel:

Lavar abundantemente con agua y jabón.

En caso de contacto con los ojos:

En caso de contacto con los ojos, lávense inmediata y abundantemente con agua y acúdase a un médico.

En caso de ingestión:

No provocar el vómito en ningún caso. CONSULTAR INMEDIATAMENTE AL MÉDICO.

En caso de inhalación:

Llevar al accidentado al aire libre y mantenerlo en reposo y abrigado.

4.2. Principales síntomas y efectos, agudos y retardados

Ninguno

4.3. Indicación de toda atención médica y de los tratamientos especiales que deban dispensarse inmediatamente

Tratamiento:

Ninguno

SECCIÓN 5. Medidas de lucha contra incendios

5.1. Medios de extinción

Medios de extinción apropiados:

Con anhídrido carbónico.

Con polvo.

Espuma

Agua vaporizada.

Medios de extinción no recomendados:

No usar chorros de agua directos

Ficha de datos de seguridad

Glass Cleaner



- 5.2. Peligros específicos derivados de la sustancia o la mezcla
No inhalar los gases producidos por la explosión y por la combustión.
La combustión produce humo pesado.
- 5.3. Recomendaciones para el personal de lucha contra incendios
Utilizar equipos respiratorios apropiados.
Recoger por separado el agua contaminada utilizada para extinguir el incendio. No descargarla en la red de alcantarillado.
Si es posible, desde el punto de vista de la seguridad, retirar de inmediato del área los contenedores no dañados.

SECCIÓN 6. Medidas en caso de vertido accidental

- 6.1. Precauciones personales, equipo de protección y procedimientos de emergencia
Usar los dispositivos de protección individual.
Llevar las personas a un lugar seguro.
Consultar las medidas de protección expuestas en los puntos 7 y 8.
- 6.2. Precauciones relativas al medio ambiente
Evitar que el producto penetre en el suelo/subsuelo. Evitar que penetre en aguas superficiales o en el alcantarillado.
Conservar el agua de lavado contaminada y eliminarla.
En caso de fuga de gas o penetración en cursos de agua, suelo o sistema de alcantarillado, informar a las autoridades responsables.
Material apropiado para la recogida: material absorbente, orgánico, arena
- 6.3. Métodos y material de contención y de limpieza
Lavar con abundante agua.
- 6.4. Referencia a otras secciones
Véanse también los apartados 8 y 13.

SECCIÓN 7. Manipulación y almacenamiento

- 7.1. Precauciones para una manipulación segura
Evitar el contacto con la piel y los ojos, la inhalación de vapores y vahos.
Remitirse también al apartado 8 para los dispositivos de protección recomendados.
- No comer ni beber durante el trabajo.
- 7.2. Condiciones de almacenamiento seguro, incluidas posibles incompatibilidades
Mantener alejado de comidas, bebidas y piensos.
Ninguna en particular.
Indicaciones para los locales:
Locales adecuadamente aireados.
- 7.3. Usos específicos finales
Ningún uso particular

SECCIÓN 8. Controles de exposición/protección individual

- 8.1. Parámetros de control
alcohol etílico - CAS: 64-17-5
ACGIH - STEL: 1000 ppm - Notas: A3 - URT irr
- Valores límites de exposición DNEL
alcohol etílico - CAS: 64-17-5
Trabajador profesional: 1900 mg/m³ - Exposición: Por inhalación humana - Frecuencia: A corto plazo (aguda)
Trabajador profesional: 950 mg/m³ - Exposición: Por inhalación humana - Frecuencia: A largo plazo, efectos sistémicos
Trabajador profesional: 343 mg/kg - Exposición: Dérmica humana - Frecuencia: A largo plazo, efectos sistémicos
- 3-Butoxiopropan-2-ol; éter monobutílico de propilenglicol - CAS: 5131-66-8

Ficha de datos de seguridad Glass Cleaner



Trabajador profesional: 52 mg/kg - Consumidor: 22 mg/kg - Exposición: Dérmica humana
- Frecuencia: A largo plazo, efectos sistémicos

Trabajador profesional: 147 mg/m³ - Consumidor: 43 mg/m³ - Exposición: Por inhalación humana - Frecuencia: A largo plazo, efectos sistémicos

Consumidor: 12.5 mg/kg - Exposición: Oral humana - Frecuencia: A largo plazo, efectos sistémicos

Valores límites de exposición PNEC

alcohol etílico - CAS: 64-17-5

Objetivo: agua dulce - Valor: 0.96 mg/l

Objetivo: Agua marina - Valor: 0.79 mg/l

Objetivo: Sedimentos de agua dulce - Valor: 3.6 mg/kg

Objetivo: Sedimentos de agua marina - Valor: 2.9 mg/kg

Objetivo: 09 - Valor: 580 mg/l

3-Butoxipropan-2-ol; éter monobutílico de propilenglicol - CAS: 5131-66-8

Objetivo: agua dulce - Valor: 0.525 mg/l

Objetivo: Agua marina - Valor: 0.0525 mg/l

Objetivo: 09 - Valor: 10 mg/l

Objetivo: Sedimentos de agua dulce - Valor: 2.36 mg/kg

Objetivo: Sedimentos de agua marina - Valor: 0.236 mg/kg

8.2. Controles de la exposición

Protección de los ojos:

Gafas con protección lateral.

Cumple con la norma EN 166

Protección de la piel:

No se requiere ninguna precaución especial para el uso normal.

Protección de las manos:

Guantes de nitrilo o de Viton.

Conformes EN 374.

Protección respiratoria:

No necesaria para el uso normal.

Riesgos térmicos:

Ninguno

Controles de la exposición ambiental:

Ninguno

Controles técnicos apropiados:

Ninguno

SECCIÓN 9. Propiedades físicas y químicas

9.1. Información sobre propiedades físicas y químicas básicas

Propiedad	Valor	Método:	Notas
Estado físico:	Líquido	--	--
Color:	Verde	--	--
Olor:	característico	--	--
Punto de fusión/punto de congelación:	N.A.	--	--
Punto de ebullición o punto inicial de ebullición e intervalo de ebullición:	N.A.	--	--
Inflamabilidad:	N.A.	--	--

Ficha de datos de seguridad Glass Cleaner



Límite superior e inferior de explosividad:	N.A.	--	--
Punto de ignición (flash point, fp):	(46°C) Not flammable for ADR/CLP	--	--
Temperatura de autoencendido:	N.A.	--	--
Temperatura de descomposición:	N.A.	--	--
pH:	10.7	--	--
Viscosidad cinemática:	N.A.	--	--
Hidrosolubilidad:	N.A.	--	--
Solubilidad en aceite:	N.A.	--	--
Coefficiente de reparto n-octanol/agua (valor logarítmico):	N.A.	--	--
Presión de vapor:	N.A.	--	--
Densidad y/o densidad relativa:	0.989 g/cm ³	--	--
Densidad de vapor relativa:	N.A.	--	--
Características de las partículas:			
Tamaño de las partículas:	N.A.	--	--

9.2. Otros datos

Ninguna otra información relevante

SECCIÓN 10. Estabilidad y reactividad

10.1. Reactividad

Estable en condiciones normales

10.2. Estabilidad química

Estable en condiciones normales

10.3. Posibilidad de reacciones peligrosas

Puede generar gases inflamables en contacto con ditiocarbamatos, mercaptanos y otros sulfuros orgánicos, elementos metálicos (alcalinos, alcalinotérreos, aleaciones en polvo o vapor) y agentes reductores fuertes.

Puede generar gases tóxicos en contacto con fluoruros inorgánicos, sustancias orgánicas halogenadas, sulfuros, nitruros, nitrilos, compuestos organofosforados, fosfotioatos, fosfoditioatos y agentes oxidantes fuertes.

Puede inflamarse en contacto con ditiocarbamatos, elementos metálicos (alcalinos, alcalinotérreos, aleaciones en polvo o vapor, láminas o barras) y nitruros.

10.4. Condiciones que deben evitarse

Estable en condiciones normales.

Ficha de datos de seguridad

Glass Cleaner



- 10.5. Materiales incompatibles
Ninguna en particular.
- 10.6. Productos de descomposición peligrosos
Ninguno.

SECCIÓN 11. Información toxicológica

11.1. Información sobre las clases de peligro definidas en el Reglamento (CE) n.o 1272/2008

Información toxicológica del producto:

Glass Cleaner

- a) toxicidad aguda
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- b) corrosión o irritación cutáneas
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- c) lesiones o irritación ocular graves
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- d) sensibilización respiratoria o cutánea
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- e) mutagenicidad en células germinales
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- f) carcinogenicidad
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- g) toxicidad para la reproducción
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- h) toxicidad específica en determinados órganos (STOT) – exposición única
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- i) toxicidad específica en determinados órganos (STOT) – exposición repetida
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- j) peligro de aspiración
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.

La información toxicológica de las sustancias principales halladas en el producto:

alcohol etílico - CAS: 64-17-5

- d) sensibilización respiratoria o cutánea:
Ensayo: Sensibilización de la piel - Vía: Piel Negativo
 - e) mutagenicidad en células germinales:
Ensayo: Genotoxicidad - Especies: vitro Negativo
 - f) carcinogenicidad:
Ensayo: Carcinogenicidad - Especies: mam Positivo
 - g) toxicidad para la reproducción:
Ensayo: NOAEL - Vía: Inhalación - Especies: Rata = 1600 ppm
- 3-Butoxipropan-2-ol; éter monobutílico de propilenglicol - CAS: 5131-66-8
- a) toxicidad aguda:
Ensayo: LD50 - Vía: Oral - Especies: Rata 3300 mg/kg
Ensayo: LD50 - Vía: Piel - Especies: Rata > 2000 mg/kg
Ensayo: LC50 - Vía: Inhalación - Especies: Rata > 3.5 mg/l - Duración: 4h

11.2. Información relativa a otros peligros

31006/13

Página nº. 6 de 10

Ficha de datos de seguridad Glass Cleaner



Propiedades de alteración endocrina:
Ningún perturbador endocrino presente en concentración $\geq 0.1\%$

SECCIÓN 12. Información ecológica

12.1. Toxicidad

Utilícese con técnicas de trabajo adecuadas, evitando la dispersión del producto en el medio ambiente.

alcohol etílico - CAS: 64-17-5

a) Toxicidad acuática aguda:

Parámetro: LC50 - Especies: Peces 14.2 GL - Duración h.: 96

Parámetro: LC50 - Especies: Daphnia 29.6 GL - Duración h.: 24

Parámetro: EC50 - Especies: Algas 19000 mg/l - Duración h.: 96

Parámetro: EC50 - Especies: batteri 39.5 GL - Duración h.: 4

b) Toxicidad acuática crónica:

Parámetro: EC50 - Especies: Peces 14536 mg/l - Duración h.: 200

Parámetro: LC50 - Especies: Daphnia 9248 mg/l - Duración h.: 48

3-Butoxiopropan-2-ol; éter monobutílico de propilenglicol - CAS: 5131-66-8

a) Toxicidad acuática aguda:

Parámetro: LC50 - Especies: Peces > 560 mg/l - Duración h.: 96

Parámetro: EC50 - Especies: Daphnia > 1000 mg/l - Duración h.: 48

Parámetro: EC50 - Especies: Algas > 1000 mg/l - Duración h.: 96

Parámetro: EC50 - Especies: fanghi > 1000 mg/l - Duración h.: 3

b) Toxicidad acuática crónica:

Parámetro: NOEC - Especies: Algas 560 mg/l - Duración h.: 96

12.2. Persistencia y degradabilidad

Ninguno

3-Butoxiopropan-2-ol; éter monobutílico de propilenglicol - CAS: 5131-66-8

Biodegradabilidad: Rápidamente degradable - Ensayo: BIOGDG12 - Duración h.: 28gg -
%: 90

12.3. Potencial de bioacumulación

N.A.

12.4. Movilidad en el suelo

N.A.

12.5. Resultados de la valoración PBT y mPmB

Sustancias vPvB: Ninguna - Sustancias PBT: Ninguna

12.6. Propiedades de alteración endocrina

Ningún perturbador endocrino presente en concentración $\geq 0.1\%$

12.7. Otros efectos adversos

Ninguno

SECCIÓN 13. Consideraciones relativas a la eliminación

13.1. Métodos para el tratamiento de residuos

Recuperar si es posible. Operar conforme con las disposiciones locales y nacionales vigentes.

SECCIÓN 14. Información relativa al transporte

14.1. Número ONU o número ID

Producto no peligroso según los criterios de la reglamentación del transporte.

14.2. Designación oficial de transporte de las Naciones Unidas

N.A.

14.3. Clase(s) de peligro para el transporte

N.A.

14.4. Grupo de embalaje

31006/13

Página nº. 7 de 10

Ficha de datos de seguridad Glass Cleaner



- N.A.
- 14.5. Peligros para el medio ambiente
ADR-Contaminante ambiental: No
IMDG-Marine pollutant: No
- 14.6. Precauciones particulares para los usuarios
N.A.
- 14.7. Transporte marítimo a granel con arreglo a los instrumentos de la OMI
N.A.

SECCIÓN 15. Información reglamentaria

15.1. Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

Dir. 98/24/CE (Riesgos relacionados con los agentes químicos durante el trabajo)

Dir. 2000/39/CE (Valores límite de exposición profesional)

Reglamento (CE) n. 1907/2006 (REACH)

Reglamento (CE) n. 1272/2008 (CLP)

Reglamento (CE) n. 790/2009 (ATP 1 CLP) y (UE) n. 758/2013

Reglamento (UE) n. 2020/878

Reglamento (UE) n. 286/2011 (ATP 2 CLP)

Reglamento (UE) n. 618/2012 (ATP 3 CLP)

Reglamento (UE) n. 487/2013 (ATP 4 CLP)

Reglamento (UE) n. 944/2013 (ATP 5 CLP)

Reglamento (UE) n. 605/2014 (ATP 6 CLP)

Reglamento (UE) n. 2015/1221 (ATP 7 CLP)

Reglamento (UE) n. 2016/918 (ATP 8 CLP)

Reglamento (UE) n. 2016/1179 (ATP 9 CLP)

Reglamento (UE) n. 2017/776 (ATP 10 CLP)

Reglamento (UE) n. 2018/669 (ATP 11 CLP)

Reglamento (UE) n. 2018/1480 (ATP 13 CLP)

Reglamento (UE) n. 2019/521 (ATP 12 CLP)

Reglamento (UE) n. 2020/217 (ATP 14 CLP)

Reglamento (UE) n. 2020/1182 (ATP 15 CLP)

Reglamento (UE) n. 2021/643 (ATP 16 CLP)

Restricciones relacionadas con el producto o las sustancias contenidas, de acuerdo con el anexo XVII del Reglamento (CE) 1907/2006 (REACH) y las modificaciones posteriores:

Restricciones relacionadas con el producto:

Ninguna restricción.

Restricciones relacionadas con las sustancias contenidas:

Restricción 40

Restricción 75

Compuestos orgánicos volátiles - COV = 7.65 %

Compuestos orgánicos volátiles - COV = 76.46 g/Kg

Compuestos orgánicos volátiles - COV = 75.62 g/l

Cuando sean aplicables, hágase referencia a las siguientes normativas:

Directiva 2012/18/EU (Seveso III)

Reglamento (CE) no 648/2004 (detergentes).

Dir. 2004/42/CE (directiva COV)

Disposiciones sobre la directiva EU 2012/18 (Seveso III):

Categoría Seveso III de acuerdo con el anexo 1, parte 1
el producto pertenece a la categoría: P5c

15.2. Evaluación de la seguridad química

No se ha realizado ninguna evaluación de la seguridad química para la mezcla

Sustancias para las cuales se ha realizado una evaluación de la seguridad química

Ficha de datos de seguridad

Glass Cleaner



alcohol etílico
3-Butoxipropan-2-ol; éter monobutílico de propilenglicol

SECCIÓN 16. Otra información

Texto de las frases utilizadas en el párrafo 3:
H225 Líquido y vapores muy inflamables.
H319 Provoca irritación ocular grave.
H315 Provoca irritación cutánea.
H315;3

Clase y categoría de peligro	Código	Descripción
Flam. Liq. 2	2.6/2	Líquidos inflamables, Categoría 2
undefined	3.2/2	Irritación cutánea, Categoría 2
Skin Irrit. 2	3.2/2	Irritación cutánea, Categoría 2
Eye Irrit. 2	3.3/2	Irritación ocular, Categoría 2

Parágrafos modificados respecto la revisión anterior

SECCIÓN 1. Identificación de la sustancia o la mezcla y de la sociedad o la empresa
SECCIÓN 3. Composición/información sobre los componentes
SECCIÓN 15. Información reglamentaria

Este documento ha sido preparado por una persona competente que ha recibido un entrenamiento adecuado

Principales fuentes bibliográficas:

ECDIN: Environmental Chemicals Data and Information Network, Centro Común de Investigación, Comisión de las Comunidades Europeas
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS, 8ª ed., Van Nostrand Reinold

La información aquí detallada se basa en nuestros conocimientos hasta la fecha señalada arriba. Se refiere exclusivamente al producto indicado y no constituye garantía de cualidades particulares. El usuario debe asegurarse de la idoneidad y exactitud de dicha información en relación al uso específico que debe hacer del producto.

Esta ficha anula y sustituye toda edición precedente.

ADR: Acuerdo europeo relativo al transporte internacional de mercancías peligrosas por carretera.
CAS: Chemical Abstracts Service (de la American Chemical Society).
CLP: Clasificación, etiquetado, embalaje.
DNEL: Nivel sin efecto derivado.
EINECS: Catálogo Europeo de Sustancias Químicas Comercializadas.
ETA: Estimación de la toxicidad aguda
ETAmix: Estimación de Toxicidad Aguda (Mezclas)
GefStoffVO: Ordenanza sobre sustancias peligrosas, Alemania.
GHS: Sistema Globalmente Armonizado de clasificación y etiquetado de productos químicos.
IATA: Asociación de Transporte Aéreo Internacional.
IATA-DGR: Normas aplicadas a las mercancías peligrosas por la "Asociación de Transporte Aéreo Internacional" (IATA).

Ficha de datos de seguridad Glass Cleaner



ICAO:	Organización de la Aviación Civil Internacional.
ICAO-TI:	Instrucciones Técnicas de la "Organización de la Aviación Civil Internacional" (OACI).
IMDG:	Código marítimo internacional de mercancías peligrosas.
INCI:	Nomenclatura internacional de ingredientes cosméticos.
KSt:	Coefficiente de explosión.
LC50:	Concentración letal para el 50% de la población expuesta.
LD50:	Dosis letal para el 50% de la población expuesta.
NA:	No aplicable
PNEC:	Concentración prevista sin efecto.
RID:	Normas relativas al transporte internacional de mercancías peligrosas por ferrocarril.
STEL:	Nivel de exposición de corta duración.
STOT:	Toxicidad específica en determinados órganos.
TLV:	Valor límite del umbral.
TWA:	Promedio ponderado en el tiempo
WGK:	Clase de peligro para las aguas (Alemania).

Exposure Scenario, 23/07/2019

Substance identity	
Chemical name	Etanolo
CAS No.	64-17-5
EINECS No.	200-578-6

Table of contents

1. **ES 1** Consumer use; Anti-freeze and de-icing products (PC4)
2. **ES 2** Consumer use; Various products (PC39, PC28)
3. **ES 3** Use at industrial site
4. **ES 4** Use at industrial site
5. **ES 5** Widespread use by professional workers
6. **ES 6** Widespread use by professional workers
7. **ES 7** Consumer use; Fuels (PC13)
8. **ES 8** Consumer use; Various products (PC1, PC3, PC8, PC18, PC23)

1. ES 1 Consumer use; Anti-freeze and de-icing products (PC4)

1.1 TITLE SECTION

Exposure Scenario name	Car care and maintenance products - De-icing and anti-icing applications
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Anti-freeze and de-icing products (PC4)

Environment Contributing Scenario

CS1 Covered by	ERC8d
----------------	-------

Consumer Contributing Scenario

CS2 Car Care - De-icing and anti-icing applications	PC4 - PC4_1
CS3 Car Care - De-icing and anti-icing applications	PC4 - PC4_2
CS4 Car Care - De-icing and anti-icing applications	PC4 - PC4_3

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

5726 Pa

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

No specific measures identified.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

1.2. CS2: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Product Categories	Anti-freeze and de-icing products (PC4)
Product (Sub-)Categories	Washing car window (PC4_1)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 1 %.

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 0.5 g

Duration:

Covers use up to 0.017 h/event

Frequency:

Covers use up to 1 uses per day

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

1.2. CS3: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Product Categories	Anti-freeze and de-icing products (PC4)
---------------------------	---

Product (Sub-)Categories	Pouring into radiator (PC4_2)
---------------------------------	-------------------------------

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 10 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 2000 g

Duration:

Covers use up to 0.17 h/event

Frequency:

Covers use up to 1 uses per day

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

Additional conditions human health

Covers skin contact area up to 482 cm²

1.2. CS4: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Product Categories	Anti-freeze and de-icing products (PC4)
---------------------------	---

Product (Sub-)Categories	Lock de-icer (PC4_3)
---------------------------------	----------------------

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 50 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 4 g

Duration:

Covers use up to 0.25 h/event

Frequency:

Covers use up to 1 uses per day

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

Additional conditions human health

Covers skin contact area up to 214 cm²

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario: Covered by (ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00443 mg/L	N/A	0.00461
freshwater sediment	0.0172 mg/kg bw/day	N/A	0.00467
marine water	0.000508 mg/L	N/A	0.000643
marine sediment	0.00194 mg/kg bw/day	N/A	0.00064
soil	0.00123 mg/kg bw/day	N/A	0.00724

1.2. CS2: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.000102 mg/m ³	N/A	8.94E-07
inhalative, local, short-term	0.000102 mg/m ³	N/A	8.94E-07
dermal, systemic, long-term	0 mg/kg bw/day	N/A	N/A
combined routes, systemic, long-term	N/A	N/A	8.94E-07

1.2. CS3: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	1.84 mg/m ³	N/A	0.0161
inhalative, local, short-term	1.84 mg/m ³	N/A	0.0161
dermal, systemic, long-term	5.62 mg/kg bw/day	N/A	0.0272
combined routes, systemic, long-term	N/A	N/A	0.0434

1.2. CS4: Consumer Contributing Scenario: Car Care - De-icing and anti-icing applications (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.51 mg/m ³	N/A	0.00447
inhalative, local, short-term	0.51 mg/m ³	N/A	0.0447
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.0679
combined routes, systemic, long-term	N/A	N/A	0.0724

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Consumer use; Various products (PC39, PC28)

2.1 TITLE SECTION

Exposure Scenario name	Cosumer other uses
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Cosmetics, personal care products (PC39) - Perfumes, fragrances (PC28)

Environment Contributing Scenario

CS1 Covered by	ERC8a
----------------	-------

Consumer Contributing Scenario

CS2 Consumer	PC39 - PC28
--------------	-------------

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) (ERC8a)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

5726 Pa

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

No specific measures identified.

2.2. CS2: Consumer Contributing Scenario: Consumer (PC39, PC28)

Product Categories	Cosmetics, personal care products - Perfumes, fragrances (PC39, PC28)
--------------------	---

2.3 Exposure estimation and reference to its source

2.3. CS1: Environment Contributing Scenario: Covered by (ERC8a)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.00236 mg/L	N/A	0.00246
freshwater sediment	0.00904 mg/kg bw/day	N/A	0.00246
marine water	0.000301 mg/L	N/A	0.000381
marine sediment	0.00115 mg/kg bw/day	N/A	0.00038
soil	0.00115 mg/kg bw/day	N/A	0.00676

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Use at industrial site

3.1 TITLE SECTION

Exposure Scenario name	Solvent
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1
CS3 Industrial	PROC2
CS4 Industrial	PROC3
CS5 Industrial	PROC4
CS6 Industrial	PROC5
CS7 Industrial	PROC7
CS8 Industrial	PROC8a
CS9 Industrial	PROC8b
CS10 Industrial	PROC10
CS11 Industrial	PROC13
CS12 Industrial	PROC15

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Product (article) characteristics

Vapour pressure:
< 10 kPa

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 3000 t(tonnes)/year

Maximum allowable site tonnage (MSafe): 124000 kg/day

Release type: Continuous release

Emission days: 300 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 90 %
Prevent discharge of undissolved substance to or recover from onsite wastewater.	Water - minimum efficiency of: 87 %

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Incineration, disposal or recycling at specific offsite provider Contain and dispose of waste according to local regulations.	Waste - minimum efficiency of: 99.98 %
--	--

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 2000 m³/h

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Contain leaks or spills within cabinets with removable trays.

3.2. CS2: Worker Contributing Scenario: Industrial (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Covers use at ambient temperatures.

3.2. CS3: Worker Contributing Scenario: Industrial (PROC2)

Process Categories	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
---------------------------	--

Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: < 10 kPa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Use in contained systems Store substance within a closed system.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Use suitable eye protection.	
Other conditions affecting worker exposure	
Temperature: Covers use at ambient temperatures.	
3.2. CS4: Worker Contributing Scenario: Industrial (PROC3)	
Process Categories	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: < 10 kPa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Use in contained systems Store substance within a closed system.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Use suitable eye protection.	
Other conditions affecting worker exposure	
Temperature: Covers use at ambient temperatures.	
3.2. CS5: Worker Contributing Scenario: Industrial (PROC4)	
Process Categories	Chemical production where opportunity for exposure arises (PROC4)
Product (article) characteristics	

Physical form of product: Liquid	
Vapour pressure: < 10 kPa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Use in contained systems Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Use suitable eye protection.	
<i>Other conditions affecting worker exposure</i>	
Temperature: Covers use at ambient temperatures.	
3.2. CS6: Worker Contributing Scenario: Industrial (PROC5)	
Process Categories	Mixing or blending in batch processes (PROC5)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Vapour pressure: < 10 kPa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Use in contained systems Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Use suitable eye protection.	
<i>Other conditions affecting worker exposure</i>	
Temperature: Covers use at ambient temperatures.	
3.2. CS7: Worker Contributing Scenario: Industrial (PROC7)	
Process Categories	Industrial spraying (PROC7)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Covers use at ambient temperatures.

3.2. CS8: Worker Contributing Scenario: Industrial (PROC8a)**Process Categories**

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics**Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Covers use at ambient temperatures.

3.2. CS9: Worker Contributing Scenario: Industrial (PROC8b)**Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics**Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Covers use at ambient temperatures.

3.2. CS10: Worker Contributing Scenario: Industrial (PROC10)**Process Categories**

Roller application or brushing (PROC10)

Product (article) characteristics**Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Covers use at ambient temperatures.

3.2. CS11: Worker Contributing Scenario: Industrial (PROC13)**Process Categories**

Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics**Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

Other conditions affecting worker exposure**Temperature:** Covers use at ambient temperatures.**3.2. CS12: Worker Contributing Scenario: Industrial (PROC15)****Process Categories**

Use as laboratory reagent (PROC15)

Product (article) characteristics**Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Use in contained systems

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

Other conditions affecting worker exposure**Temperature:** Covers use at ambient temperatures.**3.3 Exposure estimation and reference to its source****3.3. CS1: Environment Contributing Scenario: Covered by (ERC4)**

Release route	Release rate	Release estimation method
Air	0.98 %	N/A
Water	0.01 %	N/A
soil	0 %	N/A

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	6.32 mg/L	N/A	0.0109
freshwater	0.577 mg/L	N/A	0.601
freshwater sediment	2.21 mg/kg bw/day	N/A	0.601
marine water	0.0635 mg/L	N/A	0.0804
marine sediment	0.0635 mg/kg bw/day	N/A	0.0805
soil	0.0525 mg/kg bw/day	N/A	0.309

3.3. CS2: Worker Contributing Scenario: Industrial (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m ³	N/A	< 0.01
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.01
combined routes, systemic, long-term	N/A	N/A	< 0.01

3.3. CS3: Worker Contributing Scenario: Industrial (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m ³	N/A	0.01
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0141

3.3. CS4: Worker Contributing Scenario: Industrial (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m ³	N/A	0.02
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.0222

3.3. CS5: Worker Contributing Scenario: Industrial (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, systemic, long-term	38 mg/m ³	N/A	0.04
dermal, systemic, long-term	6.9 mg/kg bw/day	N/A	0.02
combined routes, systemic, long-term	N/A	N/A	0.0603

3.3. CS6: Worker Contributing Scenario: Industrial (PROC5)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m ³	N/A	0.101
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

3.3. CS7: Worker Contributing Scenario: Industrial (PROC7)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	140 mg/m ³	N/A	0.151
dermal, systemic, long-term	43 mg/kg bw/day	N/A	0.125
combined routes, systemic, long-term	N/A	N/A	0.276

3.3. CS8: Worker Contributing Scenario: Industrial (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m ³	N/A	0.101
dermal, systemic, long-term	96 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

3.3. CS9: Worker Contributing Scenario: Industrial (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m ³	N/A	0.05
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.0904

3.3. CS10: Worker Contributing Scenario: Industrial (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, systemic, long-term	96 mg/m ³	N/A	0.101
dermal, systemic, long-term	27 mg/kg bw/day	N/A	0.08
combined routes, systemic, long-term	N/A	N/A	0.181

3.3. CS11: Worker Contributing Scenario: Industrial (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m ³	N/A	0.101
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

3.3. CS12: Worker Contributing Scenario: Industrial (PROC15)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m ³	N/A	0.02
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.01
combined routes, systemic, long-term	N/A	N/A	0.0212

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Use at industrial site

4.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	22/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC7
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1
CS3 Industrial	PROC2
CS4 Industrial	PROC3
CS5 Industrial	PROC8a
CS6 Industrial	PROC8b
CS7 Industrial	PROC15
CS8 Industrial	PROC16

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Covered by (ERC7)

Environmental release categories	Use of functional fluid at industrial site (ERC7)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 10 kPa

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 20000 t(tonnes)/year

Maximum allowable site tonnage (MSafe): 14500000 kg/day

Release type: Continuous release

Emission days: 300 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Provide onsite wastewater removal efficiency of ³ (%):

Water - minimum efficiency of: 87 %

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 87 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Product residual disposal complies with applicable regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 2000 m³/day

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Adequate closed storage facilities (e.g., bulk storage tanks, intermediate bulk containers, drums) are required.

4.2. CS2: Worker Contributing Scenario: Industrial (PROC1)

Process Categories

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Handle substance within a closed system.
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

4.2. CS3: Worker Contributing Scenario: Industrial (PROC2)

Process Categories

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Handle substance within a closed system. Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Use suitable eye protection.	
4.2. CS4: Worker Contributing Scenario: Industrial (PROC3)	
Process Categories	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Vapour pressure: < 10 kPa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Handle substance within a closed system. Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Use suitable eye protection.	
4.2. CS5: Worker Contributing Scenario: Industrial (PROC8a)	
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Vapour pressure: < 10 kPa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Handle substance within a closed system. Store substance within a closed system.	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	

Personal protection

Use suitable eye protection.

4.2. CS6: Worker Contributing Scenario: Industrial (PROC8b)**Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

*Product (article) characteristics***Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

4.2. CS7: Worker Contributing Scenario: Industrial (PROC15)**Process Categories**

Use as laboratory reagent (PROC15)

*Product (article) characteristics***Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

4.2. CS8: Worker Contributing Scenario: Industrial (PROC16)**Process Categories**

Use of fuels (PROC16)

*Product (article) characteristics***Physical form of product:**

Liquid

Vapour pressure:

< 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure**Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures**Technical and organisational measures**

Handle substance within a closed system.

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

4.3 Exposure estimation and reference to its source**4.3. CS1: Environment Contributing Scenario: Covered by (ERC7)**

Release route	Release rate	Release estimation method
Air	0.0025 %	N/A
Water	1E-05 %	N/A
soil	0 %	N/A

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	0.0421 mg/L	N/A	7.26E-05
freshwater	0.00657 mg/L	N/A	0.00684
freshwater sediment	0.00685 mg/kg bw/day	N/A	0.00685
marine water	0.00363 mg/L	N/A	0.00459
marine sediment	0.0139 mg/kg bw/day	N/A	0.00459
soil	0.00694 mg/kg bw/day	N/A	0.0408

4.3. CS2: Worker Contributing Scenario: Industrial (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m ³	N/A	< 0.001
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	< 0.001

4.3. CS3: Worker Contributing Scenario: Industrial (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m ³	N/A	0.01
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0222

4.3. CS4: Worker Contributing Scenario: Industrial (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m ³	N/A	0.02
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.222

4.3. CS5: Worker Contributing Scenario: Industrial (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m ³	N/A	0.101
dermal, systemic, long-term	14 mg/m ³	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

4.3. CS6: Worker Contributing Scenario: Industrial (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m ³	N/A	0.05
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.0904

4.3. CS7: Worker Contributing Scenario: Industrial (PROC15)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m ³	N/A	0.02
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.001

combined routes, systemic, long-term	N/A	N/A	0.0112
--------------------------------------	-----	-----	--------

4.3. CS8: Worker Contributing Scenario: Industrial (PROC16)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	9.6 mg/m ³	N/A	0.01
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	0.0111

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

5. ES 5 Widespread use by professional workers

5.1 TITLE SECTION

Exposure Scenario name	Solvent
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC3
CS5 General use from professional operators	PROC4
CS6 General use from professional operators	PROC5 - PROC8a
CS7 General use from professional operators	PROC8b
CS8 General use from professional operators	PROC10
CS9 General use from professional operators	PROC11
CS10 General use from professional operators	PROC11
CS11 General use from professional operators	PROC13
CS12 General use from professional operators	PROC19

5.2 Conditions of use affecting exposure

5.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 0.1 t(tonnes)/year

Maximum allowable site tonnage (MSafe): 715 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 90 %
Prevent discharge of undissolved substance to or recover from onsite wastewater.	

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Hazardous waste incineration	Waste - minimum efficiency of: 99.98 %
------------------------------	--

5.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

5.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Process Categories	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

5.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Process Categories	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

5.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Process Categories

Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

5.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC5, PROC8a)

Process Categories

Mixing or blending in batch processes - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC5, PROC8a)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

5.2. CS7: Worker Contributing Scenario: General use from professional operators (PROC8b)

Process Categories

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

5.2. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)**Process Categories**

Roller application or brushing (PROC10)

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

5.2. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)**Process Categories**

Non industrial spraying (PROC11)

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Use suitable eye protection.

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

5.2. CS10: Worker Contributing Scenario: General use from professional operators (PROC11)**Process Categories**

Non industrial spraying (PROC11)

*Product (article) characteristics***Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Wear suitable gloves tested to EN374.

Wear a respirator conforming to EN140.

Other conditions affecting worker exposure

Outdoor use

5.2. CS11: Worker Contributing Scenario: General use from professional operators (PROC13)

Process Categories

Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Wear suitable gloves tested to EN374.

5.2. CS12: Worker Contributing Scenario: General use from professional operators (PROC19)

Process Categories

Manual activities involving hand contact (PROC19)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Wear suitable gloves tested to EN374.

5.3 Exposure estimation and reference to its source

5.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Release route	Release rate	Release estimation method
Air	0.98 %	N/A
Water	0.01 %	N/A

soil	0.01 %	N/A
------	--------	-----

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	0.000173 mg/L	N/A	2.98E-07
freshwater	0.00238 mg/L	N/A	0.00248
freshwater sediment	0.00912 mg/kg bw/day	N/A	0.00248
marine sediment	0.000303 mg/L	N/A	0.000384
marine sediment	0.00116 mg/kg bw/day	N/A	0.000383
soil	0.00116 mg/kg bw/day	N/A	0.00682

5.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m ³	N/A	< 0.001
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	< 0.001

5.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	38 mg/m ³	N/A	0.04
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0443

5.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m ³	N/A	0.05
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.0524

5.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m ³	N/A	0.101
dermal, systemic, long-term	6.9 mg/kg bw/day	N/A	0.02
combined routes, systemic, long-term	N/A	N/A	0.121

5.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC5, PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m ³	N/A	0.202
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.242

5.3. CS7: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m ³	N/A	0.202
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.141

5.3. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m ³	N/A	0.202
dermal, systemic, long-term	27 mg/kg bw/day	N/A	0.08
combined routes, systemic, long-term	N/A	N/A	0.282

5.3. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	290 mg/m ³	N/A	0.303
dermal, systemic, long-term	21 mg/kg bw/day	N/A	0.062
combined routes, systemic, long-term	N/A	N/A	0.365

5.3. CS10: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	67 mg/m ³	N/A	0.071
dermal, systemic, long-term	21 mg/kg bw/day	N/A	0.062
combined routes, systemic, long-term	N/A	N/A	0.133

5.3. CS11: Worker Contributing Scenario: General use from professional operators (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m ³	N/A	0.202
dermal, systemic, long-term	2.7 mg/kg bw/day	N/A	0.008
combined routes, systemic, long-term	N/A	N/A	0.21

5.3. CS12: Worker Contributing Scenario: General use from professional operators (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m ³	N/A	0.202
dermal, systemic, long-term	28 mg/kg bw/day	N/A	0.082
combined routes, systemic, long-term	N/A	N/A	0.284

5.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

6. ES 6 Widespread use by professional workers

6.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC9a - ERC9b
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC3
CS5 General use from professional operators	PROC8a
CS6 General use from professional operators	PROC8b
CS7 General use from professional operators	PROC16

6.2 Conditions of use affecting exposure

6.2. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)

Environmental release categories	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 1 t(tonnes)/year

Maximum allowable site tonnage (MSafe): 7190 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Product residual disposal complies with applicable regulations.

6.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Technical and organisational conditions and measures

Technical and organisational measures

Handle substance within a closed system.

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

6.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Process Categories	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Technical and organisational conditions and measures

Technical and organisational measures

Handle substance within a closed system.

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

6.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Process Categories	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Technical and organisational conditions and measures

Technical and organisational measures

Handle substance within a closed system.

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

6.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Technical and organisational conditions and measures**Technical and organisational measures**

Handle substance within a closed system.
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

6.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)**Process Categories**

Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Technical and organisational conditions and measures**Technical and organisational measures**

Handle substance within a closed system.
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

6.2. CS7: Worker Contributing Scenario: General use from professional operators (PROC16)**Process Categories**

Use of fuels (PROC16)

Product (article) characteristics**Physical form of product:**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Technical and organisational conditions and measures**Technical and organisational measures**

Handle substance within a closed system.
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation**Personal protection**

Use suitable eye protection.

6.3 Exposure estimation and reference to its source**6.3. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)**

Release route	Release rate	Release estimation method
Air	0.01 %	N/A
Water	1E-05 %	N/A

soil	0 %	N/A
------	-----	-----

6.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.019 mg/m ³	N/A	< 0.001
dermal, systemic, long-term	0.03 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	< 0.001

6.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	38 mg/m ³	N/A	0.04
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.004
combined routes, systemic, long-term	N/A	N/A	0.0443

6.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	48 mg/m ³	N/A	0.05
dermal, systemic, long-term	0.69 mg/kg bw/day	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.0524

6.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	190 mg/m ³	N/A	0.202
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.242

6.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	96 mg/m ³	N/A	0.101
dermal, systemic, long-term	14 mg/kg bw/day	N/A	0.04

combined routes, systemic, long-term	N/A	N/A	0.141
--------------------------------------	-----	-----	-------

6.3. CS7: Worker Contributing Scenario: General use from professional operators (PROC16)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	19 mg/m ³	N/A	0.02
dermal, systemic, long-term	0.34 mg/kg bw/day	N/A	< 0.001
combined routes, systemic, long-term	N/A	N/A	0.0212

6.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

7. ES 7 Consumer use; Fuels (PC13)

7.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Fuels (PC13)

Environment Contributing Scenario

CS1 Covered by	ERC9b
----------------	-------

Consumer Contributing Scenario

CS2 Consumer	PC13 - PC13_1
CS3 Consumer	PC13 - PC13_2
CS4 Consumer	PC13 - PC13_3
CS5 Consumer	PC13 - PC13_4

7.2 Conditions of use affecting exposure

7.2. CS1: Environment Contributing Scenario: Covered by (ERC9b)

Environmental release categories	Widespread use of functional fluid (outdoor) (ERC9b)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

5726 Pa

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Product residual disposal complies with applicable regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

7.2. CS2: Consumer Contributing Scenario: Consumer (PC13)

Product Categories	Fuels (PC13)
Product (Sub-)Categories	Liquid: Automotive Refuelling (PC13_1)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 85 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 37500 g

Duration:

Exposure duration 0.05 h/event

Frequency:

Covers use up to 51 times per year

Other conditions affecting consumers exposure

Outdoor use

Additional conditions human healthCovers skin contact area up to 210 cm²**7.2. CS3: Consumer Contributing Scenario: Consumer (PC13)****Product Categories**

Fuels (PC13)

Product (Sub-)Categories

Liquid Scooter Refuelling (PC13_2)

*Product (article) characteristics***Concentration of substance in product:**

Covers concentrations up to 85 %

*Amount used, frequency and duration of use/exposure***Amounts used:**

Amount per use 37500 g

Duration:

Exposure duration 0.033 h/event

Frequency:

Covers use up to 51 times per year

Other conditions affecting consumers exposure

Outdoor use

Additional conditions human healthCovers skin contact area up to 210 cm²**7.2. CS4: Consumer Contributing Scenario: Consumer (PC13)****Product Categories**

Fuels (PC13)

Product (Sub-)Categories

Liquid, Garden equipment - Use (PC13_3)

*Product (article) characteristics***Concentration of substance in product:**

Covers concentrations up to 15 %

*Amount used, frequency and duration of use/exposure***Amounts used:**

Amount per use 750 g

Duration:

Exposure duration 2 h/event

Frequency:

Covers use up to 25 times per year

Other conditions affecting consumers exposure

Outdoor use

Additional conditions human healthCovers skin contact area up to 210 cm²**7.2. CS5: Consumer Contributing Scenario: Consumer (PC13)****Product Categories**

Fuels (PC13)

Product (Sub-)Categories	Liquid: Garden equipment - Refuelling (PC13_4)
Product (article) characteristics	
Concentration of substance in product: Covers concentrations up to 85 %	
Amount used, frequency and duration of use/exposure	
Amounts used: Amount per use 750 g	
Duration: Exposure duration 0.05 h/event	
Frequency: Covers use up to 25 times per year	
Other conditions affecting consumers exposure	
Room size: Covers use in a one car garage (>34 m ³) under typical ventilation.	
Temperature: Covers use at ambient temperatures.	
Additional conditions human health Covers skin contact area up to 210 cm ²	

7.3 Exposure estimation and reference to its source

7.3. CS1: Environment Contributing Scenario: Covered by (ERC9b)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	0.0236 mg/L	N/A	0.00246
freshwater sediment	0.00905 mg/kg bw/day	N/A	0.00246
marine water	0.0003 mg/L	N/A	0.00038
marine sediment	0.0015 mg/kg bw/day	N/A	0.00038
marine sediment	0.0015 mg/kg bw/day	N/A	0.00676

7.2. CS2: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.187 mg/m ³	N/A	0.00164
inhalative, local, short-term	1.3 mg/m ³	N/A	0.0114
dermal, systemic, long-term	0.117 mg/kg bw/day	N/A	8.1E-05
combined routes, systemic, long-term	N/A	N/A	0.0114

7.2. CS3: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0612 mg/m ³	N/A	0.000544

inhalative, local, short-term	0.434 mg/m ³	N/A	0.0038
dermal, systemic, long-term	0.117 mg/kg bw/day	N/A	8.1E-05
combined routes, systemic, long-term	N/A	N/A	0.00388

7.2. CS4: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0764 mg/m ³	N/A	0.00067
inhalative, local, short-term	1.09 mg/m ³	N/A	0.00956
dermal, systemic, long-term	4.13 mg/kg bw/day	N/A	0.0014
combined routes, systemic, long-term	N/A	N/A	0.0109

7.2. CS5: Consumer Contributing Scenario: Consumer (PC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.079 mg/m ³	N/A	0.000692
inhalative, local, short-term	1.12 mg/m ³	N/A	0.00982
dermal, systemic, long-term	0.117 mg/kg bw/day	N/A	3.98E-05
combined routes, systemic, long-term	N/A	N/A	0.00986

7.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

8. ES 8 Consumer use; Various products (PC1, PC3, PC8, PC18, PC23)

8.1 TITLE SECTION

Exposure Scenario name	Cosumer other uses
Date - Version	23/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Adhesives, sealants (PC1) - Air care products (PC3) - Biocidal products (PC8) - Ink and toners (PC18) - Leather treatment products (PC23) - Lubricants, greases, release products (PC24) - Plant protection products (PC27) - Polishes and wax blends (PC31) - Textile dyes and impregnating products (PC34)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Consumer Contributing Scenario

CS2 Consumer	PC1 - PC1_1
CS3 Consumer	PC1 - PC1_3
CS4 Consumer	PC1 - PC1_4
CS5 Consumer	PC3 - PC3_1
CS6 Consumer	PC3 - PC3_2
CS7 Consumer	PC8 - PC35_1, PC8_1
CS8 Consumer	PC8 - PC8_2, PC35_2
CS9 Consumer	PC8 - PC8_3, PC35_3
CS10 Consumer	PC18
CS11 Consumer	PC23 - PC23_1, PC31_1
CS12 Consumer	PC23 - PC23_2, PC31_2
CS13 Consumer	PC24 - PC16_1, PC17_1, PC24_1, 36
CS14 Consumer	PC27
CS15 Consumer	PC31 - PC23_1, PC31_1
CS16 Consumer	PC31 - PC23_2, PC31_2

8.2 Conditions of use affecting exposure

8.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Hazardous waste incineration

Waste - minimum efficiency of: 99.8 %

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 2000 m³/day

8.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Product Categories Adhesives, sealants (PC1)

Product (Sub-)Categories Glues, hobby use (PC1_1)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 70 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 4 h/event

Frequency:

Covers exposure up to 1 events per day

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Additional conditions human health

Covers skin contact area up to 35 cm²

8.2. CS3: Consumer Contributing Scenario: Consumer (PC1)

Product Categories Adhesives, sealants (PC1)

Product (Sub-)Categories Glue from spray (PC1_3)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 30 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 4 h/event

Frequency:

Covers exposure up to 6 times per year

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Additional conditions human health

Covers skin contact area up to 35 cm²

8.2. CS4: Consumer Contributing Scenario: Consumer (PC1)

Product Categories Adhesives, sealants (PC1)

Product (Sub-)Categories	Sealants (PC1_4)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 30 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Amounts used: Amount per use 50 g	
Duration: Exposure duration 1 h/event	
Frequency: Covers exposure up to 1 events per day	
<i>Other conditions affecting consumers exposure</i>	
Room size: Covers use in room size of 20 m ³	
Additional conditions human health Covers skin contact area up to 35 cm ²	
8.2. CS5: Consumer Contributing Scenario: Consumer (PC3)	
Product Categories	Air care products (PC3)
Product (Sub-)Categories	Air care, instant action (aerosol sprays) (PC3_1)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 40 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Amounts used: Amount per use 50 g	
Duration: Exposure duration 0.3 h/event	
Frequency: Covers exposure up to 4 events per day	
<i>Other conditions affecting consumers exposure</i>	
Room size: Covers use in room size of 20 m ³	
Additional conditions human health Covers skin contact area up to 35 cm ²	
8.2. CS6: Consumer Contributing Scenario: Consumer (PC3)	
Product Categories	Air care products (PC3)
Product (Sub-)Categories	Air care, continuous action (solid and liquid) (PC3_2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 10 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Amounts used: Amount per use 50 g	
Duration: Exposure duration 8 h/event	
Frequency:	

Covers exposure up to 1 events per day

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Additional conditions human health

Covers skin contact area up to 35 cm²

8.2. CS7: Consumer Contributing Scenario: Consumer (PC8)

Product Categories	Biocidal products (PC8)
---------------------------	-------------------------

Product (Sub-)Categories	Laundry and dish washing products (PC35_1, PC8_1)
---------------------------------	---

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 15 g

Duration:

Exposure duration 0.5 h/event

Frequency:

Covers exposure up to 1 events per day

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Additional conditions human health

Covers skin contact area up to 857 cm²

8.2. CS8: Consumer Contributing Scenario: Consumer (PC8)

Product Categories	Biocidal products (PC8)
---------------------------	-------------------------

Product (Sub-)Categories	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) (PC8_2, PC35_2)
---------------------------------	--

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 0.3 h/event

Frequency:

Covers exposure up to 125 times per year

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Additional conditions human health

Covers skin contact area up to 857 cm²

8.2. CS9: Consumer Contributing Scenario: Consumer (PC8)

Product Categories	Biocidal products (PC8)
---------------------------	-------------------------

Product (Sub-)Categories	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (PC8_3, PC35_3)
---------------------------------	--

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 15 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 0.2 h/event

Frequency:

Covers exposure up to 125 times per year

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Ventilation rate: Covers use under typical household ventilation.

Additional conditions human health

Covers skin contact area up to 428 cm²

8.2. CS10: Consumer Contributing Scenario: Consumer (PC18)

Product Categories

Ink and toners (PC18)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 50 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 8 h/event

Frequency:

Covers exposure up to 1 uses per day

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Ventilation rate: Covers use under typical household ventilation.

Additional conditions human health

Covers skin contact area up to 71 cm²

8.2. CS11: Consumer Contributing Scenario: Consumer (PC23)

Product Categories

Leather treatment products (PC23)

Product (Sub-)Categories

Polishes, wax/cream (floor, furniture, shoes) (PC23_1, PC31_1)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 50 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 1.2 h/event

Frequency:

Covers exposure up to 29 times per year

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Ventilation rate: Covers use under typical household ventilation.

Additional conditions human health

Covers skin contact area up to 430 cm²

8.2. CS12: Consumer Contributing Scenario: Consumer (PC23)

Product Categories	Leather treatment products (PC23)
---------------------------	-----------------------------------

Product (Sub-)Categories	Polishes, spray (furniture, shoes) (PC23_2, PC31_2)
---------------------------------	---

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 20 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 0.3 h/event

Frequency:

Covers exposure up to 8 times per year

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Ventilation rate: Covers use under typical household ventilation.

Additional conditions human health

Covers skin contact area up to 430 cm²

8.2. CS13: Consumer Contributing Scenario: Consumer (PC24)

Product Categories	Lubricants, greases, release products (PC24)
---------------------------	--

Product (Sub-)Categories	Liquids (PC16_1, PC17_1, PC24_1, 36)
---------------------------------	--------------------------------------

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 20 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 50 g

Duration:

Exposure duration 0.2 h/event

Frequency:

Covers exposure up to 4 times per year

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Ventilation rate: Covers use under typical household ventilation.

Additional conditions human health

Covers skin contact area up to 468 cm²

8.2. CS14: Consumer Contributing Scenario: Consumer (PC27)

Product Categories	Plant protection products (PC27)
---------------------------	----------------------------------

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 50 %

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 50 g

Duration:

Exposure duration 0.3 h/event

Frequency:

Covers exposure up to 29 times per year

Other conditions affecting consumers exposure**Room size:** Covers use in room size of 20 m³**Ventilation rate:** Covers use under typical household ventilation.**Additional conditions human health**Covers skin contact area up to 857 cm²**8.2. CS15: Consumer Contributing Scenario: Consumer (PC31)****Product Categories**

Polishes and wax blends (PC31)

Product (Sub-)Categories

Polishes, wax/cream (floor, furniture, shoes) (PC23_1, PC31_1)

Product (article) characteristics**Concentration of substance in product:**

Covers concentrations up to 50 %

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 50 g

Duration:

Exposure duration 1.2 h/event

Frequency:

Covers exposure up to 29 times per year

Other conditions affecting consumers exposure**Room size:** Covers use in room size of 20 m³**Ventilation rate:** Covers use under typical household ventilation.**Additional conditions human health**Covers skin contact area up to 430 cm²**8.2. CS16: Consumer Contributing Scenario: Consumer (PC31)****Product Categories**

Polishes and wax blends (PC31)

Product (Sub-)Categories

Polishes, spray (furniture, shoes) (PC23_2, PC31_2)

Product (article) characteristics**Concentration of substance in product:**

Covers concentrations up to 10 %

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 50 g

Duration:

Exposure duration 0.3 h/event

Frequency:

Covers exposure up to 8 times per year

Other conditions affecting consumers exposure

Room size: Covers use in room size of 20 m³

Ventilation rate: Covers use under typical household ventilation.

Additional conditions human health

Covers skin contact area up to 430 cm²

8.3 Exposure estimation and reference to its source

8.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
wastewater treatment plant microbes	0.273 mg/L	N/A	0.000471
freshwater	0.0297 mg/L	N/A	0.0309
freshwater sediment	0.114 mg/kg bw/day	N/A	0.031
marine water	0.00304 mg/L	N/A	0.00385
marine sediment	0.0116 mg/kg bw/day	N/A	0.00383
soil	0.116 mg/kg bw/day	N/A	0.00676

8.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	111 mg/m ³	N/A	0.973
inhalative, local, short-term	111 mg/m ³	N/A	0.973
dermal, systemic, long-term	3.28 mg/kg bw/day	N/A	0.0159
combined routes, systemic, long-term	N/A	N/A	0.989

8.2. CS3: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.788 mg/m ³	N/A	0.00682
inhalative, local, short-term	47.3 mg/m ³	N/A	0.414
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.000112
combined routes, systemic, long-term	N/A	N/A	0.212

8.2. CS4: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
---	----------------	--------------------	-----------------------------------

inhalative, systemic, long-term	23.5 mg/m ³	N/A	0.206
inhalative, local, short-term	23.5 mg/m ³	N/A	0.206
dermal, systemic, long-term	1.4 mg/kg bw/day	N/A	0.00679
combined routes, systemic, long-term	N/A	N/A	0.212

8.2. CS5: Consumer Contributing Scenario: Consumer (PC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	38.7 mg/m ³	N/A	0.339
inhalative, local, short-term	38.7 mg/m ³	N/A	0.339
dermal, systemic, long-term	7.51 mg/kg bw/day	N/A	0.0364
combined routes, systemic, long-term	N/A	N/A	0.375

8.2. CS6: Consumer Contributing Scenario: Consumer (PC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	17.1 mg/m ³	N/A	0.15
inhalative, local, short-term	17.1 mg/m ³	N/A	0.15
dermal, systemic, long-term	0.469 mg/kg bw/day	N/A	0.00227
combined routes, systemic, long-term	N/A	N/A	0.152

8.2. CS7: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.672 mg/m ³	N/A	0.00589
inhalative, local, short-term	0.672 mg/m ³	N/A	0.00589
dermal, systemic, long-term	5.63 mg/kg bw/day	N/A	0.000273
combined routes, systemic, long-term	N/A	N/A	0.00616

8.2. CS8: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.543 mg/m ³	N/A	0.00476
inhalative, local, short-term	1.55 mg/m ³	N/A	0.0135

dermal, systemic, long-term	5.63 mg/kg bw/day	N/A	0.00956
combined routes, systemic, long-term	N/A	N/A	0.0231

8.2. CS9: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.885 mg/m ³	N/A	0.00776
inhalative, local, short-term	2.52 mg/m ³	N/A	0.0221
dermal, systemic, long-term	8.43 mg/kg bw/day	N/A	0.0143
combined routes, systemic, long-term	N/A	N/A	0.0364

8.2. CS10: Consumer Contributing Scenario: Consumer (PC18)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	86 mg/m ³	N/A	0.754
inhalative, local, short-term	86 mg/m ³	N/A	0.754
dermal, systemic, long-term	4.69 mg/kg bw/day	N/A	0.0227
combined routes, systemic, long-term	N/A	N/A	0.777

8.2. CS11: Consumer Contributing Scenario: Consumer (PC23)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	3.62 mg/m ³	N/A	0.0317
inhalative, local, short-term	45.3 mg/m ³	N/A	0.397
dermal, systemic, long-term	28.2 mg/kg bw/day	N/A	0.0109
combined routes, systemic, long-term	N/A	N/A	0.408

8.2. CS12: Consumer Contributing Scenario: Consumer (PC23)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.136 mg/m ³	N/A	0.00119
inhalative, local, short-term	6.24 mg/m ³	N/A	0.0547
dermal, systemic, long-term	1.23 mg/kg bw/day	N/A	6.5E-05
combined routes, systemic, long-term	N/A	N/A	0.0295

8.2. CS13: Consumer Contributing Scenario: Consumer (PC24)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0368 mg/m ³	N/A	0.000322
inhalative, local, short-term	3.36 mg/m ³	N/A	0.0294
dermal, systemic, long-term	1.23 mg/kg bw/day	N/A	6.5E-05
combined routes, systemic, long-term	N/A	N/A	0.0295

8.2. CS14: Consumer Contributing Scenario: Consumer (PC27)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	15.7 mg/m ³	N/A	0.137
inhalative, local, short-term	15.7 mg/m ³	N/A	0.137
dermal, systemic, long-term	11.2 mg/kg bw/day	N/A	0.0543
combined routes, systemic, long-term	N/A	N/A	0.226
oral, systemic, long-term	131.2 mg/kg bw/day	N/A	0.0344

8.2. CS15: Consumer Contributing Scenario: Consumer (PC31)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	3.62 mg/m ³	N/A	0.0317
inhalative, local, short-term	45.3 mg/m ³	N/A	0.397
dermal, systemic, long-term	28.2 mg/kg bw/day	N/A	0.0109
combined routes, systemic, long-term	N/A	N/A	0.408

8.2. CS16: Consumer Contributing Scenario: Consumer (PC31)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.0684 mg/m ³	N/A	0.0006
inhalative, local, short-term	3.12 mg/m ³	N/A	0.0273
dermal, systemic, long-term	5.65 mg/kg bw/day	N/A	0.000597
combined routes, systemic, long-term	N/A	N/A	0.0279

8.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 01/06/2021

Substance identity	
Chemical name	3-butossi-2-propanolo
CAS No.	5131-66-8
EINECS No.	225-878-4

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Consumer use; Washing and cleaning products (PC35)

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	01/06/2021 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
----------------	---

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site 3281 tonnes/day

Release type: Continuous release

Emission days: 20 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Filtration	Water - minimum efficiency of: 87.4 %
------------	---------------------------------------

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Dispose of waste product or used containers according to local regulations.
Incineration, disposal or recycling at specific offsite provider

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Use in closed process Site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

1.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)

Process Categories

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 25 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

No other specific measures identified.

Ensure operatives are trained to minimise exposures.

Supervision in place to check that the risk management measures in place are being used correctly and operation conditions followed.

Ensure control measures are regularly inspected and maintained.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Temperature: Covers use at ambient temperatures.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario: Covered by (ERC4)

Additional information on exposure estimation:

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

1.3. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)

Additional information on exposure estimation:

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers

2.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	01/06/2021 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13
---	--

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site 3821 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Filtration	Water - minimum efficiency of: 87.4 %
Wet scrubber for elimination of volatile components from waste gases	

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment	
Incineration, disposal or recycling at specific offsite provider Dispose of waste product or used containers according to local regulations.	
<i>Other conditions affecting environmental exposure</i>	
Local marine water dilution factor: 100 Local freshwater dilution factor: 10	
<i>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.</i>	
Additional Good Practice Advice: Use in closed process	
2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers percentage substance in the product up to 25 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Ensure operatives are trained to minimise exposures. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374 and sleeves. For further specification, refer to section 8 of the SDS Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140.	
<i>Other conditions affecting worker exposure</i>	
Temperature: Covers use at ambient temperatures.	
2.3 Exposure estimation and reference to its source	
2.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)	
Additional information on exposure estimation: ECETOC TRA reduction factor for local exhaust ventilation (LEV) has not been used for the calculation of dermal exposure estimates. Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented.	
2.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)	
Additional information on exposure estimation: ECETOC TRA reduction factor for local exhaust ventilation (LEV) has not been used for the calculation of dermal exposure estimates.	

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Consumer use; Washing and cleaning products (PC35)

3.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	01/06/2021 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Washing and cleaning products (PC35)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Consumer Contributing Scenario

CS2 Detergent liquids	PC35
-----------------------	------

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

Amount used, frequency and duration of use (or from service life)

Amounts used:

Daily amount per site 285 kg/day

Release type: Continuous release

Emission days: 365 days per year

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Dispose of waste product or used containers according to local regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 2000 m³/day

3.2. CS2: Consumer Contributing Scenario: Detergent liquids (PC35)

Product Categories	Washing and cleaning products (PC35)
--------------------	--------------------------------------

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

Amount used, frequency and duration of use/exposure**Amounts used:**

Amount per use 16 g

Duration:

Covers exposure up to 1 h/day

Frequency:

Covers exposure up to 365 days per year

Other conditions affecting consumers exposure

Indoor use

Room size: Covers use in room size of 15 m³

Ventilation rate: Covers use under typical household ventilation.

3.3 Exposure estimation and reference to its source

3.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Additional information on exposure estimation:

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.