

Sicherheitsdatenblatt
COCKPIT CLEANER high gloss scented
VANILLA



Sicherheitsdatenblatt vom 27/9/2024, Version 9

ABSCHNITT 1: Bezeichnung des Stoffs beziehungsweise des Gemischs und des Unternehmens

1.1. Produktidentifikator

Kennzeichnung der Mischung:

Handelsname: COCKPIT CLEANER high gloss scented VANILLA

Handelscode: 31011

1.2. Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird

Empfohlene Verwendung:

Reinigungsmittel für Armaturenbretter

Nicht empfohlene Verwendungen:

Empfohlene Verwendungen strikt einhalten.

1.3. Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

Lieferant:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Sachkundigen Person verantwortlich vom Sicherheitsdatenblatt:

arexons@arexons.it

1.4. Notrufnummer

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Austrian emergency telephone number : Vergiftungsinformationszentrale (+43 1 406 43 43)

Giftnotruf Berlin: +49 30 30686700

Antigifcentrum Brussel: 80025500 (7 jours sur 7, 24 heures sur 24).

ABSCHNITT 2: Mögliche Gefahren

2.1. Einstufung des Stoffs oder Gemischs

Kriterien der EG Verordnung 1272/2008 (CLP):

⚠ Gefahr, Aerosols 1, Extrem entzündbares Aerosol. Behälter steht unter Druck: Kann bei Erwärmung bersten.

⚠ Achtung, Skin Irrit. 2, Verursacht Hautreizungen.

⚠ Achtung, Eye Irrit. 2, Verursacht schwere Augenreizung.

⚠ Achtung, STOT SE 3, Kann Schläfrigkeit und Benommenheit verursachen.

Aquatic Chronic 3, Schädlich für Wasserorganismen, mit langfristiger Wirkung.

Für die menschlichen Gesundheit und die Umwelt gefährliche physisch-chemische Auswirkungen:

Keine weiteren Risiken

2.2. Kennzeichnungselemente

Gefahrenpiktogramme:



Gefahr

Gefahrenhinweise:


H222, H229 Extrem entzündbares Aerosol. Behälter steht unter Druck: Kann bei Erwärmung bersten.

H315 Verursacht Hautreizungen.

H319 Verursacht schwere Augenreizung.

31011/9

Seite Nr. 1 von 12



H412 Schädlich für Wasserorganismen, mit langfristiger Wirkung.

P501 Inhalt/Behälter laut Verordnung der Entsorgung zuführen.

Keine

Allergene: Benzyl salicylate

Keine weiteren Risiken

Gefährliche Bestandteile gemäß der CLP-Verordnung und dazugehörige Einstufung:

Seite Nr. 2 von 12

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented VANILLA



>= 2% - < 3%	2-Propanol; Isopropylalkohol; Isopropanol	Index- Nummer: CAS: EC: REACH No.:	603-117-00-0 67-63-0 200-661-7 01- 2119457558 -25	⚠ 2.6/2 Flam. Liq. 2 H225 ⚠ 3.3/2 Eye Irrit. 2 H319 ⚠ 3.8/3 STOT SE 3 H336
-----------------	---	--	--	--

*DECLK (CLP): Stoff eingestuft gemäß Anmerkung K im Anhang VI der Verordnung 1272/2008/EG. Die harmonisierte Einstufung als karzinogen oder keimzellmutagen wird vorgenommen, es sei denn, es kann nachgewiesen werden, dass der Stoff weniger als 0,1 Gewichtsprozent 1,3-Butadien (Einecs-Nr. 203-450-8) enthält; in diesem Fall ist auch für diese Gefahrenklassen eine Einstufung gemäß Titel II dieser Verordnung vorzunehmen. Wird der Stoff nicht als karzinogen oder keimzellmutagen eingestuft, so sind zumindest die Sicherheitshinweise (P102)-P210-P403 anzuwenden.

ABSCHNITT 4: Erste-Hilfe-Maßnahmen

4.1. Beschreibung der Erste-Hilfe-Maßnahmen

Nach Hautkontakt:

Verunreinigte Kleidung sofort ausziehen.

Körperbereiche, die mit dem Produkt in Kontakt getreten sind, bzw. bei denen dieser Verdacht besteht, müssen sofort mit viel fließendem Wasser und möglichst mit Seife gewaschen werden.

Den Körper vollständig waschen (Dusche oder Bad).

Die kontaminierten Kleidungsstücke sofort ablegen und sie auf sichere Weise entsorgen.

Im Falle von Hautkontakt sofort mit reichlich Wasser und Seife waschen.

Nach Augenkontakt:

Im Falle von Augenkontakt die Augen über einen ausreichenden Zeitraum mit Wasser spülen und die Augenlider offen halten; sofort einen Augenarzt konsultieren.

Das unverletzte Auge schützen.

Nach Verschlucken:

Auf keinen Fall Erbrechen herbeiführen. SOFORT ARZT ZUZIEHEN.

Nach Einatmen:

Den Verletzten ins Freie bringen, ihn ausruhen lassen und warm halten.

4.2. Wichtigste akute und verzögert auftretende Symptome und Wirkungen

Keine

4.3. Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung

Im Falle eines Unfalls bzw. bei Unwohlsein sofort einen Arzt konsultieren (wenn möglich, die Bedienungsanleitung bzw. das Sicherheitsdatenblatt vorzeigen).

Behandlung:

Keine

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

5.1. Löschmittel

Geeignete Löschmittel:

Mit Kohlendioxid.

Mit Pulver.

Schaum

Wassernebel.

Löschmittel nicht empfohlen:

5.2. Besondere vom Stoff oder Gemisch ausgehende Gefahren

Die Explosions- bzw. Verbrennungsgase nicht einatmen.

Durch die Verbrennung entsteht ein dichter Rauch.

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented VANILLA



5.3. Hinweise für die Brandbekämpfung

Normale Brandbekämpfungskleidung, z. B. Pressluftatmer mit offenem Atemschutz (EN 137), flammhemmender Anzug (EN469), flammhemmende Handschuhe (EN 659) und Stiefel für Feuerwehrleute (HO A29 oder A30).

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

6.1. Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren

- Die persönliche Schutzausrüstung tragen.
- Alle Entzündungsquellen entfernen.
- Die Personen an einen sicheren Ort bringen.
- Die in Punkt 7 und 8 aufgeführten Schutzmaßnahmen beachten.

6.2. Umweltschutzmaßnahmen

Das Eindringen in den Boden/Unterboden verhindern. Das Abfließen in das Grundwasser oder in die Kanalisation verhindern.

Das kontaminierte Waschwasser auffangen und entsorgen.

Bei Austritt von Gas oder bei Eintritt in Wasserläufe, den Boden oder die Kanalisation die zuständigen Behörden informieren.

Geeignetes Material zum Auffangen: absorbierende oder organische Materialien, Sand

6.3. Methoden und Material für Rückhaltung und Reinigung

Reinigung:

Flammen und/oder Funken bei Leckagen und Abfallmaterial vermeiden. Nicht rauchen. Bei Verschütten

größerer Mengen eindämmen, aufnehmen und für die Entsorgung in geeignete Behälter schaufeln. Bei

kleineren Mengen mit saugfähigem Material eindämmen. Verschmutztes Material in geeignete Behälter

geben. Entsorgung von verschmutztem Material in Übereinstimmung mit den örtlichen oder landesweiten

Bestimmungen.

6.4. Verweis auf andere Abschnitte

Siehe auch die Abschnitte 8 und 13

ABSCHNITT 7: Handhabung und Lagerung

7.1. Schutzmaßnahmen zur sicheren Handhabung

Haut- und Augenkontakt sowie das Einatmen von Dämpfen vermeiden.

Keine leeren Behälter verwenden, bevor diese nicht gereinigt wurden.

Vor dem Umfüllen sicherstellen, dass sich in den Behältern keine Reste inkompatibler Stoffe befinden.

Für die empfohlenen Schutzausrüstungen wird auf Abschnitt 8 verwiesen.

Kontaminierte Kleidungsstücke müssen vor dem Eintritt in Speiseräume gewechselt werden.

Während der Arbeit nicht essen oder trinken.

7.2. Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten

Nur im Originalbehälter aufbewahren.

Unter 50 °C lagern. Vor offenen Flammen und Wärmequellen fern halten. Keiner direkten Sonneneinstrahlung aussetzen.

Vor offenen Flammen, Zündfunken und Wärmequellen fern halten. Keiner direkten Sonneneinstrahlung aussetzen.

Lebensmittel, Getränke und Tiernahrung fern halten.

Kein spezifischer.

Angaben zu den Lagerräumen:

Kühl und ausreichend belüftet.

7.3. Spezifische Endanwendungen

Kein besonderer Verwendungszweck

Sicherheitsdatenblatt
COCKPIT CLEANER high gloss scented
VANILLA



ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

8.1. Zu überwachende Parameter

Kohlenwasserstoffe, C3-4; Gase aus der Erdölverarbeitung - CAS: 68476-40-4

MAK - TWA: 2400 mg/m³, 1000 ppm

TLV TWA - 1900 mg/m³, 800 ppm

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

EU

2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0

20101.11 - TWA: 983 mg/m³, 400 ppm

20101.12 - TWA: 492 mg/m³, 200 ppm

ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Anmerkungen: A4, BEI - Eye and URT
irr, CNS impair

DNEL-Expositionsgrenzwerte

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Arbeitnehmer Gewerbe: 300 mg/kg - Exposition: Mensch - dermal - Häufigkeit:

Langfristig, systemische Auswirkungen

Arbeitnehmer Gewerbe: 508 ppm - Exposition: Mensch - Inhalation - Häufigkeit:

Kurzfristig, systemische Auswirkungen

Verbraucher: 149 mg/kg - Exposition: Mensch - dermal - Häufigkeit: Langfristig,
systemische Auswirkungen

Verbraucher: 109 ppm - Exposition: Mensch - Inhalation - Häufigkeit: Langfristig,
systemische Auswirkungen

Verbraucher: 149 mg/kg - Exposition: Mensch - oral - Häufigkeit: Langfristig, systemische
Auswirkungen

2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0

Arbeitnehmer Gewerbe: 888 mg/kg - Verbraucher: 319 mg/kg - Exposition: Mensch -
dermal - Häufigkeit: Langfristig (wiederholt)

Arbeitnehmer Gewerbe: 500 mg/m³ - Verbraucher: 89 mg/m³ - Exposition: Mensch -
Inhalation - Häufigkeit: Langfristig (wiederholt)

Verbraucher: 26 mg/kg - Exposition: Mensch - oral - Häufigkeit: Langfristig (wiederholt)

PNEC-Expositionsgrenzwerte

2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0

Ziel: Süßwasser - Wert: 140.9 mg/l

Ziel: Süßwasser - Wert: 140.9 mg/l

Ziel: Flußsediment - Wert: 552 mg/l

Ziel: Boden (Landwirtschaft) - Wert: 28 mg/kg

Ziel: Mikroorganismen in Kläranlagen - Wert: 2251 mg/l

8.2. Begrenzung und Überwachung der Exposition

Augenschutz:

Sicherheitsbrille

Entspricht EN 166

Hautschutz:

Schutzkleidung

Handschutz:

Handschuhe aus Nitril oder Viton.

Gemäß EN 374.

Dicke: Manschette 0,10 mm; Handfläche 0,12 mm; Finger 0,145 mm

Atemschutz:

Verwenden Sie ein geeignetes Atemschutzgerät.

Wärmerisiken:

Keine

Kontrollen der Umweltexposition:

Keine

Geeignete technische Massnahmen:

Keine

Sicherheitsdatenblatt
COCKPIT CLEANER high gloss scented
VANILLA



ABSCHNITT 9: Physikalische und chemische Eigenschaften

9.1. Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften

Eigenschaft	Wert	Methode:	Anmerkungen
Aggregatzustand:	flüssig	--	--
Farbe:	farblos	--	--
Geruch:	charakteristisch	--	--
Schmelzpunkt/ Gefrierpunkt:	N.A.	--	--
Siedepunkt oder Siedebeginn und Siedebereich:	N.A.	--	--
Entzündbarkeit:	N.A.	--	--
Untere und obere Explosionsgrenze:	N.A.	--	--
Flammpunkt:	<0°C	Heptan	--
Selbstentzündungstemperatur:	N.A.	--	--
Zerfalltemperatur:	N.A.	--	--
pH:	Nicht relevant	--	--
Kinematische Viskosität:	N.A.	--	--
Wasserlöslichkeit:	unlöslich	--	--
Löslichkeit in Öl:	N.A.	--	--
Verteilungskoeffizient n- Oktanol/Wasser (log- Wert):	N.A.	--	--
Dampfdruck:	N.A.	--	--
Dichte und/oder relative Dichte:	0.7517	09	--
Relative Dampfdichte:	N.A.	--	--
Partikeleigenschaften:			
Teilchengröße:	N.A.	--	--

9.2. Sonstige Angaben

Keine weiteren relevanten Informationen

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented VANILLA



ABSCHNITT 10: Stabilität und Reaktivität

- 10.1. Reaktivität
Stabil unter Normalbedingungen
- 10.2. Chemische Stabilität
Stabil bei normalen Raumtemperaturen, wenn wie empfohlen verwendet.
- 10.3. Möglichkeit gefährlicher Reaktionen
Kann unter Einwirkung von Dithiokarbamaten, Mercaptanen und weiteren organischen Sulfiden, elementaren Metallen (Alkali- und Erdalkalimetallen), Pulverlegierungen, Dämpfen, starken Reduktionsmitteln entflammbare Gase bilden.
Kann unter Einwirkung von anorganischen Fluoriden, halogenierten organischen Stoffen, Sulfiden, Nitriden, Nitrilen, organischen Phosphaten, Phosphothioaten, Phosphodithioaten, starken Oxydationsmitteln giftige Gase bilden.
Kann sich unter Einwirkung von Dithiokarbamaten, elementaren Metallen (Alkali- und Erdalkalimetallen, Pulverlegierungen, Dämpfen, Platten oder Stangen), Nitriden entzünden.
- 10.4. Zu vermeidende Bedingungen
Übermäßige Hitze.
- 10.5. Unverträgliche Materialien
Kontakt mit brandfördernden Materialien vermeiden. Das Produkt könnte in Brand geraten.
- 10.6. Gefährliche Zersetzungsprodukte
Keine.

ABSCHNITT 11: Toxikologische Angaben

- 11.1. Angaben zu den Gefahrenklassen im Sinne der Verordnung (EG) Nr. 1272/2008
Toxikologische Informationen zum Produkt:

COCKPIT CLEANER high gloss VANILLA SPRAY ML 600

- a) akute Toxizität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- b) Ätz-/Reizwirkung auf die Haut
Das Produkt ist eingestuft: Skin Irrit. 2 H315
- c) schwere Augenschädigung/-reizung
Das Produkt ist eingestuft: Eye Irrit. 2 H319
- d) Sensibilisierung der Atemwege/Haut
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- e) Keimzell-Mutagenität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- f) Karzinogenität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- g) Reproduktionstoxizität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- h) spezifische Zielorgan-Toxizität bei einmaliger Exposition
Das Produkt ist eingestuft: STOT SE 3 H336
- i) spezifische Zielorgan-Toxizität bei wiederholter Exposition
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- j) Aspirationsgefahr
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

Toxikologische Informationen zu den Hauptbestandteilen des Produkts:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

- a) akute Toxizität:
Test: LC50 - Weg: Einatmen - Spezies: Ratte > 23.3 mg/l - Laufzeit: 4h
Test: LD50 - Weg: Oral - Spezies: Ratte > 8 ml/kg

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented VANILLA



Test: LD50 - Weg: Haut - Spezies: Kaninchen 2800-3100 mg/kg
2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0
a) akute Toxizität:
Test: LD50 - Weg: Oral - Spezies: Ratte > 5000 mg/kg
Test: LD50 - Weg: Haut - Spezies: Kaninchen > 5000 mg/kg
Test: LC50 - Weg: Einatmen - Spezies: Ratte > 10000 ppm - Laufzeit: 6h

- 11.2. Angaben über sonstige Gefahren
Endokrinschädliche Eigenschaften:
Keine endokrinen Disruptoren in Konzentrationen ≥ 0.1 %.

ABSCHNITT 12: Umweltbezogene Angaben

- 12.1. Toxizität
Im Einklang mit der GLP verwenden, nicht herumliegen lassen.
Kohlenwasserstoffe, C3-4; Gase aus der Erdölverarbeitung - CAS: 68476-40-4
a) Akute aquatische Toxizität:
Endpunkt: LC50 - Spezies: Daphnia = 14.22 mg/l - Dauer / h: 48
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
b) Chronische aquatische Toxizität:
Endpunkt: EC50 - Spezies: Algen > 10-30 mg/l - Dauer / h: 72
Endpunkt: LC50 - Spezies: Fische > 13.4 mg/l - Dauer / h: 96
2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0
a) Akute aquatische Toxizität:
Endpunkt: LC50 - Spezies: Fische 4200 mg/l - Dauer / h: 96
Endpunkt: LC50 - Spezies: Fische > 100 mg/l - Dauer / h: 48
Endpunkt: EC50 - Spezies: Daphnia > 100 mg/l - Dauer / h: 48
Endpunkt: EC50 - Spezies: Algen > 100 mg/l - Dauer / h: 72
12.2. Persistenz und Abbaubarkeit
Keine
2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0
Biologische Abbaubarkeit: Schnell abbaubar - Dauer / h: .10gg - %: 70
12.3. Bioakkumulationspotenzial
N.A.
12.4. Mobilität im Boden
N.A.
12.5. Ergebnisse der PBT- und vPvB-Beurteilung
vPvB-Stoffe: Keine - PBT-Stoffe: Keine
12.6. Endokrinschädliche Eigenschaften
Keine endokrinen Disruptoren in Konzentrationen ≥ 0.1 %.
12.7. Andere schädliche Wirkungen
Keine

ABSCHNITT 13: Hinweise zur Entsorgung

- 13.1. Verfahren der Abfallbehandlung
Nach Möglichkeit wiederverwerten. Behördlich zugelassenen Deponien oder Verbrennungsanlagen zuführen. Entsprechend den geltenden örtlichen und nationalen Bestimmungen vorgehen.
Zusatzinformationen zur Entsorgung:
"Gemäß guter Arbeitspraxis verwenden und eine Verbreitung in der Umwelt vermeiden.
Das Produkt nicht in die Kanalisation, Rohrgräben oder Wasserläufe entladen. Die geltenden gesetzlichen Bestimmungen zum Schutz von Wasser und Boden vor Verschmutzung beachten (it. Gesetzesdekret Nr. 152 vom 3.4.2006).
Das gebrauchte Produkt und die Behälter durch Übergabe an autorisierte Unternehmen gemäß den Bestimmungen des it. Gesetzesdekrets Nr. 152/2006 entsorgen (Konsolidiertes Umweltgesetz, das das Ronchi-Dekret ersetzt) in seiner geänderten Fassung.
Das gebrauchte Produkt ist als Sonderabfall zu betrachten, der gemäß der Richtlinie

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented VANILLA



2008/98/EG über Abfälle und ähnliches einzustufen ist. Wenn möglich, wiederverwerten. An autorisierte Entsorgungseinrichtungen senden oder unter kontrollierten Bedingungen verbrennen (152/2006 Art. 184).

Gemäß den geltenden örtlichen und nationalen Bestimmungen verfahren.

Die kontaminierten Verpackungen müssen weitmöglichst entleert werden. Nach der Reinigung muss das Produkt bei einer zugelassenen Stelle recycelt oder eliminiert werden."

ABSCHNITT 14: Angaben zum Transport



14.1. UN-Nummer oder ID-Nummer

ADR-UN Number: 1950
IATA-UN Number: 1950
IMDG-UN Number: 1950

14.2. Ordnungsgemäße UN-Versandbezeichnung

ADR-Shipping Name: DRUCKGASPACKUNGEN, entzündbar
IATA-Shipping Name: DRUCKGASPACKUNGEN, entzündbar
IMDG-Shipping Name: DRUCKGASPACKUNGEN, entzündbar

14.3. Transportgefahrenklassen

ADR-Class: 2
ADR - Gefahrunummer: -
IATA-Class: 2
IATA-Label: 2.1
IMDG-Class: 2
IMDG-Klasse: 2 UN 1950

14.4. Verpackungsgruppe

ADR-Packing Group: -
IATA-Packing group: -
IMDG-Packing group: -

14.5. Umweltgefahren

ADR-Umweltbelastung: Nein
IMDG-Marine pollutant: Nein
IMDG-EmS: F-D,
S-U

14.6. Besondere Vorsichtsmaßnahmen für den Verwender

ADR-Subsidiary hazards: See SP63
ADR-S.P.: 190 327 344 625
ADR-Beförderungskategorie (Tunnelbeschränkungscode):
IATA-Passenger Aircraft: 203
IATA-Subsidiary hazards: See SP63
IATA-Cargo Aircraft: 203
IATA-S.P.: A145 A167 A802
IATA-ERG: 10L
IMDG-Subsidiary hazards: See SP63
IMDG-Stowage and handling: SW1 SW22
IMDG-Segregation: SG69

2 (D)

14.7. Massengutbeförderung auf dem Seeweg gemäß IMO-Instrumenten

N.A.
Limited Quantity: 1 L
Exempted Quantity: E0

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented VANILLA



ABSCHNITT 15: Rechtsvorschriften

15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch

RL 98/24/EG (Schutz von Gesundheit und Sicherheit der Arbeitnehmer vor der Gefährdung durch chemische Arbeitsstoffe bei der Arbeit)
RL 2000/39/EG (Arbeitsplatz-Richtgrenzwerte)
Verordnung (EG) Nr. 1907/2006 (REACH)
Verordnung (EG) Nr. 1272/2008 (CLP)
Verordnung (EG) Nr. 790/2009 (1. ATP CLP) und (EU) Nr. 758/2013
Verordnung (EU) Nr. 2020/878
Verordnung (EU) Nr. 286/2011 (2. ATP CLP)
Verordnung (EU) Nr. 618/2012 (3. ATP CLP)
Verordnung (EU) Nr. 487/2013 (4. ATP CLP)
Verordnung (EU) Nr. 944/2013 (5. ATP CLP)
Verordnung (EU) Nr. 605/2014 (6. ATP CLP)
Verordnung (EU) Nr. 2015/1221 (7. ATP CLP)
Verordnung (EU) Nr. 2016/918 (8. ATP CLP)
Verordnung (EU) Nr. 2016/1179 (9. ATP CLP)
Verordnung (EU) Nr. 2017/776 (10. ATP CLP)
Verordnung (EU) Nr. 2018/669 (11. ATP CLP)
Verordnung (EU) Nr. 2018/1480 (13. ATP CLP)
Verordnung (EU) Nr. 2019/521 (12. ATP CLP)
Verordnung (EU) Nr. 2020/217 (14. ATP CLP)
Verordnung (EU) Nr. 2020/1182 (15. ATP CLP)
Verordnung (EU) Nr. 2021/643 (16. ATP CLP)
Verordnung (EU) Nr. 2021/849 (17. ATP CLP)
Verordnung (EU) Nr. 2022/692 (18. ATP CLP)

Beschränkungen zum Produkt oder zu den Inhaltsstoffen gemäß Anhang XVII der Verordnung (EG) 1907/2006 (REACH) und nachfolgenden Änderungen:

Beschränkungen zum Produkt:

Beschränkung 3

Beschränkung 40

Beschränkungen zu den Inhaltsstoffen gemäß:

Beschränkung 75

Flüchtige Organische Verbindung - FOV = 94.00 %

Flüchtige Organische Verbindung - FOV = 940.00 g/Kg

Flüchtige Organische Verbindung - FOV = 601.60 g/l

Wo möglich auf die folgenden Normen Bezug nehmen:

Richtlinie EU 2012/18 (Seveso III)

Verordnung (EG) Nr. 648/2004 (Detergenzien).

RL 2004/42/EG (FOV Richtlinie)

Anordnungen zu der Richtlinie EU 2012/18 (Seveso III):

Seveso III Kategorie gemäß dem Anhang 1, Teil 1

Das Produkt gehört zur Kategorie: P3a

15.2. Stoffsicherheitsbeurteilung

Keine Stoffsicherheitsbeurteilung wurde durchgeführt für das Gemisch

Stoffe, für die eine Stoffsicherheitsbeurteilung durchgeführt worden ist:

Kohlenwasserstoffe, C3-4; Gase aus der Erdölverarbeitung

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

2-Propanol; Isopropylalkohol; Isopropanol

ABSCHNITT 16: Sonstige Angaben

Text der verwendeten Sätze im Absatz 3:

H220 Extrem entzündbares Gas.

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented VANILLA



H280 Enthält Gas unter Druck; kann bei Erwärmung explodieren.
H225 Flüssigkeit und Dampf leicht entzündbar.
H304 Kann bei Verschlucken und Eindringen in die Atemwege tödlich sein.
H315 Verursacht Hautreizungen.
H336 Kann Schläfrigkeit und Benommenheit verursachen.
H411 Giftig für Wasserorganismen, mit langfristiger Wirkung.
EUH066 Wiederholter Kontakt kann zu spröder oder rissiger Haut führen.
H319 Verursacht schwere Augenreizung.

Gefahrenklasse und Gefahrenkategorie	Code	Beschreibung
Flam. Gas 1A	2.2/1A	Entzündbare Gas, Kategorie 1A
Aerosols 1	2.3/1	Aerosole, Kategorie 1
Press Gas (Liq.)	2.5/L	Gase unter Druck (verflüssigtes Gas)
Flam. Liq. 2	2.6/2	Entzündbare Flüssigkeiten, Kategorie 2
Asp. Tox. 1	3.10/1	Aspirationsgefahr, Kategorie 1
Skin Irrit. 2	3.2/2	Reizung der Haut, Kategorie 2
Eye Irrit. 2	3.3/2	Reizung der Augen, Kategorie 2
STOT SE 3	3.8/3	Spezifische Zielorgan-Toxizität (einmalige Exposition), Kategorie 3
Aquatic Chronic 2	4.1/C2	Chronisch (langfristig) gewässergefährdend, Kategorie 2
Aquatic Chronic 3	4.1/C3	Chronisch (langfristig) gewässergefährdend, Kategorie 3

Modifikation der Paragraphen seit der letzten Revision:

ABSCHNITT 1: Bezeichnung des Stoffs beziehungsweise des Gemischs und des Unternehmens
ABSCHNITT 5: Maßnahmen zur Brandbekämpfung
ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung
ABSCHNITT 7: Handhabung und Lagerung
ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen
ABSCHNITT 9: Physikalische und chemische Eigenschaften
ABSCHNITT 10: Stabilität und Reaktivität
ABSCHNITT 13: Hinweise zur Entsorgung
ABSCHNITT 15: Rechtsvorschriften

Einstufung und Verfahren, das zum Ableiten der Einstufung von Gemischen gemäß Verordnung (EG) 1272/2008 [CLP] verwendet wurde:

Einstufung gemäß Verordnung (EG) Nr. 1272/2008	Einstufungsverfahren
Aerosols 1, H222, H229	auf der Basis von Prüfdaten
Skin Irrit. 2, H315	Berechnungsmethode

Sicherheitsdatenblatt

COCKPIT CLEANER high gloss scented

VANILLA



Eye Irrit. 2, H319	Berechnungsmethode
STOT SE 3, H336	Berechnungsmethode
Aquatic Chronic 3, H412	Berechnungsmethode

Diese Unterlagen wurden von einem Fachmann mit entsprechender Ausbildung abgefasst.

Hauptsächliche Literatur:

ECDIN - Daten- und Informationsnetz über umweltrelevante Chemikalien - Vereinigtes
Forschungszentrum, Kommission der Europäischen Gemeinschaft
SAX's GEFÄHRliche EIGENSCHAFTEN VON INDUSTRIELLEN SUBSTANZEN - Achte
Auflage - Van Nostrand Reinold

Die vorstehenden Angaben stützen sich auf den heutigen Stand unserer Kenntnisse. Sie gelten nur für das angegebene Produkt und stellen keine Zusicherung von Eigenschaften dar.

Es obliegt dem Anwender die Zuständigkeit und die Vollständigkeit dieser Angaben für seine spezifische Anwendung zu kontrollieren.

Dieses Datenblatt ersetzt alle früheren Ausgaben.

ADR:	Europäisches Übereinkommen über die internationale Beförderung gefährlicher Güter auf der Straße
ATE:	Schätzung Akuter Toxizität
ATEGemisch:	Schätzwert der akuten Toxizität (Gemische)
CAS:	Chemical Abstracts Service (Abteilung der American Chemical Society)
CLP:	Einstufung, Verpackung und Kennzeichnung
DNEL:	Abgeleitetes Null-Effekt-Niveau (DNEL)
EINECS:	Europäisches Verzeichnis der auf dem Markt vorhandenen chemischen Stoffe
GefStoffVO:	Gefahrstoffverordnung
GHS:	Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien
IATA:	Internationale Flug-Transport-Vereinigung (IATA)
IATA-DGR:	Vorschriften über die Beförderung gefährlicher Güter der Internationalen Flug-Transport-Vereinigung (IATA)
ICAO:	Internationale Zivilluftfahrtorganisation (ICAO)
ICAO-TI:	Technische Anleitungen der Internationalen Zivilluftfahrtorganisation (ICAO)
IMDG:	Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffsverkehr (IMDG-Code)
INCI:	Internationale Nomenklatur für kosmetische Inhaltsstoffe (INCI)
KSt:	Explosions-Koeffizient
LC50:	Letale Konzentration für 50 Prozent der Testpopulation
LD50:	Letale Dosis für 50 Prozent der Testpopulation
NA:	Nicht anwendbar
PNEC:	Abgeschätzte Nicht-Effekt-Konzentration (PNEC-Wert)
RID:	Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr
STEL:	Grenzwert für Kurzzeiteexposition
STOT:	Zielorgan-Toxizität
TLV:	Arbeitsplatzgrenzwert
TWA:	Zeit gemittelte
WGK:	Wassergefährdungsklasse

Exposure Scenario, 17/07/2019

Substance identity	
Chemical name	IDROCARBURI C3-C4, Miscela (propano, butano, isobutano < 0,1% 1,3-Butadiene)
CAS No.	68476-40-4
EINECS No.	270-681-9

Table of contents

1. **ES 1** Use at industrial site

1. ES 1 Use at industrial site	
1.1 TITLE SECTION	
Exposure Scenario name	Use as a propellant
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)
Environment Contributing Scenario	
CS1 Covered by	ERC4
Worker Contributing Scenario	
CS2 Propellant	PROC1 - PROC2 - PROC3 - PROC8b - PROC9 - PROC12
1.2 Conditions of use affecting exposure	
1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
1.2. CS2: Worker Contributing Scenario: Propellant (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - Use of blowing agents in manufacture of foam (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: > 10 kPa	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Keep drains in watertight containers while awaiting dismantling or subsequent recycling Use in contained systems Ensure operatives are trained to minimise exposures. Ensure that direct skin contact is avoided. Clear transfer lines prior to de-coupling. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Drain down and flush system prior to equipment break-in or maintenance.	
Conditions and measures related to personal protection, hygiene and health evaluation	

Personal protection

Wear suitable respiratory protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 17/07/2019

Substance identity	
Chemical name	Heptane HYDROCARBONS C7, N-ALKANES, ISOALKANES, CYCLICS
EINECS No.	927-510-4

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Use at industrial site
4. **ES 4** Widespread use by professional workers

1. ES 1 Use at industrial site	
1.1 TITLE SECTION	
Exposure Scenario name	Use in coatings
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Environment Contributing Scenario	
CS1 Covered by	ERC4
Worker Contributing Scenario	
CS2 Industrial	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC9 - PROC10 - PROC13 - PROC14 - PROC15
1.2 Conditions of use affecting exposure	
1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
<i>Amount used, frequency and duration of use (or from service life)</i>	
Amounts used: Annual site tonnage 400 t(tonnes)/year Daily amount per site 20000 kg/day	
Maximum allowable site tonnage (MSafe): 62000 kg/day	
Release type: Continuous release	
Emission days: 20 days per year	
<i>Technical and organisational conditions and measures</i>	
Control measures to prevent releases	
Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 90 %
No discharge of substance into waste water	Water - minimum efficiency of: 88.2 %
<i>Conditions and measures related to sewage treatment plant</i>	
STP type: Municipal Sewage Treatment Plant Water - minimum efficiency of: = 96.2 %	
STP effluent (m³/day): 2000	
<i>Conditions and measures related to treatment of waste (including article waste)</i>	
Waste treatment Product residual disposal complies with applicable regulations.	
<i>Other conditions affecting environmental exposure</i>	
Local marine water dilution factor: 100 Local freshwater dilution factor: 10	
1.2. CS2: Worker Contributing Scenario: Industrial (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15)	

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - Roller application or brushing - Treatment of articles by dipping and pouring - Tableting, compression, extrusion, pelletisation, granulation - Use as laboratory reagent (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Remove spills immediately

Ensure operatives are trained to minimise exposures.

Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Wear suitable face shield.

Use suitable eye protection.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario: Covered by (ERC4)

Release route	Release rate	Release estimation method
Air	98 %	N/A
Water	0.07 %	N/A
soil	0 %	N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers

2.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15 - PROC19
---	--

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 0.15 t(tonnes)/year
Daily amount per site 0.41 kg/day

Maximum allowable site tonnage (MSafe): 1500 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):
Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Do not apply industrial sludge to natural soils.
Product residual disposal complies with applicable regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Do not use sludge as fertiliser.

2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)**Process Categories**

Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent - Manual activities involving hand contact (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)

*Product (article) characteristics***Physical form of product:**

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Use in contained systems
Ensure operatives are trained to minimise exposures.
Carry out in a vented booth or extracted enclosure.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear suitable gloves tested to EN374.
Wear suitable face shield.
Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

2.3 Exposure estimation and reference to its source**2.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)**

Release route	Release rate	Release estimation method
Air	98 %	N/A
soil	1 %	N/A
Water	0.1 %	N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Use at industrial site

3.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
----------------	---

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 74 t(tonnes)/year
Daily amount per site 3700 kg/day

Maximum allowable site tonnage (MSafe): 4600000 kg/day

Release type: Continuous release

Emission days: 20 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 70 %
Prevent discharge of undissolved substance to or recover from onsite wastewater.	

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Do not apply industrial sludge to natural soils.
External treatment and disposal of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Do not apply industrial sludge to natural soils.

3.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Remove spills immediately

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

3.3 Exposure estimation and reference to its source

3.3. CS1: Environment Contributing Scenario: Covered by (ERC4)

Release route	Release rate	Release estimation method
Air	1 %	N/A
Water	3E-06 %	N/A
soil	0 %	N/A

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Widespread use by professional workers

4.1 TITLE SECTION

Exposure Scenario name	Cleaning agent
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13
---	--

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 0.012 t(tonnes)/year
Daily amount per site 0.032 kg/day

Maximum allowable site tonnage (MSafe): 170 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):
Prevent discharge of undissolved substance to or recover from onsite wastewater.
Do not apply industrial sludge to natural soils.

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Do not apply industrial sludge to natural soils.
External treatment and disposal of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

4.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Remove spills immediately
- Ensure operatives are trained to minimise exposures.
- Handle substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Ventilation rate: Provide forced ventilation

4.3 Exposure estimation and reference to its source

4.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Release route	Release rate	Release estimation method
Air	2 %	N/A
soil	0 %	N/A
Water	1E-06 %	N/A

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 16/07/2019

Substance identity	
Chemical name	ALCOOL ISOPROPILICO; PROPAN-2-OLO
CAS No.	67-63-0
EINECS No.	200-661-7

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Use at industrial site
3. **ES 3** Widespread use by professional workers
4. **ES 4** Widespread use by professional workers
5. **ES 5** Widespread use by professional workers
6. **ES 6** Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)
7. **ES 7** Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)
8. **ES 8** Consumer use; Anti-freeze and de-icing products (PC4)

1. ES 1 Use at industrial site	
1.1 TITLE SECTION	
Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC4
Worker Contributing Scenario	
CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
1.2 Conditions of use affecting exposure	
1.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
1.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Keep drains in watertight containers while awaiting dismantling or subsequent recycling Ensure that direct skin contact is avoided. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Drain down system prior to equipment break-in or maintenance.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Use suitable eye protection.	
Other conditions affecting worker exposure	

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Use at industrial site

2.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Solvent-based process	ERC4
---------------------------	------

Worker Contributing Scenario

CS2 Industrial	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13 - PROC15
----------------	--

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

2.2. CS2: Worker Contributing Scenario: Industrial (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Keep drains in watertight containers while awaiting dismantling or subsequent recycling
- Ensure that direct skin contact is avoided.
- Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
- Carry out in a vented booth or extracted enclosure.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

2.3 Exposure estimation and reference to its source

N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Widespread use by professional workers

3.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8a - ERC8d
----------------------------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15 - PROC19
--	--

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
---	---

3.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent - Manual activities involving hand contact (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.
Carry out in a vented booth or extracted enclosure.
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Wear a respirator conforming to EN140.

3.3 Exposure estimation and reference to its source

N/A

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Widespread use by professional workers

4.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8a - ERC8d
---------------------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15
---	---

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

4.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.
Avoid carrying out activities involving exposure for more than 15 minutes per day.
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

4.3 Exposure estimation and reference to its source

N/A

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

5. ES 5 Widespread use by professional workers

5.1 TITLE SECTION

Exposure Scenario name	De-icing and anti-icing applications
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8d
----------------------------------	-------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1 - PROC2 - PROC8a - PROC8b - PROC11
--	--

5.2 Conditions of use affecting exposure

5.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
---	--

5.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC8a, PROC8b, PROC11)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Non industrial spraying (PROC1, PROC2, PROC8a, PROC8b, PROC11)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.
Avoid carrying out activities involving exposure for more than 1 hour per day.
Clear transfer lines prior to de-coupling.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

5.3 Exposure estimation and reference to its source

N/A

5.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

6. ES 6 Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)

6.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Non-metal surface treatment products (PC15) - Ink and toners (PC18) - Lubricants, greases, release products (PC24) - Polishes and wax blends (PC31) - Textile dyes and impregnating products (PC34)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8a - ERC8d
---------------------------	---------------

Consumer Contributing Scenario

CS2 Use in coatings	PC9b - PC9a - PC1 - PC4 - PC8 - PC15 - PC18 - PC24 - PC31 - PC34
---------------------	--

6.2 Conditions of use affecting exposure

6.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

6.2. CS2: Consumer Contributing Scenario: Use in coatings (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)

Product Categories	Fillers, putties, plasters, modelling clay - Coatings and paints, thinners, paint removers - Adhesives, sealants - Anti-freeze and de-icing products - Biocidal products - Non-metal surface treatment products - Ink and toners - Lubricants, greases, release products - Polishes and wax blends - Textile dyes and impregnating products (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

Concentration of substance in product:

Covers concentrations up to 50 %

Additional conditions human health

Covers skin contact area up to 430 cm²

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 10 g

Frequency:

Covers exposure up to 1 events per day

Frequency:

Covers frequency up to: 365 days per year

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

6.3 Exposure estimation and reference to its source

N/A

6.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

7. ES 7 Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)	
7.1 TITLE SECTION	
Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Air care products (PC3) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Lubricants, greases, release products (PC24) - Washing and cleaning products (PC35) - Welding and soldering products, flux products (PC38)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC8a - ERC8d
Consumer Contributing Scenario	
CS2 Detergent liquids	PC9a - PC3 - PC4 - PC8 - PC24 - PC35 - PC38
7.2 Conditions of use affecting exposure	
7.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)	
Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
7.2. CS2: Consumer Contributing Scenario: Detergent liquids (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)	
Product Categories	Coatings and paints, thinners, paint removers - Air care products - Anti-freeze and de-icing products - Biocidal products - Lubricants, greases, release products - Washing and cleaning products - Welding and soldering products, flux products (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure > 10 kPa at STP	
Concentration of substance in product: Covers concentrations up to 50 %	
Amount used, frequency and duration of use/exposure	
Amounts used: Amount per use 100 g	
Frequency: Covers use up to 365 days per year	
Frequency: Covers use up to 1 uses per day	
Other conditions affecting consumers exposure	
Room size: Covers use in a one car garage (>34 m ³) under typical ventilation.	
Temperature: Covers use at ambient temperatures.	
Additional conditions human health Covers skin contact area up to 428 cm ²	

7.3 Exposure estimation and reference to its source

N/A

7.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

8. ES 8 Consumer use; Anti-freeze and de-icing products (PC4)

8.1 TITLE SECTION

Exposure Scenario name	De-icing and anti-icing applications
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Anti-freeze and de-icing products (PC4)

Environment Contributing Scenario

CS1 Solvent-based process	ERC4
---------------------------	------

Consumer Contributing Scenario

CS2 De-icing and anti-icing applications	PC24
--	------

8.2 Conditions of use affecting exposure

8.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

8.2. CS2: Consumer Contributing Scenario: De-icing and anti-icing applications (PC24)

Product Categories	Lubricants, greases, release products (PC24)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

Concentration of substance in product:

Covers concentrations up to 10 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 2000 g

Duration:

Covers use up to 0.25 h/event

Frequency:

Covers exposure up to 365 days per year

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

Additional conditions human health

Covers skin contact area up to 428 cm²

8.3 Exposure estimation and reference to its source

N/A

8.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.