



Sicherheitsdatenblatt vom 27/10/2021, Version 8

ABSCHNITT 1: Bezeichnung des Stoffs beziehungsweise des Gemischs und des Unternehmens

1.1. Produktidentifikator

Kennzeichnung der Mischung:

Handelsname: Stoßstangenpflege

Handelscode: 31018

1.2. Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird

Empfohlene Verwendung:

Produkt zum Auffrischen von Stoßstangen

1.3. Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

Lieferant:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Sachkundigen Person verantwortlich vom Sicherheitsdatenblatt:

arexons@arexons.it

1.4. Notrufnummer

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Austrian emergency telephone number : Vergiftungsinformationszentrale (+43 1 406 43 43)

Giftnotruf Berlin: +49 30 30686790

Antigifcentrum Brussel: 80025500 (7 jours sur 7, 24 heures sur 24).

ABSCHNITT 2: Mögliche Gefahren

2.1. Einstufung des Stoffs oder Gemischs

Kriterien der EG Verordnung 1272/2008 (CLP):

⚠ Gefahr, Aerosols 1, Extrem entzündbares Aerosol. Behälter steht unter Druck: Kann bei Erwärmung bersten.

⚠ Achtung, Skin Irrit. 2, Verursacht Hautreizungen.

⚠ Achtung, Eye Irrit. 2, Verursacht schwere Augenreizung.

⚠ Achtung, STOT SE 3, Kann Schläfrigkeit und Benommenheit verursachen.

Aquatic Chronic 3, Schädlich für Wasserorganismen, mit langfristiger Wirkung.

Für die menschlichen Gesundheit und die Umwelt gefährliche physisch-chemische Auswirkungen:

Keine weiteren Risiken

2.2. Kennzeichnungselemente

Gefahrenpiktogramme:



Gefahr

Gefahrenhinweise:

H222, H229 Extrem entzündbares Aerosol. Behälter steht unter Druck: Kann bei Erwärmung bersten.

H315 Verursacht Hautreizungen.

H319 Verursacht schwere Augenreizung.

Sicherheitsdatenblatt Stoßstangenpflege



H336 Kann Schläfrigkeit und Benommenheit verursachen.
H412 Schädlich für Wasserorganismen, mit langfristiger Wirkung.

Sicherheitshinweise:

P101 Ist ärztlicher Rat erforderlich, Verpackung oder Kennzeichnungsetikett bereithalten.
P102 Darf nicht in die Hände von Kindern gelangen.
P103 Lesen Sie sämtliche Anweisungen aufmerksam und befolgen Sie diese.
P210 Von Hitze, heißen Oberflächen, Funken, offenen Flammen sowie anderen Zündquellenarten fernhalten. Nicht rauchen.
P211 Nicht gegen offene Flamme oder andere Zündquelle sprühen.
P251 Nicht durchstechen oder verbrennen, auch nicht nach Gebrauch.
P271 Nur im Freien oder in gut belüfteten Räumen verwenden.
P405 Unter Verschluss aufbewahren.
P410+P412 Vor Sonnenbestrahlung schützen und nicht Temperaturen über 50 °C/122 °F aussetzen.
P501 Inhalt/Behälter laut Verordnung der Entsorgung zuführen.

Spezielle Vorschriften:

EUH208 Enthält Citrus Oil Distilled. Kann allergische Reaktionen hervorrufen.

Enthält

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
2-Propanol; Isopropylalkohol; Isopropanol

Besondere Regelungen gemäß Anhang XVII der REACH-Verordnung nachfolgenden Änderungen:

Keine

2.3. Sonstige Gefahren

Keine PBT-, vPvB-Stoffe oder endokrine Disruptoren in Konzentrationen $\geq 0.1\%$:

Weitere Risiken:

Keine weiteren Risiken

ABSCHNITT 3: Zusammensetzung/Angaben zu Bestandteilen

3.1. Stoffe

N.A.

3.2. Gemische

Gefährliche Bestandteile gemäß der CLP-Verordnung und dazugehörige Einstufung:

$\geq 70\%$ - $< 80\%$ Kohlenwasserstoffe, C3-4; Gase aus der Erdölverarbeitung

REACH No.: 01-2119486557-22, Index-Nummer: 649-199-00-1, CAS: 68476-40-4, EC: 270-681-9

⚠ 2.2/1A Flam. Gas 1A H220

⚠ 2.5/L Press Gas (Liq.) H280

DECLK (CLP)*

$\geq 20\%$ - $< 25\%$ Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

REACH No.: 01-2119475515-33, EC: 927-510-4

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.8/3 STOT SE 3 H336

⚠ 4.1/C2 Aquatic Chronic 2 H411

EUH066

$\geq 2\%$ - $< 3\%$ 2-Propanol; Isopropylalkohol; Isopropanol

REACH No.: 01-2119457558-25, Index-Nummer: 603-117-00-0, CAS: 67-63-0, EC: 200-661-7

⚠ 2.6/2 Flam. Liq. 2 H225

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H336

Sicherheitsdatenblatt Stoßstangenpflege



>= 0.1% - < 0.25% Citrus Oil Distilled
CAS: 68647-72-3, EC: 614-678-6
⚠ 2.6/3 Flam. Liq. 3 H226
⚠ 3.10/1 Asp. Tox. 1 H304
⚠ 3.2/2 Skin Irrit. 2 H315
⚠ 3.4.2/1 Skin Sens. 1 H317
⚠ 3.3/2 Eye Irrit. 2 H319
⚠ 4.1/A1 Aquatic Acute 1 H400
⚠ 4.1/C1 Aquatic Chronic 1 H410

>= 0.02% - < 0.05% benzene,1,1'-oxybis
CAS: 101-84-8
⚠ 3.3/2 Eye Irrit. 2 H319
⚠ 4.1/C1 Aquatic Chronic 1 H410

*DECLK (CLP): Stoff eingestuft gemäß Anmerkung K im Anhang VI der Verordnung 1272/2008/EG. Die harmonisierte Einstufung als karzinogen oder keimzellmutagen wird vorgenommen, es sei denn, es kann nachgewiesen werden, dass der Stoff weniger als 0,1 Gewichtsprozent 1,3-Butadien (Einecs-Nr. 203-450-8) enthält; in diesem Fall ist auch für diese Gefahrenklassen eine Einstufung gemäß Titel II dieser Verordnung vorzunehmen. Wird der Stoff nicht als karzinogen oder keimzellmutagen eingestuft, so sind zumindest die Sicherheitshinweise (P102-)P210-P403 anzuwenden.

ABSCHNITT 4: Erste-Hilfe-Maßnahmen

4.1. Beschreibung der Erste-Hilfe-Maßnahmen

Nach Hautkontakt:

Verunreinigte Kleidung sofort ausziehen.

Körperbereiche, die mit dem Produkt in Kontakt getreten sind, bzw. bei denen dieser Verdacht besteht, müssen sofort mit viel fließendem Wasser und möglichst mit Seife gewaschen werden. Den Körper vollständig waschen (Dusche oder Bad).

Die kontaminierten Kleidungsstücke sofort ablegen und sie auf sichere Weise entsorgen.

Im Falle von Hautkontakt sofort mit reichlich Wasser und Seife waschen.

Nach Augenkontakt:

Im Falle von Augenkontakt die Augen über einen ausreichenden Zeitraum mit Wasser spülen und die Augenlider offen halten; sofort einen Augenarzt konsultieren.

Das unverletzte Auge schützen.

Nach Verschlucken:

Auf keinen Fall Erbrechen herbeiführen. SOFORT ARZT ZUZIEHEN.

Nach Einatmen:

Den Verletzten ins Freie bringen, ihn ausruhen lassen und warm halten.

4.2. Wichtigste akute und verzögert auftretende Symptome und Wirkungen

Keine

4.3. Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung

Im Falle eines Unfalls bzw. bei Unwohlsein sofort einen Arzt konsultieren (wenn möglich, die Bedienungsanleitung bzw. das Sicherheitsdatenblatt vorzeigen).

Behandlung:

Keine

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung

5.1. Löschmittel

Geeignete Löschmittel:

Mit Kohlendioxid.

Mit Pulver.



- Schaum
- Wasserdampf.
- Löschmittel nicht empfohlen:
- Keine direkten Wasserstrahlen benutzen
- 5.2. Besondere vom Stoff oder Gemisch ausgehende Gefahren
 - Die Explosions- bzw. Verbrennungsgase nicht einatmen.
 - Durch die Verbrennung entsteht ein dichter Rauch.
- 5.3. Hinweise für die Brandbekämpfung
 - Geeignete Atemgeräte verwenden.
 - Das kontaminierte Löschwasser getrennt auffangen. Nicht in der Abwasserleitung entsorgen.
 - Wenn im Rahmen der Sicherheit möglich, die unbeschädigten Behälter aus der unmittelbaren Gefahrenzone entfernen.

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung

- 6.1. Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren
 - Die persönliche Schutzausrüstung tragen.
 - Alle Entzündungsquellen entfernen.
 - Die Personen an einen sicheren Ort bringen.
 - Die in Punkt 7 und 8 aufgeführten Schutzmaßnahmen beachten.
- 6.2. Umweltschutzmaßnahmen
 - Das Eindringen in den Boden/Unterboden verhindern. Das Abfließen in das Grundwasser oder in die Kanalisation verhindern.
 - Das kontaminierte Waschwasser auffangen und entsorgen.
 - Bei Austritt von Gas oder bei Eintritt in Wasserläufe, den Boden oder die Kanalisation die zuständigen Behörden informieren.
 - Geeignetes Material zum Auffangen: absorbierende oder organische Materialien, Sand
- 6.3. Methoden und Material für Rückhaltung und Reinigung
 - Mit reichlich Wasser waschen.
- 6.4. Verweis auf andere Abschnitte
 - Siehe auch die Abschnitte 8 und 13

ABSCHNITT 7: Handhabung und Lagerung

- 7.1. Schutzmaßnahmen zur sicheren Handhabung
 - Haut- und Augenkontakt sowie das Einatmen von Dämpfen vermeiden.
 - Keine leeren Behälter verwenden, bevor diese nicht gereinigt wurden.
 - Vor dem Umfüllen sicherstellen, dass sich in den Behältern keine Reste inkompatibler Stoffe befinden.
 - Für die empfohlenen Schutzausrüstungen wird auf Abschnitt 8 verwiesen.

Kontaminierte Kleidungsstücke müssen vor dem Eintritt in Speiseräume gewechselt werden.
Während der Arbeit nicht essen oder trinken.
- 7.2. Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten
 - Unter 50 °C lagern. Vor offenen Flammen und Wärmequellen fern halten. Keiner direkten Sonneneinstrahlung aussetzen.
 - Vor offenen Flammen, Zündfunken und Wärmequellen fern halten. Keiner direkten Sonneneinstrahlung aussetzen.
 - Lebensmittel, Getränke und Tiernahrung fern halten.
 - Kein spezifischer.
 - Angaben zu den Lagerräumen:
Kühl und ausreichend belüftet.
- 7.3. Spezifische Endanwendungen
 - Kein besonderer Verwendungszweck



ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

8.1. Zu überwachende Parameter

Kohlenwasserstoffe, C3-4; Gase aus der Erdölverarbeitung - CAS: 68476-40-4

MAK - TWA: 2400 mg/m³, 1000 ppm

TLV TWA - 1900 mg/m³, 800 ppm

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

EU

2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0

20101.11 - TWA: 983 mg/m³, 400 ppm

20101.12 - TWA: 492 mg/m³, 200 ppm

ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Anmerkungen: A4, BEI - Eye and URT irr, CNS impair

benzene,1,1'-oxybis - CAS: 101-84-8

EU - TWA(8h): 7 mg/m³, 1 ppm - STEL: 14 mg/m³, 2 ppm

ACGIH - TWA(8h): 1 ppm - STEL: 2 ppm - Anmerkungen: (V) - URT and eye irr, nausea

DNEL-Expositionsgrenzwerte

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Arbeitnehmer Gewerbe: 300 mg/kg - Exposition: Mensch - dermal - Häufigkeit: Langfristig, systemische Auswirkungen

Arbeitnehmer Gewerbe: 508 ppm - Exposition: Mensch - Inhalation - Häufigkeit: Kurzfristig, systemische Auswirkungen

Verbraucher: 149 mg/kg - Exposition: Mensch - dermal - Häufigkeit: Langfristig, systemische Auswirkungen

Verbraucher: 109 ppm - Exposition: Mensch - Inhalation - Häufigkeit: Langfristig, systemische Auswirkungen

Verbraucher: 149 mg/kg - Exposition: Mensch - oral - Häufigkeit: Langfristig, systemische Auswirkungen

2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0

Arbeitnehmer Gewerbe: 888 mg/kg - Verbraucher: 319 mg/kg - Exposition: Mensch - dermal - Häufigkeit: Langfristig (wiederholt)

Arbeitnehmer Gewerbe: 500 mg/m³ - Verbraucher: 89 mg/m³ - Exposition: Mensch - Inhalation - Häufigkeit: Langfristig (wiederholt)

Verbraucher: 26 mg/kg - Exposition: Mensch - oral - Häufigkeit: Langfristig (wiederholt)

PNEC-Expositionsgrenzwerte

2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0

Ziel: Süßwasser - Wert: 140.9 mg/l

Ziel: Süßwasser - Wert: 140.9 mg/l

Ziel: Flußsediment - Wert: 552 mg/l

Ziel: Boden (Landwirtschaft) - Wert: 28 mg/kg

Ziel: Mikroorganismen in Kläranlagen - Wert: 2251 mg/l

8.2. Begrenzung und Überwachung der Exposition

Augenschutz:

Die Sicherheitsvisiere schließen, keine Kontaktlinsen verwenden.

Hautschutz:

Bei normaler Verwendung sind besondere Vorsichtsmaßnahmen nicht notwendig.

Handschutz:

Schutzhandschuhe tragen, die einen vollständigen Schutz garantieren, z.B. aus PVC, Neopren oder Gummi.

Atemschutz:

Einen angemessenen Atemschutz verwenden.

Wärmerisiken:

Keine

Kontrollen der Umweltexposition:

Keine

Sicherheitsdatenblatt

Stoßstangenpflege



Geeignete technische Massnahmen:
Keine

ABSCHNITT 9: Physikalische und chemische Eigenschaften

9.1. Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften

Eigenschaft	Wert	Methode:	Anmerkungen
Aggregatzustand:	flüssig	--	--
Farbe:	N.A.	--	--
Geruch:	charakteristisch	--	--
Schmelzpunkt/ Gefrierpunkt:	N.A.	--	--
Siedepunkt oder Siedebeginn und Siedebereich:	N.A.	--	--
Entzündbarkeit:	N.A.	--	--
Untere und obere Explosionsgrenze:	N.A.	--	--
Flammpunkt:	N.A.	--	--
Selbstentzündungstemperatur:	N.A.	--	--
Zerfalltemperatur:	N.A.	--	--
pH:	N.A.	--	--
Kinematische Viskosität:	N.A.	--	--
Wasserlöslichkeit:	N.A.	--	--
Löslichkeit in Öl:	N.A.	--	--
Verteilungskoeffizient n- Oktanol/Wasser (log- Wert):	N.A.	--	--
Dampfdruck:	N.A.	--	--
Dichte und/oder relative Dichte:	N.A.	--	--
Relative Dampfdichte:	N.A.	--	--
Partikeleigenschaften:			
Teilchengröße:	N.A.	--	--

9.2. Sonstige Angaben

31018/8

Seite Nr. 6 von 12



Keine weiteren relevanten Informationen

ABSCHNITT 10: Stabilität und Reaktivität

- 10.1. Reaktivität
Stabil unter Normalbedingungen
- 10.2. Chemische Stabilität
Stabil unter Normalbedingungen
- 10.3. Möglichkeit gefährlicher Reaktionen
Keine
- 10.4. Zu vermeidende Bedingungen
Unter normalen Umständen stabil.
- 10.5. Unverträgliche Materialien
Kontakt mit brandfördernden Materialien vermeiden. Das Produkt könnte in Brand geraten.
- 10.6. Gefährliche Zersetzungsprodukte
Keine.

ABSCHNITT 11: Toxikologische Angaben

11.1. Angaben zu den Gefahrenklassen im Sinne der Verordnung (EG) Nr. 1272/2008

Toxikologische Informationen zum Produkt:

EXTERIOR PLASTIC TREATMENT SPRAY ML 600

- a) akute Toxizität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- b) Ätz-/Reizwirkung auf die Haut
Das Produkt ist eingestuft: Skin Irrit. 2 H315
- c) schwere Augenschädigung/-reizung
Das Produkt ist eingestuft: Eye Irrit. 2 H319
- d) Sensibilisierung der Atemwege/Haut
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- e) Keimzell-Mutagenität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- f) Karzinogenität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- g) Reproduktionstoxizität
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- h) spezifische Zielorgan-Toxizität bei einmaliger Exposition
Das Produkt ist eingestuft: STOT SE 3 H336
- i) spezifische Zielorgan-Toxizität bei wiederholter Exposition
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.
- j) Aspirationsgefahr
Nicht klassifiziert
Aufgrund der verfügbaren Daten sind die Einstufungskriterien nicht erfüllt.

Toxikologische Informationen zu den Hauptbestandteilen des Produkts:

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

- a) akute Toxizität:
 - Test: LC50 - Weg: Einatmen - Spezies: Ratte > 23.3 mg/l - Laufzeit: 4h
 - Test: LD50 - Weg: Oral - Spezies: Ratte > 8 ml/kg
 - Test: LD50 - Weg: Haut - Spezies: Kaninchen 2800-3100 mg/kg
- 2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0

Sicherheitsdatenblatt Stoßstangenpflege



- a) akute Toxizität:
Test: LD50 - Weg: Oral - Spezies: Ratte > 5000 mg/kg
Test: LD50 - Weg: Haut - Spezies: Kaninchen > 5000 mg/kg
Test: LC50 - Weg: Einatmen - Spezies: Ratte > 10000 ppm - Laufzeit: 6h

- 11.2. Angaben über sonstige Gefahren
Endokrinschädliche Eigenschaften:
Keine endokrinen Disruptoren in Konzentrationen ≥ 0.1 %.

ABSCHNITT 12: Umweltbezogene Angaben

- 12.1. Toxizität
Im Einklang mit der GLP verwenden, nicht herumliegen lassen.
Kohlenwasserstoffe, C3-4; Gase aus der Erdölverarbeitung - CAS: 68476-40-4
a) Akute aquatische Toxizität:
Endpunkt: LC50 - Spezies: Daphnia = 14.22 mg/l - Dauer / h: 48
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics
b) Chronische aquatische Toxizität:
Endpunkt: EC50 - Spezies: Algen > 10-30 mg/l - Dauer / h: 72
Endpunkt: LC50 - Spezies: Fische > 13.4 mg/l - Dauer / h: 96
2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0
a) Akute aquatische Toxizität:
Endpunkt: LC50 - Spezies: Fische 4200 mg/l - Dauer / h: 96
Endpunkt: LC50 - Spezies: Fische > 100 mg/l - Dauer / h: 48
Endpunkt: EC50 - Spezies: Daphnia > 100 mg/l - Dauer / h: 48
Endpunkt: EC50 - Spezies: Algen > 100 mg/l - Dauer / h: 72
- 12.2. Persistenz und Abbaubarkeit
Keine
2-Propanol; Isopropylalkohol; Isopropanol - CAS: 67-63-0
Biologische Abbaubarkeit: Schnell abbaubar - Dauer / h: .10gg - %: 70
- 12.3. Bioakkumulationspotenzial
N.A.
- 12.4. Mobilität im Boden
N.A.
- 12.5. Ergebnisse der PBT- und vPvB-Beurteilung
vPvB-Stoffe: Keine - PBT-Stoffe: Keine
- 12.6. Endokrinschädliche Eigenschaften
Keine endokrinen Disruptoren in Konzentrationen ≥ 0.1 %.
- 12.7. Andere schädliche Wirkungen
Keine

ABSCHNITT 13: Hinweise zur Entsorgung

- 13.1. Verfahren der Abfallbehandlung
Nach Möglichkeit wiederverwerten. Behördlich zugelassenen Deponien oder
Verbrennungsanlagen zuführen. Entsprechend den geltenden örtlichen und nationalen
Bestimmungen vorgehen.

ABSCHNITT 14: Angaben zum Transport



- 14.1. UN-Nummer oder ID-Nummer
ADR-UN Number: 1950

31018/8

Seite Nr. 8 von 12

Sicherheitsdatenblatt Stoßstangenpflege



IATA-UN Number:	1950	
IMDG-UN Number:	1950	
14.2. Ordnungsgemäße UN-Versandbezeichnung		
ADR-Shipping Name:	DRUCKGASPACKUNGEN, entzündbar	
IATA-Shipping Name:	DRUCKGASPACKUNGEN, entzündbar	
IMDG-Shipping Name:	DRUCKGASPACKUNGEN, entzündbar	
14.3. Transportgefahrenklassen		
ADR-Class:	2	
ADR - Gefahrennummer:	-	
IATA-Class:	2	
IATA-Label:	2.1	
IMDG-Class:	2	
IMDG-Klasse:	2	
14.4. Verpackungsgruppe		
ADR-Packing Group:	-	
IATA-Packing group:	-	
IMDG-Packing group:	-	
14.5. Umweltgefahren		
ADR-Umweltbelastung:	Nein	
IMDG-Marine pollutant:	Nein	
IMDG-EmS:	F-D, S-U	
14.6. Besondere Vorsichtsmaßnahmen für den Verwender		
ADR-Subsidiary hazards:	See SP63	
ADR-S.P.:	190 327 344 625	
ADR-Beförderungskategorie (Tunnelbeschränkungscode):		2 (D)
IATA-Passenger Aircraft:	203	
IATA-Subsidiary hazards:	See SP63	
IATA-Cargo Aircraft:	203	
IATA-S.P.:	A145 A167 A802	
IATA-ERG:	10L	
IMDG-Subsidiary hazards:	See SP63	
IMDG-Stowage and handling:	SW1 SW22	
IMDG-Segregation:	SG69	
14.7. Massengutbeförderung auf dem Seeweg gemäß IMO-Instrumenten		
N.A.		
Limited Quantity:	1 L	
Exempted Quantity:	E0	

ABSCHNITT 15: Rechtsvorschriften

15.1. Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder

- RL 98/24/EG (Schutz von Gesundheit und Sicherheit der Arbeitnehmer vor der Gefährdung durch chemische Arbeitsstoffe bei der Arbeit)
- RL 2000/39/EG (Arbeitsplatz-Richtgrenzwerte)
- Verordnung (EG) Nr. 1907/2006 (REACH)
- Verordnung (EG) Nr. 1272/2008 (CLP)
- Verordnung (EG) Nr. 790/2009 (1. ATP CLP) und (EU) Nr. 758/2013
- Verordnung (EU) Nr. 2020/878
- Verordnung (EU) Nr. 286/2011 (2. ATP CLP)
- Verordnung (EU) Nr. 618/2012 (3. ATP CLP)
- Verordnung (EU) Nr. 487/2013 (4. ATP CLP)
- Verordnung (EU) Nr. 944/2013 (5. ATP CLP)
- Verordnung (EU) Nr. 605/2014 (6. ATP CLP)
- Verordnung (EU) Nr. 2015/1221 (7. ATP CLP)
- Verordnung (EU) Nr. 2016/918 (8. ATP CLP)

Sicherheitsdatenblatt

Stoßstangenpflege



- Verordnung (EU) Nr. 2016/1179 (9. ATP CLP)
- Verordnung (EU) Nr. 2017/776 (10. ATP CLP)
- Verordnung (EU) Nr. 2018/669 (11. ATP CLP)
- Verordnung (EU) Nr. 2018/1480 (13. ATP CLP)
- Verordnung (EU) Nr. 2019/521 (12. ATP CLP)
- Verordnung (EU) Nr. 2020/217 (14. ATP CLP)
- Verordnung (EU) Nr. 2020/1182 (15. ATP CLP)
- Verordnung (EU) Nr. 2021/643 (16. ATP CLP)

Beschränkungen zum Produkt oder zu den Inhaltsstoffen gemäß Anhang XVII der Verordnung (EG) 1907/2006 (REACH) und nachfolgenden Änderungen:

Beschränkungen zum Produkt:

- Beschränkung 3
- Beschränkung 40

Beschränkungen zu den Inhaltsstoffen gemäß:
Beschränkung 75

- Flüchtige Organische Verbindung - FOV = 94.02 %
- Flüchtige Organische Verbindung - FOV = 940.15 g/Kg
- Flüchtige Organische Verbindung - FOV = 571.61 g/l
- Wo möglich auf die folgenden Normen Bezug nehmen:
 - Richtlinie EU 2012/18 (Seveso III)
 - Verordnung (EG) Nr. 648/2004 (Detergenzien).
 - RL 2004/42/EG (FOV Richtlinie)

Anordnungen zu der Richtlinie EU 2012/18 (Seveso III):
Seveso III Kategorie gemäß dem Anhang 1, Teil 1
Das Produkt gehört zur Kategorie: P3a

15.2. Stoffsicherheitsbeurteilung

Keine Stoffsicherheitsbeurteilung wurde durchgeführt für das Gemisch
Stoffe, für die eine Stoffsicherheitsbeurteilung durchgeführt worden ist:
Keine

ABSCHNITT 16: Sonstige Angaben

Text der verwendeten Sätze im Absatz 3:

- H220 Extrem entzündbares Gas.
- H280 Enthält Gas unter Druck; kann bei Erwärmung explodieren.
- H225 Flüssigkeit und Dampf leicht entzündbar.
- H304 Kann bei Verschlucken und Eindringen in die Atemwege tödlich sein.
- H315 Verursacht Hautreizungen.
- H336 Kann Schläfrigkeit und Benommenheit verursachen.
- H411 Giftig für Wasserorganismen, mit langfristiger Wirkung.
- EUH066 Wiederholter Kontakt kann zu spröder oder rissiger Haut führen.
- H319 Verursacht schwere Augenreizung.
- H226 Flüssigkeit und Dampf entzündbar.
- H317 Kann allergische Hautreaktionen verursachen.
- H400 Sehr giftig für Wasserorganismen.
- H410 Sehr giftig für Wasserorganismen mit langfristiger Wirkung.

Gefahrenklasse und Gefahrenkategorie	Code	Beschreibung
Flam. Gas 1A	2.2/1A	Entzündbare Gas, Kategorie 1A
Aerosols 1	2.3/1	Aerosole, Kategorie 1

Sicherheitsdatenblatt Stoßstangenpflege



Press Gas (Liq.)	2.5/L	Gase unter Druck (verflüssigtes Gas)
Flam. Liq. 2	2.6/2	Entzündbare Flüssigkeiten, Kategorie 2
Flam. Liq. 3	2.6/3	Entzündbare Flüssigkeiten, Kategorie 3
Asp. Tox. 1	3.10/1	Aspirationsgefahr, Kategorie 1
Skin Irrit. 2	3.2/2	Reizung der Haut, Kategorie 2
Eye Irrit. 2	3.3/2	Reizung der Augen, Kategorie 2
Skin Sens. 1	3.4.2/1	Sensibilisierung der Haut, Kategorie 1
STOT SE 3	3.8/3	Spezifische Zielorgan-Toxizität (einmalige Exposition), Kategorie 3
Aquatic Acute 1	4.1/A1	Akut gewässergefährdend, Kategorie 1
Aquatic Chronic 1	4.1/C1	Chronisch (langfristig) gewässergefährdend, Kategorie 1
Aquatic Chronic 2	4.1/C2	Chronisch (langfristig) gewässergefährdend, Kategorie 2
Aquatic Chronic 3	4.1/C3	Chronisch (langfristig) gewässergefährdend, Kategorie 3

Dieses Sicherheitsdatenblatt wurde vollständig gemäß Verordnung 2020/878 angepasst. Einstufung und Verfahren, das zum Ableiten der Einstufung von Gemischen gemäß Verordnung (EG) 1272/2008 [CLP] verwendet wurde:

Einstufung gemäß Verordnung (EG) Nr. 1272/2008	Einstufungsverfahren
Aerosols 1, H222, H229	auf der Basis von Prüfdaten
Skin Irrit. 2, H315	Berechnungsmethode
Eye Irrit. 2, H319	Berechnungsmethode
STOT SE 3, H336	Berechnungsmethode
Aquatic Chronic 3, H412	Berechnungsmethode

Diese Unterlagen wurden von einem Fachmann mit entsprechender Ausbildung abgefasst.
Hauptsächliche Literatur:

ECDIN - Daten- und Informationsnetz über umweltrelevante Chemikalien - Vereinigtes
Forschungszentrum, Kommission der Europäischen Gemeinschaft
SAX's GEFÄHRLICHE EIGENSCHAFTEN VON INDUSTRIELLEN SUBSTANZEN - Achte
Auflage - Van Nostrand Reinold

Die vorstehenden Angaben stützen sich auf den heutigen Stand unserer Kenntnisse. Sie gelten nur für das angegebene Produkt und stellen keine Zusicherung von Eigenschaften dar.
Es obliegt dem Anwender die Zuständigkeit und die Vollständigkeit dieser Angaben für seine spezifische Anwendung zu kontrollieren.
Dieses Datenblatt ersetzt alle früheren Ausgaben.

Sicherheitsdatenblatt Stoßstangenpflege



ADR:	Europäisches Übereinkommen über die internationale Beförderung gefährlicher Güter auf der Straße
ATE:	Schätzung Akuter Toxizität
ATEGemisch:	Schätzwert der akuten Toxizität (Gemische)
CAS:	Chemical Abstracts Service (Abteilung der American Chemical Society)
CLP:	Einstufung, Verpackung und Kennzeichnung
DNEL:	Abgeleitetes Null-Effekt-Niveau (DNEL)
EINECS:	Europäisches Verzeichnis der auf dem Markt vorhandenen chemischen Stoffe
GefStoffVO:	Gefahrstoffverordnung
GHS:	Global harmonisiertes System zur Einstufung und Kennzeichnung von Chemikalien
IATA:	Internationale Flug-Transport-Vereinigung (IATA)
IATA-DGR:	Vorschriften über die Beförderung gefährlicher Güter der Internationalen Flug-Transport-Vereinigung (IATA)
ICAO:	Internationale Zivilluftfahrtorganisation (ICAO)
ICAO-TI:	Technische Anleitungen der Internationalen Zivilluftfahrtorganisation (ICAO)
IMDG:	Gefahrgutkennzeichnung für gefährliche Güter im Seeschiffsverkehr (IMDG-Code)
INCI:	Internationale Nomenklatur für kosmetische Inhaltsstoffe (INCI)
KSt:	Explosions-Koeffizient
LC50:	Letale Konzentration für 50 Prozent der Testpopulation
LD50:	Letale Dosis für 50 Prozent der Testpopulation
NA:	Nicht anwendbar
PNEC:	Abgeschätzte Nicht-Effekt-Konzentration (PNEC-Wert)
RID:	Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr
STEL:	Grenzwert für Kurzzeitexposition
STOT:	Zielorgan-Toxizität
TLV:	Arbeitsplatzgrenzwert
TWA:	Zeit gemittelte
WGK:	Wassergefährdungsklasse

Exposure Scenario, 17/07/2019

Substance identity	
Chemical name	IDROCARBURI C3-C4, Miscela (propano, butano, isobutano < 0,1% 1,3-Butadiene)
CAS No.	68476-40-4
EINECS No.	270-681-9

Table of contents

1. **ES 1** Use at industrial site

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use as a propellant
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Propellant	PROC1 - PROC2 - PROC3 - PROC8b - PROC9 - PROC12
----------------	---

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

1.2. CS2: Worker Contributing Scenario: Propellant (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - Use of blowing agents in manufacture of foam (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

> 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Keep drains in watertight containers while awaiting dismantling or subsequent recycling
- Use in contained systems
- Ensure operatives are trained to minimise exposures.
- Ensure that direct skin contact is avoided.
- Clear transfer lines prior to de-coupling.
- Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
- Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 17/07/2019

Substance identity

Chemical name	Heptane HYDROCARBONS C7, N-ALKANES, ISOALKANES, CYCLICS
EINECS No.	927-510-4

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Use at industrial site
4. **ES 4** Widespread use by professional workers

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC9 - PROC10 - PROC13 - PROC14 - PROC15
----------------	---

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 400 t(tonnes)/year
Daily amount per site 20000 kg/day

Maximum allowable site tonnage (MSafe): 62000 kg/day

Release type: Continuous release

Emission days: 20 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 90 %
No discharge of substance into waste water	Water - minimum efficiency of: 88.2 %

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Product residual disposal complies with applicable regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

1.2. CS2: Worker Contributing Scenario: Industrial (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15)

Process Categories

Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - Roller application or brushing - Treatment of articles by dipping and pouring - Tableting, compression, extrusion, pelletisation, granulation - Use as laboratory reagent (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Remove spills immediately
- Ensure operatives are trained to minimise exposures.
- Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

- Wear suitable gloves tested to EN374.
- Wear suitable face shield.
- Use suitable eye protection.

1.3 Exposure estimation and reference to its source

1.3. CS1: Environment Contributing Scenario: Covered by (ERC4)

Release route	Release rate	Release estimation method
Air	98 %	N/A
Water	0.07 %	N/A
soil	0 %	N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers

2.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15 - PROC19
---	--

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 0.15 t(tonnes)/year
Daily amount per site 0.41 kg/day

Maximum allowable site tonnage (MSafe): 1500 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):
Prevent discharge of undissolved substance to or recover from onsite wastewater.

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Do not apply industrial sludge to natural soils.
Product residual disposal complies with applicable regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Do not use sludge as fertiliser.

2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)
Process Categories

Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent - Manual activities involving hand contact (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)

*Product (article) characteristics***Physical form of product:**

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

*Technical and organisational conditions and measures***Technical and organisational measures**

Use in contained systems
Ensure operatives are trained to minimise exposures.
Carry out in a vented booth or extracted enclosure.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear suitable gloves tested to EN374.
Wear suitable face shield.
Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

2.3 Exposure estimation and reference to its source
2.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Release route	Release rate	Release estimation method
Air	98 %	N/A
soil	1 %	N/A
Water	0.1 %	N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Use at industrial site

3.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
----------------	---

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 74 t(tonnes)/year
Daily amount per site 3700 kg/day

Maximum allowable site tonnage (MSafe): 4600000 kg/day

Release type: Continuous release

Emission days: 20 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):	Air - minimum efficiency of: 70 %
Prevent discharge of undissolved substance to or recover from onsite wastewater.	

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Do not apply industrial sludge to natural soils.
External treatment and disposal of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Do not apply industrial sludge to natural soils.

3.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Remove spills immediately

Ensure operatives are trained to minimise exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

3.3 Exposure estimation and reference to its source

3.3. CS1: Environment Contributing Scenario: Covered by (ERC4)

Release route	Release rate	Release estimation method
Air	1 %	N/A
Water	3E-06 %	N/A
soil	0 %	N/A

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Widespread use by professional workers

4.1 TITLE SECTION

Exposure Scenario name	Cleaning agent
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13
---	--

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual site tonnage 0.012 t(tonnes)/year
Daily amount per site 0.032 kg/day

Maximum allowable site tonnage (MSafe): 170 kg/day

Release type: Continuous release

Emission days: 365 days per year

Technical and organisational conditions and measures

Control measures to prevent releases

Treat air emission to provide the required removal efficiency of (%):
Prevent discharge of undissolved substance to or recover from onsite wastewater.
Do not apply industrial sludge to natural soils.

Conditions and measures related to sewage treatment plant

STP type:

Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 96.2 %

STP effluent (m³/day): 2000

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Do not apply industrial sludge to natural soils.
External treatment and disposal of waste should comply with applicable local and/or national regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

4.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

< 20 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Remove spills immediately
- Ensure operatives are trained to minimise exposures.
- Handle substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

Ventilation rate: Provide forced ventilation

4.3 Exposure estimation and reference to its source

4.3. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Release route	Release rate	Release estimation method
Air	2 %	N/A
soil	0 %	N/A
Water	1E-06 %	N/A

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 16/07/2019

Substance identity	
Chemical name	ALCOOL ISOPROPILICO; PROPAN-2-OLO
CAS No.	67-63-0
EINECS No.	200-661-7

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Use at industrial site
3. **ES 3** Widespread use by professional workers
4. **ES 4** Widespread use by professional workers
5. **ES 5** Widespread use by professional workers
6. **ES 6** Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)
7. **ES 7** Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)
8. **ES 8** Consumer use; Anti-freeze and de-icing products (PC4)

1. ES 1 Use at industrial site	
1.1 TITLE SECTION	
Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)
Environment Contributing Scenario	
CS1 Solvent-based process	ERC4
Worker Contributing Scenario	
CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13
1.2 Conditions of use affecting exposure	
1.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
1.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring (PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13)
Product (article) characteristics	
Physical form of product: Liquid, vapour pressure 0,5 - 10 kPa at STP	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Technical and organisational conditions and measures	
Technical and organisational measures Keep drains in watertight containers while awaiting dismantling or subsequent recycling Ensure that direct skin contact is avoided. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Drain down system prior to equipment break-in or maintenance.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection Use suitable eye protection.	
Other conditions affecting worker exposure	

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Use at industrial site

2.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Solvent-based process	ERC4
---------------------------	------

Worker Contributing Scenario

CS2 Industrial	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC7 - PROC8a - PROC8b - PROC10 - PROC13 - PROC15
----------------	--

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

2.2. CS2: Worker Contributing Scenario: Industrial (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Industrial spraying - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC5, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Keep drains in watertight containers while awaiting dismantling or subsequent recycling
- Ensure that direct skin contact is avoided.
- Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
- Carry out in a vented booth or extracted enclosure.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

2.3 Exposure estimation and reference to its source

N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Widespread use by professional workers

3.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8a - ERC8d
----------------------------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC5 - PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15 - PROC19
--	--

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
---	---

3.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)

Process Categories	Mixing or blending in batch processes - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent - Manual activities involving hand contact (PROC5, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.
Carry out in a vented booth or extracted enclosure.
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Wear a respirator conforming to EN140.

3.3 Exposure estimation and reference to its source

N/A

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Widespread use by professional workers

4.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Solvent-based process ERC8a - ERC8d

Worker Contributing Scenario

CS2 General use from professional operators PROC1 - PROC2 - PROC3 - PROC4 - PROC8a - PROC8b - PROC10 - PROC11 - PROC13 - PROC15

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

Environmental release categories
Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)

4.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)

Process Categories
Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Chemical production where opportunity for exposure arises - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Roller application or brushing - Non industrial spraying - Treatment of articles by dipping and pouring - Use as laboratory reagent (PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15)

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.
Avoid carrying out activities involving exposure for more than 15 minutes per day.
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
Store substance within a closed system.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

4.3 Exposure estimation and reference to its source

N/A

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

5. ES 5 Widespread use by professional workers

5.1 TITLE SECTION

Exposure Scenario name	De-icing and anti-icing applications
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8d
----------------------------------	-------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1 - PROC2 - PROC8a - PROC8b - PROC11
--	--

5.2 Conditions of use affecting exposure

5.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
---	--

5.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC8a, PROC8b, PROC11)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Non industrial spraying (PROC1, PROC2, PROC8a, PROC8b, PROC11)
---------------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure 0,5 - 10 kPa at STP

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.
Avoid carrying out activities involving exposure for more than 1 hour per day.
Clear transfer lines prior to de-coupling.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Use suitable eye protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

5.3 Exposure estimation and reference to its source

N/A

5.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

6. ES 6 Consumer use; Various products (PC9b, PC9a, PC1, PC4, PC8)

6.1 TITLE SECTION

Exposure Scenario name	Use in coatings
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Fillers, putties, plasters, modelling clay (PC9b) - Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Non-metal surface treatment products (PC15) - Ink and toners (PC18) - Lubricants, greases, release products (PC24) - Polishes and wax blends (PC31) - Textile dyes and impregnating products (PC34)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8a - ERC8d
----------------------------------	---------------

Consumer Contributing Scenario

CS2 Use in coatings	PC9b - PC9a - PC1 - PC4 - PC8 - PC15 - PC18 - PC24 - PC31 - PC34
----------------------------	--

6.2 Conditions of use affecting exposure

6.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
---	---

6.2. CS2: Consumer Contributing Scenario: Use in coatings (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)

Product Categories	Fillers, putties, plasters, modelling clay - Coatings and paints, thinners, paint removers - Adhesives, sealants - Anti-freeze and de-icing products - Biocidal products - Non-metal surface treatment products - Ink and toners - Lubricants, greases, release products - Polishes and wax blends - Textile dyes and impregnating products (PC9b, PC9a, PC1, PC4, PC8, PC15, PC18, PC24, PC31, PC34)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

Concentration of substance in product:

Covers concentrations up to 50 %

Additional conditions human health

Covers skin contact area up to 430 cm²

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 10 g

Frequency:

Covers exposure up to 1 events per day

Frequency:

Covers frequency up to: 365 days per year

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

6.3 Exposure estimation and reference to its source

N/A

6.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

7. ES 7 Consumer use; Various products (PC3, PC4, PC8, PC24, PC35)

7.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Air care products (PC3) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Lubricants, greases, release products (PC24) - Washing and cleaning products (PC35) - Welding and soldering products, flux products (PC38)

Environment Contributing Scenario

CS1 Solvent-based process	ERC8a - ERC8d
----------------------------------	---------------

Consumer Contributing Scenario

CS2 Detergent liquids	PC9a - PC3 - PC4 - PC8 - PC24 - PC35 - PC38
------------------------------	---

7.2 Conditions of use affecting exposure

7.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
---	---

7.2. CS2: Consumer Contributing Scenario: Detergent liquids (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)

Product Categories	Coatings and paints, thinners, paint removers - Air care products - Anti-freeze and de-icing products - Biocidal products - Lubricants, greases, release products - Washing and cleaning products - Welding and soldering products, flux products (PC9a, PC3, PC4, PC8, PC24, PC35, PC38)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

Concentration of substance in product:

Covers concentrations up to 50 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 100 g

Frequency:

Covers use up to 365 days per year

Frequency:

Covers use up to 1 uses per day

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

Additional conditions human health

Covers skin contact area up to 428 cm²

7.3 Exposure estimation and reference to its source

N/A

7.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

8. ES 8 Consumer use; Anti-freeze and de-icing products (PC4)

8.1 TITLE SECTION

Exposure Scenario name	De-icing and anti-icing applications
Date - Version	16/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Anti-freeze and de-icing products (PC4)

Environment Contributing Scenario

CS1 Solvent-based process	ERC4
---------------------------	------

Consumer Contributing Scenario

CS2 De-icing and anti-icing applications	PC24
--	------

8.2 Conditions of use affecting exposure

8.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

8.2. CS2: Consumer Contributing Scenario: De-icing and anti-icing applications (PC24)

Product Categories	Lubricants, greases, release products (PC24)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid, vapour pressure > 10 kPa at STP

Concentration of substance in product:

Covers concentrations up to 10 %

Amount used, frequency and duration of use/exposure

Amounts used:

Amount per use 2000 g

Duration:

Covers use up to 0.25 h/event

Frequency:

Covers exposure up to 365 days per year

Other conditions affecting consumers exposure

Room size: Covers use in a one car garage (>34 m³) under typical ventilation.

Temperature: Covers use at ambient temperatures.

Additional conditions human health

Covers skin contact area up to 428 cm²

8.3 Exposure estimation and reference to its source

N/A

8.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.