

#### Safety Data Sheet dated 1/3/2022, version 11

1.1. Product identifier	he substance/mixture and of the company/undertaking
Mixture identification:	
Trade name:	Diesel FAP/DPF treatment
Trade code:	31034
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Recommended use:	
Fuel additive	
1.3. Details of the supplier of	the safety data sheet
Supplier:	
Arexons S.p.A.	
via Antica di Cassano,	, 23, 20063
Cernusco sul Naviglio	(MI), Italy
Arexons S.p.A.	
Tel. +39 (0)2/924361 -	- Fax +39 (0)2/92436306
Competent person responsib	ble for the safety data sheet:
arexons@arexons.it	
1.4. Emergency telephone nu	umber
Arexons S.p.A.	
Tel. +39 (0)2/924361 -	- Fax +39 (0)2/92436306
In England and Wales	: NHS 111 - dial 111
In Scotland: NHS 24 -	
In Ireland: Beaumont H	Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 -
22:00)	
In South Africa: Poisor	n Information Helpline 0861 555 777
In Malta: emergency n	

#### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP):
◆ Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways. Aquatic Chronic 3, Harmful to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking.
Adverse physicochemical, human health and environmental effects: No other hazards
2.2. Label elements
Hazard pictograms:



Danger Hazard statements:

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.

31034/11 Page n. 1 of 11



P331 Do NOT induce vomiting. P405 Store locked up. P501 Dispose of contents/container in accordance with applicable regulations. Special Provisions: EUH066 Repeated exposure may cause skin dryness or cracking. PACK1 The packing must be featured by a safety lock for children. PACK2 The packing must have tactive indications of danger for blind people. Contains Distillates (petroleum), hydrotreated light Solvent naphtha (petroleum), heavy arom.; Special provisions according to Annex XVII of REACH and subsequent amendments: None 2.3. Other hazards No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1% Other Hazards: No other hazards **SECTION 3: Composition/information on ingredients** 3.1. Substances ΝA 3.2. Mixtures Hazardous components within the meaning of the CLP regulation and related classification: >= 70% - < 80% Distillates (petroleum), hydrotreated light REACH No.: 01-2119456620-43, EC: 926-141-6 3.10/1 Asp. Tox. 1 H304 EUH066 >= 15% - < 20% 2-Ethylhexyl nitrate REACH No.: 01-2119539586-27, CAS: 27247-96-7, EC: 248-363-6 3.1/4/Oral Acute Tox. 4 H302 3.1/4/Dermal Acute Tox. 4 H312 3.1/4/Inhal Acute Tox. 4 H332 4.1/C2 Aquatic Chronic 2 H411 EUH044 EUH066 >= 2% - < 3% Solvent naphtha (petroleum), heavy arom.; CAS: 64742-94-5, EC: 265-198-5 1.2/2 Skin Irrit. 2 H315 1.8/3 STOT SE 3 H336 4.1/C2 Aquatic Chronic 2 H411 3.10/1 Asp. Tox. 1 H304 >= 0.5% - < 1% 2-Ethylhexan-1-ol REACH No.: 01-2119487289-20, CAS: 104-76-7, EC: 203-234-3 1335 3.8/3 STOT SE 3 H335 1.3/2 Eye Irrit. 2 H319 1.2/2 Skin Irrit. 2 H315 



#### **SECTION 4: First aid measures**

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash with plenty of water and soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

- Remove casualty to fresh air and keep warm and at rest.
- 4.2. Most important symptoms and effects, both acute and delayed None
- 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment: None

#### **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Appropriate Extinguishing Media: To dust. To carbon dioxide. Foam Water spray. Not Recommended Extinguishing Media: Do not use direct water jets.

- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

#### **SECTION 6: Accidental release measures**

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove persons to safety.
- See protective measures under point 7 and 8.
- 6.2. Environmental precautions
  Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
  Retain contaminated washing water and dispose it.
  In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
  Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
- Wash with plenty of water.
- 6.4. Reference to other sections See also section 8 and 13

31034/11 Page n. 3 of 11



## **SECTION 7: Handling and storage**

	<ul> <li>Precautions for safe handling Avoid contact with skin and eyes, inhalation of vapours and mists. Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. See also section 8 for recommended protective equipment. Advice on general occupational hygiene: Contamined clothing should be changed before entering eating areas. Do not eat or drink while working.</li> <li>Conditions for safe storage, including any incompatibilities</li> </ul>
	Keep away from food, drink and feed. None in particular. Instructions as regards storage premises: Adequately ventilated premises.
7.3	S. Specific end use(s) None in particular
	N 8: Exposure controls/personal protection
8.1	. Control parameters
	Distillates (petroleum), hydrotreated light 20101.12 - TWA: 1200 mg/m3, 165 ppm
	2-Ethylhexyl nitrate - CAS: 27247-96-7
	20101.13 - TWA(8h): 1 ppm
	2-Ethylhexan-1-ol - CAS: 104-76-7
	EU - TWA(8h): 5.4 mg/m3, 1 ppm
DN	IEL Exposure Limit Values
	2-Ethylhexyl nitrate - CAS: 27247-96-7
	Worker Professional: 1 mg/kg - Consumer: 0.52 mg/kg - Exposure: Human Dermal -
	Frequency: Long Term, systemic effects Worker Professional: 0.35 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term,
	systemic effects
PN	EC Exposure Limit Values
	2-Ethylhexyl nitrate - CAS: 27247-96-7
	Target: Fresh Water - Value: 0.008 mg/l
	Target: Marine water - Value: 0.00008 mg/l
8.2	. Exposure controls
Ey	e protection:
	Eye glasses with side protection.
D	Compliant with EN 166
Pro	otection for skin:
Dre	protective clothing otection for hands:
PIC	Nitrile or Viton gloves.
	Compliant with EN 374.
Re	spiratory protection:
1.0	Not needed for normal use.
Th	ermal Hazards:
	None
En	vironmental exposure controls: None
Ар	propriate engineering controls: None



## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	Light yellow		
Odour:	Characteristic		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	N.A.		
Flammability:	N.A.		
Lower and upper explosion limit:	N.A.		
Flash point:	> 65°C		
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	N.A.		
Kinematic viscosity:	<= 14 mm2/ sec (40 °C)		
Solubility in water:	N.A.		
Solubility in oil:	N.A.		
Partition coefficient n- octanol/water (log value):	N.A.		
Vapour pressure:	N.A.		
Density and/or relative density:	0,854 g/ml		
Relative vapour density:	N.A.		
Particle characteristics:			
Particle size:	N.A.		

#### 9.2. Other information

No other relevant information

#### **SECTION 10: Stability and reactivity**

31034/11 Page n. 5 of 11



10.1. Reactivity	
Stable under normal conditions	
10.2. Chemical stability	
Stable under normal conditions	
10.3. Possibility of hazardous reactions 10.4. Conditions to avoid	
Stable under normal conditions.	
10.5. Incompatible materials	
None in particular.	
10.6. Hazardous decomposition products	
None.	
SECTION 11: Toxicological information	
11.1. Information on hazard classes as defined in Regulation (EC) No 1	272/2008
Toxicological information of the product:	
DIESEL PARTICULATE FILTER TREATMENT ML 250	
a) acute toxicity Not classified	
Based on available data, the classification criteria are not r	net
b) skin corrosion/irritation	net
Not classified	
Based on available data, the classification criteria are not r	net
c) serious eye damage/irritation	
Not classified	
Based on available data, the classification criteria are not r	net
d) respiratory or skin sensitisation	
Not classified	
Based on available data, the classification criteria are not r	net
e) germ cell mutagenicity Not classified	
Based on available data, the classification criteria are not r	net
f) carcinogenicity	
Not classified	
Based on available data, the classification criteria are not r	net
g) reproductive toxicity	
Not classified	
Based on available data, the classification criteria are not r	net
h) STOT-single exposure	
Not classified Based on available data, the classification criteria are not r	not
i) STOT-repeated exposure	not
Not classified	
Based on available data, the classification criteria are not r	net
j) aspiration hazard	
The product is classified: Asp. Tox. 1 H304	
Toxicological information of the main substances found in the product:	
Distillates (petroleum), hydrotreated light	
a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m	3 Duration: 8h
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg	15 - Duration. on
Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg	
b) skin corrosion/irritation:	
Test: OECD TG 404 - Route: Skin Negative	
c) serious eye damage/irritation:	
Test: OECD TG 405 - Route: EYE Negative	
d) respiratory or skin sensitisation:	
31034/11	

Page n. 6 of 11



**Test: Inhalation Sesitization 3** Test: Skin Sensitization 3 i) aspiration hazard: Test: May be fatal if swallowed and enters airways (physical-chemical properties) - Route: **Oral Positive** 2-Ethylhexyl nitrate - CAS: 27247-96-7 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat > 9600 mg/kg Test: LC50 - Route: Inhalation - Species: Rat > 4.6 mg/l - Duration: 1h Test: LD50 - Route: Skin - Species: Rabbit > 4800 mg/kg b) skin corrosion/irritation: Test: Skin Irritant - Route: Skin - Species: Rabbit Negative c) serious eye damage/irritation: Test: Eye Irritant - Route: EYE - Species: Rabbit Negative d) respiratory or skin sensitisation: Test: Skin Sensitization - Route: Skin - Species: IND Negative e) germ cell mutagenicity: Test: oecd - Species: vitro Negative f) carcinogenicity: Test: oecd 4 - Species: Rat Negative - Notes: Teratogenicità g) reproductive toxicity: Test: OECD 421 - Route: Oral - Species: Rat Positive - Notes: Tossicità materna 11.2. Information on other hazards Endocrine disrupting properties: No endocrine disruptor substances present in concentration >= 0.1%

#### **SECTION 12: Ecological information**

12.1. Toxicity Adopt good working practices, so that the product is not released into the environment. Distillates (petroleum), hydrotreated light a) Aquatic acute toxicity: Endpoint: EL0 - Species: Daphnia 1000 mg/l - Duration h: 48 Endpoint: EL0 - Species: Algae 1000 mg/l - Duration h: 72 Endpoint: CE7 - Species: Fish 1000 mg/l - Duration h: 96 2-Ethylhexyl nitrate - CAS: 27247-96-7 a) Aquatic acute toxicity: Endpoint: EL50 - Species: Algae 3.22 mg/l - Duration h: 72 Endpoint: EL50 - Species: Daphnia > 12.6 mg/l - Duration h: 48 Endpoint: EL50 - Species: fanghi > 1000 mg/l - Duration h: 3 Endpoint: LC50 - Species: Fish 2 mg/l - Duration h: 96 b) Aquatic chronic toxicity: Endpoint: EL10 - Species: Algae 1.54 mg/l - Duration h: 72 Solvent naphtha (petroleum), heavy arom.; - CAS: 64742-94-5 a) Aquatic acute toxicity: Endpoint: EC50 - Species: Daphnia > 1 mg/l - Duration h: 48 Endpoint: LC50 - Species: Fish > 1 mg/l - Duration h: 96 12.2. Persistence and degradability None Distillates (petroleum), hydrotreated light Biodegradability: Readily biodegradable - Duration: 28gg - %: 69 2-Ethylhexyl nitrate - CAS: 27247-96-7 Biodegradability: Non-readily biodegradable - Test: OECD TG 310 - Duration: 28gg - %: 0 12.3. Bioaccumulative potential 2-Ethylhexyl nitrate - CAS: 27247-96-7 Bioaccumulation: Bioaccumulative - Test: Kow - Partition coefficient 5.24 31034/11

Page n. 7 of 11



12.4. Mobility in soil

#### N.A.

- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties
- No endocrine disruptor substances present in concentration >= 0.1%
- 12.7. Other adverse effects None

#### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

#### **SECTION 14: Transport information**

14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

- 14.2. UN proper shipping name
  - N.A.
- 14.3. Transport hazard class(es) N.A.
- 14.4. Packing group
- N.A.
- 14.5. Environmental hazards ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No
- 14.6. Special precautions for user N.A.
- 14.7. Maritime transport in bulk according to IMO instruments N.A.

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 2020/878 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP)

31034/11 Page n. 8 of 11



Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: Restrictions related to the product: Restrictions related to the substances contained: No restriction.

Volatile Organic compounds - VOCs = 94.68 % Volatile Organic compounds - VOCs = 946.75 g/Kg Volatile Organic compounds - VOCs = 808.53 g/l Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture. Substances for which a Chemical Safety Assessment has been carried out: None

#### **SECTION 16: Other information**

Text of phrases referred to under heading 3:

H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H332 Harmful if inhaled.
H411 Toxic to aquatic life with long lasting effects.
EUH044 Risk of explosion if heated under confinement.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H335 May cause respiratory irritation.
H319 Causes serious eye irritation.

Hazard class and hazard category	Code	Description
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2



STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

**SECTION 9: Physical and chemical properties** 

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of
	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport
	Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.



LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.

## Exposure Scenario, 18/07/2019

Substance identity	
Chemical name	ldrocarburi , C11- C14 , n-alcani , isoalcani, ciclici,< 2% aromatici.
CAS No.	64742-47-8
EINECS No.	926-141-6

## Table of contents

- 1. **ES 1** Use at industrial site
- 2. **ES 2** Widespread use by professional workers
- 3. ES 3 Consumer use; Fuels (PC13)

1. ES 1 Use a	t industrial site		
<b>1.1 TITLE SECTION</b>			
Exposure Scenario name	Fuel		
Date - Version	18/07/2019 - 1.0		
Life Cycle Stage	Use at industrial site		
Main user group	Industrial uses		
Sector(s) of use	Industrial uses (SU3)		
Environment Contributing Sce	enario		
CS1 Covered by		ERC7	
Worker Contributing Scenario	•		
CS2 Industrial		PROC1 - PROC2 - PROC3 - PROC8a - PROC8b - PROC16	
1.2 Conditions of use	affecting exposure		
1.2. CS1: Environment Contrib	outing Scenario: Covered by (ERC7)		
Environmental release categories	Use of functional fluid at industrial site (FRC7)		
1.2. CS2: Worker Contributing	Scenario: Industrial (PROC1, PROC2, PROC3, PRO	C8a, PROC8b, PROC16)	
Process CategoriesChemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at non- dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated 			
Product (article) character		-,,	
Physical form of product: Liquid			
<b>Concentration of substance in product:</b> Covers percentage substance in the product up to 100 %.			
Amount used, frequency and duration of use/exposure			
Duration: Covers daily exposures up to 8 hours			
1.3 Exposure estimation and reference to its source			
N/A			
1.4 Guidance to DU t the ES	o evaluate whether he works inside	e the boundaries set by	

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Widespread use by professional workers 2. ES 2

### **2 1 TITLE SECTION**

2.1 IIILE SECTION				
Exposure Scenario name	Fuel			
Date - Version	18/07/2019 - 1.0			
Life Cycle Stage	Widespread use by professional workers	Widespread use by professional workers		
Main user group	Professional uses			
Environment Contributing S	cenario			
CS1 Solids based process		ERC9a - ERC9b		
Worker Contributing Scenario				
CS2 General use from professional operators PROC1 - PROC2 - PROC3 - PROC8a - PROC8b - PROC16				
2.2 Conditions of us	e affecting exposure			
2.2. CS1: Environment Cont	ibuting Scenario: Solids based process (ERC9a, ERC	:9b)		
Environmental release categories	Widespread use of functional fluid (indoor) - Widespread (ERC9a, ERC9b)	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)		
2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)				
Process CategoriesChemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed 				
Product (article) characte	ristics			

#### Product (article) characteristics

**Concentration of substance in product:** 

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

#### **Duration:**

Covers daily exposures up to 8 hours

### 2.3 Exposure estimation and reference to its source

#### N/A

## 2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Consu	ımer use; Fuels (PC13)					
3.1 TITLE SECTION						
Exposure Scenario name	Fuel					
Date - Version	18/07/2019 - 1.0					
Life Cycle Stage	Consumer use					
Main user group	Consumer uses					
Sector(s) of use	Consumer uses (SU21)					
Product Categories	Fuels (PC13)					
Environment Contributing Scenario						
CS1 Covered by	ered by ERC9a - ERC9b					
Consumer Contributing Scenario						
CS2 Consumer		PC13				
3.2 Conditions of use affecting exposure						
3.2. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)						
Environmental release categories	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)					
3.2. CS2: Consumer Contributing Scenario: Consumer (PC13)						
Product Categories	Fuels (PC13)					
3.3 Exposure estimation and reference to its source						
N/A						
3.4 Guidance to DU to evaluate whether he works inside the boundaries set by						

### the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

## Exposure Scenario, 07/04/2020

Substance identity	
Chemical name	2-Ethylhexyl nitrate
CAS No.	27247-96-7
EINECS No.	248-363-6

## Table of contents

1. **ES 1** Consumer use; Fuels (PC13)

1. ES 1 Consu	meruse: Euels (DC13)						
1. ES 1Consumer use; Fuels (PC13)1.1 TITLE SECTION							
Exposure Scenario name	Fuel additive						
Date - Version							
Life Cycle Stage	07/04/2020 - 1.0						
	Consumer use						
Main user group	Consumer uses						
Sector(s) of use	Consumer uses (SU21)						
Product Categories	Fuels (PC13)						
Environment Contributing Sce	nario						
CS1 Covered by		ERC9a - ERC9b					
Consumer Contributing Scenar	rio						
CS2 Fuel additives							
	1.2 Conditions of use affecting exposure						
	1.2. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)						
Environmental release categories	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)						
Product (article) characteri	stics						
Physical form of product: Liquid							
Other conditions affecting e							
Local marine water dilution factor: 100 Local freshwater dilution factor: 10							
1.2. CS2: Consumer Contributi	ng Scenario: Fuel additives (PC13)						
Product Categories	Fuels (PC13)						
Product (article) characteri	Product (article) characteristics						
Physical form of product: Liquid							
Amount used, frequency and duration of use/exposure							
Amounts used: Amount per use 120 g for event							
Information and behavioural advice for consumers							
Information and behavioural advice for consumers: Keep away from children.							
Other conditions affecting consumers exposure							
Covers indoor and outdoor use Ventilation rate: Open windows during application to ensure natural ventilation. Body parts exposed: Palm of one hand							
1.3 Exposure estimation and reference to its source							
1.2. CS2: Consumer Contributing Scenario: Fuel additives (PC13)							

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
combined routes, systemic, long-term	N/A	EASY TRA v4.1	N/A

# 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES\_\_\_\_\_

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.