

Ficha de datos de seguridad

LEATHER TREATMENT



Ficha de datos de seguridad del 16/9/2024, Revisión 4

SECCIÓN 1. Identificación de la sustancia o la mezcla y de la sociedad o la empresa

1.1. Identificador de producto

Identificación del preparado:

Nombre comercial: LEATHER TREATMENT

Código comercial: 31104E

1.2. Usos pertinentes identificados de la sustancia o de la mezcla y usos desaconsejados

Uso recomendado:

Detergente para interiores de piel

Usos no recomendados:

Respetar estrictamente los usos recomendados.

1.3. Datos del proveedor de la ficha de datos de seguridad

Proveedor:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Persona competente responsable de la ficha de datos de seguridad:

arexons@arexons.it

1.4. Teléfono de emergencia

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Teléfono de emergencias: + 34 91 562 04 20 (Solo emergencias toxicológicas. Información en español (24h/365 días))

SECCIÓN 2. Identificación de los peligros

2.1. Clasificación de la sustancia o de la mezcla

Criterios Reglamentación CE 1272/2008 (Clasificación, Etiquetado y Empacado):

El producto no se considera peligroso de acuerdo con el Reglamento CE 1272/2008 (CLP).

Efectos físico-químicos nocivos para la salud humana y para el medio ambiente:

Ningún otro riesgo

2.2. Elementos de la etiqueta

El producto no se considera peligroso de acuerdo con el Reglamento CE 1272/2008 (CLP).

Pictogramas de peligro:

Ninguna

Indicaciones de peligro:

Ninguna

Consejos de prudencia:

Ninguna

Disposiciones especiales:

EUH208 Contiene 1,2-Bencisotiazol-3(2H)-ona; 1,2-bencisotiazolin-3-ona. Puede provocar una reacción alérgica.

Disposiciones especiales de acuerdo con el anexo XVII del Reglamento REACH y sus posteriores modificaciones:

Ninguna

Reglamento (CE) no 648/2004 (detergentes).

Contenido del producto:

Policarboxilatos, Tensioactivos anfotéricos, Tensioactivos no iónicos < 5 %

Contiene también: Perfumes

31104E/4

Página nº. 1 de 11

Ficha de datos de seguridad

LEATHER TREATMENT



Conservantes: Piridina-2-tiol-1-óxido, sal de sodio, Laurylamine
Dipropylenediamine, 1,2-Bencisotiazol-3(2H)-ona; 1,2-bencisotiazolin-3-ona, Masa de reacción de 5-cloro-2-metil-2H-isotiazol-3-ona y 2-metil-2H-isotiazol-3-ona (3:1)

2.3. Otros peligros

Ninguna sustancia PBT, mPmB o perturbador endocrino presente en concentración $\geq 0.1\%$

Otros riesgos:

Ningún otro riesgo

SECCIÓN 3. Composición/información sobre los componentes

3.1. Sustancias

N.A.

3.2. Mezclas

Componentes peligrosos según el Reglamento CLP y su correspondiente clasificación:

Cantidad	Nombre	Número de identif.	Clasificación
$\geq 1\%$ - $< 2\%$	Etanodiol; etilenglicol	Número Index: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 REACH No.: 01-2119456816-28	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.9/2 STOT RE 2 H373 (riñones) (oral)
$\geq 0,5\%$ - $< 1\%$	Amines, C12-14(even numbered)-alkyldimethyl, N-oxides	EC: 931-292-6 REACH No.: 01-2119490061-47	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 4.1/A1 Aquatic Acute 1 H400 ⚠ 4.1/C2 Aquatic Chronic 2 H411
$\geq 0,01\%$ - $< 0,02\%$	1,2-Bencisotiazol-3(2H)-ona; 1,2-bencisotiazolin-3-ona	Número Index: 613-088-00-6 CAS: 2634-33-5 EC: 220-120-9	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.1/2/Inhal Acute Tox. 2 H330 ⚠ 3.2/2 Skin Irrit. 2 H315 ⚠ 3.4.2/1A Skin Sens. 1A H317 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 4.1/A1 Aquatic Acute 1 H400 ⚠ 4.1/C1 Aquatic Chronic 1 H410 Límites de concentración específicos: C $\geq 0,036\%$: Skin Sens. 1A H317 Estimación de la toxicidad aguda: ETA - Oral 450 mg/kg pc ETA - Inhalación (Polvo o niebla) 0, 21 mg/l

SECCIÓN 4. Primeros auxilios

4.1. Descripción de los primeros auxilios

En caso de contacto con la piel:

Lavar abundantemente con agua y jabón.

En caso de contacto con los ojos:

En caso de contacto con los ojos, lávense inmediata y abundantemente con agua y acúdase a un médico.

En caso de ingestión:

31104E/4

Página nº. 2 de 11

Ficha de datos de seguridad

LEATHER TREATMENT



No provocar el vómito en ningún caso. CONSULTAR INMEDIATAMENTE AL MÉDICO.

En caso de inhalación:

Llevar al accidentado al aire libre y mantenerlo en reposo y abrigado.

4.2. Principales síntomas y efectos, agudos y retardados

Ninguno

4.3. Indicación de toda atención médica y de los tratamientos especiales que deban dispensarse inmediatamente

Tratamiento:

Ninguno

SECCIÓN 5. Medidas de lucha contra incendios

5.1. Medios de extinción

Medios de extinción apropiados:

Con anhídrido carbónico.

Con polvo.

Espuma

Agua vaporizada.

Medios de extinción no recomendados:

No usar chorros de agua directos

5.2. Peligros específicos derivados de la sustancia o la mezcla

No inhalar los gases producidos por la explosión y por la combustión.

La combustión produce humo pesado.

5.3. Recomendaciones para el personal de lucha contra incendios

Ropa normal para la lucha contra incendios, como un aparato respiratorio de aire comprimido de circuito abierto (EN 137), traje ignífugo (EN469), guantes ignífugos (EN 659) y botas de bombero (HO A29 o A30).

SECCIÓN 6. Medidas en caso de vertido accidental

6.1. Precauciones personales, equipo de protección y procedimientos de emergencia

Usar los dispositivos de protección individual.

Llevar las personas a un lugar seguro.

Consultar las medidas de protección expuestas en los puntos 7 y 8.

6.2. Precauciones relativas al medio ambiente

Evitar que el producto penetre en el suelo/subsuelo. Evitar que penetre en aguas superficiales o en el alcantarillado.

Conservar el agua de lavado contaminada y eliminarla.

En caso de fuga de gas o penetración en cursos de agua, suelo o sistema de alcantarillado, informar a las autoridades responsables.

Material apropiado para la recogida: material absorbente, orgánico, arena

6.3. Métodos y material de contención y de limpieza

Limpieza:

Evitar la presencia de llamas y/o chispas cerca de la pérdida y productos de desecho. No fumar.

Contener

en caso de vertido de cantidades relevantes del producto y absorber cuando disperse. Contener el

derrame de pequeñas cantidades de producto con tierra, arena, sepiolita, trapos u otro absorbente inerte.

Recuperar con paletas después de la absorción de disolvente y transferir en contenedores adecuados.

Desechar los residuos según la normativa vigente.

6.4. Referencia a otras secciones

Véanse también los apartados 8 y 13.

SECCIÓN 7. Manipulación y almacenamiento

31104E/4

Página nº. 3 de 11

Ficha de datos de seguridad

LEATHER TREATMENT



- 7.1. Precauciones para una manipulación segura
Evitar el contacto con la piel y los ojos, la inhalación de vapores y vahos.
Remitirse también al apartado 8 para los dispositivos de protección recomendados.

No comer ni beber durante el trabajo.

- 7.2. Condiciones de almacenamiento seguro, incluidas posibles incompatibilidades
Conservar solo en el recipiente original.
Mantener alejado de comidas, bebidas y piensos.
Ninguna en particular.
Indicaciones para los locales:
Locales adecuadamente aireados.

- 7.3. Usos específicos finales
Ningún uso particular

SECCIÓN 8. Controles de exposición/protección individual

- 8.1. Parámetros de control
Etanodiol; etilenglicol - CAS: 107-21-1
UE - TWA(8h): 52 mg/m³, 20 ppm - STEL: 104 mg/m³, 40 ppm - Notas: Skin
ACGIH - STEL: 10 mg/m³ - Notas: (I, H), A4 - URT irr
- Valores límites de exposición DNEL
Etanodiol; etilenglicol - CAS: 107-21-1
Trabajador profesional: 35 mg/m³ - Consumidor: 7 mg/m³ - Exposición: Por inhalación humana
Trabajador profesional: 106 mg/kg - Consumidor: 53 mg/kg - Exposición: Dérmica humana
- Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
Trabajador profesional: 6.2 mg/m³ - Consumidor: 1.53 mg/m³ - Exposición: Por inhalación humana - Frecuencia: A largo plazo, efectos sistémicos
Trabajador profesional: 11 mg/kg - Consumidor: 5.5 mg/kg - Exposición: Dérmica humana - Frecuencia: A largo plazo, efectos locales
Consumidor: 0.44 mg/kg - Exposición: Oral humana - Frecuencia: A largo plazo, efectos sistémicos
- Valores límites de exposición PNEC
Etanodiol; etilenglicol - CAS: 107-21-1
Objetivo: agua dulce - Valor: 10 mg/l
Objetivo: Agua marina - Valor: 1 mg/l
Objetivo: Sedimentos de agua dulce - Valor: 37 mg/kg
Objetivo: Suelo (agricultura) - Valor: 1.53 mg/kg
- Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
Objetivo: agua dulce - Valor: 0.0335 mg/l
Objetivo: Agua marina - Valor: 0.00335 mg/l
Objetivo: Sedimentos de agua dulce - Valor: 0.0335 mg/kg
Objetivo: Sedimentos de agua marina - Valor: 0.0335 mg/kg
Objetivo: 09 - Valor: 24 mg/l
- 8.2. Controles de la exposición
Protección de los ojos:
Gafas con protección lateral.
Cumple con la norma EN 166
- Protección de la piel:
ropa protectora
- Protección de las manos:
Guantes de nitrilo o de Viton.
Conformes EN 374.
Grosor: Puño 0,10 mm; palma 0,12 mm; dedos 0,145 mm
- Protección respiratoria:
No necesaria para el uso normal.
- Riesgos térmicos:

Ficha de datos de seguridad

LEATHER TREATMENT



Ninguno
 Controles de la exposición ambiental:
 Ninguno
 Controles técnicos apropiados:
 Ninguno

SECCIÓN 9. Propiedades físicas y químicas

9.1. Información sobre propiedades físicas y químicas básicas

Propiedad	Valor	Método:	Notas
Estado físico:	Líquido	--	--
Color:	beis	--	--
Olor:	característico	--	--
Punto de fusión/punto de congelación:	N.A.	--	--
Punto de ebullición o punto inicial de ebullición e intervalo de ebullición:	N.A.	--	--
Inflamabilidad:	N.A.	--	--
Límite superior e inferior de explosividad:	N.A.	--	--
Punto de ignición (flash point, fp):	no inflamable	08	--
Temperatura de autoencendido:	N.A.	--	--
Temperatura de descomposición:	N.A.	--	--
pH:	7.2	ASTM D1287	--
Viscosidad cinemática:	> 20,5 mm ² /sec (40 °C)	--	--
Hidrosolubilidad:	soluble	--	--
Solubilidad en aceite:	N.A.	--	--
Coeficiente de reparto n-octanol/agua (valor logarítmico):	N.A.	--	--
Presión de vapor:	N.A.	--	--
Densidad y/o densidad relativa:	0,98 g/cm ³	09	--
Densidad de vapor relativa:	N.A.	--	--
Características de las partículas:			

Ficha de datos de seguridad

LEATHER TREATMENT



Tamaño de las partículas:	N.A.	--	--
9.2. Otros datos Ninguna otra información relevante Viscosidad:	60000 cP (48°C)	08	--

SECCIÓN 10. Estabilidad y reactividad

- 10.1. Reactividad
Estable en condiciones normales
- 10.2. Estabilidad química
Estable a las temperaturas ambiente normales y si se usa como está recomendado.
- 10.3. Posibilidad de reacciones peligrosas
Puede generar gases inflamables en contacto con ditiocarbamatos, mercaptanos y otros sulfuros orgánicos, elementos metálicos (alcalinos, alcalinotérreos, aleaciones en polvo o vapor) y agentes reductores fuertes.
Puede generar gases tóxicos en contacto con fluoruros inorgánicos, sustancias orgánicas halogenadas, sulfuros, nitruros, nitrilos, compuestos organofosforados, fosfotioatos, fosfoditioatos y agentes oxidantes fuertes.
Puede inflamarse en contacto con ditiocarbamatos, elementos metálicos (alcalinos, alcalinotérreos, aleaciones en polvo o vapor, láminas o barras) y nitruros.
- 10.4. Condiciones que deben evitarse
Estable en condiciones normales.
- 10.5. Materiales incompatibles
Ninguna en particular.
- 10.6. Productos de descomposición peligrosos
Ninguno.

SECCIÓN 11. Información toxicológica

- 11.1. Información sobre las clases de peligro definidas en el Reglamento (CE) n.º 1272/2008
Información toxicológica del producto:
LEATHER TREATMENT 150 ml
 - a) toxicidad aguda
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
 - b) corrosión o irritación cutáneas
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
 - c) lesiones o irritación ocular graves
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
 - d) sensibilización respiratoria o cutánea
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
 - e) mutagenicidad en células germinales
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
 - f) carcinogenicidad
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
 - g) toxicidad para la reproducción
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
 - h) toxicidad específica en determinados órganos (STOT) – exposición única
No clasificado

Ficha de datos de seguridad

LEATHER TREATMENT



- A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- i) toxicidad específica en determinados órganos (STOT) – exposición repetida
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- j) peligro de aspiración
No clasificado
A la vista de los datos disponibles, no se cumplen los criterios de clasificación.
- La información toxicológica de las sustancias principales halladas en el producto:
Etanodiol; etilenglicol - CAS: 107-21-1
- a) toxicidad aguda:
Ensayo: LC50 - Vía: Oral - Especies: Rata 7712 mg/kg
Ensayo: LC50 - Vía: Inhalación - Especies: Rata 2.5 mg/l - Duración: 6h
Ensayo: LD50 - Vía: Piel - Especies: Ratón 3500 mg/kg
- Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
- a) toxicidad aguda:
Ensayo: LD50 - Vía: Oral - Especies: Rata 1064 mg/kg
- g) toxicidad para la reproducción:
Ensayo: NOEL - Vía: Oral 100 mg/kg - Fuente: OECD 422
Ensayo: arx1 - Vía: Oral 25 mg/kg
- i) toxicidad específica en determinados órganos (STOT) – exposición repetida:
Ensayo: NOAEL - Vía: Oral 88 mg/kg
- 1,2-Bencisotiazol-3(2H)-ona; 1,2-bencisotiazolin-3-ona - CAS: 2634-33-5
- a) toxicidad aguda
ETA - Oral 450 mg/kg pc
ETA - Inhalación (Polvo o niebla) 0,21 mg/l
Ensayo: LD50 - Vía: Oral - Especies: Rata 1193 mg/kg
Ensayo: LD50 - Vía: Piel - Especies: Rata 4115 mg/kg
- b) corrosión o irritación cutáneas:
Ensayo: Irritante para la piel Positivo
- c) lesiones o irritación ocular graves:
Ensayo: Corrosivo para los ojos Positivo
- d) sensibilización respiratoria o cutánea:
Ensayo: Sensibilización de la piel - Vía: Piel Positivo

- 11.2. Información relativa a otros peligros
Propiedades de alteración endocrina:
Ningún perturbador endocrino presente en concentración $\geq 0.1\%$

SECCIÓN 12. Información ecológica

- 12.1. Toxicidad
Utilícese con técnicas de trabajo adecuadas, evitando la dispersión del producto en el medio ambiente.
Etanodiol; etilenglicol - CAS: 107-21-1
- a) Toxicidad acuática aguda:
Parámetro: LC50 - Especies: Peces 49-72.86 GL - Duración h.: 96
Parámetro: EC50 - Especies: Daphnia 100 mg/l - Duración h.: 48
Parámetro: LC50 - Especies: Daphnia 74.448 GL - Duración h.: 242
Parámetro: EC0 - Especies: Daphnia 100 mg/l - Duración h.: 48
Parámetro: CE4 - Especies: Algas 10.94 GL - Duración h.: 96
- b) Toxicidad acuática crónica:
Parámetro: NOEC - Especies: Peces 49 mg/l - Duración h.: 504
Parámetro: LC50 - Especies: Peces 1.5 GL - Duración h.: 504
Parámetro: NOEC - Especies: Daphnia 8.59-24 mg/l - Duración h.: 168
Parámetro: NOEC - Especies: Algas 1000 mg/l - Duración h.: 72
- Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
- a) Toxicidad acuática aguda:
Parámetro: LC50 - Especies: Peces 2.67 mg/l

Ficha de datos de seguridad

LEATHER TREATMENT



- Parámetro: EC50 - Especies: Daphnia 3.1 mg/l
Parámetro: CE6 - Especies: Algas 0.19 mg/l
- b) Toxicidad acuática crónica:
Parámetro: NOEC - Especies: Algas 0.067 mg/l
1,2-Bencisotiazol-3(2H)-ona; 1,2-bencisotiazolin-3-ona - CAS: 2634-33-5
- a) Toxicidad acuática aguda:
Parámetro: LC50 - Especies: Peces 2.18 mg/l - Duración h.: 96
Parámetro: EC50 - Especies: Daphnia 2.94 mg/l - Duración h.: 48
Parámetro: CE6 - Especies: Algas 0.11 mg/l - Duración h.: 72
- 12.2. Persistencia y degradabilidad
Ninguno
Etanodiol; etilenglicol - CAS: 107-21-1
Biodegradabilidad: Rápidamente degradable - Ensayo: BIOGDG13 - Duración h.: 10gg - %: 90-10
Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
Biodegradabilidad: Rápidamente degradable - Duración h.: 28gg - %: 80
1,2-Bencisotiazol-3(2H)-ona; 1,2-bencisotiazolin-3-ona - CAS: 2634-33-5
Biodegradabilidad: Rápidamente degradable - Ensayo: BIOGDG06
- 12.3. Potencial de bioacumulación
Etanodiol; etilenglicol - CAS: 107-21-1
Bioacumulación: No bioacumulable
Amines, C12-14(even numbered)-alkyldimethyl, N-oxides
Ensayo: log Pow 2.7
- 12.4. Movilidad en el suelo
Etanodiol; etilenglicol - CAS: 107-21-1
Movilidad en el suelo: Móvil
- 12.5. Resultados de la valoración PBT y mPmB
Sustancias vPvB: Ninguna - Sustancias PBT: Ninguna
- 12.6. Propiedades de alteración endocrina
Ningún perturbador endocrino presente en concentración $\geq 0.1\%$
- 12.7. Otros efectos adversos
Ninguno

SECCIÓN 13. Consideraciones relativas a la eliminación

- 13.1. Métodos para el tratamiento de residuos
Recuperar si es posible. Operar conforme con las disposiciones locales y nacionales vigentes.
- Información adicional sobre eliminación:
"Utilice el producto según las buenas prácticas de trabajo, evitando la dispersión en el medio ambiente.
No descargue en alcantarillados, canales o cursos de agua. Respete la legislación vigente en materia de protección del agua y el suelo contra la contaminación (Decreto Legislativo n.º 152 del 3/4/2006).
Elimine el producto y los envases usados entregándolos a empresas autorizadas, de acuerdo con lo establecido en el Decreto Legislativo n.º 152/2006 (Texto Refundido de la Ley de Medio Ambiente, que sustituyó al Decreto Ronchi) en su versión modificada.
El producto usado debe considerarse residuo especial que debe clasificarse de acuerdo con la Directiva n.º 2008/98/CE sobre residuos y asuntos relacionados. Recupere el producto si es posible. Envíe a plantas de eliminación autorizadas o incineración en condiciones controladas (152/2006 Art. 184).
Trabajar según las disposiciones locales y nacionales vigentes.
Los embalajes contaminados se deben vaciar, siempre que sea posible. Después de la limpieza, reciclar o eliminar en un centro autorizado."

SECCIÓN 14. Información relativa al transporte

31104E/4

Página n.º 8 de 11

Ficha de datos de seguridad

LEATHER TREATMENT



- 14.1. Número ONU o número ID
Producto no peligroso según los criterios de la reglamentación del transporte.
- 14.2. Designación oficial de transporte de las Naciones Unidas
N.A.
- 14.3. Clase(s) de peligro para el transporte
N.A.
- 14.4. Grupo de embalaje
N.A.
- 14.5. Peligros para el medio ambiente
ADR-Contaminante ambiental: No
IMDG-Marine pollutant: No
- 14.6. Precauciones particulares para los usuarios
N.A.
- 14.7. Transporte marítimo a granel con arreglo a los instrumentos de la OMI
N.A.

SECCIÓN 15. Información reglamentaria

- 15.1. Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

Dir. 98/24/CE (Riesgos relacionados con los agentes químicos durante el trabajo)

Dir. 2000/39/CE (Valores límite de exposición profesional)

Reglamento (CE) n. 1907/2006 (REACH)

Reglamento (CE) n. 1272/2008 (CLP)

Reglamento (CE) n. 790/2009 (ATP 1 CLP) y (UE) n. 758/2013

Reglamento (UE) n. 2020/878

Reglamento (UE) n. 286/2011 (ATP 2 CLP)

Reglamento (UE) n. 618/2012 (ATP 3 CLP)

Reglamento (UE) n. 487/2013 (ATP 4 CLP)

Reglamento (UE) n. 944/2013 (ATP 5 CLP)

Reglamento (UE) n. 605/2014 (ATP 6 CLP)

Reglamento (UE) n. 2015/1221 (ATP 7 CLP)

Reglamento (UE) n. 2016/918 (ATP 8 CLP)

Reglamento (UE) n. 2016/1179 (ATP 9 CLP)

Reglamento (UE) n. 2017/776 (ATP 10 CLP)

Reglamento (UE) n. 2018/669 (ATP 11 CLP)

Reglamento (UE) n. 2018/1480 (ATP 13 CLP)

Reglamento (UE) n. 2019/521 (ATP 12 CLP)

Reglamento (UE) n. 2020/217 (ATP 14 CLP)

Reglamento (UE) n. 2020/1182 (ATP 15 CLP)

Reglamento (UE) n. 2021/643 (ATP 16 CLP)

Reglamento (UE) n. 2021/849 (ATP 17 CLP)

Reglamento (UE) n. 2022/692 (ATP 18 CLP)

Restricciones relacionadas con el producto o las sustancias contenidas, de acuerdo con el anexo XVII del Reglamento (CE) 1907/2006 (REACH) y las modificaciones posteriores:

Restricciones relacionadas con el producto:

Ninguna restricción.

Restricciones relacionadas con las sustancias contenidas:

Restricción 40

Restricción 57

Restricción 75

Compuestos orgánicos volátiles - COV = 1.00 %

Compuestos orgánicos volátiles - COV = 10.02 g/Kg

Compuestos orgánicos volátiles - COV = 9.82 g/l

Cuando sean aplicables, hágase referencia a las siguientes normativas:

Ficha de datos de seguridad

LEATHER TREATMENT



Directiva 2012/18/EU (Seveso III)
Reglamento (CE) no 648/2004 (detergentes).
Dir. 2004/42/CE (directiva COV)

Disposiciones sobre la directiva EU 2012/18 (Seveso III):
Categoría Seveso III de acuerdo con el anexo 1, parte 1
Ninguno

15.2. Evaluación de la seguridad química
No se ha realizado ninguna evaluación de la seguridad química para la mezcla
Sustancias para las cuales se ha realizado una evaluación de la seguridad química
Etanodiol; etilenglicol

SECCIÓN 16. Otra información

Texto de las frases utilizadas en el párrafo 3:
H302 Nocivo en caso de ingestión.
H373 (riñones) (oral) Puede provocar daños en los órganos (riñones) tras exposiciones prolongadas o repetidas por ingestión.
H315 Provoca irritación cutánea.
H318 Provoca lesiones oculares graves.
H400 Muy tóxico para los organismos acuáticos.
H411 Tóxico para los organismos acuáticos, con efectos nocivos duraderos.
H330 Mortal en caso de inhalación.
H317 Puede provocar una reacción alérgica en la piel.
H410 Muy tóxico para los organismos acuáticos, con efectos nocivos duraderos.

Clase y categoría de peligro	Código	Descripción
Acute Tox. 2	3.1/2/Inhal	Toxicidad aguda (por inhalación), Categoría 2
Acute Tox. 4	3.1/4/Oral	Toxicidad aguda (oral), Categoría 4
Skin Irrit. 2	3.2/2	Irritación cutánea, Categoría 2
Eye Dam. 1	3.3/1	Lesiones oculares graves, Categoría 1
Skin Sens. 1A	3.4.2/1A	Sensibilización cutánea, Categoría 1A
STOT RE 2	3.9/2	Toxicidad específica en determinados órganos (exposiciones repetidas), Categoría 2
Aquatic Acute 1	4.1/A1	Peligro agudo para el medio ambiente acuático, Categoría 1
Aquatic Chronic 1	4.1/C1	Peligro crónico (a largo plazo) para el medio ambiente acuático, Categoría 1
Aquatic Chronic 2	4.1/C2	Peligro crónico (a largo plazo) para el medio ambiente acuático, Categoría 2

Parágrafos modificados respecto la revisión anterior

SECCIÓN 9. Propiedades físicas y químicas

Este documento ha sido preparado por una persona competente que ha recibido un entrenamiento

Ficha de datos de seguridad

LEATHER TREATMENT



adecuado

Principales fuentes bibliográficas:

ECDIN: Environmental Chemicals Data and Information Network, Centro Común de Investigación, Comisión de las Comunidades Europeas

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS, 8ª ed., Van Nostrand Reinold

La información aquí detallada se basa en nuestros conocimientos hasta la fecha señalada arriba. Se refiere exclusivamente al producto indicado y no constituye garantía de cualidades particulares.

El usuario debe asegurarse de la idoneidad y exactitud de dicha información en relación al uso específico que debe hacer del producto.

Esta ficha anula y sustituye toda edición precedente.

ADR:	Acuerdo europeo relativo al transporte internacional de mercancías peligrosas por carretera.
CAS:	Chemical Abstracts Service (de la American Chemical Society).
CLP:	Clasificación, etiquetado, embalaje.
DNEL:	Nivel sin efecto derivado.
EINECS:	Catálogo Europeo de Sustancias Químicas Comercializadas.
ETA:	Estimación de la toxicidad aguda
ETAmix:	Estimación de Toxicidad Aguda (Mezclas)
GefStoffVO:	Ordenanza sobre sustancias peligrosas, Alemania.
GHS:	Sistema Globalmente Armonizado de clasificación y etiquetado de productos químicos.
IATA:	Asociación de Transporte Aéreo Internacional.
IATA-DGR:	Normas aplicadas a las mercancías peligrosas por la "Asociación de Transporte Aéreo Internacional" (IATA).
ICAO:	Organización de la Aviación Civil Internacional.
ICAO-TI:	Instrucciones Técnicas de la "Organización de la Aviación Civil Internacional" (OACI).
IMDG:	Código marítimo internacional de mercancías peligrosas.
INCI:	Nomenclatura internacional de ingredientes cosméticos.
KSt:	Coeficiente de explosión.
LC50:	Concentración letal para el 50% de la población expuesta.
LD50:	Dosis letal para el 50% de la población expuesta.
NA:	No aplicable
PNEC:	Concentración prevista sin efecto.
RID:	Normas relativas al transporte internacional de mercancías peligrosas por ferrocarril.
STEL:	Nivel de exposición de corta duración.
STOT:	Toxicidad específica en determinados órganos.
TLV:	Valor límite del umbral.
TWA:	Promedio ponderado en el tiempo
WGK:	Clase de peligro para las aguas (Alemania).

Exposure Scenario, 19/07/2019

Substance identity	
Chemical name	ETHYLENE GLYCOL
CAS No.	107-21-1
EINECS No.	203-473-3

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Widespread use by professional workers
4. **ES 4** Consumer use; Various products (PC9a, PC1, PC4, PC8, PC15)

1. ES 1 Use at industrial site	
1.1 TITLE SECTION	
Exposure Scenario name	Use in cleaning agents
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)
Environment Contributing Scenario	
CS1 Covered by	ERC4
Worker Contributing Scenario	
CS2 Industrial	PROC1
CS3 Industrial	PROC2
CS4 Industrial	PROC3
CS5 Industrial	PROC4
CS6 Industrial	PROC8b
CS7 Industrial	PROC7
CS8 Industrial	PROC8a
CS9 Industrial	PROC10
CS10 Industrial	PROC13
1.2 Conditions of use affecting exposure	
1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)	
Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
<i>Product (article) characteristics</i>	
Physical form of product:	Liquid
Vapour pressure:	0.123 hPa
1.2. CS2: Worker Contributing Scenario: Industrial (PROC1)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
<i>Product (article) characteristics</i>	
Concentration of substance in product:	Covers percentage substance in the product up to 100 %.
<i>Amount used, frequency and duration of use/exposure</i>	
Duration:	Covers daily exposures up to 8 hours
Frequency:	Use frequency 240 days per year
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection	

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS3: Worker Contributing Scenario: Industrial (PROC2)

Process Categories

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS4: Worker Contributing Scenario: Industrial (PROC3)

Process Categories

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

1.2. CS5: Worker Contributing Scenario: Industrial (PROC4)

Process Categories

Chemical production where opportunity for exposure arises (PROC4)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection Wear suitable gloves tested to EN374.	
<i>Other conditions affecting worker exposure</i>	
Indoor use	
1.2. CS6: Worker Contributing Scenario: Industrial (PROC8b)	
Process Categories	Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: Use frequency 240 days per year	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374.	
<i>Other conditions affecting worker exposure</i>	
Indoor use	
1.2. CS7: Worker Contributing Scenario: Industrial (PROC7)	
Process Categories	Industrial spraying (PROC7)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Amounts used: Amount per use 1 L/min	
Duration: Covers daily exposures up to 8 hours	
Frequency: Use frequency 5 days per week	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection	
Wear suitable gloves tested to EN374.	Derma - minimum efficiency of: 90 %
<i>Other conditions affecting worker exposure</i>	
Indoor use	
Room size: Covers use in room size of > 1000 m ³	
1.2. CS8: Worker Contributing Scenario: Industrial (PROC8a)	
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

Ventilation rate: > 90 %

1.2. CS9: Worker Contributing Scenario: Industrial (PROC10)

Process Categories

Roller application or brushing (PROC10)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

1.2. CS10: Worker Contributing Scenario: Industrial (PROC13)

Process Categories

Treatment of articles by dipping and pouring (PROC13)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

1.3 Exposure estimation and reference to its source

1.3. CS2: Worker Contributing Scenario: Industrial (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.001
inhalative, local, long-term	N/A	EASY TRA v2.0	0.001
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.004

1.3. CS3: Worker Contributing Scenario: Industrial (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.07
inhalative, local, long-term	N/A	EASY TRA v2.0	0.07
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.08

1.3. CS4: Worker Contributing Scenario: Industrial (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.22
inhalative, local, long-term	N/A	EASY TRA v2.0	0.22
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.223

1.3. CS5: Worker Contributing Scenario: Industrial (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS6: Worker Contributing Scenario: Industrial (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37

inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS7: Worker Contributing Scenario: Industrial (PROC7)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.28
inhalative, local, long-term	N/A	EASY TRA v2.0	0.28
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.52
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.8

1.3. CS8: Worker Contributing Scenario: Industrial (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.43

1.3. CS9: Worker Contributing Scenario: Industrial (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.03
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.77

1.3. CS10: Worker Contributing Scenario: Industrial (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01

combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.75
--------------------------------------	-----	---------------	------

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers

2.1 TITLE SECTION

Exposure Scenario name	Use in cleaning agents
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8d
----------------	---------------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC3
CS5 General use from professional operators	PROC4
CS6 General use from professional operators	PROC8b
CS7 General use from professional operators	PROC8a
CS8 General use from professional operators	PROC10
CS9 General use from professional operators	PROC11
CS10 General use from professional operators	PROC13

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8a, ERC8d)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration: Covers daily exposures up to 8 hours	
Frequency: Use frequency 240 days per year	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374. Use suitable eye protection.	
<i>Other conditions affecting worker exposure</i>	
Indoor use	
2.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)	
Process Categories	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: Use frequency 240 days per year	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374. Use suitable eye protection.	
<i>Other conditions affecting worker exposure</i>	
Indoor use	
2.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)	
Process Categories	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)
<i>Product (article) characteristics</i>	
Physical form of product: Liquid	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: Use frequency 240 days per year	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374. Use suitable eye protection.	
<i>Other conditions affecting worker exposure</i>	
Indoor use	

2.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Process Categories	Chemical production where opportunity for exposure arises (PROC4)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Process Categories	Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

2.2. CS7: Worker Contributing Scenario: General use from professional operators (PROC8a)

Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %**2.2. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)****Process Categories**

Roller application or brushing (PROC10)

*Product (article) characteristics***Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

Frequency:

Use frequency 240 days per year

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear suitable gloves tested to EN374.

Use suitable eye protection.

Wear suitable respiratory protection.

Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Ventilation rate: 80 %**2.2. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)****Process Categories**

Non industrial spraying (PROC11)

*Product (article) characteristics***Physical form of product:**

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use/exposure***Amounts used:**

Amount per use 0.05 L/min

Duration:

Exposure duration 180 min

Frequency:

Use frequency < 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Provide a good standard of controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374. Use suitable eye protection.	Inhalation - minimum efficiency of: 90 %
Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 80 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 100 m³

Ventilation rate: 80 %

2.2. CS10: Worker Contributing Scenario: General use from professional operators (PROC13)

Process Categories	Treatment of articles by dipping and pouring (PROC13)
---------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Use frequency < 240 days per year

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374. Use suitable eye protection.	Inhalation - minimum efficiency of: 90 %
---	--

Other conditions affecting worker exposure

Indoor use

2.3 Exposure estimation and reference to its source

2.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.001
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.001
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.003

dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.004
-----------------------------	-----	------------------------	-------

2.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.01
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.38

2.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.22
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.22
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.003
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.223

2.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.006
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.8

2.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.06
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.8

2.3. CS7: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.13
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.5

2.3. CS8: Worker Contributing Scenario: General use from professional operators (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.37
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.37
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.3
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.4

2.3. CS9: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.4
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.4
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.51
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.91

2.3. CS10: Worker Contributing Scenario: General use from professional operators (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.74
dermal, local, long-term	N/A	ECETOC TRA worker v2.0	0.74
inhalative, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.01
dermal, systemic, long-term	N/A	ECETOC TRA worker v2.0	0.75

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Widespread use by professional workers

3.1 TITLE SECTION

Exposure Scenario name	Use in antifreeze products
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)

Environment Contributing Scenario

CS1 Covered by	ERC8d
----------------	-------

Worker Contributing Scenario

CS2 General use from professional operators	PROC1
CS3 General use from professional operators	PROC2
CS4 General use from professional operators	PROC8a
CS5 General use from professional operators	PROC8b
CS6 General use from professional operators	PROC11

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
----------------------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.123 hPa

3.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)
--------------------	--

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

<i>Other conditions affecting worker exposure</i>	
Indoor use	
3.2. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)	
Process Categories	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: Covers exposure up to 240 days per year	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Use in contained systems	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection Wear suitable gloves tested to EN374.	
<i>Other conditions affecting worker exposure</i>	
Indoor use	
3.2. CS4: Worker Contributing Scenario: General use from professional operators (PROC8a)	
Process Categories	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Covers daily exposures up to 8 hours	
Frequency: Covers exposure up to 240 days per year	
<i>Technical and organisational conditions and measures</i>	
Technical and organisational measures Use in contained systems	
<i>Conditions and measures related to personal protection, hygiene and health evaluation</i>	
Personal protection	
Wear suitable gloves tested to EN374.	
Wear suitable respiratory protection.	Inhalation - minimum efficiency of: 80 %
<i>Other conditions affecting worker exposure</i>	
Indoor use	
Ventilation rate: 80 %	
3.2. CS5: Worker Contributing Scenario: General use from professional operators (PROC8b)	
Process Categories	Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers exposure up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Other conditions affecting worker exposure

Indoor use

3.2. CS6: Worker Contributing Scenario: General use from professional operators (PROC11)

Process Categories

Non industrial spraying (PROC11)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Exposure duration 180 min

Frequency:

Covers exposure up to 5 days per week

Technical and organisational conditions and measures

Technical and organisational measures

Use in contained systems

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.

Dermal - minimum efficiency of: 90 %

Other conditions affecting worker exposure

Indoor use

Room size: Covers use in room size of > 100 m³

3.3 Exposure estimation and reference to its source

3.3. CS2: Worker Contributing Scenario: General use from professional operators (PROC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.001
inhalative, local, long-term	N/A	EASY TRA v2.0	0.001
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.003

combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.004
--------------------------------------	-----	---------------	-------

3.3. CS3: Worker Contributing Scenario: General use from professional operators (PROC2)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.01
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.38

3.3. CS4: Worker Contributing Scenario: General use from professional operators (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.37
inhalative, local, long-term	N/A	EASY TRA v2.0	0.37
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.13
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.5

3.3. CS5: Worker Contributing Scenario: General use from professional operators (PROC8b)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.74
inhalative, local, long-term	N/A	EASY TRA v2.0	0.74
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.06
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.8

3.3. CS6: Worker Contributing Scenario: General use from professional operators (PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	EASY TRA v2.0	0.4
inhalative, local, long-term	N/A	EASY TRA v2.0	0.4
dermal, systemic, long-term	N/A	EASY TRA v2.0	0.51
combined routes, systemic, long-term	N/A	EASY TRA v2.0	0.91

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

4. ES 4 Consumer use; Various products (PC9a, PC1, PC4, PC8, PC15)

4.1 TITLE SECTION

Exposure Scenario name	Consumer goods
Date - Version	19/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Product Categories	Coatings and paints, thinners, paint removers (PC9a) - Adhesives, sealants (PC1) - Anti-freeze and de-icing products (PC4) - Biocidal products (PC8) - Non-metal surface treatment products (PC15) - Heat transfer fluids (PC16) - Hydraulic fluids (PC17) - Ink and toners (PC18) - Leather treatment products (PC23) - Polishes and wax blends (PC31) - Polymer preparations and compounds (PC32) - Textile dyes and impregnating products (PC34) - Washing and cleaning products (PC35)

Environment Contributing Scenario

CS1 Covered by	ERC8a - ERC8c - ERC8d - ERC8f - ERC9a - ERC9b
----------------	---

Consumer Contributing Scenario

CS2 Consumer	PC1
CS3 Consumer	PC4 - PC16 - PC17 - PC4_1
CS4 Consumer	PC4 - PC4_2
CS5 Consumer	PC9a - PC15 - PC9a_2, PC15_2
CS6 Consumer	PC8
CS7 Consumer	PC18
CS8 Consumer	PC31
CS9 Consumer	PC32
CS10 Consumer	PC35 - PC8_2, PC35_2
CS11 Consumer	PC35 - PC8_3, PC35_3
CS12 Consumer	PC15 - PC23 - PC34 - PC9a_1, PC15_1

4.2 Conditions of use affecting exposure

4.2. CS1: Environment Contributing Scenario: Covered by (ERC8a, ERC8c, ERC8d, ERC8f, ERC9a, ERC9b)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) - Widespread use leading to inclusion into/onto article (indoor) - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) - Widespread use leading to inclusion into/onto article (outdoor) - Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC8a, ERC8c, ERC8d, ERC8f, ERC9a, ERC9b)
----------------------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

4.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Product Categories	Adhesives, sealants (PC1)
--------------------	---------------------------

<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 0.75 %	
4.2. CS3: Consumer Contributing Scenario: Consumer (PC4, PC16, PC17)	
Product Categories	Anti-freeze and de-icing products - Heat transfer fluids - Hydraulic fluids (PC4, PC16, PC17)
Product (Sub-)Categories	Washing car window (PC4_1)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 45 %	
<i>Amount used, frequency and duration of use/exposure</i>	
Duration: Exposure duration < 15 min	
4.2. CS4: Consumer Contributing Scenario: Consumer (PC4)	
Product Categories	Anti-freeze and de-icing products (PC4)
Product (Sub-)Categories	Pouring into radiator (PC4_2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 100 %.	
4.2. CS5: Consumer Contributing Scenario: Consumer (PC9a, PC15)	
Product Categories	Coatings and paints, thinners, paint removers - Non-metal surface treatment products (PC9a, PC15)
Product (Sub-)Categories	Solvent rich, high solid, water borne paint (PC9a_2, PC15_2)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 10 %	
4.2. CS6: Consumer Contributing Scenario: Consumer (PC8)	
Product Categories	Biocidal products (PC8)
4.2. CS7: Consumer Contributing Scenario: Consumer (PC18)	
Product Categories	Ink and toners (PC18)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
4.2. CS8: Consumer Contributing Scenario: Consumer (PC31)	
Product Categories	Polishes and wax blends (PC31)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers concentrations up to 10 %	
4.2. CS9: Consumer Contributing Scenario: Consumer (PC32)	
Product Categories	Polymer preparations and compounds (PC32)
<i>Product (article) characteristics</i>	
Concentration of substance in product: Covers percentage substance in the product up to 5 %.	
4.2. CS10: Consumer Contributing Scenario: Consumer (PC35)	

Product Categories	Washing and cleaning products (PC35)
Product (Sub-)Categories	Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) (PC8_2, PC35_2)

Product (article) characteristics

Concentration of substance in product:

Covers concentrations up to 20 %

4.2. CS11: Consumer Contributing Scenario: Consumer (PC35)

Product Categories	Washing and cleaning products (PC35)
Product (Sub-)Categories	Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) (PC8_3, PC35_3)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 5 %.

4.2. CS12: Consumer Contributing Scenario: Consumer (PC15, PC23, PC34)

Product Categories	Non-metal surface treatment products - Leather treatment products - Textile dyes and impregnating products (PC15, PC23, PC34)
Product (Sub-)Categories	Waterborne latex wall paint (PC9a_1, PC15_1)

4.3 Exposure estimation and reference to its source

4.2. CS2: Consumer Contributing Scenario: Consumer (PC1)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.59
dermal, systemic, long-term	N/A	N/A	0.005
combined routes, systemic, long-term	N/A	N/A	0.505

4.2. CS3: Consumer Contributing Scenario: Consumer (PC4, PC16, PC17)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.28
dermal, systemic, long-term	N/A	N/A	0.08
combined routes, systemic, long-term	N/A	N/A	0.36

4.2. CS4: Consumer Contributing Scenario: Consumer (PC4)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0
dermal, systemic, long-term	N/A	N/A	0.09
combined routes, systemic, long-term	N/A	N/A	0.09

4.2. CS5: Consumer Contributing Scenario: Consumer (PC9a, PC15)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.04
dermal, systemic, long-term	N/A	N/A	0.02
combined routes, systemic, long-term	N/A	N/A	0.06

4.2. CS6: Consumer Contributing Scenario: Consumer (PC8)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0
dermal, systemic, long-term	N/A	N/A	0.006
combined routes, systemic, long-term	N/A	N/A	0.006

4.2. CS7: Consumer Contributing Scenario: Consumer (PC18)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.18
dermal, systemic, long-term	N/A	N/A	0
combined routes, systemic, long-term	N/A	N/A	0.18

4.2. CS8: Consumer Contributing Scenario: Consumer (PC31)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.56
dermal, systemic, long-term	N/A	N/A	0.04
combined routes, systemic, long-term	N/A	N/A	0.6

4.2. CS9: Consumer Contributing Scenario: Consumer (PC32)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.009
dermal, systemic, long-term	N/A	N/A	0.001
combined routes, systemic, long-term	N/A	N/A	0.01

4.2. CS10: Consumer Contributing Scenario: Consumer (PC35)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.09
dermal, systemic, long-term	N/A	N/A	0.22
combined routes, systemic, long-term	N/A	N/A	0.31

4.2. CS11: Consumer Contributing Scenario: Consumer (PC35)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	N/A	N/A	0.02
dermal, systemic, long-term	N/A	N/A	0.002
combined routes, systemic, long-term	N/A	N/A	0.022

4.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.