

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



Safety Data Sheet dated 24/11/2025, version 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: VORTEX - Wash & Wax Shampoo

Trade code: 8107

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Product to wash external car surfaces.

Uses advised against:

Strictly adhere to the recommended uses.

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: emergency number 112

In South Africa: Poison Information Helpline 0861 555 777

In Malta: emergency number 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

⚠ Danger, Eye Dam. 1, Causes serious eye damage.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H318 Causes serious eye damage.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P280 Wear protective gloves/clothing and eye/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.



Safety Data Sheet

VORTEX - Wash & Wax Shampoo

P310 Immediately call a POISON CENTER.

Special Provisions:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

Contains

Alcohols, C9-11-iso-, C10-rich, ethoxylated

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

Regulation (EC) nr 648/2004 (detergents).

Product contents:

Non-ionic surfactants

5 - 15 %

The product also contains:

Perfumes

Allergens:

linalool; 3,7-dimethyl-1,6-octadien-3-ol; dl-linalool

Preservatives:

1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one, 2-Methyl-2H-isothiazol-3-one, PHENOXYETHANOL, LAURYLAMINE DIPROPYLENEDIAMINE, BENZISOTHIAZOLINONE

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
$\geq 7\%$ - $< 10\%$	Alcohols, C9-11-iso-, C10-rich, ethoxylated	CAS: 78330-20-8	⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.3/1 Eye Dam. 1 H318
$\geq 0,25\%$ - $< 0,5\%$	2-aminoethanol; ethanolamine	Index number: CAS: 141-43-5 EC: 205-483-3 REACH No.: 01- 2119486455 -28	⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.1/4/Oral Acute Tox. 4 H302 ⚠ 3.2/1B Skin Corr. 1B H314 ⚠ 3.3/1 Eye Dam. 1 H318 ⚠ 3.8/3 STOT SE 3 H335 4.1/C3 Aquatic Chronic 3 H412 Specific Concentration Limits: C $\geq 5\%$: STOT SE 3 H335
$\geq 0,1\%$ - $< 0,25\%$	Ossidi di alluminio	CAS: 1344-28-1 EC: 215-691-6	The product is not classified as hazardous according to Regulation EC 1272/2008 (CLP).
$\geq 0,001\%$ - $< 0,005\%$	sodium hydroxide; caustic soda	Index number: CAS: 1310-73-2 EC: 215-185-5	⚠ 2.16/1 Met. Corr. 1 H290 ⚠ 3.2/1A Skin Corr. 1A H314 ⚠ 3.3/1 Eye Dam. 1 H318 Specific Concentration Limits:

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



		REACH No.: 02-2119457892-27	C >= 5%: Skin Corr. 1A H314 2% <= C < 5%: Skin Corr. 1B H314 0,5% <= C < 2%: Skin Irrit. 2 H315 0,5% <= C < 2%: Eye Irrit. 2 H319
7 ppm	xylene	Index number: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 REACH No.: 01-2119488216-32	<ul style="list-style-type: none"> ⚠ 2.6/3 Flam. Liq. 3 H226 ⚠ 3.1/4/Dermal Acute Tox. 4 H312 ⚠ 3.1/4/Inhal Acute Tox. 4 H332 ⚠ 3.2/2 Skin Irrit. 2 H315
6 ppm	p-Mentha-1,4(8)-diene TERPINOLENE	CAS: 586-62-9 EC: 209-578-0	<ul style="list-style-type: none"> ⚠ 3.10/1 Asp. Tox. 1 H304 ⚠ 3.4.2/1B Skin Sens. 1B H317 ⚠ 4.1/A1 Aquatic Acute 1 H400 ⚠ 4.1/C1 Aquatic Chronic 1 H410

Substances in nanoform:
 >= 0,1% - < 0,25% Ossidi di alluminio
 CAS: 1344-28-1, EC: 215-691-6

Nanoform characteristics	Value
Particle size distribution:	D50: 25 nm

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Treatment of spasms intravenously with diazepam and calcium gluconium (10%).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Appropriate Extinguishing Media:

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



To carbon dioxide.

To dust.

Foam

Water spray.

Not Recommended Extinguishing Media:

Do not use direct water jets.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Normal fire-fighting clothing, such as an open-circuit compressed air breathing apparatus (EN 137), flame-resistant suit (EN469), flame-resistant gloves (EN 659) and firefighter's boots (HO A29 or A30).

Keep containers cool with water spray.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

See protective measures under point 7 and 8.

Provide adequate ventilation.

For emergency responders:

See protective measures under point 7 and 8.

Fist-gloves.

Remove all sources of ignition.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

For cleaning up:

Avoid flame and/or spark near leak and produced waste. Do not smoke. In case of large spills dike,

absorb and shovel up into suitable containers for disposal. Contain small spills with absorbent material.

Put dirty material in suitable container. Dispose of dirty material in accordance with local or national regulations.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



Only store in the original container.
Keep away from food, drink and feed.
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.

7.3. Specific end use(s)
None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-aminoethanol; ethanolamine - CAS: 141-43-5
20101.11 - TWA: 7.6 mg/m³, 3 ppm
EU - TWA(8h): 2.5 mg/m³, 1 ppm - STEL: 7.6 mg/m³, 3 ppm - Notes: Skin
ACGIH - TWA(8h): 3 ppm - STEL: 6 ppm - Notes: Eye and skin irr
Ossidi di alluminio - CAS: 1344-28-1
ACGIH - TWA(8h): 1 mg/m³
sodium hydroxide; caustic soda - CAS: 1310-73-2
20101.10 - TWA: 2 mg/m³
ACGIH - STEL: Ceiling 2 mg/m³ - Notes: URT, eye, and skin irr
NIOSH - Notes: Metodo raccomandato per il monitoraggio: NIOSH 7401
xylene - CAS: 1330-20-7
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: Skin
ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS
impair

DNEL Exposure Limit Values

2-aminoethanol; ethanolamine - CAS: 141-43-5
Consumer: 3.75 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic
effects
Worker Professional: 0.51 mg/m³ - Consumer: 0.18 mg/m³ - Exposure: Human
Inhalation - Frequency: Long Term, local effects
Worker Professional: 3 mg/kg - Consumer: 1.5 mg/kg - Exposure: Human Dermal -
Frequency: Long Term, systemic effects
sodium hydroxide; caustic soda - CAS: 1310-73-2
Worker Professional: 1 mg/m³ - Consumer: 1 mg/l - Exposure: Human Inhalation -
Frequency: Long Term, local effects

PNEC Exposure Limit Values

2-aminoethanol; ethanolamine - CAS: 141-43-5
Target: Fresh Water - Value: 0.07 mg/l
Target: Marine water - Value: 0.007 mg/l
Target: Freshwater sediments - Value: 0.357 mg/kg
Target: Marine water sediments - Value: 0.0357 mg/kg
Target: 09 - Value: 100 mg/l

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.
Compliant with EN 166

Protection for skin:

Safety shoes.
Chemical protection clothing.

Protection for hands:

Nitrile or Viton gloves.
Compliant with EN 374.
Thickness: Cuff 0.10 mm; Palm 0.12 mm; Fingers 0.145 mm
Gloves must be selected according to the specific type of use and the permeation time of the
material. The permeation time depends on the type of glove, its thickness and the type of
chemical. Consult the gloves' supplier to determine the appropriate permeation time. Replace
the gloves immediately if signs of wear or contamination are observed.

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



Respiratory protection:
 Filter for organic vapours. Type A. (EN14387)
 Thermal Hazards:
 None
 Environmental exposure controls:
 None
 Appropriate engineering controls:
 None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid	--	--
Colour:	Whitish	--	--
Odour:	Characteristic	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	N.A.	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
pH:	7.5	ASTM D1287	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	Soluble	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	1,000 g/cm ³	ASTM D 4052-96	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



Particle size:	N.A.	--	--
Nanoforms:	See Nanoform information in Section 3.	--	--

- 9.2. Other information
No other relevant information

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable at normal ambient temperatures and when used as recommended.
- 10.3. Possibility of hazardous reactions
None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

VORTEX - SHAMPOO CON CERA - ARX PRO

- a) acute toxicity
Not classified
Based on available data, the classification criteria are not met
- b) skin corrosion/irritation
Not classified
Based on available data, the classification criteria are not met
- c) serious eye damage/irritation
The product is classified: Eye Dam. 1 H318
- d) respiratory or skin sensitisation
Not classified
Based on available data, the classification criteria are not met
- e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
- f) carcinogenicity
Not classified
Based on available data, the classification criteria are not met
- g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
- h) STOT-single exposure
Not classified
Based on available data, the classification criteria are not met
- i) STOT-repeated exposure
Not classified
Based on available data, the classification criteria are not met
- j) aspiration hazard

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

2-aminoethanol; ethanolamine - CAS: 141-43-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 1089 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit = 2504 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 1.3 mg/l - Duration: 4h

b) skin corrosion/irritation:

Test: Eye Corrosive Positive - Notes: due to physical-chemical data (pH = 13)

Test: Skin Corrosive Positive - Notes: due to physical-chemical data (pH = 13)

xylene - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5000 mg/kg

p-Mentha-1,4(8)-diene TERPINOLENE - CAS: 586-62-9

a) acute toxicity:

Test: LD50 - Route: Skin > 5000 mg/kg

Test: LD50 - Route: Oral = 3850 mg/kg

Test: LC50 - Route: Inhalation > 100 mg/l

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration \geq 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Alcohols, C9-11-iso-, C10-rich, ethoxylated - CAS: 78330-20-8

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1 mg/l - Notes: OECD TG 203

Endpoint: EC50 - Species: Daphnia > 1 mg/l - Notes: OECD TG 202

Endpoint: EC50 - Species: Algae > 1 mg/l - Notes: OECD TG 201

2-aminoethanol; ethanolamine - CAS: 141-43-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 349 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 27.04 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 2.8 mg/l - Duration h: 2.8

sodium hydroxide; caustic soda - CAS: 1310-73-2

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 40.4 mg/l - Duration h: 48

12.2. Persistence and degradability

None

Alcohols, C9-11-iso-, C10-rich, ethoxylated - CAS: 78330-20-8

Biodegradability: Readily biodegradable

2-aminoethanol; ethanolamine - CAS: 141-43-5

Biodegradability: Readily biodegradable - Test: BIOGDG14 - Duration: 21GG - %: 91

12.3. Bioaccumulative potential

Alcohols, C9-11-iso-, C10-rich, ethoxylated - CAS: 78330-20-8

Bioaccumulation: Not bioaccumulative

sodium hydroxide; caustic soda - CAS: 1310-73-2

Bioaccumulation: Not bioaccumulative

12.4. Mobility in soil

sodium hydroxide; caustic soda - CAS: 1310-73-2

Mobility in soil: Not mobile

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



No endocrine disruptor substances present in concentration $\geq 0.1\%$

- 12.7. Other adverse effects
None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Additional disposal information:

The leftover product is to be considered special waste to be classified in accordance with Directive No. 2008/98/EC on waste and related matters. Recover if possible. Send to authorised disposal facilities or incineration under controlled conditions. Packaging can be taken to separate collection if emptied of its contents, checking the regulations of your municipality. Otherwise, it is always necessary to take it to an authorised centre or recycling point in your municipality.

SECTION 14: Transport information

14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Environmental Pollutant: No

IMDG-Marine pollutant: No

14.6. Special precautions for user

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)



Safety Data Sheet

VORTEX - Wash & Wax Shampoo

Regulation (EU) n. 2020/217 (ATP 14 CLP)
Regulation (EU) n. 2020/1182 (ATP 15 CLP)
Regulation (EU) n. 2021/643 (ATP 16 CLP)
Regulation (EU) n. 2021/849 (ATP 17 CLP)
Regulation (EU) n. 2022/692 (ATP 18 CLP)
Regulation (EU) n. 2023/707
Regulation (EU) n. 2023/1434 (ATP 19 CLP)
Regulation (EU) n. 2023/1435 (ATP 20 CLP)
Regulation (EU) n. 2024/197 (ATP 21 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 40

Restriction 75

Volatile Organic compounds - VOCs = 0.29 %

Volatile Organic compounds - VOCs = 2.92 g/Kg

Volatile Organic compounds - VOCs = 2.92 g/l

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

2-aminoethanol; ethanolamine

xylene

SECTION 16: Other information

Text of phrases referred to under heading 3:

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Safety Data Sheet
VORTEX - Wash & Wax Shampoo



Hazard class and hazard category	Code	Description
Met. Corr. 1	2.16/1	Substance or mixture corrosive to metals, Category 1
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1A	3.2/1A	Skin corrosion, Category 1A
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1B	3.4.2/1B	Skin Sensitisation, Category 1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

- SECTION 3: Composition/information on ingredients
- SECTION 6: Accidental release measures
- SECTION 8: Exposure controls/personal protection
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Eye Dam. 1, H318	Calculation method

This document was prepared by a competent person who has received appropriate training.

Safety Data Sheet

VORTEX - Wash & Wax Shampoo



Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.

Continued on next page - This SDS has been integrated with one or more Exposure scenarios. The exposure scenarios that follow must be considered as part of the SDS.

Exposure Scenario, 10/07/2019

Substance identity	
Chemical name	2-Aminoetanolo
CAS No.	141-43-5
EINECS No.	205-483-3

Table of contents

1. **ES 1** Consumer use; Washing and cleaning products (PC35)
2. **ES 2** Widespread use by professional workers; Washing and cleaning products (PC35)
3. **ES 3** Use at industrial site; Polymer preparations and compounds (PC32)

1. ES 1 Consumer use; Washing and cleaning products (PC35)

1.1 TITLE SECTION

Exposure Scenario name	Consumer goods
Date - Version	10/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Washing and cleaning products (PC35)

Environment Contributing Scenario

CS1 Water-based process ERC8d

Consumer Contributing Scenario

CS2 Detergent liquids PC35

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Water-based process (ERC8d)

Environmental release categories Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)

Amount used, frequency and duration of use (or from service life)

Amounts used:

Annual amount per site 60000000 kg

Release type: Continuous release

Emission days: 365 days per year

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Contain and dispose of waste according to local regulations.

Waste - minimum efficiency of: 87 %

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 18000 m³/day

Covers indoor and outdoor use

1.2. CS2: Consumer Contributing Scenario: Detergent liquids (PC35)

Product Categories Washing and cleaning products (PC35)

Product (article) characteristics

Vapour pressure:

0.539 hPa

Concentration of substance in product:

Covers concentrations up to 5 %

Amount used, frequency and duration of use/exposure

Duration:

Application duration 0.3 min

Frequency:

Covers exposure up to 365 days per year

Duration:

Exposure duration 0.75 min

Information and behavioural advice for consumers**Information and behavioural advice for consumers:**

Avoid contact with eyes

Other conditions affecting consumers exposure**Room size:** Covers use in room size of 1 m³**Ventilation rate:** Covers use under typical household ventilation.**Body parts exposed:**

Palm of one hand Hands and forearms

1.3 Exposure estimation and reference to its source**1.3. CS1: Environment Contributing Scenario: Water-based process (ERC8d)**

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	9.6 kg/d	ECETOC TRA environment v2.0	0.514

1.2. CS2: Consumer Contributing Scenario: Detergent liquids (PC35)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
inhalative, systemic, long-term	0.01 mg/m ³	N/A	0.01
inhalative, systemic, short-term	0.01 mg/m ³	N/A	0.01
dermal, systemic, long-term	0.008 mg/kg KW	N/A	0.03
dermal, systemic, long-term	0.002 mg/kg KW	N/A	0.01
oral, systemic, long-term	0.002 mg/kg KW	N/A	0.01

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2

Widespread use by professional workers; Washing and cleaning products (PC35)

2.1 TITLE SECTION

Exposure Scenario name	Cleaning agent
Date - Version	10/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses
Sector(s) of use	Professional uses (SU22)
Product Categories	Washing and cleaning products (PC35)

Environment Contributing Scenario

CS1 Water-based process	ERC8d
-------------------------	-------

Worker Contributing Scenario

CS2 Cleaning	PROC3
CS3 Cleaning	PROC8a
CS4 Cleaning	PROC10
CS5 Cleaning	PROC7 - PROC11
CS6 Cleaning	PROC13
CS7 Cleaning	PROC19

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Water-based process (ERC8d)

Environmental release categories	Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) (ERC8d)
----------------------------------	--

*Product (article) characteristics***Physical form of product:**

Liquid

Concentration of substance in product:

Covers concentrations up to 10 %

*Amount used, frequency and duration of use (or from service life)***Amounts used:**

Annual amount per site 65000000 kg

Release type: Continuous release**Emission days:** 220 days per year*Conditions and measures related to sewage treatment plant***STP type:**Municipal Sewage Treatment Plant
Water - minimum efficiency of: = 87 %**Additional information on STP:**

Acclimated biological treatment

STP sludge treatment:

STP effluent (m³/day): 2300

Conditions and measures related to treatment of waste (including article waste)

Waste treatment

Product residual disposal complies with applicable regulations.

Other conditions affecting environmental exposure

Local marine water dilution factor: 100

Local freshwater dilution factor: 10

Receiving surface water flow: 1800 m³/day

Covers indoor and outdoor use

2.2. CS2: Worker Contributing Scenario: Cleaning (PROC3)

Process Categories

Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.539 hPa

Concentration of substance in product:

Covers concentrations up to 10 %

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers use up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 98 %
Wear suitable respiratory protection.	Dermal - minimum efficiency of: 90 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Indoor use

Ventilation rate: Provide forced ventilation 80 %

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure regular inspection, cleaning and maintenance of equipment and machines.

2.2. CS3: Worker Contributing Scenario: Cleaning (PROC8a)

Process Categories

Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.539 hPa

Concentration of substance in product:

Covers concentrations up to 10 %

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

Frequency:

Covers use up to 240 days per year

*Technical and organisational conditions and measures***Technical and organisational measures**

Ensure that direct skin contact is avoided.

*Conditions and measures related to personal protection, hygiene and health evaluation***Personal protection**

Wear suitable gloves tested to EN374.	Derma - minimum efficiency of: 98 %
Wear suitable respiratory protection.	Derma - minimum efficiency of: 90 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Indoor use

Ventilation rate: Provide forced ventilation 80 %*Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.***Additional Good Practice Advice:**

Ensure regular inspection, cleaning and maintenance of equipment and machines.

2.2. CS4: Worker Contributing Scenario: Cleaning (PROC10)**Process Categories**

Roller application or brushing (PROC10)

*Product (article) characteristics***Physical form of product:**

Liquid

Vapour pressure:

0.539 hPa

Concentration of substance in product:

Covers concentrations up to 10 %

*Amount used, frequency and duration of use/exposure***Duration:**

Covers daily exposures up to 8 hours

Frequency:

Covers use up to 240 days per year

*Technical and organisational conditions and measures***Technical and organisational measures**

Ensure that direct skin contact is avoided.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 98 %
Wear suitable respiratory protection.	Dermal - minimum efficiency of: 90 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Indoor use

Ventilation rate: Provide forced ventilation 80 %

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure regular inspection, cleaning and maintenance of equipment and machines.

2.2. CS5: Worker Contributing Scenario: Cleaning (PROC7, PROC11)

Process Categories Industrial spraying - Non industrial spraying (PROC7, PROC11)

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

0.539 hPa

Concentration of substance in product:

Covers concentrations up to 10 %

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Frequency:

Covers use up to 240 days per year

Technical and organisational conditions and measures

Technical and organisational measures

Ensure that direct skin contact is avoided.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.	Dermal - minimum efficiency of: 98 %
Wear suitable respiratory protection.	Dermal - minimum efficiency of: 90 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Indoor use

Ventilation rate: Provide forced ventilation 80 %

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure regular inspection, cleaning and maintenance of equipment and machines.

2.2. CS6: Worker Contributing Scenario: Cleaning (PROC13)

Process Categories	Treatment of articles by dipping and pouring (PROC13)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: 0.539 hPa	
Concentration of substance in product: Covers concentrations up to 10 %	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Frequency: Covers use up to 240 days per year	
Technical and organisational conditions and measures	
Technical and organisational measures Ensure that direct skin contact is avoided.	
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection	
Wear suitable gloves tested to EN374.	Derma - minimum efficiency of: 98 %
Wear suitable respiratory protection.	Derma - minimum efficiency of: 90 %
Use suitable eye protection.	
Other conditions affecting worker exposure	
Indoor use	
Ventilation rate: Provide forced ventilation 80 %	
Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.	
Additional Good Practice Advice: Ensure regular inspection, cleaning and maintenance of equipment and machines.	
2.2. CS7: Worker Contributing Scenario: Cleaning (PROC19)	
Process Categories	Manual activities involving hand contact (PROC19)
Product (article) characteristics	
Physical form of product: Liquid	
Vapour pressure: 0.539 hPa	
Concentration of substance in product: Covers concentrations up to 10 %	
Amount used, frequency and duration of use/exposure	
Duration: Covers daily exposures up to 8 hours	
Frequency: Covers use up to 240 days per year	
Technical and organisational conditions and measures	

Technical and organisational measures

Ensure that direct skin contact is avoided.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable gloves tested to EN374.	Derma - minimum efficiency of: 98 %
Wear suitable respiratory protection.	Derma - minimum efficiency of: 90 %
Use suitable eye protection.	

Other conditions affecting worker exposure

Indoor use

Ventilation rate: Provide forced ventilation 80 %

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply.

Additional Good Practice Advice:

Ensure regular inspection, cleaning and maintenance of equipment and machines.

2.3 Exposure estimation and reference to its source

2.3. CS1: Environment Contributing Scenario: Water-based process (ERC8d)

protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	9343 kg/d	ECETOC TRA environment v2.0	0.482

2.3. CS2: Worker Contributing Scenario: Cleaning (PROC3)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.01 mg/kg KW	ECETOC TRA worker v2.0	0.01
inhalative, systemic, long-term	0.15 mg/m ³	ECETOC TRA worker v2.0	0.05
inhalative, systemic, short-term	0.15 mg/m ³	ECETOC TRA worker v2.0	0.05

2.3. CS3: Worker Contributing Scenario: Cleaning (PROC8a)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.03 mg/kg KW	ECETOC TRA worker v2.0	0.03
inhalative, systemic, long-term	1.27 mg/m ³	ECETOC TRA worker v2.0	0.39

2.3. CS4: Worker Contributing Scenario: Cleaning (PROC10)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.05 mg/kg KW	ECETOC TRA worker v2.0	0.05

inhalative, systemic, long-term	0.76 mg/m ³	ECETOC TRA worker v2.0	0.23
---------------------------------	------------------------	------------------------	------

2.3. CS5: Worker Contributing Scenario: Cleaning (PROC7, PROC11)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.21 mg/kg KW	ECETOC TRA worker v2.0	0.21
inhalative, systemic, long-term	1.53 mg/m ³	ECETOC TRA worker v2.0	0.46

2.3. CS6: Worker Contributing Scenario: Cleaning (PROC13)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.03 mg/kg KW	ECETOC TRA worker v2.0	0.03
inhalative, systemic, long-term	0.25 mg/m ³	ECETOC TRA worker v2.0	0.08

2.3. CS7: Worker Contributing Scenario: Cleaning (PROC19)

Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.28 mg/kg KW	ECETOC TRA worker v2.0	0.28
inhalative, systemic, long-term	0.38 mg/m ³	ECETOC TRA worker v2.0	0.12

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3

Use at industrial site; Polymer preparations and compounds (PC32)

3.1 TITLE SECTION

Exposure Scenario name	Additive
Date - Version	10/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Product Categories	Polymer preparations and compounds (PC32)

Environment Contributing Scenario

CS1 Solvent-based process	ERC5
---------------------------	------

Worker Contributing Scenario

CS2 Additive	PROC14
--------------	--------

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Solvent-based process (ERC5)

Environmental release categories	Use at industrial site leading to inclusion into/onto article (ERC5)
----------------------------------	--

*Product (article) characteristics***Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

*Amount used, frequency and duration of use (or from service life)***Amounts used:**

Annual amount per site 6720000 kg

Release type: Continuous release**Emission days:** 365 days per year*Conditions and measures related to sewage treatment plant***STP type:**

Municipal Sewage Treatment Plant

Water - minimum efficiency of: = 87 %

Additional information on STP:

Biological elimination

STP sludge treatment:

No application of sewage sludge to soil

STP effluent (m³/day): 2300*Conditions and measures related to treatment of waste (including article waste)***Waste treatment**

Do not apply industrial sludge to natural soils.

*Other conditions affecting environmental exposure***Local marine water dilution factor:** 100**Local freshwater dilution factor:** 10**Receiving surface water flow:** 18000 m³/day

3.2. CS2: Worker Contributing Scenario: Additive (PROC14)

Process Categories	Tabletting, compression, extrusion, pelletisation, granulation (PROC14)		
Product (article) characteristics			
Physical form of product: Liquid			
Vapour pressure: 0.539 hPa			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
Amount used, frequency and duration of use/exposure			
Duration: Covers use up to 480 min			
Frequency: Covers frequency up to: 240 days per year			
Conditions and measures related to personal protection, hygiene and health evaluation			
Personal protection			
Use suitable eye protection.			
Wear suitable gloves tested to EN374.		Inhalation - minimum efficiency of: 90 %	
Other conditions affecting worker exposure			
Indoor use			
Ventilation rate: Provide forced ventilation 90 %			
3.3 Exposure estimation and reference to its source			
3.3. CS1: Environment Contributing Scenario: Solvent-based process (ERC5)			
protection target	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
freshwater	6.28 kg/d	N/A	N/A
3.3. CS2: Worker Contributing Scenario: Additive (PROC14)			
Exposure route, Health effect, Exposure indicator	Exposure level	Calculation method	Risk Characterization Ratio (RCR)
dermal, systemic, long-term	0.07 mg/kg bw/day	ECETOC TRA worker v3	0.07
inhalative, systemic, long-term	1.27 mg/m ³	ECETOC TRA worker v3	0.39
inhalative, local, long-term	1.27 mg/m ³	ECETOC TRA worker v3	0.39
3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES			
Guidance to check compliance with the exposure scenario:			
Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.			