

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



Safety Data Sheet dated 27/10/2021, version 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PULITORE IMPIANTO GPL SPRAY 120 ML

Trade code: 9837

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Fuel additive

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: Beaumont Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 - 22:00)

In South Africa: Poison Information Helpline 0861 555 777

In Malta: emergency number 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

⚠ Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

⚠ Danger, Eye Dam. 1, Causes serious eye damage.

⚠ Warning, STOT RE 2, May cause damage to organs through prolonged or repeated exposure. Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P280 Wear protective gloves/clothing and eye/face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
- P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

PACK2 The packing must have tactile indications of danger for blind people.

Contains

potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

$\geq 40\%$ - $< 50\%$ Hydrocarbons, C3-4; Petroleum gas

REACH No.: 01-2119486557-22, Index number: 649-199-00-1, CAS: 68476-40-4, EC: 270-681-9

⚠ 2.2/1A Flam. Gas 1A H220

⚠ 2.5/L Press Gas (Liq.) H280

DECLK (CLP)*

$\geq 25\%$ - $< 30\%$ Distillates (petroleum), hydrotreated light

REACH No.: 01-2119456620-43, EC: 926-141-6

⚠ 3.10/1 Asp. Tox. 1 H304

EUH066

$\geq 3\%$ - $< 5\%$ Hydrocarbons, C10, Aromatics, $>1\%$ Naphthalene

REACH No.: 01-2119463588-24, EC: 919-284-0

⚠ 3.8/3 STOT SE 3 H336

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 4.1/C2 Aquatic Chronic 2 H411

EUH066

$\geq 3\%$ - $< 5\%$ potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate

REACH No.: 01-2119919740-39, EC: 231-308-5

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

$\geq 3\%$ - $< 5\%$ Diossido di carbonio liquido refrigerato

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



CAS: 124-38-9, EC: 204-696-9
◇ 2.5/RL Press Gas (Ref. Liq.) H281

>= 3% - < 5% Polyolefin phenolic alkylamine , proprietà di Afton comP.di HiTEC

⚠ 3.2/2 Skin Irrit. 2 H315

>= 2% - < 3% Polyether polyol

4.1/C3 Aquatic Chronic 3 H412

>= 1% - < 2% Petroleum distillates, hydrotreated light
REACH No.: 01-2119484819-18, EC: 265-149-8

◇ 2.6/3 Flam. Liq. 3 H226

◇ 3.10/1 Asp. Tox. 1 H304

>= 1% - < 2% Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics
EC: 919-164-8

◇ 3.10/1 Asp. Tox. 1 H304

◇ 3.9/1 STOT RE 1 H372

4.1/C3 Aquatic Chronic 3 H412

>= 0.25% - < 0.5% naphthalene

CAS: 91-20-3, EC: 202-049-5

◇ 3.6/2 Carc. 2 H351

⚠ 3.1/4/Oral Acute Tox. 4 H302

⚠ 4.1/A1 Aquatic Acute 1 H400 M=1.

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.

◇ 2.7/2 Flam. Sol. 2 H228

>= 0.25% - < 0.5% 1,2,4-trimethylbenzene

CAS: 95-63-6, EC: 202-436-9

◇ 2.6/3 Flam. Liq. 3 H226

⚠ 3.1/4/Inhal Acute Tox. 4 H332

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.1% - < 0.25% 2-Ethylhexan-1-ol

REACH No.: 01-2119487289-20, CAS: 104-76-7, EC: 203-234-3

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.1/4/Inhal Acute Tox. 4 H332

>= 0.1% - < 0.25% Diethylbenzene

CAS: 25340-17-4, EC: 246-874-9

◇ 2.6/3 Flam. Liq. 3 H226

⚠ 3.2/2 Skin Irrit. 2 H315

◇ 3.10/1 Asp. Tox. 1 H304

⚠ 4.1/A1 Aquatic Acute 1 H400 M=1.

⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.

>= 0.1% - < 0.25% Mesitylene

CAS: 108-67-8, EC: 203-604-4

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



- ◆ 2.6/3 Flam. Liq. 3 H226
- ◆ 3.2/2 Skin Irrit. 2 H315
- ◆ 3.3/2 Eye Irrit. 2 H319
- ◆ 3.8/3 STOT SE 3 H335
- ◆ 3.10/1 Asp. Tox. 1 H304
- ◆ 4.1/C2 Aquatic Chronic 2 H411

>= 0.01% - < 0.02% cumene

Index number: 601-024-00-X, CAS: 98-82-8, EC: 202-704-5

- ◆ 2.6/3 Flam. Liq. 3 H226
- ◆ 3.6/2 Carc. 2 H351
- ◆ 3.8/3 STOT SE 3 H335
- ◆ 3.10/1 Asp. Tox. 1 H304
- ◆ 4.1/C2 Aquatic Chronic 2 H411

>= 0.005% - < 0.01% naphthalene

REACH No.: 01-2119561346-37, Index number: 601-052-00-2, CAS: 91-20-3, EC: 202-049-5

- ◆ 3.6/2 Carc. 2 H351
- ◆ 3.1/4/Oral Acute Tox. 4 H302
- ◆ 4.1/A1 Aquatic Acute 1 H400
- ◆ 4.1/C1 Aquatic Chronic 1 H410
- ◆ 2.7/2 Flam. Sol. 2 H228

*DECLK (CLP): Substance classified in accordance with Note K, Annex VI of EC Regulation (EC) 1272/2008. The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



None

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Appropriate Extinguishing Media:
 - To carbon dioxide.
 - To dust.
 - Foam
 - Water spray.
 - Not Recommended Extinguishing Media:
 - Do not use direct water jets.
- 5.2. Special hazards arising from the substance or mixture
 - Do not inhale explosion and combustion gases.
 - Burning produces heavy smoke.
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus .
 - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
 - Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove all sources of ignition.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.
 - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - See also section 8 for recommended protective equipment.
 - Advice on general occupational hygiene:
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
 - Store at below 50 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.
 - Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.
 - Keep away from food, drink and feed.
 - None in particular.
 - Instructions as regards storage premises:
 - Cool and adequately ventilated.
- 7.3. Specific end use(s)

9837/8

Page n. 5 of 18

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hydrocarbons, C3-4; Petroleum gas - CAS: 68476-40-4

MAK - TWA: 2400 mg/m³, 1000 ppm

TLV TWA - 1900 mg/m³, 800 ppm

Distillates (petroleum), hydrotreated light

20101.12 - TWA: 1200 mg/m³, 165 ppm

Diossido di carbonio liquido refrigerato - CAS: 124-38-9

EU - TWA(8h): 9000 mg/m³, 5000 ppm

ACGIH - TWA(8h): 5000 ppm - STEL: 30000 ppm - Notes: Asphyxia

Petroleum distillates, hydrotreated light

20101.13 - TWA: 200 mg/m³

naphthalene - CAS: 91-20-3

EU - TWA(8h): 50 mg/m³, 10 ppm

ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia

1,2,4-trimethylbenzene - CAS: 95-63-6

EU - TWA(8h): 100 mg/m³, 20 ppm

2-Ethylhexan-1-ol - CAS: 104-76-7

EU - TWA(8h): 5.4 mg/m³, 1 ppm

Diethylbenzene - CAS: 25340-17-4

EU - TWA(8h): 10 mg/m³

Mesitilene - CAS: 108-67-8

EU - TWA(8h): 100 mg/m³, 20 ppm

cumene - CAS: 98-82-8

EU - TWA(8h): 50 mg/m³, 10 ppm - STEL: 250 mg/m³, 50 ppm - Notes: Skin

ACGIH - TWA(8h): 50 ppm - Notes: Eye, skin, and URT irr, CNS impair

naphthalene - CAS: 91-20-3

20101.13 - TWA: 50 mg/m³, 10 ppm

EU - TWA(8h): 50 mg/m³, 10 ppm

ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia

DNEL Exposure Limit Values

Hydrocarbons, C10, Aromatics, >1% Naphthalene

Worker Professional: 25 mg/kg - Consumer: 11 mg/kg - Exposure: Human Dermal

Worker Professional: 150 mg/m³ - Consumer: 32 mg/m³ - Exposure: Human Inhalation

Consumer: 11 mg/kg - Exposure: Human Oral

naphthalene - CAS: 91-20-3

Worker Professional: 1 mg/kg - Consumer: 0.5 mg/kg - Exposure: Human Oral

Worker Professional: 3.57 mg/kg - Consumer: 1.5 mg/kg - Exposure: Human Dermal

Worker Professional: 25 mg/m³ - Consumer: 0.0183 mg/m³ - Exposure: Human Inhalation

2-Ethylhexan-1-ol - CAS: 104-76-7

Consumer: 2.3 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 23 mg/kg - Consumer: 11.4 mg/m³ - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

naphthalene - CAS: 91-20-3

Target: Fresh Water - Value: 0.0024 mg/l

Target: Marine water - Value: 0.0024 mg/l

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Compliant with EN 166

Protection for skin:

9837/8

Page n. 6 of 18

Safety Data Sheet
PULITORE IMPIANTO GPL SPRAY 120 ML



protective clothing
 Protection for hands:
 Nitrile or Viton gloves.
 Compliant with EN 374.
 Respiratory protection:
 Not needed for normal use.
 Thermal Hazards:
 None
 Environmental exposure controls:
 None
 Appropriate engineering controls:
 None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid	--	--
Colour:	Light yellow	--	--
Odour:	Characteristic	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	N.A.	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
pH:	N.A.	--	--
Kinematic viscosity:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	N.A.	--	--

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

- 9.2. Other information
No other relevant information

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

- 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

PULITORE IMPIANTO GPL SPRAY 120 ML

- a) acute toxicity
Not classified
Based on available data, the classification criteria are not met
- b) skin corrosion/irritation
Not classified
Based on available data, the classification criteria are not met
- c) serious eye damage/irritation
The product is classified: Eye Dam. 1 H318
- d) respiratory or skin sensitisation
Not classified
Based on available data, the classification criteria are not met
- e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
- f) carcinogenicity
Not classified
Based on available data, the classification criteria are not met
- g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
- h) STOT-single exposure
Not classified
Based on available data, the classification criteria are not met
- i) STOT-repeated exposure
The product is classified: STOT RE 2 H373
- j) aspiration hazard

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



Not classified

Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

Distillates (petroleum), hydrotreated light

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m³ - Duration: 8h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

b) skin corrosion/irritation:

Test: OECD TG 404 - Route: Skin Negative

c) serious eye damage/irritation:

Test: OECD TG 405 - Route: EYE Negative

d) respiratory or skin sensitisation:

Test: Inhalation Sensitization 3

Test: Skin Sensitization 3

j) aspiration hazard:

Test: May be fatal if swallowed and enters airways (physical-chemical properties) - Route:

Oral Positive

Hydrocarbons, C10, Aromatics, >1% Naphthalene

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5.28 mg/m³ - Duration: 4h

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

c) serious eye damage/irritation:

Test: Eye Irritant - Route: EYE - Species: Rat Negative

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Species: IND Negative

e) germ cell mutagenicity:

Test: Mutagenesis - Species: vitro Negative

g) reproductive toxicity:

Test: Reproductive Toxicity - Route: Oral - Species: Rat Negative

potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate

b) skin corrosion/irritation:

Test: Skin Sensitization Negative

h) STOT-single exposure:

Test: Respiratory Tract Irritant Positive

Polyolefin phenolic alkyleneamine, proprietà di Afton comP.di HiTEC

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit Positive

c) serious eye damage/irritation:

Test: Eye Irritant - Route: EYE - Species: Rabbit Negative

g) reproductive toxicity:

Test: Reproductive Toxicity - Route: Oral - Species: Rat Positive

Polyether polyol

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit > 3000 mg/kg

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

b) skin corrosion/irritation:

Test: Skin Irritant - Route: Skin - Species: Rabbit Negative

c) serious eye damage/irritation:

Test: Eye Irritant - Route: EYE - Species: Rabbit Negative

d) respiratory or skin sensitisation:

Test: Skin Sensitization - Route: Skin - Species: IND Negative

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



- e) germ cell mutagenicity:
 - Test: Mutagenesis - Species: vitro Negative
- Petroleum distillates, hydrotreated light
- j) aspiration hazard:
 - Test: May be fatal if swallowed and enters airways (physical-chemical properties) Positive
- Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics
- i) STOT-repeated exposure:
 - Route: Inhalation Positive
- j) aspiration hazard:
 - Test: May be fatal if swallowed and enters airways (physical-chemical properties) Positive
- naphthalene - CAS: 91-20-3
- a) acute toxicity:
 - Test: LC50 - Route: Inhalation Vapour - Species: Rat > 0.4 mg/l - Duration: 4h
 - Test: LD50 - Route: Skin - Species: Rat > 16000 mg/kg
 - Test: LD50 - Route: Oral - Species: Mouse 533 mg/kg
- b) skin corrosion/irritation:
 - Test: Skin Irritant - Route: Skin - Species: Rabbit Negative
- c) serious eye damage/irritation:
 - Test: Eye Irritant - Route: EYE - Species: Rabbit Negative
- d) respiratory or skin sensitisation:
 - Test: Skin Sensitization - Route: Skin - Species: IND Negative
- f) carcinogenicity:
 - Test: Carcinogeneticity - Route: Inhalation - Species: Rat Positive
- g) reproductive toxicity:
 - Test: Reproductive Toxicity - Route: Inhalation - Species: Rat Positive
- 1,2,4-trimethylbenzene - CAS: 95-63-6
- a) acute toxicity:
 - Test: LD50 - Route: Skin - Species: Rat > 3440 mg/kg
 - Test: LD50 - Route: Oral - Species: Rat 6000 mg/kg
 - Test: LC50 - Route: Inhalation - Species: Rat > 10200 mg/l - Duration: 4h
- b) skin corrosion/irritation:
 - Test: Skin Irritant - Route: Skin - Species: Rabbit Positive
- c) serious eye damage/irritation:
 - Test: Eye Irritant - Route: EYE - Species: Rabbit Positive
- d) respiratory or skin sensitisation:
 - Test: Skin Sensitization - Route: Skin - Species: IND Negative
- e) germ cell mutagenicity:
 - Test: Mutagenesis - Species: vitro Negative
- g) reproductive toxicity:
 - Test: Reproductive Toxicity - Route: Inhalation - Species: Rat Positive
- 2-Ethylhexan-1-ol - CAS: 104-76-7
- a) acute toxicity:
 - Test: LD50 - Route: Oral - Species: Rat 2040 mg/kg
 - Test: LD50 - Route: Skin - Species: Rat 1970 mg/kg
 - Test: LC50 - Route: Inhalation - Species: Rat 0.89-5.3 mg/l - Duration: 4h
- b) skin corrosion/irritation:
 - Test: Skin Irritant - Route: Skin - Species: Rabbit Positive
- c) serious eye damage/irritation:
 - Test: Eye Irritant - Route: EYE - Species: Rabbit Positive
- e) germ cell mutagenicity:
 - Test: Mutagenesis - Species: vitro Negative
- f) carcinogenicity:
 - Test: Carcinogeneticity - Route: Oral - Species: Mouse Negative
- g) reproductive toxicity:
 - Test: Reproductive Toxicity - Route: Oral - Species: Rat Negative
- Diethylbenzene - CAS: 25340-17-4

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



- a) acute toxicity:
 - Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg
 - Test: LD50 - Route: Oral - Species: Rat 2050 mg/kg
 - b) skin corrosion/irritation:
 - Test: Skin Irritant - Route: Skin - Species: Rabbit Positive
 - c) serious eye damage/irritation:
 - Test: Eye Irritant - Route: EYE - Species: Rabbit Positive
 - d) respiratory or skin sensitisation:
 - Test: Skin Sensitization - Route: Skin - Species: IND Negative
 - e) germ cell mutagenicity:
 - Test: Mutagenesis - Species: vitro Negative
 - f) carcinogenicity:
 - Test: Carcinogeneticity - Route: Skin - Species: Mouse Negative
 - g) reproductive toxicity:
 - Test: Reproductive Toxicity - Route: Oral - Species: Rat Negative
- Mesitilene - CAS: 108-67-8
- a) acute toxicity:
 - Test: LC50 - Route: Inhalation - Species: Rat > 10.2 mg/l - Duration: 4h
 - Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg
 - Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
 - b) skin corrosion/irritation:
 - Test: Skin Irritant - Route: Skin - Species: Rabbit Positive
 - c) serious eye damage/irritation:
 - Test: Eye Irritant - Route: EYE - Species: Rabbit Positive
 - d) respiratory or skin sensitisation:
 - Test: Skin Sensitization - Route: Skin - Species: IND Negative
 - e) germ cell mutagenicity:
 - Test: Mutagenesis - Species: vitro Negative
 - g) reproductive toxicity:
 - Test: Reproductive Toxicity - Route: Inhalation - Species: Rat Positive
- cumene - CAS: 98-82-8
- a) acute toxicity:
 - Test: LC50 - Route: Inhalation - Species: Rat 40 mg/l - Duration: 4h
 - Test: LD50 - Route: Skin - Species: Rabbit > 10000 mg/kg
 - Test: LD50 - Route: Oral - Species: Rat 2260 mg/kg
 - b) skin corrosion/irritation:
 - Test: Eye Irritant - Species: Rabbit Negative
 - Test: Skin Irritant - Species: Rabbit Negative
 - d) respiratory or skin sensitisation:
 - Test: Skin Sensitization - Species: IND Negative
 - e) germ cell mutagenicity:
 - Test: oecd - Species: vitro Negative
 - f) carcinogenicity:
 - Test: Carcinogeneticity - Route: Inhalation - Species: Rat Positive
 - g) reproductive toxicity:
 - Route: Inhalation - Species: Rat Positive
- naphthalene - CAS: 91-20-3
- e) germ cell mutagenicity:
 - Test: Mutagenesis - Species: vitro Positive
 - f) carcinogenicity:
 - Test: Carcinogeneticity - Route: Inhalation - Species: Rat Positive - Notes: IARC 2B
 - i) STOT-repeated exposure:
 - Test: oecd 16 Positive

11.2. Information on other hazards

Endocrine disrupting properties:

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Hydrocarbons, C3-4; Petroleum gas - CAS: 68476-40-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia = 14.22 mg/l - Duration h: 48

Distillates (petroleum), hydrotreated light

a) Aquatic acute toxicity:

Endpoint: EL0 - Species: Daphnia 1000 mg/l - Duration h: 48

Endpoint: EL0 - Species: Algae 1000 mg/l - Duration h: 72

Endpoint: CE7 - Species: Fish 1000 mg/l - Duration h: 96

Hydrocarbons, C10, Aromatics, >1% Naphthalene

a) Aquatic acute toxicity:

Endpoint: EL50 - Species: Algae > 1 mg/l - Duration h: 72

Endpoint: EL50 - Species: Daphnia = 1.4 mg/l - Duration h: 48

Endpoint: LL50 - Species: Fish = 2-5 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEL - Species: Fish = 1 mg/l - Duration h: 72

Endpoint: NOEL - Species: Daphnia = 0.48 mg/l - Duration h: 504

potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 27.2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 6.6 mg/l - Duration h: 48

c) Bacteria toxicity:

Endpoint: EC50 - Species: fanghi 164 mg/l - Duration h: 1

Polyolefin phenolic alkyleneamine, proprietà di Afton comP.di HiTEC

a) Aquatic acute toxicity:

Endpoint: EL50 - Species: Algae 5.4 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae 3.65 mg/l - Duration h: 96

Endpoint: NOEC - Species: bioluminescence method, NVN 6516 3.38 mg/l - Duration h: 504

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 10.01-100 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia > 100.1-200 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 10.01-100 mg/l - Duration h: 72

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Algae 3 mg/l - Duration h: 72

naphthalene - CAS: 91-20-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Algae 2.96 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 2.16 mg/l - Duration h: 48

Endpoint: EC50 - Species: Fish 0.96 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEC - Species: Daphnia 0.59 mg/l - Duration h: 3000

Endpoint: NOEC - Species: Fish 0.12 mg/l - Duration h: 960

1,2,4-trimethylbenzene - CAS: 95-63-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Daphnia 3.6 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish 7.72 mg/l - Duration h: 96

2-Ethylhexan-1-ol - CAS: 104-76-7

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 39 mg/l - Duration h: 48

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



- Endpoint: EL50 - Species: Algae 16.6 mg/l - Duration h: 72
Endpoint: LC50 - Species: Fish 17.1 mg/l - Duration h: 96
- b) Aquatic chronic toxicity:
Endpoint: EL10 - Species: Algae 5.3 mg/l - Duration h: 72
- Diethylbenzene - CAS: 25340-17-4
- a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Algae 1.21 mg/l - Duration h: 72
Endpoint: EC50 - Species: Daphnia 2.01 mg/l - Duration h: 48
Endpoint: LC50 - Species: Fish 0.673 mg/l - Duration h: 96
Endpoint: NOEC - Species: fanghi > 1000 mg/l - Duration h: 3
- b) Aquatic chronic toxicity:
Endpoint: NOEC - Species: Algae 0.547 mg/l - Duration h: 72
- Mesitilene - CAS: 108-67-8
- a) Aquatic acute toxicity:
Endpoint: EL50 - Species: Algae 53 mg/l - Duration h: 48
Endpoint: LL50 - Species: Daphnia 6 mg/l - Duration h: 48
Endpoint: LL50 - Species: Fish 12.52 mg/l - Duration h: 96
- b) Aquatic chronic toxicity:
Endpoint: EL10 - Species: Algae 16 mg/l - Duration h: 48
Endpoint: NOEC - Species: Daphnia 0.4 mg/l - Duration h: 504
- cumene - CAS: 98-82-8
- a) Aquatic acute toxicity:
Endpoint: EC50 - Species: Algae 2.01 mg/l - Duration h: 72
Endpoint: EC50 - Species: Daphnia 2.14 mg/l - Duration h: 48
Endpoint: EL50 - Species: fanghi > 2000 mg/l - Duration h: 3
Endpoint: LC50 - Species: Fish 4.8 mg/l - Duration h: 96
- b) Aquatic chronic toxicity:
Endpoint: CE5 - Species: Algae 1.35 mg/l - Duration h: 72
Endpoint: NOEC - Species: Daphnia 0.35 mg/l - Duration h: 504
Endpoint: NOEC - Species: Fish 0.38 mg/l - Duration h: 672
- 12.2. Persistence and degradability
- None
- Distillates (petroleum), hydrotreated light
Biodegradability: Readily biodegradable - Duration: 28gg - %: 69
- Hydrocarbons, C10, Aromatics, >1% Naphthalene
Biodegradability: 4 - Test: BIOGDG10 - Duration: 28gg - %: 58.6
- potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate
Biodegradability: 4 - Test: BIOGDG08 - Duration: 28gg - %: 66.7
Test: BIOGDG07 - Duration: 28gg - %: 91.2
- Polyolefin phenolic alkyleneamine , proprietà di Afton comP.di HiTEC
Biodegradability: Non-readily biodegradable - Test: BIOGDG08 - Duration: 28gg - %: 4
- Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics
Test: BIOGDG10 - Duration: 28gg - %: 74.4
- naphthalene - CAS: 91-20-3
Biodegradability: Non-readily biodegradable - Test: OECD 302C - Duration: 28gg - %: 0-2
- 2-Ethylhexan-1-ol - CAS: 104-76-7
Biodegradability: Readily biodegradable - Test: BIOGDG09 - Duration: 14 days - %: 100
- Diethylbenzene - CAS: 25340-17-4
Biodegradability: Non-readily biodegradable - Test: BIOGDG06 - Duration: 28gg - %: 4.7
- Mesitilene - CAS: 108-67-8
Biodegradability: Non-readily biodegradable - Duration: 28gg - %: 42
- cumene - CAS: 98-82-8
Biodegradability: Readily biodegradable - Duration: 20dd - %: 70
- 12.3. Bioaccumulative potential
- Hydrocarbons, C10, Aromatics, >1% Naphthalene
Test: log Pow 2.8-6.5

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



- Test: BCF - Bioconcentration factor 99-5780
potassium 1,2-bis(2-ethylhexyloxycarbonyl)ethanesulphonate
Test: Kow - Partition coefficient 1.98
naphthalene - CAS: 91-20-3
Test: log Pow 3.4
Test: BCF - Bioconcentration factor 36.5-168
1,2,4-trimethylbenzene - CAS: 95-63-6
Test: log Pow 3.63
Test: BCF - Bioconcentration factor 243
2-Ethylhexan-1-ol - CAS: 104-76-7
Test: BCF - Bioconcentration factor 25.33
Test: log Pow 2.9
Diethylbenzene - CAS: 25340-17-4
Test: BCF - Bioconcentration factor 320-629
Mesitilene - CAS: 108-67-8
Test: log Pow 3.42
Test: BCF - Bioconcentration factor 161
cumene - CAS: 98-82-8
Test: log Pow 3.55
Test: BCF - Bioconcentration factor 35.48
- 12.4. Mobility in soil
N.A.
- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties
No endocrine disruptor substances present in concentration $\geq 0.1\%$
- 12.7. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information



- 14.1. UN number or ID number
ADR-UN Number: 1950
IATA-UN Number: 1950
IMDG-UN Number: 1950
- 14.2. UN proper shipping name
ADR-Shipping Name: AEROSOLS, flammable
IATA-Shipping Name: AEROSOLS, flammable
IMDG-Shipping Name: AEROSOLS, flammable
- 14.3. Transport hazard class(es)
ADR-Class: 2
ADR - Hazard identification number: -
IATA-Class: 2
IATA-Label: 2.1
IMDG-Class: 2

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



Sea (IMO):	2
14.4. Packing group	
ADR-Packing Group:	-
IATA-Packing group:	-
IMDG-Packing group:	-
14.5. Environmental hazards	
ADR-Environmental Pollutant:	No
IMDG-Marine pollutant:	No
IMDG-EmS:	F-D, S-U
14.6. Special precautions for user	
Rail (RID):	2
ADR-Subsidiary hazards:	See SP63
ADR-S.P.:	190 327 344 625
ADR-Transport category (Tunnel restriction code):	2 (D)
IATA-Passenger Aircraft:	203
IATA-Subsidiary hazards:	See SP63
IATA-Cargo Aircraft:	203
IATA-S.P.:	A145 A167 A802
IATA-ERG:	10L
IMDG-Subsidiary hazards:	See SP63
IMDG-Stowage and handling:	SW1 SW22
IMDG-Segregation:	SG69
14.7. Maritime transport in bulk according to IMO instruments	
N.A.	
Limited Quantity:	1 L
Exempted Quantity:	E0

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Dir. 98/24/EC (Risks related to chemical agents at work)
 - Dir. 2000/39/EC (Occupational exposure limit values)
 - Regulation (EC) n. 1907/2006 (REACH)
 - Regulation (EC) n. 1272/2008 (CLP)
 - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
 - Regulation (EU) n. 2020/878
 - Regulation (EU) n. 286/2011 (ATP 2 CLP)
 - Regulation (EU) n. 618/2012 (ATP 3 CLP)
 - Regulation (EU) n. 487/2013 (ATP 4 CLP)
 - Regulation (EU) n. 944/2013 (ATP 5 CLP)
 - Regulation (EU) n. 605/2014 (ATP 6 CLP)
 - Regulation (EU) n. 2015/1221 (ATP 7 CLP)
 - Regulation (EU) n. 2016/918 (ATP 8 CLP)
 - Regulation (EU) n. 2016/1179 (ATP 9 CLP)
 - Regulation (EU) n. 2017/776 (ATP 10 CLP)
 - Regulation (EU) n. 2018/669 (ATP 11 CLP)
 - Regulation (EU) n. 2018/1480 (ATP 13 CLP)
 - Regulation (EU) n. 2019/521 (ATP 12 CLP)
 - Regulation (EU) n. 2020/217 (ATP 14 CLP)
 - Regulation (EU) n. 2020/1182 (ATP 15 CLP)
 - Regulation (EU) n. 2021/643 (ATP 16 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
- Restrictions related to the product:
 - Restriction 3
 - Restriction 40

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



Restrictions related to the substances contained:
Restriction 75

Volatile Organic compounds - VOCs = 86.32 %
Volatile Organic compounds - VOCs = 863.16 g/Kg
Volatile Organic compounds - VOCs = 572.28 g/l

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)
Regulation (EC) nr 648/2004 (detergents).
Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):
Seveso III category according to Annex 1, part 1
Product belongs to category: P3a

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:
None

SECTION 16: Other information

Text of phrases referred to under heading 3:

H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H281 Contains refrigerated gas; may cause cryogenic burns or injury.
H412 Harmful to aquatic life with long lasting effects.
H226 Flammable liquid and vapour.
H372 Causes damage to organs through prolonged or repeated exposure.
H351 Suspected of causing cancer.
H302 Harmful if swallowed.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H228 Flammable solid.
H332 Harmful if inhaled.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Hazard class and hazard category	Code	Description
Flam. Gas 1A	2.2/1A	Flammable gas, Category 1A
Aerosols 1	2.3/1	Aerosol, Category 1
Press Gas (Liq.)	2.5/L	Gases under pressure (Liquefied gas)
Press Gas (Ref. Liq.)	2.5/RL	Gases under pressure (Refrigerated liquefied gas)
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3

Safety Data Sheet
PULITORE IMPIANTO GPL SPRAY 120 ML



Flam. Sol. 2	2.7/2	Flammable solid, Category 2
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 1	3.9/1	Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2	3.9/2	Specific target organ toxicity - repeated exposure, Category 2
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data
Eye Dam. 1, H318	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.
 Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

Safety Data Sheet

PULITORE IMPIANTO GPL SPRAY 120 ML



It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.

Exposure Scenario, 17/07/2019

Substance identity	
Chemical name	IDROCARBURI C3-C4, Miscela (propano, butano, isobutano < 0,1% 1,3-Butadiene)
CAS No.	68476-40-4
EINECS No.	270-681-9

Table of contents

1. **ES 1** Use at industrial site

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Use as a propellant
Date - Version	17/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC4
----------------	------

Worker Contributing Scenario

CS2 Propellant	PROC1 - PROC2 - PROC3 - PROC8b - PROC9 - PROC12
----------------	---

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC4)

Environmental release categories	Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)
----------------------------------	--

1.2. CS2: Worker Contributing Scenario: Propellant (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Transfer of substance or mixture into small containers (dedicated filling line, including weighing) - Use of blowing agents in manufacture of foam (PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12)
--------------------	--

Product (article) characteristics

Physical form of product:

Liquid

Vapour pressure:

> 10 kPa

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

Technical and organisational conditions and measures

Technical and organisational measures

- Keep drains in watertight containers while awaiting dismantling or subsequent recycling
- Use in contained systems
- Ensure operatives are trained to minimise exposures.
- Ensure that direct skin contact is avoided.
- Clear transfer lines prior to de-coupling.
- Provide a good standard of controlled ventilation (10 to 15 air changes per hour).
- Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection

Wear suitable respiratory protection.

Other conditions affecting worker exposure

Temperature: Assumes use at not more than 20 °C above ambient temperature.

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES**Guidance to check compliance with the exposure scenario:**

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Exposure Scenario, 18/07/2019

Substance identity	
Chemical name	Idrocarburi , C11- C14 , n-alcani , isoalcani, ciclici,< 2% aromatici.
CAS No.	64742-47-8
EINECS No.	926-141-6

Table of contents

1. **ES 1** Use at industrial site
2. **ES 2** Widespread use by professional workers
3. **ES 3** Consumer use; Fuels (PC13)

1. ES 1 Use at industrial site

1.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Use at industrial site
Main user group	Industrial uses
Sector(s) of use	Industrial uses (SU3)

Environment Contributing Scenario

CS1 Covered by	ERC7
----------------	------

Worker Contributing Scenario

CS2 Industrial	PROC1 - PROC2 - PROC3 - PROC8a - PROC8b - PROC16
----------------	--

1.2 Conditions of use affecting exposure

1.2. CS1: Environment Contributing Scenario: Covered by (ERC7)

Environmental release categories	Use of functional fluid at industrial site (ERC7)
----------------------------------	---

1.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)

Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Use of fuels (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)
--------------------	---

Product (article) characteristics

Physical form of product:

Liquid

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

1.3 Exposure estimation and reference to its source

N/A

1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

2. ES 2 Widespread use by professional workers

2.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses

Environment Contributing Scenario

CS1 Solids based process ERC9a - ERC9b

Worker Contributing Scenario

CS2 General use from professional operators PROC1 - PROC2 - PROC3 - PROC8a - PROC8b - PROC16

2.2 Conditions of use affecting exposure

2.2. CS1: Environment Contributing Scenario: Solids based process (ERC9a, ERC9b)

Environmental release categories Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)

2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)

Process Categories Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Use of fuels (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

2.3 Exposure estimation and reference to its source

N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Consumer use; Fuels (PC13)

3.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Fuels (PC13)

Environment Contributing Scenario

CS1 Covered by	ERC9a - ERC9b
----------------	---------------

Consumer Contributing Scenario

CS2 Consumer	PC13
--------------	------

3.2 Conditions of use affecting exposure

3.2. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)

Environmental release categories	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)
----------------------------------	---

3.2. CS2: Consumer Contributing Scenario: Consumer (PC13)

Product Categories	Fuels (PC13)
--------------------	--------------

3.3 Exposure estimation and reference to its source

N/A

3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.