

Safety Data Sheet
PULITORE INIETTORI BENZINA PROFESSIONAL
ML 350



Safety Data Sheet dated 7/7/2019, version 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PULITORE INIETTORI BENZINA PROFESSIONAL ML 350
Trade code: 9843

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Fuel additive

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.
via Antica di Cassano, 23, 20063
Cernusco sul Naviglio (MI), Italy
Arexons S.p.A.
Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Centro Antiveleni di Pavia IRCCS- Fondazione Maugeri tel. +39 (0)382 24444 (h24; it, en)

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: Beaumont Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 - 22:00)

In South Africa: Poison Information Helpline 0861 555 777

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

⚠ Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P331 Do NOT induce vomiting.

Safety Data Sheet

PULITORE INIETTORI BENZINA PROFESSIONAL ML 350



P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

PACK1 The packing must be featured by a safety lock for children.

PACK2 The packing must have tactile indications of danger for blind people.

Contains

Distillates (petroleum), hydrotreated light

Hydrocarbons, C10, aromatics, <1% naphthalene

Hydrocarbons, C10, aromatics, >1% naphthalene.

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 70% - < 80% Distillates (petroleum), hydrotreated light

REACH No.: 01-2119456620-43, Index number: 649-422-00-2, CAS: 64742-47-8, EC: 926-141-6

⚠ 3.10/1 Asp. Tox. 1 H304

EUH066

>= 12.5% - < 15% Hydrocarbons, C10, aromatics, <1% naphthalene

REACH No.: 01-2119463583-34, Index number: 649-424-00-3, EC: 918-811-1

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.8/3 STOT SE 3 H336

⚠ 4.1/C2 Aquatic Chronic 2 H411

EUH066

DECLP (CLP)*

>= 3% - < 5% 1-propene, 2-methyl-, homopolymer, hydroformylation products, reaction products with ammonia

CAS: 337367-30-3

⚠ 3.2/2 Skin Irrit. 2 H315

4.1/C3 Aquatic Chronic 3 H412

>= 1% - < 2% Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

REACH No.: 01-2119475608-26, EC: 929-018-5

⚠ 3.10/1 Asp. Tox. 1 H304

EUH066

>= 1% - < 2% Hydrocarbons, C10, aromatics, >1% naphthalene.

REACH No.: 01-2119463588-24, EC: 919-284-0

⚠ 4.1/C2 Aquatic Chronic 2 H411

⚠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.8/3 STOT SE 3 H336

EUH066

Safety Data Sheet

PULITORE INIETTORI BENZINA PROFESSIONAL ML 350



>= 1% - < 2% Naphtha (petroleum), hydrotreated heavy
REACH No.: 01-2119457273-39, Index number: 649-327-00-6, CAS: 64742-48-9, EC:
265-150-3
⚠ 3.10/1 Asp. Tox. 1 H304
EUH066
DECLP (CLP)*

>= 0.1% - < 0.25% naphthalene
Index number: 601-052-00-2, CAS: 91-20-3, EC: 202-049-5
⚠ 3.6/2 Carc. 2 H351
⚠ 3.1/4/Oral Acute Tox. 4 H302
⚠ 4.1/A1 Aquatic Acute 1 H400 M=1.
⚠ 4.1/C1 Aquatic Chronic 1 H410 M=1.

*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.
Wash with plenty of water and soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Appropriate Extinguishing Media:

To carbon dioxide.

To dust.

Foam

Water spray.

Not Recommended Extinguishing Media:

Do not use direct water jets.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Safety Data Sheet

PULITORE INIETTORI BENZINA PROFESSIONAL ML 350



Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment.
 - Remove persons to safety.
 - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
 - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
 - Retain contaminated washing water and dispose it.
 - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
 - Avoid contact with skin and eyes, inhalation of vapours and mists.
 - Don't use empty container before they have been cleaned.
 - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
 - See also section 8 for recommended protective equipment.
 - Advice on general occupational hygiene:
 - Contaminated clothing should be changed before entering eating areas.
 - Do not eat or drink while working.
- 7.2. Conditions for safe storage, including any incompatibilities
 - Keep away from food, drink and feed.
 - None in particular.
 - Instructions as regards storage premises:
 - Adequately ventilated premises.
- 7.3. Specific end use(s)
 - None in particular

SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters
 - Hydrocarbons, C10, aromatics, <1% naphthalene - Index number: 649-424-00-3
 - EU - TWA: 100 mg/m³, 17 ppm
 - naphthalene - CAS: 91-20-3
 - 20101.13 - TWA: 50 mg/m³, 10 ppm
 - EU - TWA(8h): 50 mg/m³, 10 ppm
 - ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia
- DNEL Exposure Limit Values
 - Hydrocarbons, C10, aromatics, <1% naphthalene - Index number: 649-424-00-3
 - Consumer: 7.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects
 - Worker Professional: 151 mg/m³ - Consumer: 32 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
 - Worker Professional: 12.5 mg/kg - Consumer: 7.5 mg/kg - Exposure: Human Inhalation
- PNEC Exposure Limit Values
 - N.A.



Safety Data Sheet

PULITORE INIETTORI BENZINA PROFESSIONAL ML 350

8.2. Exposure controls

Eye protection:

Safety goggles.
Compliant with EN 166

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Nitrile or Viton gloves.
Compliant with EN 374.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Liquid	--	--
Odour:	N.A.	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	>65°C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	0.825 g/ml	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-	N.A.	--	--

Safety Data Sheet
PULITORE INIETTORI BENZINA PROFESSIONAL
ML 350



octanol/water):			
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	1.9 mm ² /s @40°C	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

NA=not applicable

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
None
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects
Toxicological information of the product:
PULITORE INIETTORI BENZINA PROFESSIONAL ML 350
a) acute toxicity

Based on available data, the classification criteria are not met
b) skin corrosion/irritation

Based on available data, the classification criteria are not met
c) serious eye damage/irritation

Based on available data, the classification criteria are not met

Safety Data Sheet
PULITORE INIETTORI BENZINA PROFESSIONAL
ML 350



d) respiratory or skin sensitisation

Based on available data, the classification criteria are not met
e) germ cell mutagenicity

Based on available data, the classification criteria are not met
f) carcinogenicity

Based on available data, the classification criteria are not met
g) reproductive toxicity

Based on available data, the classification criteria are not met
h) STOT-single exposure

Based on available data, the classification criteria are not met
i) STOT-repeated exposure

Based on available data, the classification criteria are not met
j) aspiration hazard

The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

Distillates (petroleum), hydrotreated light - CAS: 64742-47-8

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m³ - Duration: 8h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

b) skin corrosion/irritation:

Test: OECD TG 404 - Route: Skin Negative

c) serious eye damage/irritation:

Test: OECD TG 405 - Route: EYE Negative

d) respiratory or skin sensitisation:

Test: Inhalation Sensitization 3

Test: Skin Sensitization 3

j) aspiration hazard:

Test: May be fatal if swallowed and enters airways (physical-chemical properties) - Route:

Oral Positive

Hydrocarbons, C10-C13, n-alkanes, <2% aromatics

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5 mg/l - Duration: 8h

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

g) reproductive toxicity:

Test: NOAEL - Route: Oral - Species: Rat = 1000 mg/kg

naphthalene - CAS: 91-20-3

e) germ cell mutagenicity:

Test: Mutagenesis - Species: vitro Positive

f) carcinogenicity:

Test: Carcinogeneticity - Route: Inhalation - Species: Rat Positive - Notes: IARC 2B

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Distillates (petroleum), hydrotreated light - CAS: 64742-47-8

a) Aquatic acute toxicity:

Endpoint: EL0 - Species: Daphnia 1000 mg/l - Duration h: 48

Endpoint: EL0 - Species: Algae 1000 mg/l - Duration h: 72

Safety Data Sheet

PULITORE INIETTORI BENZINA PROFESSIONAL ML 350



- Endpoint: CE7 - Species: Fish 1000 mg/l - Duration h: 96
Hydrocarbons, C10-C13, n-alkanes, <2% aromatics
- a) Aquatic acute toxicity:
Endpoint: LL50 - Species: Fish > 10-100 mg/l - Duration h: 96
Endpoint: EL50 - Species: Daphnia > 100 mg/l - Duration h: 48
Endpoint: EL50 - Species: Algae > 100 mg/l - Duration h: 72
Endpoint: NOELR - Species: Algae > 100 mg/l - Duration h: 72
- 12.2. Persistence and degradability
None
Hydrocarbons, C10-C13, n-alkanes, <2% aromatics
Biodegradability: Readily biodegradable - Duration: 28gg - %: 61
- 12.3. Bioaccumulative potential
Hydrocarbons, C10-C13, n-alkanes, <2% aromatics
Bioaccumulation: Not bioaccumulative
- 12.4. Mobility in soil
N.A.
- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.
- Additional disposal information:
CER 14 06 03 other solvents and solvent mixtures.
Contaminated packaging must be emptied as far as possible. After cleaning, send to an authorised centre for recycling or disposal.
Reuse if possible. Act in accordance with the local and national laws in force.

SECTION 14: Transport information

- 14.1. UN number
Not classified as dangerous in the meaning of transport regulations.
- 14.2. UN proper shipping name
N.A.
- 14.3. Transport hazard class(es)
N.A.
- 14.4. Packing group
N.A.
- 14.5. Environmental hazards
ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
- 14.6. Special precautions for user
N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code
No

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)

Safety Data Sheet

PULITORE INIETTORI BENZINA PROFESSIONAL ML 350



Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)
Regulation (EU) n. 2016/918 (ATP 8 CLP)
Regulation (EU) n. 2016/1179 (ATP 9 CLP)
Regulation (EU) n. 2017/776 (ATP 10 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

No restriction.

Pronto all'Uso

Volatile Organic compounds - VOCs = 93.42 %

Volatile Organic compounds - VOCs = 934.17 g/Kg

Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

None

SECTION 16: Other information

Text of phrases referred to under heading 3:

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting effects.

H351 Suspected of causing cancer.

H302 Harmful if swallowed.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4

Safety Data Sheet
PULITORE INIETTORI BENZINA PROFESSIONAL
ML 350



Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 5: Firefighting measures
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

- ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
- SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
- ATE: Acute Toxicity Estimate
- ATEmix: Acute toxicity Estimate (Mixtures)
- CAS: Chemical Abstracts Service (division of the American Chemical

Safety Data Sheet

PULITORE INIETTORI BENZINA PROFESSIONAL ML 350



	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.