

Safety Data Sheet dated 27/10/2021, version 8

1.1. Product identifier	substance/mixture and of the company/undertaking
Mixture identification:	
Trade name:	DISPERDENTE D'ACQUA - USO PROFESSIONALE - DA SERBATOIO ML 325 ML
Trade code:	9845
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Recommended use:	
Fuel additive	
1.3. Details of the supplier of the	e safety data sheet
Supplier:	
Arexons S.p.A.	
via Antica di Cassano, 23	3, 20063
Cernusco sul Naviglio (M	II), Italy
Arexons S.p.A.	
Tel. +39 (0)2/924361 - Fa	ax +39 (0)2/92436306
Competent person responsible	for the safety data sheet:
arexons@arexons.it	
1.4. Emergency telephone num	ber
Arexons S.p.A.	
Tel. +39 (0)2/924361 - Fa	ax +39 (0)2/92436306
In England and Wales: N	HS 111 - dial 111
In Scotland: NHS 24 - dia	al 111
In Ireland: Beaumont Hos 22:00)	spital - National Poisons Information Centre 01 809 2166 (7days, 8:0
,	aformation Holpling 0861 555 777
In Malta: emergency num	nformation Helpline 0861 555 777

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture
EC regulation criteria 1272/2008 (CLP):
Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways. EUH066 Repeated exposure may cause skin dryness or cracking.
Adverse physicochemical, human health and environmental effects: No other hazards
2.2. Label elements
Hazard pictograms:



Danger Hazard statements: H304 May be fatal if swallowed and enters airways. Precautionary statements: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.

9845/8 Page n. 1 of 11



P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations. Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

PACK1 The packing must be featured by a safety lock for children.

PACK2 The packing must have tactive indications of danger for blind people.

Contains

Distillates (petroleum), hydrotreated light

Special provisions according to Annex XVII of REACH and subsequent amendments: Restricted to professional users.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1% Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification: >= 80% - < 90% Distillates (petroleum), hydrotreated light

>= 1% - < 2% Distillati (petrolio), paraffinici pesanti "hydrotreating" CAS: 64742-54-7, EC: 265-157-1 Substance with a Union workplace exposure limit.

>= 1% - < 2% Distillati (petrolio), frazione paraffinica pesante decerata con solvente REACH No.: 01-2119471299-27, CAS: 64742-65-0, EC: 265-169-7 Substance with a Union workplace exposure limit.

>= 0.1% - < 0.25% Mineral oil - mixture -

3.10/1 Asp. Tox. 1 H304

SVHC, PBT, vPvB, endocrine disruptor substances: >= 0.005% - < 0.01% ethylenediamine; 1,2-diaminoethane Index number: 612-006-00-6, CAS: 107-15-3, EC: 203-468-6

9845/8 Page n. 2 of 11



SVHC

SECTION 4: First aid measures

- 4.1. Description of first aid measures
- In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash with plenty of water and soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed None
- 4.3. Indication of any immediate medical attention and special treatment needed
 - In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:
 - None

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Appropriate Extinguishing Media: To carbon dioxide. To dust. Foam Water spray. Not Recommended Extinguishing Media: Do not use direct water jets.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters

Use suitable breathing apparatus . Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove persons to safety. See protective measures under point 7 and 8.
 6.2. Environmental precautions Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
 - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections

9845/8 Page n. 3 of 11



See also section 8 and 13

SECTION 7: Handling and storage 7.1. Precautions for safe handling

7.1. Precautions for sale handling
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in
the containers.
See also section 8 for recommended protective equipment.
Advice on general occupational hygiene:
Contamined clothing should be changed before entering eating areas.
Do not eat or drink while working.
7.2. Conditions for safe storage, including any incompatibilities
Store in well-closed containers, preferably in a cool place, away from sources of heat and direct
sunlight.
Avoid exposure to direct sunlight.
Only store in the original container.
Keep away from food, drink and feed.
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.
7.3. Specific end use(s)
None in particular
SECTION & Experime controls/personal protection
SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Distillates (petroleum), hydrotreated light
20101.12 - TWA: 1200 mg/m3, 165 ppm
Distillati (petrolio), paraffinici pesanti "hydrotreating" - CAS: 64742-54-7
EU - TWA(8h): 5 mg/m3
Distillati (petrolio), frazione paraffinica pesante decerata con solvente - CAS: 64742-65-0
EU - TWA(8h): 5 mg/m3 - STEL(): 10 mg/m3
Mineral oil - mixture -
EU - TWA(8h): 5 mg/m3 - STEL(): 10 mg/m3
EU - STEL(): 3 mg/m3 - Notes: Lituania, Svezia
ethylenediamine; 1,2-diaminoethane - CAS: 107-15-3
ACGIH - TWA(8h): 10 ppm - Notes: Skin, A4
EU - TWA(8h): 10 ppm
DNEL Exposure Limit Values
N.A.
PNEC Exposure Limit Values
N.A.
8.2. Exposure controls
Eye protection:
Safety goggles.
Compliant with EN 166
Protection for skin:
Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton
Protection for hands:
Nitrile or Viton gloves.
Compliant with EN 374.
Respiratory protection:
Not needed for normal use.
Thermal Hazards:
None
9845/8
Page n. 4 of 11



Environmental exposure controls: None Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties			
Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	Yellow		
Odour:	Characteristic		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	N.A.		
Flammability:	N.A.		
Lower and upper explosion limit:	N.A.		
Flash point:	> 70°C		
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	N.A.		
Kinematic viscosity:	<= 14 mm2/ sec (40 °C)		
Solubility in water:	N.A.		
Solubility in oil:	N.A.		
Partition coefficient n- octanol/water (log value):	N.A.		
Vapour pressure:	N.A.		
Density and/or relative density:	N.A.		
Relative vapour density:	N.A.		
	Particle cha	racteristics:	
Particle size:	N.A.		

9.2. Other information

9845/8 Page n. 5 of 11



No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

- 10.2. Chemical stability
 - Stable under normal conditions
- 10.3. Possibility of hazardous reactions None
- 10.4. Conditions to avoid Stable under normal conditions.
- 10.5. Incompatible materials None in particular.
- 10.6. Hazardous decomposition products None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the product: DISPERDENTE D'ACQUA - USO PROFESSIONALE - DA SERBATOIO ML 325 ML a) acute toxicity Not classified Based on available data, the classification criteria are not met b) skin corrosion/irritation Not classified Based on available data, the classification criteria are not met c) serious eye damage/irritation Not classified Based on available data, the classification criteria are not met d) respiratory or skin sensitisation Not classified Based on available data, the classification criteria are not met e) germ cell mutagenicity Not classified Based on available data, the classification criteria are not met f) carcinogenicity Not classified Based on available data, the classification criteria are not met g) reproductive toxicity Not classified Based on available data, the classification criteria are not met h) STOT-single exposure Not classified Based on available data, the classification criteria are not met i) STOT-repeated exposure Not classified Based on available data, the classification criteria are not met j) aspiration hazard The product is classified: Asp. Tox. 1 H304 Toxicological information of the main substances found in the product: Distillates (petroleum), hydrotreated light a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m3 - Duration: 8h Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

9845/8 Page n. 6 of 11

Safety Data Sheet DISPERDENTE D'ACQUA - USO PROFESSIONALE - DA SERBATOIO ML 325 ML Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg



Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg b) skin corrosion/irritation: Test: OECD TG 404 - Route: Skin Negative c) serious eye damage/irritation: Test: OECD TG 405 - Route: EYE Negative d) respiratory or skin sensitisation: Test: Inhalation Sesitization 3 Test: Skin Sensitization 3 j) aspiration hazard: Test: May be fatal if swallowed and enters airways (physical-chemical properties) - Route: **Oral Positive** Distillati (petrolio), paraffinici pesanti "hydrotreating" - CAS: 64742-54-7 a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat > 5.53 mg/l - Duration: 4h Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg b) skin corrosion/irritation: Test: Skin Irritant - Species: Rabbit Negative c) serious eye damage/irritation: Test: Eye Irritant - Species: Rabbit Negative d) respiratory or skin sensitisation: Test: Skin Sensitization - Species: IND Negative e) germ cell mutagenicity: Test: oecd - Species: vitro Negative g) reproductive toxicity: Test: OECD 421 - Route: Oral - Species: Rat Negative Distillati (petrolio), frazione paraffinica pesante decerata con solvente - CAS: 64742-65-0 a) acute toxicity: Test: LC50 - Route: Inhalation - Species: Rat > 5.53 mg/l - Duration: 4h Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg b) skin corrosion/irritation: Test: Skin Irritant - Species: Rabbit Negative Test: Skin Irritant - Species: Rabbit Negative d) respiratory or skin sensitisation: Test: Skin Sensitization - Species: IND Negative e) germ cell mutagenicity: Test: oecd - Species: vitro Negative g) reproductive toxicity: Test: OECD 421 - Route: Oral - Species: Rat Negative Mineral oil - mixture a) acute toxicity: Test: LC50 - Route: Inhalation Vapour - Species: Rat > 5000 mg/kg - Duration: 4h Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg ethylenediamine; 1,2-diaminoethane - CAS: 107-15-3 a) acute toxicity: Test: LD50 - Route: Skin - Species: Rabbit 657 mg/kg Test: LD50 - Route: Oral - Species: IND 470 mg/kg Test: LD50 - Route: Oral - Species: Rat 700-1460 mg/kg 11.2. Information on other hazards Endocrine disrupting properties: No endocrine disruptor substances present in concentration >= 0.1%



SECTION 12: Ecological information

NOI	12: Ecological information
12.1.	Toxicity
	Adopt good working practices, so that the product is not released into the environment.
	Distillates (petroleum), hydrotreated light
	a) Aquatic acute toxicity:
	Endpoint: EL0 - Species: Daphnia 1000 mg/l - Duration h: 48
	Endpoint: EL0 - Species: Algae 1000 mg/l - Duration h: 72
	Endpoint: CE7 - Species: Fish 1000 mg/l - Duration h: 96
	Distillati (petrolio), paraffinici pesanti "hydrotreating" - CAS: 64742-54-7
	a) Aquatic acute toxicity:
	Endpoint: EL50 - Species: Daphnia > 10000 mg/l - Duration h: 48
	Endpoint: LL50 - Species: Fish > 100 mg/l - Duration h: 96
	b) Aquatic chronic toxicity:
	Endpoint: NOEL - Species: Algae > 100 mg/l - Duration h: 72
	Endpoint: NOEL - Species: Daphnia 10 mg/l - Duration h: 504
	Endpoint: NOEL - Species: Fish 1000 mg/l - Duration h: 312
	Distillati (petrolio), frazione paraffinica pesante decerata con solvente - CAS: 64742-65-0
	a) Aquatic acute toxicity:
	Endpoint: EL50 - Species: Daphnia > 10000 mg/l - Duration h: 48
	Endpoint: LL50 - Species: Fish > 100 mg/l - Duration h: 96
	b) Aquatic chronic toxicity:
	Endpoint: NOEL - Species: Algae > 100 mg/l - Duration h: 72
	Endpoint: NOEL - Species: Daphnia 10 mg/l - Duration h: 504
	Endpoint: NOEL - Species: Fish 1000 mg/l - Duration h: 312
12.2	Persistence and degradability
	None
	Distillates (petroleum), hydrotreated light
	Biodegradability: Readily biodegradable - Duration: 28gg - %: 69
	Distillati (petrolio), paraffinici pesanti "hydrotreating" - CAS: 64742-54-7
	Biodegradability: Non-readily biodegradable - Test: BIOGDG10 - Duration: 28gg - %: 31
	Distillati (petrolio), frazione paraffinica pesante decerata con solvente - CAS: 64742-65-0
	Biodegradability: Non-readily biodegradable - Test: BIOGDG10 - Duration: 28gg - %: 31
12.3.	Bioaccumulative potential
	N.A.
12.4	Mobility in soil
	N.A.
12.5	Results of PBT and vPvB assessment
	vPvB Substances: None - PBT Substances: None
12 6	Endocrine disrupting properties
.2.0.	No endocrine disruptor substances present in concentration >= 0.1%
12 7	Other adverse effects
	None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Additional disposal information:

CER 14 06 03 other solvents and solvent mixtures.

Contaminated packaging must be emptied as far as possible. After cleaning, send to an authorised centre for recycling or disposal.

Reuse if possible. Act in accordance with the local and national laws in force.

SECTION 14: Transport information

9845/8 Page n. 8 of 11



14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

- 14.2. UN proper shipping name
 - N.A.
- 14.3. Transport hazard class(es) N.A.
- 14.4. Packing group N.A. 14.5. Environmental hazards ADR-Enviromental Pollutant: No No
 - IMDG-Marine pollutant:
- 14.6. Special precautions for user N.A.
- 14.7. Maritime transport in bulk according to IMO instruments N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 2020/878 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained: **Restriction 28**

Restriction 75

Pronto all'Uso Volatile Organic compounds - VOCs = 87.33 % Volatile Organic compounds - VOCs = 873.30 g/Kg Volatile CMR substances = 0.00 % Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

9845/8 Page n. 9 of 11



Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)
SVHC Substances:
Substances in candidate list (Art. 59 Reg. 1907/2006, REACH): ethylenediamine; 1,2-diaminoethane Respiratory Sensitisation
Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 None

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture. Substances for which a Chemical Safety Assessment has been carried out: None

SECTION 16: Other information

Text of phrases referred to under heading 3:

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Hazard class and hazard category	Code	Description
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Resp. Sens. 1B	3.4.1/1B	Respiratory Sensitisation, Category 1B
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1

This safety data sheet has been completely updated in compliance to Regulation 2020/878. Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Asp. Tox. 1, H304	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

9845/8 Page n. 10 of 11



Commission of the European Communities

SAX'S DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of
	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.

Exposure Scenario, 18/07/2019

Substance identity	
Chemical name	ldrocarburi , C11- C14 , n-alcani , isoalcani, ciclici,< 2% aromatici.
CAS No.	64742-47-8
EINECS No.	926-141-6

Table of contents

- 1. **ES 1** Use at industrial site
- 2. **ES 2** Widespread use by professional workers
- 3. ES 3 Consumer use; Fuels (PC13)

1. ES 1 Use at industrial site			
1.1 TITLE SECTION			
Exposure Scenario name	Fuel		
Date - Version	18/07/2019 - 1.0		
Life Cycle Stage	Use at industrial site		
Main user group	Industrial uses		
Sector(s) of use	Industrial uses (SU3)		
Environment Contributing Sce	enario		
CS1 Covered by		ERC7	
Worker Contributing Scenario	•		
CS2 Industrial		PROC1 - PROC2 - PROC3 - PROC8a - PROC8b - PROC16	
1.2 Conditions of use	affecting exposure		
1.2. CS1: Environment Contrib	outing Scenario: Covered by (ERC7)		
Environmental release categories	Use of functional fluid at industrial site (FRC7)		
1.2. CS2: Worker Contributing	Scenario: Industrial (PROC1, PROC2, PROC3, PRO	C8a, PROC8b, PROC16)	
Process Categories	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at non- dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Use of fuels (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)		
Product (article) character		, , ,	
Physical form of product: Liquid			
Concentration of substance in product: Covers percentage substance in the product up to 100 %.			
Amount used, frequency and duration of use/exposure			
Duration: Covers daily exposures up to 8 hours			
1.3 Exposure estimation and reference to its source			
N/A			
1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES			

Guidance to check compliance with the exposure scenario: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Widespread use by professional workers 2. ES 2

2 1 TITLE SECTION

2.1 IIILE SECTION				
Exposure Scenario name	Fuel			
Date - Version	18/07/2019 - 1.0			
Life Cycle Stage	Widespread use by professional workers	Widespread use by professional workers		
Main user group	Professional uses			
Environment Contributing S	cenario			
CS1 Solids based process		ERC9a - ERC9b		
Worker Contributing Scenario				
CS2 General use from professional operators PROC1 - PROC2 - PROC3 - PROC8a PROC8b - PROC16		PROC1 - PROC2 - PROC3 - PROC8a - PROC8b - PROC16		
2.2 Conditions of use affecting exposure				
2.2. CS1: Environment Contributing Scenario: Solids based process (ERC9a, ERC9b)				
Environmental release categories	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)			
2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)				
Process CategoriesChemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at non- dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated 				
Product (article) characte	ristics			

Product (article) characteristics

Concentration of substance in product:

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

Duration:

Covers daily exposures up to 8 hours

2.3 Exposure estimation and reference to its source

N/A

2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

3. ES 3 Consumer use; Fuels (PC13)			
3.1 TITLE SECTION			
Exposure Scenario name	Fuel		
Date - Version	18/07/2019 - 1.0		
Life Cycle Stage	Consumer use		
Main user group	Consumer uses		
Sector(s) of use	Consumer uses (SU21)		
Product Categories	Fuels (PC13)		
Environment Contributing Scenario			
CS1 Covered by	ERC9a - ERC9b		
Consumer Contributing Scena	rio		
CS2 Consumer	PC13		
3.2 Conditions of use	affecting exposure		
3.2. CS1: Environment Contrib	outing Scenario: Covered by (ERC9a, ERC9b)		
Environmental release categories	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)		
3.2. CS2: Consumer Contributing Scenario: Consumer (PC13)			
Product Categories	Fuels (PC13)		
3.3 Exposure estimation and reference to its source			
N/A			
3.4 Guidance to DU to evaluate whether he works inside the boundaries set by			

the ES

Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.