



**Safety Data Sheet dated 7/7/2019, version 4**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Mixture identification:

Trade name: DIESEL MIX 500 ML

Trade code: 9849

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Diesel additive

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.

via Antica di Cassano, 23, 20063

Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Centro Antiveleni di Pavia IRCCS- Fondazione Maugeri tel. +39 (0)382 24444 (h24; it, en)

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

In Ireland: Beaumont Hospital - National Poisons Information Centre 01 809 2166 (7days, 8:00 - 22:00)

In South Africa: Poison Information Helpline 0861 555 777

**SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

⚠ Warning, STOT SE 3, May cause drowsiness or dizziness.

⚠ Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

⚠ Aquatic Chronic 2, Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

## Safety Data Sheet

### DIESEL MIX 500 ML



P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.  
P331 Do NOT induce vomiting.  
P391 Collect spillage.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with applicable regulations.

#### Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.  
PACK1 The packing must be featured by a safety lock for children.  
PACK2 The packing must have tactile indications of danger for blind people.

#### Contains

Hydrocarbons, C10, aromatics, <1% naphthalene  
Hydrocarbons, C10, aromatics, >1% naphthalene  
Distillates (petroleum), hydrotreated light

Special provisions according to Annex XVII of REACH and subsequent amendments:  
None

#### 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

#### Other Hazards:

No other hazards

---

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 40% - < 50% Distillates (petroleum), hydrotreated light

REACH No.: 01-2119456620-43, Index number: 649-422-00-2, CAS: 64742-47-8, EC: 926-141-6

☠ 3.10/1 Asp. Tox. 1 H304

EUH066

>= 30% - < 40% Hydrocarbons, C10, aromatics, <1% naphthalene

REACH No.: 01-2119463583-34, Index number: 649-424-00-3, EC: 918-811-1

☠ 3.10/1 Asp. Tox. 1 H304

⚠ 3.8/3 STOT SE 3 H336

⚠ 4.1/C2 Aquatic Chronic 2 H411

EUH066

DECLP (CLP)\*

>= 10% - < 12.5% Hydrocarbons, C10, aromatics, >1% naphthalene

REACH No.: 01-2119463588-24, EC: 919-284-0

☠ 3.10/1 Asp. Tox. 1 H304

⚠ 4.1/C2 Aquatic Chronic 2 H411

⚠ 3.8/3 STOT SE 3 H336

⚠ 2.6/3 Flam. Liq. 3 H226

>= 0.5% - < 1% 1,2,4-trimethylbenzene

Index number: 601-043-00-3, CAS: 95-63-6, EC: 202-436-9

⚠ 2.6/3 Flam. Liq. 3 H226

⚠ 3.1/4/Inhal Acute Tox. 4 H332

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

## Safety Data Sheet

### DIESEL MIX 500 ML



⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.5% - < 1% naphthalene

Index number: 601-052-00-2, CAS: 91-20-3, EC: 202-049-5

- ⚠ 3.6/2 Carc. 2 H351
- ⚠ 3.1/4/Oral Acute Tox. 4 H302
- ⚠ 4.1/A1 Aquatic Acute 1 H400
- ⚠ 4.1/C1 Aquatic Chronic 1 H410
- ⚠ 2.7/2 Flam. Sol. 2 H228

>= 0.25% - < 0.5% Benzene , 1,3,5-trimethyl-

CAS: 108-67-8, EC: 203-604-4

- ⚠ 2.6/3 Flam. Liq. 3 H226
- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.3/2 Eye Irrit. 2 H319
- ⚠ 3.8/3 STOT SE 3 H335
- ⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.1% - < 0.25% 1,2,3-Trimetilbenzene

EC: 208-394-8

- ⚠ 2.6/3 Flam. Liq. 3 H226
- ⚠ 3.3/2 Eye Irrit. 2 H319
- ⚠ 3.2/2 Skin Irrit. 2 H315

>= 0.05% - < 0.1% 1,2,4-trimethylbenzene

Index number: 601-043-00-3, CAS: 95-63-6, EC: 202-436-9

- ⚠ 2.6/3 Flam. Liq. 3 H226
- ⚠ 3.1/4/Inhal Acute Tox. 4 H332
- ⚠ 3.2/2 Skin Irrit. 2 H315
- ⚠ 3.3/2 Eye Irrit. 2 H319
- ⚠ 3.8/3 STOT SE 3 H335
- ⚠ 4.1/C2 Aquatic Chronic 2 H411

>= 0.05% - < 0.1% naphthalene

Index number: 601-052-00-2, CAS: 91-20-3, EC: 202-049-5

- ⚠ 2.7/1 Flam. Sol. 1 H228
- ⚠ 3.1/4/Oral Acute Tox. 4 H302
- ⚠ 3.6/2 Carc. 2 H351
- ⚠ 4.1/A1 Aquatic Acute 1 H400
- ⚠ 4.1/C1 Aquatic Chronic 1 H410

>= 0.01% - < 0.02% Trimethylbenzene

CAS: 25551-13-7, EC: 247-099-9

- ⚠ 2.6/3 Flam. Liq. 3 H226
- ⚠ 3.1/4/Dermal Acute Tox. 4 H312
- ⚠ 3.1/4/Oral Acute Tox. 4 H302
- ⚠ 3.3/2 Eye Irrit. 2 H319

\*DECLP (CLP): Substance classified in accordance with Note P, Annex VI of EC Regulation (EC) 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.

---

#### SECTION 4: First aid measures

9849/4

Page n. 3 of 13

## Safety Data Sheet

### DIESEL MIX 500 ML



#### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

#### 4.2. Most important symptoms and effects, both acute and delayed

None

#### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Appropriate Extinguishing Media:

To carbon dioxide.

Foam

To dust.

Water spray.

Not Recommended Extinguishing Media:

Do not use direct water jets.

#### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

#### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

#### 6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

#### 6.4. Reference to other sections

See also section 8 and 13



## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in hermetically sealed containers, preferably in a cool place, away from sources of heat and direct sunlight.

Avoid exposure to direct sunlight.

Only store in the original container.

Keep away from food, drink and feed.

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

### 7.3. Specific end use(s)

None in particular

---

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

Hydrocarbons, C10, aromatics, <1% naphthalene - Index number: 649-424-00-3

EU - TWA: 100 mg/m<sup>3</sup>, 17 ppm

Hydrocarbons, C10, aromatics, >1% naphthalene

EU - TWA: 200 mg/m<sup>3</sup>

1,2,4-trimethylbenzene - CAS: 95-63-6

EU - TWA(8h): 100 mg/m<sup>3</sup>, 20 ppm

naphthalene - CAS: 91-20-3

ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia

EU - TWA(8h): 50 mg/m<sup>3</sup>, 10 ppm

Benzene, 1,3,5-trimethyl- - CAS: 108-67-8

EU - TWA(8h): 100 mg/m<sup>3</sup>, 20 ppm

1,2,3-Trimethylbenzene

EU - TWA: 100 mg/m<sup>3</sup>, 20 ppm

1,2,4-trimethylbenzene - CAS: 95-63-6

EU - TWA(8h): 100 mg/m<sup>3</sup>, 20 ppm

naphthalene - CAS: 91-20-3

EU - TWA(8h): 50 mg/m<sup>3</sup>, 10 ppm

ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia

Trimethylbenzene - CAS: 25551-13-7

EU - TWA(8h): 100 mg/m<sup>3</sup>, 20 ppm

ACGIH - TWA(8h): 25 ppm - Notes: CNS impair, asthma, hematologic eff

### DNEL Exposure Limit Values

Hydrocarbons, C10, aromatics, <1% naphthalene - Index number: 649-424-00-3

Consumer: 7.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

Worker Professional: 151 mg/m<sup>3</sup> - Consumer: 32 mg/m<sup>3</sup> - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Professional: 12.5 mg/kg - Consumer: 7.5 mg/kg - Exposure: Human Inhalation

### PNEC Exposure Limit Values

N.A.

### 8.2. Exposure controls

#### Eye protection:

Eye glasses with side protection.

Compliant with EN 166

## Safety Data Sheet

### DIESEL MIX 500 ML



**Protection for skin:**

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

**Protection for hands:**

Nitrile or Viton gloves.  
Compliant with EN 374.

**Respiratory protection:**

Use adequate protective respiratory equipment.

**Thermal Hazards:**

None

**Environmental exposure controls:**

None

**Appropriate engineering controls:**

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Liquid limpido	--	--
Odour:	Characteristic	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	N.A.	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	56	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	N.A.	--	--
Solubility in water:	N.A.	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition	N.A.	--	--

## Safety Data Sheet DIESEL MIX 500 ML



temperature:			
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

### 9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

NA=not applicable

---

## SECTION 10: Stability and reactivity

- 10.1. Reactivity  
Stable under normal conditions
- 10.2. Chemical stability  
Stable under normal conditions
- 10.3. Possibility of hazardous reactions  
None
- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
None in particular.
- 10.6. Hazardous decomposition products  
None.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicological information of the product:

DIESEL MIX 500 ML

a) acute toxicity

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

Based on available data, the classification criteria are not met

c) serious eye damage/irritation

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation

Based on available data, the classification criteria are not met

e) germ cell mutagenicity

Based on available data, the classification criteria are not met

## Safety Data Sheet

### DIESEL MIX 500 ML



f) carcinogenicity

Based on available data, the classification criteria are not met

g) reproductive toxicity

Based on available data, the classification criteria are not met

h) STOT-single exposure

The product is classified: STOT SE 3 H336

i) STOT-repeated exposure

Based on available data, the classification criteria are not met

j) aspiration hazard

The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

Distillates (petroleum), hydrotreated light - CAS: 64742-47-8

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m<sup>3</sup> - Duration: 8h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

b) skin corrosion/irritation:

Test: OECD TG 404 - Route: Skin Negative

c) serious eye damage/irritation:

Test: OECD TG 405 - Route: EYE Negative

d) respiratory or skin sensitisation:

Test: Inhalation Sensitization 3

Test: Skin Sensitization 3

j) aspiration hazard:

Test: May be fatal if swallowed and enters airways (physical-chemical properties) - Route:

Oral Positive

Hydrocarbons, C10, aromatics, >1% naphthalene

b) skin corrosion/irritation:

Test: Skin Sensitization Negative

i) STOT-repeated exposure:

Positive

j) aspiration hazard:

Test: Respiratory Tract Irritant Positive

1,2,4-trimethylbenzene - CAS: 95-63-6

h) STOT-single exposure:

Test: Respiratory Tract Irritant Positive

naphthalene - CAS: 91-20-3

e) germ cell mutagenicity:

Species: vitro Positive

Species: vivo Negative

f) carcinogenicity:

Species: Rat Positive

i) STOT-repeated exposure:

Test: oecd 16 Positive

Benzene, 1,3,5-trimethyl- - CAS: 108-67-8

h) STOT-single exposure:

Test: Respiratory Tract Irritant Positive

1,2,3-Trimethylbenzene

g) reproductive toxicity:

Test: Respiratory Tract Irritant Positive

1,2,4-trimethylbenzene - CAS: 95-63-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit 3160 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat 18000 mg/l - Duration: 4h





---

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.  
Distillates (petroleum), hydrotreated light - CAS: 64742-47-8

#### a) Aquatic acute toxicity:

Endpoint: EL0 - Species: Daphnia 1000 mg/l - Duration h: 48

Endpoint: EL0 - Species: Algae 1000 mg/l - Duration h: 72

Endpoint: CE7 - Species: Fish 1000 mg/l - Duration h: 96

Hydrocarbons, C10, aromatics, >1% naphthalene

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 2 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 3 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae 1.1 mg/l - Duration h: 96

1,2,4-trimethylbenzene - CAS: 95-63-6

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 7.72 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia 3.6 mg/l - Duration h: 48

naphthalene - CAS: 91-20-3

#### a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 3.4 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish 0.51 mg/l - Duration h: 96

Benzene, 1,3,5-trimethyl- - CAS: 108-67-8

#### a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 6 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae 25 mg/l - Duration h: 48

1,2,4-trimethylbenzene - CAS: 95-63-6

#### b) Aquatic chronic toxicity:

Endpoint: LC50 - Species: Daphnia 6.14 mg/l - Duration h: 48

### 12.2. Persistence and degradability

None

Hydrocarbons, C10, aromatics, >1% naphthalene

Biodegradability: 4 - Test: BIOGDG10 - Duration: 28gg - %: 58

### 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil

N.A.

### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

### 12.6. Other adverse effects

None

---

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

#### Additional disposal information:

Reuse if possible. Act in accordance with the local and national laws in force.

CER 14 06 03 other solvents and solvent mixtures.

Contaminated packaging must be emptied as far as possible. After cleaning, send to an authorised centre for recycling or disposal.

---

## **SECTION 14: Transport information**

## Safety Data Sheet DIESEL MIX 500 ML



- 14.1. UN number  
ADR-UN Number: 3082  
IATA-UN Number: 3082  
IMDG-UN Number: 3082
- 14.2. UN proper shipping name  
ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(naphthalene, Hydrocarbons, C10, aromatics, >1% naphthalene)  
IATA-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(naphthalene, Hydrocarbons, C10, aromatics, >1% naphthalene)  
IMDG-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.(naphthalene, Hydrocarbons, C10, aromatics, >1% naphthalene)
- 14.3. Transport hazard class(es)  
ADR-Class: 9  
ADR - Hazard identification number: 90  
IATA-Class: 9  
IATA-Label: 9  
IMDG-Class: 9
- 14.4. Packing group  
ADR-Packing Group: III  
IATA-Packing group: III  
IMDG-Packing group: III
- 14.5. Environmental hazards  
ADR-Environmental Pollutant: Yes  
IMDG-Marine pollutant: Marine Pollutant
- 14.6. Special precautions for user  
ADR-Subsidiary hazards: -  
ADR-S.P.: 274 335 375 601  
ADR-Transport category (Tunnel restriction code): 3 (-)  
IATA-Passenger Aircraft: 964  
IATA-Subsidiary hazards: -  
IATA-Cargo Aircraft: 964  
IATA-S.P.: A97 A158 A197  
IATA-ERG: 9L  
IMDG-EmS: F-A,  
S-F  
IMDG-Subsidiary hazards: -  
IMDG-Stowage and handling: Category A  
IMDG-Segregation: -
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
No  
Limited Quantity: 5 L  
Exempted Quantity: E1

### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)

## Safety Data Sheet

### DIESEL MIX 500 ML



Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) 2015/830  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
Regulation (EU) n. 2016/918 (ATP 8 CLP)  
Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
Regulation (EU) n. 2017/776 (ATP 10 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

No restriction.

Volatile Organic compounds - VOCs = 97.40 %

Volatile Organic compounds - VOCs = 973.96 g/Kg

Volatile Organic compounds - VOCs = 830.79 g/l

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: E2

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

Substances for which a Chemical Safety Assessment has been carried out:

None

---

## SECTION 16: Other information

Text of phrases referred to under heading 3:

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H302 Harmful if swallowed.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H228 Flammable solid.

H312 Harmful in contact with skin.

**Safety Data Sheet**  
**DIESEL MIX 500 ML**



<b>Hazard class and hazard category</b>	<b>Code</b>	<b>Description</b>
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Flam. Sol. 1	2.7/1	Flammable solid, Category 1
Flam. Sol. 2	2.7/2	Flammable solid, Category 2
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

Paragraphs modified from the previous revision:

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 7: Handling and storage
- SECTION 8: Exposure controls/personal protection
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information
- SECTION 15: Regulatory information
- SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
STOT SE 3, H336	Calculation method
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 2, H411	Calculation method

## Safety Data Sheet

### DIESEL MIX 500 ML



This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
NA:	Not applicable
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.