

#### Safety Data Sheet dated 2/10/2024, version 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: PULITORE INIETTORI BENZINA

Trade code: 9658

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Fuel additive

Uses advised against:

Strictly adhere to the recommended uses.

1.3. Details of the supplier of the safety data sheet

Supplier:

Arexons S.p.A.

via Antica di Cassano, 23, 20063 Cernusco sul Naviglio (MI), Italy

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306

Competent person responsible for the safety data sheet:

arexons@arexons.it

1.4. Emergency telephone number

Arexons S.p.A.

Tel. +39 (0)2/924361 - Fax +39 (0)2/92436306 In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111
In Ireland: emergency number 112

In South Africa: Poison Information Helpline 0861 555 777

In Malta: emergency number 112

#### **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways. Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:



Danger

Hazard statements:

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER.



P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

**Special Provisions:** 

EUH066 Repeated exposure may cause skin dryness or cracking.

PACK1 The packing must be featured by a safety lock for children.

PACK2 The packing must have tactive indications of danger for blind people.

Contains

Distillates (petroleum), hydrotreated light

Hydrocarbons ,C10, aromatics, > 1% naphthalene

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%

Other Hazards:

No other hazards

#### **SECTION 3: Composition/information on ingredients**

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

stta	Name	Ident. Numb	er	Classification
>= 80% - < 90%	Distillates (petroleum), hydrotreated light	EC: REACH No.:	926-141-6 01- 2119456620 -43	
>= 7% - < 10%	Hydrocarbons ,C10, aromatics, > 1% naphthalene	EC: REACH No.:	919-284-0 01- 2119463588 -24	<ul> <li>         \$3.10/1 Asp. Tox. 1 H304</li> <li>         \$3.8/3 STOT SE 3 H336</li> <li>         \$4.1/C2 Aquatic Chronic 2 H411</li> <li>EUH066</li> </ul>
>= 1% - < 2%	2-Ethylhexan-1-ol	CAS: EC: REACH No.:	104-76-7 203-234-3 01- 2119487289 -20	<ul> <li></li></ul>
>= 0,25% - < 0,5%	naphthalene	Index number: CAS: EC:	601-052-00-2 91-20-3 202-049-5	<ul> <li>◆ 2.7/2 Flam. Sol. 2 H228</li> <li>◆ 3.6/2 Carc. 2 H351</li> <li>◆ 3.1/4/Oral Acute Tox. 4 H302</li> <li>◆ 4.1/A1 Aquatic Acute 1 H400</li> <li>M=1.</li> <li>◆ 4.1/C1 Aquatic Chronic 1 H410</li> <li>M=1.</li> </ul>

#### **SECTION 4: First aid measures**

4.1. Description of first aid measures In case of skin contact:

9658/10

Page n. 2 of 12



Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash with plenty of water and soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Appropriate Extinguishing Media:

To carbon dioxide.

To dust.

Foam

Water spray.

Not Recommended Extinguishing Media:

Do not use direct water jets.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Normal fire-fighting clothing, such as an open-circuit compressed air breathing apparatus (EN 137), flame-resistant suit (EN469), flame-resistant gloves (EN 659) and firefighter's boots (HO A29 or A30).

#### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

For cleaning up:

Avoid flame and/or spark near leak and produced waste. Do not smoke. In case of large spills

absorb and shovel up into suitable containers for disposal. Contain small spills with absorbent material

Put dirty material in suitable container. Dispose of dirty material in accordance with local or national

9658/10

Page n. 3 of 12



regulations.

6.4. Reference to other sections

See also section 8 and 13

#### **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

7.2. Conditions for safe storage, including any incompatibilities

Only store in the original container.

Keep away from food, drink and feed.

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

#### **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

2-Ethylhexan-1-ol - CAS: 104-76-7

EU - TWA(8h): 5.4 mg/m3, 1 ppm

naphthalene - CAS: 91-20-3

20101.13 - TWA: 50 mg/m3, 10 ppm

EU - TWA(8h): 50 mg/m3, 10 ppm

ACGIH - TWA(8h): 10 ppm - Notes: Skin, A3 - URT irr, cataracts, hemolytic anemia

**DNEL Exposure Limit Values** 

Hydrocarbons ,C10, aromatics, > 1% naphthalene

Worker Professional: 12.5 mg/kg - Consumer: 7.5 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Worker Professional: 151 mg/m3 - Consumer: 32 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Consumer: 7.5 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-Ethylhexan-1-ol - CAS: 104-76-7

Worker Professional: 53.2 mg/m3 - Consumer: 26.6 mg/m3 - Exposure: Human

Inhalation - Frequency: Short Term, local effects

Worker Professional: 23 mg/kg - Consumer: 11.4 mg/kg - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Worker Professional: 12.8 mg/m3 - Consumer: 2.3 mg/m3 - Exposure: Human Inhalation

- Frequency: Long Term, systemic effects

Worker Professional: 53.2 mg/m3 - Consumer: 26.6 mg/m3 - Exposure: Human

Inhalation - Frequency: Long Term, local effects

Consumer: 1.1 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects naphthalene - CAS: 91-20-3

Worker Professional: 25 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term,

Worker Professional: 3.57 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

**PNEC Exposure Limit Values** 

2-Ethylhexan-1-ol - CAS: 104-76-7

Target: Fresh Water - Value: 0.017 mg/l Target: Marine water - Value: 0.0017 mg/l

9658/10

Page n. 4 of 12



Target: Freshwater sediments - Value: 0.284 mg/kg Target: Marine water sediments - Value: 0.0284 mg/kg

Target: 09 - Value: 10 mg/l naphthalene - CAS: 91-20-3 Target: 09 - Value: 2.9 mg/l

Target: Marine water - Value: 2.4 03

Target: Marine water sediments - Value: 67.2 μg/kg Target: Freshwater sediments - Value: 2.4 03 Target: Freshwater sediments - Value: 67.2 μg/kg

8.2. Exposure controls

Eye protection:

Eye glasses with side protection.

Compliant with EN 166

Protection for skin:

protective clothing

Protection for hands:

Nitrile or Viton gloves. Compliant with EN 374.

Thickness: Cuff 0.10 mm; Palm 0.12 mm; Fingers 0.145 mm

Respiratory protection:

Use a suitable respiratory protection device.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

#### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	Light yellow		
Odour:	Characteristic		
Melting point/freezing point:	N.A.		
Boiling point or initial boiling point and boiling range:	N.A.		
Flammability:	N.A.		
Lower and upper explosion limit:	N.A.		
Flash point:	>65°C	IP 170	
Auto-ignition temperature:	N.A.		
Decomposition temperature:	N.A.		
pH:	N.A.		



Kinematic viscosity:	<= 14 mm2/ sec (40 °C)		
Solubility in water:	N.A.		
Solubility in oil:	N.A.		
Partition coefficient n-octanol/water (log value):	N.A.		
Vapour pressure:	N.A.		
Density and/or relative density:	0,833 g/ml	ASTM D 4052-96	
Relative vapour density:	N.A.		
Particle characteristics:			
Particle size:	N.A.		

9.2. Other information

No other relevant information

#### **SECTION 10: Stability and reactivity**

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

#### **SECTION 11: Toxicological information**

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the product:

BENZINA PULITORE INIETTORI

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

Not classified

Based on available data, the classification criteria are not met

c) serious eye damage/irritation

Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity



Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity

Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity

Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure

Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure

Not classified

Based on available data, the classification criteria are not met

i) aspiration hazard

The product is classified: Asp. Tox. 1 H304

Toxicological information of the main substances found in the product:

Distillates (petroleum), hydrotreated light

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m3 - Duration: 8h

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

b) skin corrosion/irritation:

Test: OECD TG 404 - Route: Skin Negative

c) serious eye damage/irritation:

Test: OECD TG 405 - Route: EYE Negative

d) respiratory or skin sensitisation:

Test: Inhalation Sesitization 3

Test: Skin Sensitization 3

i) aspiration hazard:

Test: May be fatal if swallowed and enters airways (physical-chemical properties) - Route:

**Oral Positive** 

Hydrocarbons .C10, aromatics, > 1% naphthalene

a) acute toxicity:

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

2-Ethylhexan-1-ol - CAS: 104-76-7

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat 2047 mg/kg bw Test: LD50 - Route: Skin - Species: Rabbit 1970 mg/kg Test: LC50 - Route: Inhalation - Species: Rat 0.89-5.3 mg/l

naphthalene - CAS: 91-20-3 e) germ cell mutagenicity:

Test: Mutagenesis - Species: vitro Positive

f) carcinogenicity:

Test: Carcinogeneticy - Route: Inhalation - Species: Rat Positive - Notes: IARC 2B

#### 11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

#### **SECTION 12: Ecological information**

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Distillates (petroleum), hydrotreated light

a) Aquatic acute toxicity:

Endpoint: EL0 - Species: Daphnia 1000 mg/l - Duration h: 48 Endpoint: EL0 - Species: Algae 1000 mg/l - Duration h: 72



Endpoint: CE7 - Species: Fish 1000 mg/l - Duration h: 96

2-Ethylhexan-1-ol - CAS: 104-76-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish 17.1 mg/l Endpoint: LC50 - Species: Fish 28.2 mg/l Endpoint: EC50 - Species: Daphnia 39 mg/l Endpoint: EC50 - Species: Algae 11.5 mg/l Endpoint: CE6 - Species: Algae 16.6 mg/l Endpoint: CE6 - Species: Algae 11.5 mg/l

12.2. Persistence and degradability

None

2-Ethylhexan-1-ol - CAS: 104-76-7

Biodegradability: Readily biodegradable

12.3. Bioaccumulative potential

2-Ethylhexan-1-ol - CAS: 104-76-7

Test: log Pow 2.9

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects

None

#### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

Additional disposal information:

"Use in accordance with good working practices, avoiding dispersal in the environment. Do not discharge into drains, ground water or water courses. Comply with current legislation on the protection of water and soil from pollution (Legislative Decree No. 152 of 3/4/2006). Dispose of used product and containers by handing them over to authorised companies, in accordance with the provisions of

Legislative Decree No. 152/2006 (Consolidated Environmental Act, which replaced the Ronchi Decree) as amended.

The used product is to be considered special waste to be classified in accordance with Directive No. 2008/98/EC on waste and related matters. Recover if possible. Send to authorised disposal plants or incineration under

controlled conditions (152/2006 art. 184).

Act in accordance with the local and national laws in force.

Contaminated packaging must be emptied as far as possible. After cleaning, send to an authorised centre for recycling or disposal."

#### **SECTION 14: Transport information**

#### 14.1. UN number or ID number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

9658/10

Page n. 8 of 12



14.4. Packing group

N.A.

14.5. Environmental hazards

ADR-Environmental Pollutant: No IMDG-Marine pollutant: No

14.6. Special precautions for user

N.A.

14.7. Maritime transport in bulk according to IMO instruments

N.A.

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2020/878

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2021/849 (ATP 17 CLP)

Regulation (EU) n. 2022/692 (ATP 18 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

Restriction 40

Restriction 75

Volatile Organic compounds - VOCs = 89.98 %

Volatile Organic compounds - VOCs = 899.85 g/Kg

Volatile Organic compounds - VOCs = 749.57 g/l

Where applicable, refer to the following regulatory provisions:

Directive 2012/18/EU (Seveso III)

Regulation (EC) nr 648/2004 (detergents).

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

None

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.



Substances for which a Chemical Safety Assessment has been carried out: Distillates (petroleum), hydrotreated light

#### **SECTION 16: Other information**

Text of phrases referred to under heading 3:

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H335 May cause respiratory irritation.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H228 Flammable solid.

H351 Suspected of causing cancer.

H302 Harmful if swallowed.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Hazard class and hazard category	Code	Description
Flam. Sol. 2	2.7/2	Flammable solid, Category 2
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Acute Tox. 4	3.1/4/Oral	Acute toxicity (oral), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

#### Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 2: Hazards identification

SECTION 3: Composition/information on ingredients

SECTION 4: First aid measures

SECTION 5: Firefighting measures

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection



SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity
SECTION 11: Toxicological information
SECTION 12: Ecological information
SECTION 13: Disposal considerations
SECTION 14: Transport information
SECTION 15: Regulatory information
SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Asp. Tox. 1, H304	Calculation method
Aquatic Chronic 3, H412	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NA: Not applicable

PNEC: Predicted No Effect Concentration.



RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average
WGK: German Water Hazard Class.

## Exposure Scenario, 18/07/2019

Substance identity	
Chemical name	Idrocarburi , C11- C14 , n-alcani , isoalcani, ciclici,< 2% aromatici.
CAS No.	64742-47-8
EINECS No.	926-141-6

### Table of contents

- 1. **ES 1** Use at industrial site
- 2. **ES 2** Widespread use by professional workers
- 3. **ES 3** Consumer use; Fuels (PC13)

1. ES 1 Use at industrial site		
1.1 TITLE SECTION		
Exposure Scenario name	Fuel	
Date - Version	18/07/2019 - 1.0	
Life Cycle Stage	Use at industrial site	
Main user group	Industrial uses	
Sector(s) of use	Industrial uses (SU3)	
Environment Contributing Scenario		
CS1 Covered by		ERC7
Worker Contributing Scenario		
CS2 Industrial		PROC1 - PROC2 - PROC3 - PROC8a - PROC8b - PROC16
1.2 Conditions of use affecting exposure		
1.2. CS1: Environment Contributing Scenario: Covered by (ERC7)		
Environmental release		

Environmental release	Use of functional fluid at industrial site (ERC7)
categories	

#### 1.2. CS2: Worker Contributing Scenario: Industrial (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)

Process Categories

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Use of fuels (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)

#### Product (article) characteristics

#### Physical form of product:

Liquid

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

#### **Duration:**

Covers daily exposures up to 8 hours

### 1.3 Exposure estimation and reference to its source

N/A

# 1.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### 2. ES 2 Widespread use by professional workers

#### 2.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Widespread use by professional workers
Main user group	Professional uses

#### **Environment Contributing Scenario**

CS1 Solids based process ERC9a - ERC9b

#### **Worker Contributing Scenario**

CS2 General use from professional operators

PROC1 - PROC2 - PROC3 - PROC8a -

PROC8b - PROC16

### 2.2 Conditions of use affecting exposure

#### 2.2. CS1: Environment Contributing Scenario: Solids based process (ERC9a, ERC9b)

<b>Environmental release</b>	Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor)
categories	(ERC9a, ERC9b)

## 2.2. CS2: Worker Contributing Scenario: General use from professional operators (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)

### **Process Categories**

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions - Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities - Transfer of substance or mixture (charging and discharging) at dedicated facilities - Use of fuels (PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16)

#### Product (article) characteristics

#### **Concentration of substance in product:**

Covers percentage substance in the product up to 100 %.

Amount used, frequency and duration of use/exposure

#### **Duration:**

Covers daily exposures up to 8 hours

#### 2.3 Exposure estimation and reference to its source

N/A

# 2.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

### 3. ES 3 Consumer use; Fuels (PC13)

#### 3.1 TITLE SECTION

Exposure Scenario name	Fuel
Date - Version	18/07/2019 - 1.0
Life Cycle Stage	Consumer use
Main user group	Consumer uses
Sector(s) of use	Consumer uses (SU21)
Product Categories	Fuels (PC13)

#### **Environment Contributing Scenario**

CS1 Covered by ERC9a - ERC9b

#### **Consumer Contributing Scenario**

CS2 Consumer PC13

### 3.2 Conditions of use affecting exposure

#### 3.2. CS1: Environment Contributing Scenario: Covered by (ERC9a, ERC9b)

**Environmental release** Widespread use of functional fluid (indoor) - Widespread use of functional fluid (outdoor) categories (ERC9a, ERC9b)

#### 3.2. CS2: Consumer Contributing Scenario: Consumer (PC13)

**Product Categories** Fuels (PC13)

### 3.3 Exposure estimation and reference to its source

N/A

# 3.4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

#### Guidance to check compliance with the exposure scenario:

Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.