



EXPERIENCE TO PERFORM

## TECHNICAL DATA SHEET

# GASKET SEALING

### - DESCRIPTION OF THE PRODUCT

Product with natural resin and alcohol solvent base.  
It forms a transparent film with excellent adhesive properties. It can be used to hold preformed gaskets in place before assembly.

### - FIELDS OF USE

As an adjuvant for any type of preformed gasket.  
Used to seal couplings for engines, machine tools, hydraulic couplings, fuel tanks.

### - TECHNICAL FEATURES

(before solvent evaporation)

- Appearance Viscous liquid
- Colour Yellow-Brown
- Odour Alcoholic
- Reticulation Solvent evaporation
- Density 0,970 g/ml
- Viscosity 500-700 cp

(after solvent evaporation)

- Seal type hard, dry to touch
- Thickness 1-2 mm
- Heat resistance max 110°C
- Low temperature resistance to -20°C
- Water resistance excellent
- Petrol resistance excellent
- Mineral oil resistance to 80°C
- Synthetic oil resistance to 80°C
- Synthetic grease resistance to 80°C

### - INSTRUCTIONS

Use on clean, degreased surfaces. Spread a thin, even layer with a brush. Proceed with assembly of the performed gasket. Close the surface after about 15 minutes.

Crosslinking may be accelerated by using heat.

### - STORAGE

In unopened package at ambient temperature and out of direct sunlight: at least 3 years

### - PACKAGE

Plastic bottle

Code 0017 Content 100 ml

Code 0019 Content 200 ml

### - NOTES

See the Safety Data Sheet for more information on product safety.

R&D 01/02/2008

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user.  
For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO  
Via Antica di Cassano, 23  
20063 Cernusco sul Naviglio (MI) Italy  
Capitale Sociale: € 15.000.000,00 I.V.  
Registro delle Imprese di Milano n. 09728360968  
Codice Fiscale e Partita IVA 09728360968  
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.  
Centralino 02 92436.1  
Fax 02 92436.306  
[www.arexons.com](http://www.arexons.com)

Sistemi di gestione di qualità della società Arexons S.p.A.  
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.  
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.



A wholly-owned subsidiary of PETRONAS