



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

X-POWER BATTERIES*Cars and vans***- PRODUCT DESCRIPTION**

Complete line of batteries produced with the **ISO 9001** certified quality system. Manufactured in accordance with the **ISO TS 16949** standards, which car producers demand of original equipment manufacturers (OEM).

Plates in special Pb/Ca alloy ensure lower self-discharge and virtually no water consumption. Thanks to this technology, the batteries develop a greater power surge on start-up. They also ensure a greater reserve of energy, particularly important for the new generation of cars with many electronic components.

Magic Eye: Indicator on the lid that allows the battery's charge level to be kept under control and, as a consequence, enables the status to be known in real time. The magic eye is provided on those batteries that must deliver the most challenging performances to support the high number of electronic components.

- WARNINGS

The batteries contain sulfuric acid at a concentration of 32 b  (corrosive product), beware of the liquid content.

The batteries have vent holes indispensable for proper operation; it is important that these vents are left clear and not blocked. Ensure the battery is not tipped over since acid could leak through the vent holes.

Dispose of in accordance with the current regulations.

- METHODS OF USE

They are ready to use and require no maintenance.

- TECHNICAL SPECIFICATIONS

code	Amperage (Ah)	Surge (A EN)	Box
X-POWER			
0881	35	280	53520
0882	35	280	53522
0883	45	400	L0
0884	45	400	L1
0885	50	450	L1
0886	55	550	L1
0887	60	600	L2
0888	74	680	L3
0889	80	750	L3
0890	92	800	L4
0891	100	850	L5
0892	100	760	GR28
0893	100	760	59518
0897	45	300	54523/84
0898	45	300	54524/51
0899	45	300	54577
0900	45	300	54579
X-POWER PLUS			
0894	50	420	L1B
0895	62	600	L2B
0896	73	630	L3B

NB: codes 0882, 0893, 0898, 08900 have positive terminals on the left.

TS 02.10.18

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

Sistemi di gestione di qualit  della societ  Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della societ  Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.



A wholly-owned subsidiary of **PETRONAS**