



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

100% ACRYLIC GLOSS

Acrylic gloss for all surfaces

- PRODUCT DESCRIPTION

100% Acrylic Gloss is a spray gloss based on high quality, fast drying acrylic resins suitable for outdoor and indoor use. Has high grip on most surfaces. Can be applied on any surface such as metal, wood, masonry, ceramics, glass, paper, cardboard, plastic (after treatment with an appropriate primer). Do not apply on polystyrene.

New formula with low VOC content. Contains new generation solvents derived from renewable sources, absolutely not hazardous for humans and the environment. Does not contain Xylene. New formulation with low solvent odour, does not contain ammonia.

The paint film dries to the touch in just 9 - 15 minutes. The product can be painted over, after complete drying, with any type of paint, has excellent coverage, high yield.

Dispenser button designed to limit drips and obtain spray cone uniformity.

Self-cleaning valve.

Contains micronized pigments for high coverage and homogeneous film.

Special additives make it resistant to scratches and impacts.

- USAGE INSTRUCTIONS

Thoroughly clean surfaces from dust, grease and rust. Make sure the surface is completely dry. Shake the can for at least one minute holding it upside down. Spray from a distance of 20 - 30 cm.

To avoid drips, apply two or more light and criss-cross coats. After use, turn the can upside down and spray until only gas comes out to clean the dispenser.

- TECHNICAL CHARACTERISTICS

Appearance	Aerosol
Propellant	Propane butane
Yield	1.5 - 2 m ²
Composition	Acrylic resins
Smell	Pleasant
Density at 20°C	0.75 - 0.80 g/ml
Drying times:	
dust dry	10 minutes
dry to touch	20 minutes
dry in depth	24 hrs.
Temperature resistance	100° - 120°C

The above data does not constitute specifications and is subject to normal manufacturing tolerances

- SHELF LIFE

At least 3 years when stored under the following conditions: in the original sealed package, in a closed environment and away from direct sunlight, at a temperature of between 5°C and 35°C.

- PACKAGING

400 ml aerosol can – for codes see colour chart

- WARNINGS

For information on product safety please consult the Safety Data Sheet. In the case of storage or use in conditions other than those indicated, please contact the company

TS 12.05.2017

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO

Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

A wholly-owned subsidiary of PETRONAS

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

