



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

INFLATE & REPAIR

PRODUCT FEATURES

Inflate & repair seals punctures and simultaneously re-inflates the tyre. Suitable for any type of puncture, intended for both tyres with inner tube and tubeless. Allows any activity to be carried out without the need to dismount the tyre and without getting your hands dirty. It is not suitable in the event of laceration of the tyre.

FIELDS OF APPLICATION

Inflate & repair is an essential accessory for your bike and car. Eliminates the drawbacks of a "forced stop" in articular situations: in the rain, snow, fog or in heavy traffic.

CHEMICAL AND PHYSICAL PROPERTIES

• Appearance	Liquid
• Colour	White
• Odour	Typical
• Density at 20°C	0,692 g/cm ³
• pH	Approx. 9

The reported data are subject to normal manufacturing tolerances

DIRECTIONS FOR USE

- a. Arrange the tyre with the valve pointing upwards
- b. Remove the object causing the puncture
- c. Deflate the tyre completely
- d. Shake the can thoroughly; if it is cold heat it up with your hands
- e. Clean the thread of the valve and apply the fitting of the can
- f. Keeping the can upright, keep the dispensing button pressed until the tyre is fully inflated
- g. Unscrew the fitting and close the valve

h. Start off again immediately to facilitate distribution of the product inside the tyre

i. As soon as possible, check the pressure, replace the **Inflate & Repair** gas with compressed air and inflate to the pressure specified by the manufacturer.

WARNINGS

Use **Inflate & repair** carefully following the instruction on the packaging.

Protect the can from direct sunlight and do not expose it to temperatures exceeding 50°C

SHELF LIFE

Unopened and stored at room temperature away from direct sunlight, at least 2 years Protect from frost.

PACKAGING

Aerosol can

Code 8470 400 ml

Code 8473 300 ml

ADDITIONAL INFORMATION

For further information about product safety, please consult the safety data sheet.

R&D 04.06.15 rev.0

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

A wholly-owned subsidiary of PETRONAS

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

