

TECHNICAL DATA SHEET

SYSTEM LITHIUM GREASE

- PRODUCT DESCRIPTION

Lubricant based on lithium soap able to reduce friction and protect from corrosion.

It eliminates friction on hinges, guides, locks, pins, gears and for all uses where a specific lubricant is not required. It protects from corrosion, humidity, dust and frost. Good resistance to heat and water, including sea water.

- It does not drip
- It does not leave gummy residues
- It does not oxidize and remains unaltered over time

- FIELDS OF USE

System Lithium Grease lubricates mechanical parts subject to loads and, in any event, where a specific lubrication is not required.

- STORAGE

Product validity in sealed packaging and stored at room temperature: at least 3 years.

- PACKAGING

PE tube Contents 100 ml Code 9806

- NOTES

For information on product safety, please consult Material Safety Data Sheet.

Property	Test method	Unit of	Typical values
		measurement	
 Appearance 			Creamy
• Color			Amber
• Odor			Typical
 Thickener 			Lithium soap
 NLG classification 	ASTM D217		2
 Specific weight 	ASTM D1298	Kg/l	0.90
 Dropping point 	ASTM D566	°C	180
• Manipulated penetration (around 60 to 25°C)	ASTM D217	1/10 mm	265 / 295
 Base oil viscosity at 40°C 	ASTM D445	cSt	100
 Recommended usage temperatures 		°C	-25 to +120

R&D 11.02.2008

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO Via Antica di Cassano, 23

20063Cernusco sul Naviglio (MI) Italy Capitale Sociale: € 15.000.000,00 I.V. Registro delle Imprese di Milano n. 09728360968 Codice Fiscale e Partita IVA 09728360968

Codice Fiscale e Partita IVA 09728360968 Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V. Centralino 02 92436.1

Fax 02 92436.306

certificati ISO 9001 da LRQA.

Sistemi di gestione di qualità della società Arexons S.p.A.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A. certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

