

TECHNICAL DATA SHEET

DIESEL MIX "SPECIAL TRUCK"

- PRODUCT DESCRIPTION

"DIESEL MIX" prevents the freezing of diesel in the engines of Diesel and Turbo Diesel heavy vehicles. In winter, it protects against freezing, impeding the crystallization of paraffin and consequent filter clogging, aiding starting under the coldest conditions. Diesel mix:

- protects against ice
- improves fluidity of diesel
- impedes the clogging of the filter
- improves combustion
- eliminates rust deposits
- reduces emissions

- FIELDS OF USE

For all engines fueled with diesel.

- TECHNICAL SPECIFICATIONS

•	Appearance	Liquid
•	Color	Straw-yellow
•	Odor	Typical
•	Density at 15°C ASTM D1298	0.895 g/ml
•	Viscosity at 40°C ASTM D445	12.4 cSt
•	Flash Point	110°C
prover a data are subject to normal manufacturing telerances		

The reported data are subject to normal manufacturing tolerances.

- METHOD OF USE

Pour the product directly into the tank before refueling.

- DOSAGE

- 5 L are treatment for 2000 liters of diesel.
- 1 L treats 400 liters of diesel.

"**DIESEL MIX**", in recommended dosage, ensures pumpability of the fuel up to -20°C (depending type and quality of the diesel).

- STORAGE

Unopened and stored at room temperature away from direct sunlight, for at least 3 years.

- PACKAGING

Metal tank. Code 9824 5 L

- NOTES

For information on product safety, please consult Material Safety Data Sheet.

R.& D. 12.04.2011

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO Via Antica di Cassano, 23 20063Cernusco sul Naviglio (MI) Italy Capitale Sociale: € 15.000.000,00 I.V. Registro delle Imprese di Milano n. 09728360968 Codice Fiscale e Partita IVA 09728360968 Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V. Centralino 02 92436.1 Fax 02 92436.306 www.arexons.com

Sistemi di gestione di qualità della società Arexons S.p.A. certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A. certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.



A wholly-owned subsidiary of PETRONAS