



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

FAP/DPF ADDITIVE DIESEL

- **PRODUCT DESCRIPTION**

"FAP/DPF ADDITIVE" contributes to the reduction of particulate matter (pm10) and carbon deposits keeping the "FAF/DPF" particulate filter clean and efficient for a longer time. This performance is due to the latest technology that allows the fuel system to be cleaned quickly, improving the ignition speed and increasing the lubrication. The additive also prevents the formation of foam during refueling and facilitates the separation of water, which will subsequently be retained by the diesel filter.

- It extends the FAP/DPF particulate filter maintenance intervals reducing the regeneration cycles
- Extreme cleanliness with a single treatment on a single tank of fuel. XUD-9 and CEC DW 10 Test
- Quick cleaning of deposits on injectors
- It increases the cetane number by approx. 5 CN*
- It optimizes the combustion process
- It reduces the emission of harmful substances by optimizing the exhaust gases opacity values
- It restores to the engine its original power
- It prevents foaming when refueling
- It contributes to "fuel economy" (reduction in fuel consumption)
- Compatible with biodiesel currently in distribution

* The average increase of 5 CN (at the recommended dosage) results in the reduction of particulate matter, improved cold starting, reduced noise levels and greater engine operation flexibility.

- **FIELDS OF USE**

Suitable for all types of diesel engines, including DI, IDI and Common Rail systems.

- **TECHNICAL SPECIFICATIONS**

- | | |
|------------------------------|------------------------|
| • Appearance | Liquid |
| • Color | Amber |
| • Odor | Typical |
| • Density at 15°C ASTM D1298 | 0,905 g/ml |
| • Viscosity at 40°C | 9,5 mm ² /s |

- **METHOD OF USE**

Pour directly into the tank. Repeat the treatment every 10,000 km approx. or at every scheduled service. Dose 325 ml are recommended to treat 40-50 liters of diesel.

- **STORAGE**

Unopened and stored at room temperature away from direct sunlight, for at least 3 years.

- **PACKAGING**

Metal can

Code 9842 325 ml

- **NOTES**

For information on product safety, please consult Safety Data Sheet.

TS 07.01.19

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO
Via Antica di Cassano, 23
20063 Cernusco sul Naviglio (MI) Italy
Capitale Sociale: € 15.000.000,00 I.V.
Registro delle Imprese di Milano n. 09728360968
Codice Fiscale e Partita IVA 09728360968
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.
Centralino 02 92436.1
Fax 02 92436.306
www.arexons.com

A wholly-owned subsidiary of PETRONAS

Sistemi di gestione di qualità della società Arexons S.p.A.
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

