



EXPERIENCE TO PERFORM

TECHNICAL DATA SHEET

# NOISY TRANSMISSION/GEARBOX TREATMENT PROFESSIONAL USE ONLY

## PRODUCT FEATURES

Specific additive for both manual and differential gearboxes and reducer. It provides perfect lubrication and protection from wear, especially during speed variation. Good protection from "pitting" even in severe conditions such as high temperature and high load. Compatible with all materials such as synchronizers, seals, etc... and all transmission lubricants (excluding ATF type). Ensures effective reduction of transmission noises. Stabilizes oil viscosity and contributes to reduce fuel consumption. Increasing oil viscosity also helps widening the range of service temperature.

## AREA OF USE (APPLICATIONS)

Suitable for all manual transmissions, differentials, steering gears and gearboxes, where GL3, GL4, GL5 specifications oil is required as long as an extreme pressure characteristic one.

## CHEMICAL AND PHYSICAL PROPERTIES

- Appearance Viscous liquid
- Color Straw yellow
- Odor Typical
- Density at 20°C 0,895g/cm<sup>3</sup>
- Viscosity at 100°C 30 ÷ 33 cSt
- Flash point >140°C

The reported data are subject to normal manufacturing tolerances

## DIRECTIONS FOR USE

Add the content of a pipe to the lubricant, preferably a new one.

125ml are enough for the treatment of 2÷3 liters of lubricant (recommended dose is 4÷6% of additive)

R&D 05.11.2011 rev.0

The data contained herein are the result of technological research by our laboratories and are given for informative purposes only. We exclude any liability deriving from the incorrect choice or application of the product and from the lack of the necessary precautions, which should be carefully checked by the user. For information, please contact our Technical Dept. on no. +39 02924361

AREXONS S.p.A. A SOCIO UNICO  
Via Antica di Cassano, 23  
20063 Cernusco sul Naviglio (MI) Italy  
Capitale Sociale: € 15.000.000,00 I.V.  
Registro delle Imprese di Milano n. 09728360968  
Codice Fiscale e Partita IVA 09728360968  
Direzione e coordinamento ex art. 2497 c.c. PLI (Netherlands) B.V.  
Centralino 02 92436.1  
Fax 02 92436.306  
[www.arexons.com](http://www.arexons.com)

Sistemi di gestione di qualità della società Arexons S.p.A.  
certificati ISO 9001 da LRQA.

Sistemi di gestione di ambiente e sicurezza della società Arexons S.p.A.  
certificati ISO 14001 e OHSAS 18001 da Bureau Veritas.

